

NEWDOS/80

Apparat, Inc. takes great pleasure in presenting NEWDOS/80 Version 2.0, a Disk Operating System for the TRS-80 Model I and Model III computers. The following is an attempt to meet an ever increasing demand for information on our Disk Operating System. The information presented here by no means discusses every feature available nor explains every command. We attempt only to mention the more outstanding features.

Almost all disk based computer systems use a Disk Operating System (known as DOS) to provide a software interface between the user program performing disk I/O and the actual disk drives and their controllers. Usually these operating systems perform many other functions as well, such as controlling what the user program is executing and the allocation of disk files and file space. Believe it or not, the primary function of a DOS is to make life easier for the computer users and programmers.

NEWDOS/80 Version 2 (released August, 1981) is one of a number of Disk Operating Systems that operate with the TRS-80 and is the replacement for NEWDOS/80 Version 1 (released June, 1980) and for NEWDOS/21 (released March, 1979). NEWDOS/80 Version 2.0 is designed to operate on the TRS-80 Model I and the TRS-80 Model III. A particular NEWDOS/80 Version 2 master diskette is tailored to operate only on one of the two TRS-80 models; if you wish to operate on both the Model I and the Model III you must purchase different NEWDOS/80's for each. The TRS-80 model being used must have at least 32K of RAM and at least one 5 1/4 inch, single sided, 35 (40 for the Model III) track disk drive (mounted on drive 0).

A FEW OF THE NEWDOS/80 FEATURES INCLUDE:

1. Single and/or double density operation supported.
2. Single and/or double sided drive whose diskettes are treated as a single volume.
3. 80 Track disk drives can read 35/40 track diskettes.
4. Mix and match 35, 40, 77 and 80 track disk drives.
5. Single density 8" disk drives supported; double density if CPU speed is equal to or greater than 3.55 MHZ.
6. CPU speeds to 4 MHZ ok. (CPU slow down, if required, is NOT supported by NEWDOS/80).
7. Lower case, blinking cursor and repeat key software built-in.
8. Model I to/from Model III file portability under NEWDOS/80 Ver. 2.0.
9. Enhanced copy features (28 different parameters available).
10. Single drive, two diskette file/diskette copy.
11. Copy to or from Model III or Model I TRSDOS diskettes, but will not directly operate with TRSDOS Model III or Model I 2.3B diskettes.
12. MINI-DOS (allows DOS commands while user program is executing).
13. SUPERZAP (a diskette display and modify program).
14. DIRCHECK (validates directory integrity).
15. Built in RENUMber, variable REFERencing.
16. Enhanced BASIC functions including five new disk I/O file structures.
17. Dynamic MERGing, DELETing, variable passing.

* * * * *

NEWDOS/80 Version 2.0 (\$149.00) may be purchased from your local dealer or directly from Apparat, Inc., 4401 S Tamarac Parkway, Denver, CO 80237. Phone (303) 741-1778 or (800) 525-7674.

DISK BASIC, NON I/O ENHANCEMENTS

GENERAL FEATURES

The NEWDOS/80 DISK BASIC allows the user to pass File Areas and Variables between programs.

BASIC programs may disable the BREAK key via CMD"BREAK,N" and reenable it by CMD"BREAK,Y".

To avoid unintentional Text Line deletes, the NEWDOS/80 DISK BASIC requires that the DELETE or D command be used to delete a Text Line.

CMD"doscnd"

Allows the user to execute ALL DOS commands from a BASIC program. Also used to call extended NEWDOS/80 DISK BASIC commands.

The following is a listing of extended NEWDOS/80 DISK BASIC commands:

SASZ	Change BASIC's string area size without affecting or clearing the variables.
ERASE	Allows the specified variables to be cleared.
KEEP	Allows the specified variables to be kept; all others are cleared.
DELETE	Allows text lines from a specified line number to a specified line number to be deleted during program execution.
SWAP	Swapping of variable contents.
SS	Allows the programmer to step through a program one line at a time from the beginning or starting with a specified line number, displaying the pending line number in the upper right hand corner of the display.
O	Main memory sort allowing direct and indirect sorting of up to 9 arrays. Ascending or descending order may be specified.

RENEW

Reinstate a program deleted by the command NEW.

BASIC

BASIC may be entered using part or all of the following parameters:

BASIC,N,M,RUN"filespec" or BASIC,N,M,LOAD"filespec"

Where N sets the number of file areas to be reserved, and M sets BASIC's memory size. If not specified, the default is 3 file areas and DOS's HIMEM value.

The following direct commands are recognized:

.	(Period)	Lists current text line.
↓	down-arrow	Lists the next text line.
↑	up-arrow	Lists the previous text line.
;	or shift-up-arrow	List the first text line.
/	or shift-down-arrow	List the last text line.
:		Scroll one page toward the start of the text.
@		Scroll one page toward the end of the text.
,		Edit the current text line.

A or a Auto line numbering.
D or d Delete line number(s).
E or e Edit line number.
L or l List line number(s).

DI Move line n1 to line n2.
DU Duplicate line n1 at line n2.

MERGE

MERGE will merge either an ASCII or a packed text file. It may be executed as a direct statement, or as a BASIC program statement (loading an overlay text code section and continuing execution without disturbing the variables).

RENUM

The current BASIC program or a part of it may be renumbered while it resides in the text area.

REF

The BASIC statement REF allows the BASIC programmer to find all places in the program where a line number, an integer, a variable, a string, a function code, a packed sequence of characters, or an unpacked sequence of characters is referenced. A complete reference table may be generated at any time going to the display or to the printer.

DISK BASIC I/O ENHANCEMENTS

The TRSDOS standard file structures (SEQUENTIAL or PRINT/INPUT and RANDOM or FIELD ITEM) are supported as well as two new file structures called **MARKED ITEM** and **FIXED ITEM**. For marked item and fixed item files, the programmer GETs or PUTs an item-group of data at one time. The only limitations on the amount of data transmitted are file size and, if applicable, record size. Logical records can be any length between 1 and 4095 bytes. The special functions designed for field item file ops, (MKD\$, MKI\$, MKS\$, CVD, CVI, CVS, LSET, RSET, etc.) function as before. However, the use of MKD\$, MKI\$, MKS\$, CVD, CVI, and CVS may be dropped for marked item or fixed item file operation as GET and PUT will transmit numeric as well as string data.

The FI file types are :

- MI A marked item file not segmented into records.
- MU A marked item file segmented into records of varying lengths, where the length is determined by searching for either EOF or the next record's Start Of Record item.
- MF A marked item file segmented into fixed length records.

The FF file types are :

- FI A fixed item file not record segmented.
- FF A fixed item file of fixed length records.

The five new file types (MI, MU, MF, FI, FF) may be used sequentially or randomly except that MI and FI types cannot be updated. MU Records can only be updated if the new record length is not greater than the old record length.

These new file types (The choice of which is up to the user) are initially difficult to understand, but once understood, make file I/O both easier and more flexible. The manual has two appendices to assist the user's education into the use of these file types.

DOS LIBRARY COMMANDS

APPEND Append one file onto the end of another.
ATTRIB Assign attributes to a file.
AUTO Define the DOS command to be executed at reset.
BASIC2 Activate non-disk BASIC (Model I only).
BLINK Enable/disable cursor blinking.
BOOT Reset the computer.
BREAK Enable/disable the BREAK key.
CHAIN Shift to keyboard input from disk.
CHNON Alter chaining state.
CLEAR Clear user memory, routes, timer and logical sequences.
CLOCK Display the time every second.
CLS Clear the display.
COPY Copy single or multiple files or a full diskette.
CREATE Pre-allocate a disk file.
DATE Set computer's date.
DEBUG Enable/disable the DEBUG facility.
DIR Display a diskette's directory information.
DO Shift to keyboard input from disk.
DUMP Dump memory contents to disk.
ERROR Display DOS error message.
FORMAT Format a diskette for use with the NEWDOS/80 system.
FORMS Set printer parameters (Model III only).
FREE Display free granule count of each mounted diskette.
HIMEM Set DOS's high memory value.
JKL Send current contents of display to the printer.
KILL Delete a file.
LC Set keyboard a-z toggle switch to the specified state.
LCDVR Lower case driver.
LIB Display NEWDOS/80 library commands.
LIST List a text file on the display.
LOAD Load a Z-80 machine language file into RAM.
MDBORT Terminate MINI-DOS and return to main program.
MDCOPY Copy a file while under MINI-DOS.
MDRET Exit from MINI-DOS and return to main program.
PAUSE Display message and pause on ENTER.
PDRIVE Assign default attributes to a physical drive.
PRINT List a text file on the printer.
PROT Alter some diskette control data.
PURGE Selectively KILL files from a diskette.
R Repeat the previous DOS command.
RENAME Rename a file.
ROUTE Route one device to or from another.
SETCOM Set RS-232C interface parameters (Model III only).
STMT Display specified message.
SYSTEM Change system.
TIME Set the real time clock.
VERIFY Require verify read after every disk write.
WRDIRP Write directory sectors protected.

DOS FEATURES

JKL

Is a routine for dumping the contents of the display screen to the printer. This allows the operator to print information that would otherwise be lost as soon as the display is used for something else. This function may be invoked from DOS by simultaneously depressing the keys, J, K and L or by execution of the DOS command "JKL".

MINI-DOS

There are many times when, during the execution of a main program, the operator would like to momentarily exit the main program, execute one or more of the DOS library commands and then resume main program execution without any change having occurred to the main program's state during the exit. This can be accomplished via MINI-DOS. To enter MINI-DOS simultaneously depress the keys D, F and G. Three MINI-DOS commands are added to the library, MDRET (return from MINI-DOS), MDCOPY (copy files), MDBORT (abort and return to NEWDOS/80 READY).

CHAINING

This function is invoked via the DOS commands CHAIN or DO. For most TRS-80 users there are functions which use the same series of DOS commands and/or program responses, and for each of these functions it would save a lot of key stroking, operator time and errors if this keyboard character sequence could be saved in a disk file to be called upon when the operator wishes to execute a specific function. A chain file may be sectioned, allowing the use of one file to hold many separate JCL files, thus minimizing disk storage. Message with pause may be inserted in the chain text. Comment lines are allowed within the chain text. Message lines can be displayed. Branching to other chain file sections is allowed. DOS commands CHNON Y, D and N can be embedded in the chaining text.

RUN ONLY

Is a feature that allows the programmer to create turnkey programs in which data input and output is controlled by the program (i.e., BASIC, ASSEMBLER, COBOL, etc.). MINI-DOS, DEBUG, JKL, the CLEAR key, and the BREAK key may be disabled.

DEBUG

As an aid primarily for the machine language programmer but also for use by higher level language programmers, NEWDOS/80 includes an improved DEBUG facility for interrupting current execution, inspecting memory, altering memory, inspecting disk, altering disk, single step execution, etc. DEBUG may be entered by simultaneously depressing the three keyboard keys 1, 2 and 3.

DOS-CALL

NEWDOS/80 allows any machine language program to call the DOS routine at 4419H to execute a DOS command or user program. BASIC also uses this command to execute the CMD"doscnd" function.

SUPPLIED NEWDOS/80 UTILITIES

SUPERZAP (Machine coded)

This handy utility provides the user with the means to read and write standard 256 byte diskette sectors or any part of main memory, except writing to ROM. Superzap will locate for display/update any sector of a file regardless of whether the file sectors are contiguous or spread throughout the disk.

Verify Disk Sectors will allow superzap to check each sector for parity errors.

Zero Disk Sectors lets the user "zero out" disk sectors.

Copy Disk Sectors lets you copy contiguous disk sectors from one disk to another or to itself.

Copy Disk Data lets the user copy up to 65535 bytes anywhere on the disk or to another diskette.

Display PassWord Encode will take a password, encode it and display the resulting encode in hexadecimal as it would appear in a directory FPDE.

Display Name/Type Hashcode command of SUPERZAP will take the name and extension of a filespec and display the resulting hashcode in hexadecimal as it would appear in the directory HIT table.

DIRCHECK (Machine coded)

This module tests and lists the target diskette's directory. If errors are found in checking the directory, they are listed before the directory listing of active files. It also allows the option of cleaning up (not repairing) the directory, and, as an aid to moving single density diskettes back and forth between the Models I & III under NEWDOS/80, allows the option of writing the directory protected. The information presented may be listed to the printer or display.

CHAINBLD (Basic coded)

A mini-text editor that simplifies the creation and modification of chain files. Allows inserting of new text lines, deletion of lines, extending of existing text lines, duplication of existing text lines, relocation of text lines.

EDTASM (Machine coded)

We have converted Radio Shack's original Model I tape Editor Assembler to work with disk, 15 line page scrolling on the display, list symbols in alphabetical order with reference list, accept upper and lower-case, display the total number of bytes left in the text area so the user can judge his approach to symbol table overflow or text buffer overflow. Use of this program requires the user be an owner of Radio Shack's original tape Editor Assembler (1978).

DISASSEMBLER 2.0 (Machine coded)

This is a utility supplied with NEWDOS/80 2.0 which disassembles Z80 code from a standard TRS-80 load module or from memory. The disassembled code is sent to the display or to the printer. Generated source text may be sent to disk and a location cross table may be generated.

When source is routed to disk it is converted to EDTASM format. The disassembler will reference all Jump Relative (JR) commands.

LMOFFSET (Machine coded)

This utility reads a tape or disk load module (CMD), displays its load information, optionally changes the program's load area, optionally attaches an appendage enabling the program at execution time to move itself from its load area to its execution area, optionally prepares the module to run under non-disk BASIC via SYSTEM, and stores the module onto disk or tape with a new name.

ASPOOL (Machine coded)

Written by H. S. Gentry and modified by APPARAT to operate with NEWDOS/80 and to self relocate. This program will automatically direct your printer output to disk files, and then automatically print it on the printer. It will print in the background while your foreground main program is executing provided the main program every second or so either sends a byte to be spooled or checks the keyboard for a new input character.

ON GOING SUPPORT

Apparat has, since the first NEWDOS/21 release, always provided continuous and ongoing support for its users. We provide this support by answering customer questions and providing written corrections, known as ZAPS, at no charge to the customer. Zaps are distributed by mail to all REGISTERED owners (only those who send their registration cards are registered) whenever a large number of zaps have been accumulated.

When Apparat receives a registration card, the latest copy of the zaps will soon thereafter be mailed to the registered owner. This lets the owner know that Apparat has received the registration card and provides the owner with any zaps generated since either that manual (containing zaps as chapter 13) was made up or that NEWDOS/80 diskette was created. Apparat has an original diskette update service for those users who would prefer that Apparat apply the zaps. This service is performed ONLY on the MASTER diskette for a \$10.00 service and handling charge.

DOS ROUTINES - FOR ASSEMBLY LANGUAGE PROGRAMMERS

402DH No Error Exit.
4030H Error-already-displayed DOS Error Exit.
4400H No-Error Exit.
4405H Enter DOS and execute a command.
4409H DOS Error Exit.
440DH Enter DEBUG.
4410H Enqueue a user timer interrupt routine.
4413H Dequeue a user timer interrupt routine.
4416H Keep drives rotating.
4419H DOS-CALL Execute a DOS command and return.
441CH Extract a filespec.
4420H Open a FCB to new or existing disk file.
4424H Open a FCB to a existing file.
4428H Close a FCB.
442CH Kill FCB's associated file.
4430H Load a program file.
4433H Load and commence execution of a program file.
4436H Read sector or logical record from disk.
4439H Write sector or logical record to disk.
443CH Write sector or logical record to disk with verify read.
443FH Position FCB to start of file.
4442H Position FCB to specified file record.
4445H Position FCB back one record.
4448H Position FCB to EOF.
444BH Allocate File Space.
444EH Position FCB to specified RBA.
4451H Write EOF value from the FCB to the directory.
445BH Select and power up the specified drive.
445EH Test for mounted diskette.
4461H *name routine enqueue.
4464H *name routine dequeue.
4467H Send message to the display.
446AH Send message to the printer.
446DH Convert clock time to HH:MM:SS character format.
4470H Convert the date to MM/DD/YY character format.
4473H Insert default name extension into filespec.
0013H Read a byte from a disk file.
001BH Write a byte to a disk file.
447BH Model III only (performs the same as Model I 4410H).

REGISTRATION NUMBER 025401

402D New Dos/80 ver II

NEWDOS/80

FOR THE TRS-80

MODEL I MICRO COMPUTER

Apparat Incorporated takes pleasure in presenting NEWDOS/80, Version 2.0. Above is the registration number of your NEWDOS/80. This registration number must be the same as the registration number you find on your diskette label and the enclosed registration card. If they are not, return them to the dealer from whom you purchased your NEWDOS/80 to be reissued. This registration Number is your assurance of receiving any corrections or minor revisions to NEWDOS/80 that may be released. The registration card should be completed and returned to Apparat at your earliest convenience. **PLEASE RETURN THE CARD IT IS IMPORTANT!** It is our only method of determining who has purchased this copy of the system. This number should be included in all correspondence with Apparat.



Apparat, Inc.

4401 So. Tamarac Parkway • Denver, Colorado 80237

NOTICE

NEWDOS/80 is distributed on an "AS IS" basis only and without warranty. Neither Apparat Inc. nor any authorized dealer of NEWDOS/80 shall have liability or responsibility to any person or entity with respect to any liability, loss or damage caused or alleged to be caused by the computer programs constituting NEWDOS/80, including but not limited to any interruption of service, loss of business or anticipatory profits or consequential damages resulting from the use or operation of such computer programs.

Good programming practices dictate that frequent backup copies be made to protect active files. Also, valued data should not be used under an unknown system until it has been thoroughly tested.

All rights reserved. Reproduction or use, without express written permission, in any manner, is prohibited. No liability is assumed with respect to the use of nor for any damages that may result from the use of any information contained herein.

All NEWDOS/80 software is copyrighted by Apparat Inc., who authorizes each NEWDOS/80 owner the right of duplicating the contents of the NEWDOS/80 diskette, provided such duplication is for the sole personal use of said owner. Any other duplication of NEWDOS/80, in whole or in part, is strictly prohibited.

TABLE OF CONTENTS

Chapter 1 INTRODUCTION

1.1	REGISTRATION.....	1-1
1.2	Trademark Credits.....	1-1
1.3	What is Apparat's NEWDOS/80 version 2?.....	1-1
1.4	Duplicate and Specify the System.....	1-2
1.5	Apply Outstanding Zaps.....	1-4
1.6	Commence Using NEWDOS/80.....	1-5
1.7	Acknowledgements.....	1-5

Chapter 2 DOS LIBRARY COMMANDS

2.1	Notation Conventions and General Information.....	2-1
2.2	APPEND Append one file onto the end of another.....	2-2
2.3	ATTRIB Assign attributes to a file.....	2-3
2.4	AUTO Define the DOS command to be executed at reset.....	2-5
2.5	BASIC2 Activate non-disk BASIC (Model I only).....	2-5
2.6	BLINK Enable/disable cursor blinking.....	2-5
2.7	BOOT Reset the computer.....	2-6
2.8	BREAK Enable/disable the BREAK key.....	2-6
2.9	CHAIN Shift to keyboard input from disk.....	2-6
2.10	CHNON Alter chaining state.....	2-7
2.11	CLEAR Clear user memory, routes, timer and logical enqueues....	2-8
2.12	CLOCK Display the time every second.....	2-9
2.13	CLS Clear the display.....	2-9
2.14	COPY Copy single or multiple files or a full diskette.....	2-9
2.15	CREATE Pre-allocate a disk file.....	2-18
2.16	DATE Set computer's date.....	2-19
2.17	DEBUG Enable or disable the DEBUG facility.....	2-20
2.18	DIR Display a diskette's directory information.....	2-20
2.19	DO Shift to keyboard input from disk.....	2-22
2.20	DUMP Dump memory contents to disk.....	2-22
2.21	ERROR Display DOS error message.....	2-24
2.22	FORMAT Format a diskette for use with the NEWDOS/80 system.....	2-24
2.23	FORMS Set printer parameters (Model III only).....	2-26
2.24	FREE Display free granule count of each mounted diskette.....	2-27
2.25	HIMEM Set DOS's high memory value.....	2-27
2.26	JKL Send current contents of display to the printer.....	2-27
2.27	KILL Delete a file.....	2-28
2.28	LC Set keyboard a-z toggle switch to the specified state....	2-29
2.29	LCDVR Lower case driver (Model I only).....	2-29
2.30	LIB Display NEWDOS/80 library commands.....	2-30
2.31	LIST List a text file on the display.....	2-30
2.32	LOAD Load a Z-80 machine language file into RAM.....	2-31
2.33	MDBORT Terminate MINI-DOS and go to DOS READY.....	2-31
2.34	MDCOPY Copy a file while under MINI-DOS.....	2-32
2.35	MDRET Exit from MINI-DOS and return to main program.....	2-32
2.36	PAUSE Display message and pause on ENTER.....	2-33
2.37	PDRIVE Assign default attributes to a physical drive.....	2-33

2.38	PRINT	List a text file on the printer.....	2-39
2.39	PROT	Alter some diskette control data.....	2-40
2.40	PURGE	Selectively KILL files from a diskette.....	2-41
2.41	R	Repeat the previous DOS command.....	2-41
2.42	RENAME	Rename a file.....	2-42
2.43	ROUTE	Route one device to or from another.....	2-42
2.44	SETCOM	Set RS=232 interface parameters (Model III only).....	2-44
2.45	STMT	Display specified message.....	2-45
2.46	SYSTEM	Change system.....	2-45
2.47	TIME	Set the real time clock.....	2-50
2.48	VERIFY	Require verify read after every disk write.....	2-51
2.49	WRDIRP	Write directory sectors protected.....	2-52

Chapter 3 DOS ROUTINES

3.1	Specifications Defined.....	3-1
3.2	402DH No-Error Exit.....	3-1
3.3	4030H Error-already-displayed DOS Error Exit.....	3-2
3.4	4400H No-Error Exit.....	3-2
3.5	4405H Enter DOS and execute a command.....	3-2
3.6	4409H DOS Error Exit.....	3-2
3.7	440DH Enter DEBUG	3-3
3.8	4410H Enqueue a user timer interrupt routine.....	3-3
3.9	4413H Dequeue a user timer interrupt routine.....	3-4
3.10	4416H Keep drives rotating.....	3-4
3.11	4419H DOS-CALL Execute a DOS command and return.....	3-4
3.12	441CH Extract a filespec.....	3-5
3.13	4420H Open a FCB to new or existing disk file.....	3-5
3.14	4424H Open a FCB to a existing file.....	3-6
3.15	4428H Close a FCB.....	3-7
3.16	442CH Kill FCB's associated file.....	3-7
3.17	4430H Load a program file.....	3-7
3.18	4433H Load and commence execution of a program file.....	3-7
3.19	4436H Read sector or logical record from disk.....	3-7
3.20	4439H Write sector or logical record to disk.....	3-8
3.21	443CH Write sector or logical record to disk with verify read.....	3-9
3.22	443FH Position FCB to start of file.....	3-9
3.23	4442H Position FCB to specified file record.....	3-9
3.24	4445H Position FCB back one record.....	3-9
3.25	4448H Position FCB to EOF.....	3-9
3.26	444BH Allocate File Space.....	3-10
3.27	444EH Position FCB to specified RBA.....	3-10
3.28	4451H Write the EOF value from the FCB to the directory.....	3-10
3.29	445BH Select and power up the specified drive.....	3-10
3.30	445EH Test for mounted diskette.....	3-10
3.31	4461H *name routine enqueue.....	3-10
3.32	4464H *name routine dequeue.....	3-11
3.33	4467H Send message to the display.....	3-11
3.34	446AH Send message to the printer.....	3-11
3.35	446DH Convert clock time to HH:MM:SS character format.....	3-11
3.36	4470H Convert the date to MM/DD/YY character format.....	3-11
3.37	4473H Insert default name extension into filespec.....	3-12
3.38	0013H Read a byte from a disk file.....	3-12

3.39	001BH	Write a byte to a disk file.....	3-12
3.40	447BH	Model III only (performs as Model I 4410H).....	3-12

Chapter 4 DOS FEATURES

4.1	DEBUG Facility.....	4-1
4.2	MINI-DOS.....	4-5
4.3	CHAINING.....	4-7
4.4	DOS-CALL.....	4-12
4.5	JKL.....	4-13
4.6	Asynchronous Execution.....	4-14

Chapter 5 DOS MODULES, DATA STRUCTURES, AND MISCELLANEOUS INFORMATION

5.1	Files Required on each diskette used with NEWDOS/80.....	5-1
5.2	NEWDOS/80 DOS system modules.....	5-1
5.3	NEWDOS/80 BASIC Modules.....	5-2
5.4	Other Modules on the NEWDOS/80 diskette.....	5-3
5.5	Reduced Sized Systems.....	5-4
5.6	Diskette Directory Structure.....	5-4
5.7	FPDE File Primary Directory Entry.....	5-7
5.8	FXDE File Extended Directory Entry.....	5-9
5.9	FCB File Control Block.....	5-9

Chapter 6 ADDITIONAL PROGRAMS SUPPLIED ON NEWDOS/80 DISKETTE

6.1	SUPERZAP Inspect/Change Disk/Main Memory.....	6-1
6.2	DISASSEM Disassemble Z-80 Code.....	6-5
6.3	LMOFFSET Move Module to New Load Position.....	6-9
6.4	DIRCHECK Inspect and List a Directory.....	6-12
6.5	EDTASM Editor/Assembler.....	6-14
6.6	CHAINBLD Create and Modify Chain Files.....	6-16
6.7	ASPOOL Automatic Spooler.....	6-19

Chapter 7 DISK BASIC, NON I/O ENHANCEMENTS

7.1	INTRODUCTION, Requirements.....	7-1
7.2	General Comments.....	7-1
7.3	Activating DISK BASIC.....	7-2
7.4	DIRECT Scrolling/Editing Commands.....	7-3
7.5	Text Editing Command Truncation.....	7-4
7.6	DI and DU text editing functions.....	7-4
7.7	RUN and LOAD (optionally retaining variables).....	7-4
7.8	MERGE Dynamic loading of overlay program.....	7-5
7.9	RENUM renumber the current BASIC program.....	7-5
7.10	REF List references to variables, line numbers and keywords.....	7-7
7.11	Lower Case Supression (Model I only).....	7-8

7.12	RUN-ONLY.....	7-8
7.13	Comparisons in the use of CMD between NEWDOS/80 and TRSDOS.....	7-8
7.14	CMD"doscmd".....	7-11
7.15	CMD"F=POPS", CMD"=POPR" and CMD"F=POPN".....	7-12
7.16	CMD"F=SASZ".....	7-12
7.17	CMD"F=ERASE" and CMD"F=KEEP".....	7-12
7.18	CMD"F",DELETE.....	7-13
7.19	CMD"F=SWAP".....	7-13
7.20	CMD"F=SS".....	7-14
7.21	CMD"O".....	7-15
7.22	RENEW.....	7-17

Chapter 8 DISK BASIC, I/O ENHANCEMENTS

8.1	Introduction.....	8-1
8.2	File Type.....	8-1
8.3	File type differences.....	8-2
8.4	Components of GET and PUT.....	8-3
8.5	Fixed item files.....	8-7
8.6	Marked item files.....	8-7
8.7	OPEN.....	8-9
8.8	GET.....	8-12
8.9	PUT.....	8-14
8.10	REMRA and REMBA.....	8-16
8.11	Pseudo FIELD Function.....	8-17
8.12	LOC Function.....	8-18
8.13	I/O Error Recovery.....	8-19
8.14	Additional notes about BASIC I/O.....	8-20

Chapter 9 ERROR MESSAGES

9.1	DOS Error Codes and Messages.....	9-1
9.2	DISK BASIC Error Codes and Messages.....	9-2

Chapter 10 GLOSSARY

Chapter 11 NEWDOS/80 PATCHING (ZAPPING)

11.1	Introduction.....	11-1
11.2	Incompatibility Handling.....	11-1
11.3	Reporting of NEWDOS/80 Errors and Incompatibilities.....	11-2
11.4	Format of NEWDOS/80 Zaps.....	11-2
11.5	Zapping Procedure.....	11-4
11.6	NEWDOS/80 Zap Distribution.....	11-5
11.7	Initial Installation of Zaps.....	11-5
11.8	Subsequent Installation of Zaps.....	11-6
11.9	Diskette Update Service.....	11-6
11.10	ZAP Duplication.....	11-7

Chapter 12 MISCELLANEOUS COMMENTS

12.1	RABs gain in respectability.....	12-1
12.2	Converting from Ver. 1 to Ver. 2 on the Model I.....	12-2
12.3	Converting from Ver. 1 Model I to Ver. 2 Model III.....	12-5
12.4	NEWDOS/80 Ver. 2 incompatibilities with TRSDOS Ver. 2.3.....	12-6
12.5	NEWDOS/80 Ver. 2 incompatibilities with TRSDOS Ver. 1.3.....	12-7
12.6	Miscellaneous Comments.....	12-8

Chapter 13 ZAPS (PATCHES)

APPENDIX A Discussion and example of NEWDOS/80 file routines.

APPENDIX B Example of fixed and marked item file usage

INDEX



1. INTRODUCTION.

1.1. Registration.

As soon as you receive your NEWDOS/80, fill out and mail the registration card. Apparat will limit its assistance and patches (zaps) to registered owners only. In your communications with Apparat, always state your name, address and your NEWDOS/80's registration number. For Version 1 of NEWDOS/80 we had many complaints of not receiving zaps from users who had not sent in the registration card. Apparat does not require the owner to agree to anything when filling out the NEWDOS/80 Version 2 registration card; just let us know who you are.

1.2 Trademark Credits.

Throughout this manual certain trademarked names will be used to refer to those trademarked products. Since our printers do not have the tm symbol, we will acknowledge the trademarked names here. If we have missed rendering an acknowledgement, please forgive us as we do not mean for any trademarked name to be used to refer to anything that the trademark holder does not mean it to refer to. In some cases, such as VTOS, the primary manual for that system shows the name trademarked but does not say who it is trademarked to.

1. TRS-80 is a registered trademark of Radio Shack, Inc.
2. TRSDOS is a registered trademark of Radio Shack, Inc.
3. VTOS is a registered trademark.
4. LDOS is a registered trademark of Lobo Drives International.
5. DOUBLER is a registered trademark of Percom Data Company, Inc.
6. SCRIPSIT is a registered trademark of Radio Shack, Inc.

1.3. What Is Apparat's NEWDOS/80 Version 2?

Almost all disk based computer systems use a Disk Operating System (known as a DOS) to provide a software interface between the user program performing disk I/O and the actual disk drives and their controllers. Usually these operating systems perform many other functions as well such as controlling what user program is executing and the allocation of disk files and file space. Believe it or not, the primary function of a DOS is to make life easier for the computer users and programmers. NEWDOS/80 is one of a number of DOSs that operate with the TRS-80; in this case only the Model I and Model III are supported.

NEWDOS/80 Version 2 is the replacement for NEWDOS/80 Version 1 that was released in June, 1980 and for NEWDOS/21 that was released in March, 1979. NEWDOS/80 Version 2 is a disk operating system designed to operate on the TRS-80 Model I and the TRS-80 Model III. A particular NEWDOS/80 Version 2 master diskette is tailored to operate on only one of the two TRS-80 models; if you wish to operate on both the Model I and the Model III, you must purchase different NEWDOS/80's for each. The TRS-80 model being used must have at least 32K of RAM and at least one 5 inch, single sided, 35 (40 for the Model III)

track disk drive (mounted on drive 0). Model I NEWDOS/80 Version 2 is distributed on a 35 track, single sided, single density diskette, and Model III NEWDOS/80 Version 2 master diskette is distributed on a 40 track, single sided, double density diskette. You must have a disk drive capable of handling the master diskette.

NEWDOS/80 Version 2 for the Model I and NEWDOS/80 Version 2 for the Model III are mostly downward compatible with NEWDOS/80 Version 1, NEWDOS/21 and Model I TRSDOS 2.3, but it will be necessary to maintain certain programs with different copies for all four systems for incompatibilities do exist. NEWDOS/80 Version 2 is more incompatible with the Model III TRSDOS than it is with the Model I TRSDOS, and most programs and files will have to be maintained differently in the two systems. In the past, while TRSDOS was largely dormant, attempts were made to limit the incompatibilities between NEWDOS and TRSDOS, but now that TRSDOS is being actively updated more and more incompatibilities are appearing between the two systems. TRSDOS is going one way; NEWDOS/80 is going another. If this limits and eventually destroys NEWDOS's usefulness to the users, so be it. NEWDOS cannot and should not exist to be a mirror image of TRSDOS; if the user wants that, then please use TRSDOS. NEWDOS was accidentally created in the huge vacuum left by Model I TRSDOS, has always incorporated features not in TRSDOS and, in Version 2, has not implemented many of the newer features of the Model III TRSDOS. Chapter 12, sections 12.1 through 12.5 give some of the incompatibilities of NEWDOS/80 Version 2 with NEWDOS/80 Version 1 and with the Model I and III TRSDOSs.

The DOS and DISK BASIC portions of NEWDOS/80 are total rewrites from that offered in NEWDOS/21. The requirement that the user purchase TRSDOS as a precondition of use of NEWDOS/21 is not required for NEWDOS/80. It is still recommended that the user purchase TRSDOS, and NEWDOS/80 users are expected to have purchased the TRSDOS manual and be knowledgeable of its contents as use of NEWDOS/80 assumes this user knowledge. Users of the EDTASM module are still required, as a precondition of use of NEWDOS/80's EDTASM, to have purchased Radio Shack's tape editor/assembler.

Though NEWDOS/80, Version 2 was tested more extensively than Version 1, there will still be errors, and many programs will require at least a zap to work with NEWDOS/80 Version 2. Error reporting procedures are discussed in chapter 11, and the outstanding zaps are in chapter 13.

1.4. Duplicate and Specify the System.

NEWDOS/80 is not a simple system. When the NEWDOS/80 user is ready to initially use NEWDOS/80, he/she should spend one to two hours studying the documentation before doing anything with the NEWDOS/80 diskette.

When ready, put a write protect tab on your NEWDOS/80 Version 2 master diskette. Then power up your computer, place the master diskette in drive 0 and press reset. The NEWDOS/80 banner should appear optionally followed by requests for date and time. If date and time are requested, please give realistic values. Next, NEWDOS/80 READY will be displayed to indicate DOS is waiting for something to do.

It is good practice to never mount on a disk drive the NEWDOS/80 master diskette except to make copies of the diskette and to very carefully apply mandatory zaps (see chapter 11). When zapping, you should first apply the zaps to a working Version 2 system diskette and test them out before applying them to the master diskette. Keep the master diskette stored away in a safe place; do not keep it in your NEWDOS/80 manual and do not use it in normal operations. Apparat will not replace a lost master diskette though it will, under the terms for the diskette update service offered in section 11.9, replace a damaged diskette.

Enter, via the keyboard, the DOS command:

LIB

A list of all the DOS library commands will be displayed to you. These commands are defined in chapter 2 with examples.

Enter the DOS command:

DIR,0,S,I

A list of all the files on the NEWDOS/80 Version 2 master diskette will be displayed. These files, except for NWD82V2/ILF and NWD82V2/XLF, are discussed in chapter 5.

Enter the DOS command:

SYSTEM,0

NEWDOS/80 offers the user certain system options which are specified via the DOS library command SYSTEM (see section 2.46) and activated during each computer reset. The DOS command SYSTEM,0 you just executed has displayed the state of all SYSTEM options, and you should compare these value carefully against the specifications. You may decide that your system is to use different SYSTEM specifications. You may change them now if absolutely necessary; otherwise you should wait until after you have made a few backup copies of the master diskette. Whenever you decide to update the master diskette, don't forget to take off the write protect tab.

Enter the DOS command

PDRIVE,0

NEWDOS/80 can operate with a limited mixture of disk drive and interface types. The characteristics of each of the physical drives 0 - 3 must be specified to the system via the DOS library command PDRIVE (see section 2.39). These characteristics are then read by DOS during each computer reset. The PDRIVE command you just executed has displayed the existing drive specifications plus 6 pseudo drive specifications. You may want to change the specifications for one or more drives. You may do so now if absolutely necessary; otherwise you should wait until you have a few backup copies of the master diskette.

Now you must make three or more copies of the NEWDOS/80 Version 2 master diskette. If possible, perform these initial backups without changing any of the SYSTEM or PDRIVE parameters. If not possible, change them the minimum neces-

sary and do a reset when done. You should carefully study sections 2.14, 2.39 and 2.46.

NEWDOS/80 does NOT have a BACKUP module; format 5 or 6 of DOS library command COPY (see section 2.14) is used instead. For each of the backups you are about to do, the master diskette is both the system and the source diskette while the destination diskette is the diskette to contain the new working copy of the NEWDOS/80 system. Some examples of the COPY command you will use to make copies of the NEWDOS/80 Version 2 master diskette are:

COPY,0,0,,FMT,USD For a single drive system where the master and copy diskettes have the same PDRIVE characteristics.

COPY,0,1,,FMT,USD For a multiple drive system where the master and copy (mounted on drive 1) diskettes have the same PDRIVE characteristics.

COPY,0,0,,FMT,USD,CBF,DPDN=4 For single drive system wherein the destination diskette has PDRIVE characteristics different from the master diskette. You must have previously altered the master diskette PDRIVE specification for drive 4 (remember to use the A option or to reset the computer after changing the drive 4 specification).

COPY,0,1,,FMT,USD,CBF For a multiple drive system where the drive 1 drive will be moved to drive 0 after the copy and the destination drive has different PDRIVE characteristics than does the current drive 0. You must have previously altered the master diskette's PDRIVE specification for drive 1.

Each system diskette has its own set of SYSTEM and PDRIVE characteristics. Therefore, for each working copy of NEWDOS/80 Version 2 you make, after the copy is completed, you need to set that system diskette's SYSTEM and PDRIVE characteristics for the operating conditions it is to operate with.

The NEWDOS/80 owner is authorized to make as many copies as necessary of the NEWDOS/80 diskette or individual programs thereon for his/her own personal use. NEWDOS/80 owners and users are specifically prohibited from copying the NEWDOS/80 diskette or individual programs thereon for use by others. See COPY, formats 2 and 4, in section 2.14.

1.5. Apply Outstanding Zaps.

Before your NEWDOS/80 is ready to run user programs, review the outstanding zaps to both NEWDOS/80 modules and to other modules (such as EDIT/CMD and SCRIPSIT) that require patches to work properly with NEWDOS/80. Chapter 11 explains how to apply zaps (patches), and with your NEWDOS/80 should have come a chapter 13 which contains the zaps. If part or all of chapter 13 is not in the proper place in the manual, please put it there. Mandatory zaps must be applied; optional zaps are at user discretion.

Mandatory zaps to NEWDOS/80 modules should be applied to all copies of the NEWDOS/80 Version 2 master diskette and to the NEWDOS/80 Version 2 master diskette. DO NOT start applying the zaps until you have at least 2 or 3 good backup copies made of the NEWDOS/80 diskette.

1.6. Commence Using NEWDOS/80.

Once all backup copies of the NEWDOS/80 Version 2 system are made, zaps applied, system options and drive characteristics specified, you are now ready to use NEWDOS/80.

Put away the master diskette and mount in drive 0 one of the system diskette just made. Then press reset to re-initialize DOS using the new diskette. NEWDOS/80 READY will then appear. The user may now type in a DOS command, which is either a DOS library command as discussed in chapter 2 or the name or name/ext of a user program to be loaded and run. If a user program does not have a name extension, name extension CMD is assumed. Examples:

BASIC causes the load and execution of program BASIC/CMD.

SCRIPSIT/LC causes the load and execution of program SCRIPSIT/LC.

If the DOS library command or the user program requires or allows for parameters within the DOS command, one or more spaces or a comma must follow the command name and precede the parameter(s). Examples:

```
BASIC,5,65000  
DIR 1 A
```

For virtually all programs to be executed under NEWDOS/80, there are instructions on how to use the program that usually comes with the program when you buy it. For NEWDOS/80 program modules, the instructions are in chapter 6 except for BASIC which is covered in chapters 7 and 8.

Those users upgrading from NEWDOS/80 Version 1, NEWDOS/21 or TRSDOS to NEWDOS/80 Version 2 should read sections 12.1 through 12.5 carefully.

1.7. Apparat Thanks Its Beta Testers.

Over forty persons throughout the United States and Canada were involved in the testing of NEWDOS/80 Version 2, finding errors, suggesting enhancements and providing criticism. Apparat and the NEWDOS/80 author thank each one of these beta testers for the long hours spent working with the three beta releases that were sent out. It is Apparat's policy that each beta tester receive a complimentary copy of the final release of NEWDOS/80 Version 2.



2. DOS LIBRARY COMMANDS.

2.1. Notation Conventions and General Information.

All DOS commands terminate with an ENTER. In subsequent specifications, the ENTER is not shown, but the user is to supply it.

DOS commands are limited to a total of 80 characters, including the concluding ENTER.

[] A set of brackets are used to enclose an optional parameter. When using the optional parameter in a DOS command, the [] are not included.

Example:

```
[,PROT=xxx][,ASE=yn][,ASC=yn]
could be coded as
    ,PROT=READ,ASC=N
```

Upper case A - Z and non alphanumeric characters are to be included exactly as shown. See the above example.

Lower case letters or words with or without trailing decimal digits. These represent prototype values for which the user is to substitute the appropriate actual values. See the above example.

In some cases where the prototype will be replaced by one and only one character, the prototype word contains, in lower case, all the characters legal for that value. This helps serve as a reminder of which characters are legal replacement for that prototype value. For example, if ASC=Y and ASC=N are the only two legal ASC values, then the prototype will usually be written as ASC=yn.

Where commas are used in DOS commands, they may be replaced by one or more consecutive spaces.

Numeric values without a suffixed H are considered decimal values unless otherwise specified. Hexadecimal values must be suffixed with an H unless otherwise specified. Example:

4000H and 16384 are the same value.

When specifying a disk file, the term 'filespec' is used. A filespec is of the form:

```
namel[/extl][.passwordl][:dnl]
```

Parameters must be specified in the above order.

namel is the file's name consisting of 1 - 8 chars of which the first must be A - Z and the others A - Z or 0 - 9.

extl is the name extension (i.e., CMD, BAS, OBJ, CIM, TXT, DOC, COM, etc.) which classifies a file. A file need not have a name extension, but if it

APPEND

does it must be 1 - 3 chars of which the first must be A - Z and the others A - Z or 0 - 9. If a file has a name extension, all filespecs referencing the file must include the name extension, unless a default name extension is provided for (i.e., /CMD).

password1 is 1 - 8 chars of which the first must be A - Z and the others A - Z or 0 - 9. Password1 is the value given to both the access and update passwords for a file when it is created. Password1 is value used in password checking when an existing file is opened. Password1 is required in a filespec if passwords are enabled and the file has passwords assigned; otherwise it is not.

dnl is the drive # of the drive which has the diskette containing the file. Examples:

```
MYFILE80/BAS.YOURPW80:0  
MYFILE:3  
YOURFILE.YOURPW
```

NEWDOS/80 will accept lowercase in all DOS library commands and any further input that might be queried for.

For each DOS library command, the command keyword is stated along with a brief definition. Next, if the command is allowed parameters, a prototype of the command is given, listing all required and optional parameters. Next comes explanations of the command, parameters and options. Lastly, some examples of the DOS command are given.

For documentation ease, the prototype command is sometimes shown spread over multiple lines in this document; however, the user should consider each command as one contiguous statement.

Unless otherwise stated, a DOS library command is executable under MINI-DOS (see section 4.2).

NEWDOS/80 differs from TRSDOS in NOT using parenthesis to enclose parameters. In NEWDOS/80 version 1, parenthesis around the operands were optional for BREAK, CLOCK, DEBUG, DIR, PROT, and VERIFY; they are NOT allowed in version 2.

In the same vein, version 1 allowed the keywords ON or OFF to be used instead of Y or N in the DOS commands BREAK, CLOCK, DEBUG and VERIFY; this is NOT allowed in version 2.

2.2. APPEND Append one file onto the end of another.

```
APPEND,filespec1,[TO,]filespec2
```

This command will append the file filespec1 onto the end of the file filespec2. The EOF from file filespec2's directory FPDE determines the point at which file filespec1 is appended. This may be trouble if file filespec2 had explicit EOF characters, such as in BASIC program files or assembler source files.

File filespec1 is not altered. The original contents of file filespec2 are not altered; the file is only added to.

APPEND is not executable under MINI-DOS.

APPEND examples:

1. APPEND,XXX:1,YYY/DAT:Ø The contents of file XXX on drive 1 are appended onto the end of file YYY/DAT which is on drive Ø.
2. APPEND AAA TO BBB The contents of file AAA are appended onto the end of file BBB. DOS searches the currently mounted diskettes to find both files.

2.3. ATTRIB Assign attributes to a file.

```
ATTRIB,filespec1[,INV][,VIS][,PROT=xxx][,ACC=password1][,UPD=password2]
[,ASE=e][,ASC=c][,UDF=u]
```

This command assigns attributes to the filespec1 file. At least one of the optional parameters must be specified.

If passwords are enabled in your system, then filespec1 must specify the existing update password, if any, for that file.

INV gives the file the invisible attribute. Unless the I option is specified in DIR, the file will not be listed by DIR.

VIS takes away the invisible attribute, whether the file had it or not.

PROT=xxx specifies the access level to be used during file I/O if passwords are enabled (see system option AA) and the access, not the update, password was used to open the file. The levels are defined for values of xxx as:

LOCK Level 7. No access allowed to the file at all, except by the system's overlay loader.

EXEC Level 6. Access allowed only to execute the file as a program. BASIC will require either RUN or LOAD with R option, and will disable the BREAK key, thereby preventing the user from stopping the RUN and disallowing direct statement execution.

READ Level 5. Access allowed for execute or to read the file's contents.

WRITE Level 4. Access allowed for execute, read or write of the file.

RENAME or **NAME** Level 2. Access allowed for execute, read, write or to rename the file.

KILL Level 1. Access allowed for execute, read, write, rename or to kill the file.

ATTRIB

FULL Level 6. All operations are allowed on the file.

ACC=password1 Password1 is assigned as the access password for the file. If null, a value of all blanks is assumed; otherwise the value must be 1 - 8 characters with the 1st = A - Z and the others A - Z or 0 - 9. Assigning the access password via this parameter of ATTRIB is the only way that will enable use of the PROT=xxx protection and then only if the access password is different from the update password. If a password is specified when the file is created, it is assumed both the update and the access password, and the update password has priority at open time. If passwords are enabled, the password specified in the filespec at open time is not the update password, and it is the access password, the current protection level is stored into the FCB for later use by the DOS read, write, load, etc. routines. Subsequently, if an access is attempted in violation of the access level, 'ILLEGAL ACCESS TRIED TO A PROTECTED FILE' error will occur.

UPD=password2 Password2 is assigned as the update password for the file. The update password is of the same configuration as the access password. During file open where passwords are enabled, the password specified in the filespec is checked first against the file's update password. If they match, then FULL access is allowed to the file.

ASE=e where e is either Y or N. This parameter has been added to allow DOS to automatically allocate diskette space to a file if ASE=Y or to disallow further allocation if ASE=N. ASE=Y is the default condition when a file is created.

ASC=c where c is either Y or N. This parameter has been added to allow DOS to automatically deallocate file diskette space beyond the EOF during a CLOSE operation if ASC=Y is specified, and to disallow this deallocation if ASC=N. ASC=Y is the default setting when a file is created.

UDF=u where u is either Y or N. This parameter has been added to mark the file as updated if UDF=Y is specified or to clear the updated mark if UDF=N is specified. The DOS system marks a file as updated whenever it is about to update a sector to that file and it finds the file's directory entry not marked as updated.

ATTRIB command examples:

1. ATTRIB,XXX/CMD:1,UPD=ZXCVB,ACC=NMLKJ,PROT=EXEC Assigns to file XXX/CMD located on drive 1 the update password ZXCVB, the access password NMLKJ and protection level 6 which allows the program to be executed but not read or written to. Since the filespec XXX/CMD:1 did not specify a password, we must assume that either password checking was disabled (SYSTEM option AA=N) or the file did not have an update password prior to the ATTRIB command.

2. ATTRIB YYY/DAT.QZBV INV ASE=N ASC=N UDF=N This command tests if file YYY/DAT has update password QZBV, and if so, assigns the file the invisible attribute, flags that extra space allocation and excess space deallocation are not to be allowed, and lastly clears the file's updated flag.

2.4. AUTO Define the DOS command to be executed at reset.

AUTO[,doscmd]

This command allows the user to specify a 1 - 31 character DOS command to be invoked automatically at reset time. This command is stored in the last 32 bytes of GAT sector of the current system diskette.

If doscmd is not specified, then a null command is stored in the GAT sector to indicate to reset/power-on that no AUTO command exists.

If SYSTEM option AB = N and BC = Y, by pressing ENTER during reset, the auto command in the GAT sector will be ignored, and the system will go to DOS READY.

AUTO is useful to the user who usually executes the same command or chain of commands (see CHAIN, sections 2.9 and 4.3, and DO, section 2.19) at reset time. By setting system option AB=Y or BC=N, the user is forced to this command or chain of commands, thus allowing the person(s) controlling a computer to restrict the activity of users of the computer.

AUTO command examples:

1. AUTO BASIC RUN"XXX/BAS" causes subsequent reset/power-ons to activate BASIC and to start the execution of the BASIC program XXX/BAS.
2. AUTO DO RS ACTION causes subsequent reset/power-ons to activate chaining from file RS ACTION/JCL, thus executing the DOS and other program commands contained therein.
3. AUTO causes subsequent reset/power-ons to go to the normal DOS READY, awaiting the next DOS command to be inputted from the keyboard.

2.5. BASIC2 Activate non-disk BASIC (Model I only).

This command puts the system into non-disk BASIC. NEWDOS/80 is no longer in the system.

2.6. BLINK Enable/disable cursor blinking.

BLINK[,yn]

BLINK or BLINK,Y Blinking of the display cursor is turned on.

BLINK,N Blinking of the display cursor is turned off.

SYSTEM option BH can be used to set the cursor blinking state at reset/power-on.

2.7. BOOT Reset the computer.

On the Model I, this command deselects the drives and then executes Z-80 instruction HALT, which causes both a hardware and a software reset. For the Model III, since HALT does not cause a hardware reset, this instruction causes a jump to location 0 to execute a software reset.

2.8. BREAK Enable/disable the BREAK key.

BREAK[,yn]

BREAK or BREAK,Y The BREAK key is enabled as a normal input key (hexadecimal code 01) until the next normal DOS READY, when it is set according to system option AG.

BREAK,N The BREAK key is disabled as a normal input key until the next normal DOS READY, when it is set according to system option AG.

The BREAK command is useful for those programs that want the BREAK key enabled, and enable it via a DOS-CALL (vector 4419H). The same applies to programs that definitely want BREAK disabled. NOTE: Executing BREAK from DOS READY is useless since the immediate return to DOS READY resets the BREAK key according to system option AG.

In NEWDOS/80 the BREAK key may also be enabled by storing a 0C9H byte in Model I location 4312H (Model III location 4478H) and may be disabled by storing a 0C3H byte in that location. In NEWDOS/80 version 1, the break key was also manipulated by changing bit 4 of location 4369H (Model I only); in version 2 for the Model I, setting or clearing this bit does nothing and is harmless. However, programs on the Model III must NOT alter that bit, as that location is now in the system buffer.

2.9. CHAIN Shift to keyboard input from disk.

CHAIN,filespec[,sectionid]

DOS command DO performs exactly the same as CHAIN.

The purpose of the CHAIN command is to cause a predefined set of characters to be treated as input from the keyboard. This predefined set of characters has been previously stored in the file filespec.

The CHAIN command places NEWDOS/80 in chaining mode, if not already there. The file filespec is opened. If sectionid is not specified, the file is positioned at the beginning. If sectionid is specified, the file is searched for the matching sectionid record, leaving the file positioned at the byte following the section ID record.

Subsequently, input that is supposed to come from the keyboard comes from the

chain file until chaining is terminated by the encounter of either end of file or end of section or until chaining is temporarily halted by the execution of the DOS command CHNON,N.

Keyboard data is input from the chaining file in one of two modes.

If SYSTEM option AT = N, chaining operates in record mode. In this mode, whenever NEWDOS/80, BASIC or any program requests a new record from the keyboard via the standard ROM keyboard record input routine at 05D9H, the record will come from the chain file. Any other requests for keyboard input are honored from the keyboard and not the chain file.

If SYSTEM option AT = Y, chaining operates in byte mode. In this mode, all requests for keyboard input characters via the standard keyboard input routine are honored from the chain file.

The CHAIN command may be issued via DOS-CALL or via BASIC's CMD function. When so, DOS does not immediately return to the calling program but instead continues to execute commands from the chain file until either end of file, end of section, command CHNON,N or command CHNON,Y is encountered.

CHAIN is not legal under MINI-DOS.

The chain file creator/maintainer is responsible for assuring that chaining does not create impossible situations for the system or user programs.

NEWDOS/80 cannot have more than one chain file active at a time. If the new DOS command from the current chain file is itself a CHAIN or DO command, processing in the current file ceases and the new chain file is opened, becoming the new current chain file.

When the system opens a chain file, name extension in the filespec defaults to JCL if the filespec doesn't give one.

CHAINING is discussed further in section 4.3.

CHAIN or DO command examples:

1. CHAIN,XXX:0 Chaining starts at the beginning of file XXX/JCL:0.
2. DO YYY/CHN:1,QQQ Chaining starts at the first byte of the chain section named QQQ within file YYY/CHN.

2.10. CHNON Alter chaining state.

CHNON,ynd

The CHNON command is used during chaining. An error will occur if a chain file is not currently open. A CHNON command should not be the last entry in an unsectioned chain file or the last entry in a chain file section as the command will be meaningless.

CHNON - CLEAR

CHNON,N The current position within the chain file is remembered and chaining is temporarily suspended so that subsequent keyboard characters to come from the keyboard. If chaining was being done under DOS-CALL, the current DOS-CALL level is exited.

CHNON,Y causes subsequent keyboard characters to come from the chain file, starting at the current position within the chain file. If CHNON,Y was executed as a DOS-CALL, the current DOS-CALL level is exited.

CHNON,D causes subsequent keyboard characters to come from the chain file, starting at the current position within the chain file. If CHNON,D was executed as a DOS-CALL, DOS remains at that level and executes subsequent commands from the chain file until either CHNON,Y or CHNON,N or end of section or end of file is encountered.

See sections 2.9 and 4.3 for further discussion of chaining.

2.11. CLEAR Clear user memory routes, timer and logical enqueues.

CLEAR[,START=addr1][,END=addr2][,MEM=addr3]

The CLEAR command performs the following functions:

1. Performs ROUTE,CLEAR DOS command function.
2. Dequeues all user routines in the timer interrupt routine chain that were enqueued by the 4410H (Model I) or 447BH (Model III) call to DOS. This includes turning the clock display off.
3. Dequeues all *name routines that were enqueued by a 4461H call to DOS. This includes the NEWDOS/80 spooler, if active, but not its graceful termination. The spooler, if in use, should be fully terminated before executing CLEAR.
4. Resets HIMEM to addr3 or, if addr3 not specified, to the highest memory address.
5. Zeroes memory from addr1 or 5200H, whichever ever is greater, through addr3 or HIMEM, whichever is lower. addr1 must be greater than or equal to 5200H and less than or equal to addr3.

CLEAR command examples:

1. CLEAR,START=6000H,MEM=0DFFFH All routes are cleared, and all timer and *name routines dequeued. HIMEM is set to 0DFFFH. The main memory between 6000H and 0DFFFH is zeroed.
2. CLEAR All routes are cleared, and all timer and *name routines dequeued. HIMEM is set to the highest main memory location, and all memory from 5200H to HIMEM is zeroed.

2.12. CLOCK Display the time every second.

CLOCK[,yn]

CLOCK or CLOCK,Y The current value of the clock is displayed every second in positions 53-60 of the display's top line in HH:MM:SS format.

CLOCK,N The displaying of the clock ceases.

Users are warned that the clock will continuously lose time. There is no hardware clock in the sense of seconds, minutes and hours. Computation of clock time is done from the 25ms interrupt chain in the Model I (in the Model III, it is done in the ROM from the timer interrupt). Whenever the interrupts are left off for more than 25ms (33 or 40 ms on the Model III), one or more interrupts are lost and for each one lost, the clock loses 25ms (33 or 40 ms on the Model III). Lost interrupts are very frequent when disk I/O is being done, is massive when tape I/O is done, and can also be frequent if other routines hung off the 25ms chain are more than a few milliseconds long.

2.13. CLS Clear the display.

CLS simply clears the display, resetting it to 64 character mode. On the Model III, reserved top display lines are not cleared.

2.14. COPY

The COPY command is used to copy a single file, multiple files or a full diskette. COPY has 6 formats:

1. COPY,filespec1[,TO],filespec2[,SPDN=dn3][,DPDN=dn4]
2. COPY,\$filespec1[,TO],filespec2[,SPDN=dn3][,DPDN=dn4]
3. COPY,[:]dn1,filespec1[,TO],filespec2[,SPDN=dn3][,DPDN=dn4]
4. COPY,[:]dn1,\$filespec1[,TO],filespec2[,SPDN=dn3][,DPDN=dn4]
5. COPY,[:]dn1[=tc1][,TO],[:]dn2[=tc2],mm/dd/yy[,Y][,N]
 [,NDMW][,FMT][,NFMT][,SPDN=dn3][,DPDN=dn4][,SPW=password1]
 [,NDPW=password3][,DDND][,ODN=namel][,KDN][,KDD][,NDN=name2]
 [,SN=name3][,USD][,BDU][,UBB]
6. COPY,[:]dn1[,TO],[:]dn2[=tc2],mm/dd/yy,CBF[,Y][,N]
 [,USR][,/ext][,UPD][,ILF=filespec3][,XLF=filespec4][,CFW0]
 [,NDMW][,FMT][,NFMT][,SPDN=dn3][,DPDN=dn4][,SPW=password1]
 [,ODPW=password2][,NDPW=password3][,DDND][,ODN=namel]
 [,KDN][,KDD][,NDN=name2][,SN=name3][,USD][,UBB]
 [,DDSL=lnl][,DDGA=gcl]

The COPY command has been significantly changed in NEWDOS/80 version 2; all users, new and old, should carefully read this section.

COPY cannot be executed under MINI-DOS; however for simple single file copies, DOS library command MDCOPY is available.

COPY

dn1 and dn2 are drive numbers and may be equal. The colon preceding dn1 and/or dn2 is optional.

Filespec1 is the source file's filespec. Filespec2 is the destination file's filespec.

Filespec1 prefixed with \$ means that either the source or the destination file or both are to be on drive 0 and are on diskette(s) that either (1) do not contain a NEWDOS/80 system identical to the one on drive 0 when COPY was initiated, (2) do not contain a NEWDOS/80 system, or (3) contain no system at all.

During processing for formats 2, 3, 4, 5 and 6, the system may ask for various diskette mounts; do what the prompts ask!!

1. When prompted for the system diskette, mount the NEWDOS/80 diskette that was on drive 0 at the start of the COPY command execution.
2. When prompted for the source diskette, mount the diskette containing file filespec1 (formats 1, 2, 3 and 4) or the data to be copied (formats 5 and 6).
3. When prompted for the destination diskette, mount the diskette to contain file filespec2 (formats 1, 2, 3 and 4) or to receive the data being copied (formats 5 and 6).

SPDN=dn3 Source PDrive Number. SPDN=dn3 tells the system that for all source drive I/O, the system diskette's PDRIVE specifications (see DOS command PDRIVE, section 2.37) for drive dn3 are to be used instead of the source drive's normal PDRIVE specifications. dn3 is a value 0 to 9, referring to a drive number listed by the PDRIVE command.

DPDN=dn4 Destination PDrive Number. DPDN=dn4 tells the system that for all destination drive I/Os, the system diskette's PDRIVE specifications for drive dn4 are to be used instead of the destination drive's normal PDRIVE specifications. dn4 is a value 0 to 9 referring to a drive number listed by the PDRIVE command.

Note that use of SPDN and DPDN for a drive 0 single drive COPY (formats 4, 5 or 6) means that three different PDRIVE specifications (one for the system diskette, one for the source diskette and one for the destination diskette) will apply during the COPY even though only one drive is used.

Format 1 is the single file copy. It is used to copy the contents of file filespec1 to file filespec2. The diskette(s) involved in the COPY must already be mounted; the system gives no mount prompts. The contents of file filespec1 are not altered. The previous contents of file filespec2, if any, are lost. If the leading part of filespec2 equals that of filespec1, filespec2 may be shortened by leaving off the leading part, the remainder of filespec2 starting with / or . or :. For example:

COPY,USERFILE/DAT:0,TO,USERFILE/DAT:1

can be shortened to:

COPY,USERFILE/DAT:0,TO,:1

Remember, the keyword TO is optional, and spaces may be used instead of commas. Thus the command could be written:

COPY USERFILE/DAT:0 :1

Format 2 is the same as format 1 except that the \$ sign prefixed onto file-spec1 indicates that a conflict exists with drive 0, the system drive, and DOS will prompt for the proper diskettes to be mounted on drive 0. If the source and destination drive numbers are both zero but the source and destination files are on separate diskettes, use format 4 instead of format 2.

Format 3 again is similar to format 1, except that the user has only 1 drive available for the copy and file filespec1 resides on a diskette different from that of file filespec2. Neither filespec can specify a drive number. DOS will prompt for the mount of the source and destination diskettes as they are needed. If drive 0 is specified, both the source and destination diskettes must contain a NEWDOS/80 system identical to the one mounted on drive 0 at the start of the COPY command; otherwise use format 4.

Format 4 performs similar to format 3 except that either file or both reside on diskettes with different NEWDOS/80 systems, non-NEWDOS/80 systems or no systems at all. DOS will prompt for the mount of the system, source and destination diskettes as they are needed. Format 4 should only be used when dnl equals 0; otherwise you are wasting time with diskette swaps that are not needed.

Formats 2 and 4 allows suppliers of programs, whether free or purchased, to send their program products on diskettes that do not contain NEWDOS systems. Aside from the supplier's programs and/or data files, the diskette need only contain the directory and the BOOT/SYS file, both created on each diskette during formatting. Suppliers must not include a NEWDOS system on their diskettes unless they have made explicit arrangements with Apparat.

NEWDOS/80 does not have a diskette BACKUP program. Instead, either formats 5 or 6 is used. Format 5 is a full diskette sector by sector copy without concern for the number and type of files. Format 6 copies some or all of the source diskette's files onto the destination diskette. Of the two, for the same amount of data transmitted, format 5 is faster while format 6 allows greater variation between source and destination diskette types and tries to reassign files to contiguous space.

Format 5 is a full diskette copy. The default specifications for the two drives are the PDRIVE specifications currently being used by DOS. The drives must have the same number of sectors per track, granules per lump and sectors per granule (five is the current NEWDOS/80 standard); otherwise format 6 must be used. The destination diskette may have more tracks than the source; if so, the destination directory is adjusted to account for the extra free granules (not done if BDU option specified). Format 5 options are defined as follows:

=tcl DOS is to use the value tcl as the source diskette's track count during the COPY rather than the source drive's default value.

=tc2 DOS is to use the value tc2 as the destination diskette's track count during the COPY rather than the destination drive's default value.

mm/dd/yy is the date to be placed in the destination diskette date

field. The mm/dd/yy may be null, and if so the system date is used. The only time mm/dd/yy may be entirely left out of the format 5 COPY command is when the command has only the two drive number parameters (example: COPY 0 1). Otherwise mm/dd/yy must be the 3rd parameter even if it is null or to be overridden by either the KDD or the USD parameter. If the mm/dd/yy is null, this must be so indicated by separating commas (not spaces) (example: COPY 0 1,,FMT CBF).

Y The user doesn't care what was previously on the destination diskette. Y is mutually exclusive with N, ODN, ODPW, DDND, KDN or KDD. Y is the default (for COPY) if none of its mutual exclusions are specified.

N At the start of the COPY or FORMAT the destination diskette must not contain recognizable data, i.e., should be in a bulk erase state. COPY will be terminated if the diskette is found to contain data. N is mutually exclusive with Y, ODN, ODPW, DDND, KDN or KDD.

NDMW No Diskette Mount Waits. DOS is to assume that all needed diskettes are already mounted on the specified drives. No mount prompts or error prompts are displayed. If an error occurs that otherwise would have caused a prompt, the copy will be terminated. If NDMW is specified and neither FMT nor NFMT are specified, FMT is assumed. NDMW is intended for use when COPY (or FORMAT) is invoked via DOS-CALL (i.e., from BASIC) and the calling program does not want operator interaction. Since NDMW causes the COPY or FORMAT to bypass error and disk mount queries, it is recommended that NDMW normally not be used when the operator is keying in the COPY (or FORMAT) command.

FMT Format. DOS formats the destination diskette before copying data. FMT is mutually exclusive with NFMT. If neither FMT or NFMT is specified and NDMW was not specified, the operator will be queried 'FORMAT DISKETTE? (Y OR N)'. If neither FMT or NFMT is specified and NDMW was specified, FMT is assumed.

NFMT No Format. DOS does not format the destination diskette before copying data. The user must assure that the destination diskette is already formatted correctly. NFMT is mutually exclusive with FMT.

SPW=password1 Source PassWord. If passwords are enabled (system option AA = Y) and system option AR = N, then COPY requires a source diskette master password match. If password1 does not match the source diskette's password, the copy function will be terminated.

NDPW=password3 New Destination PassWord. Password3 must conform to rules for passwords and is assigned as the destination diskette's new password. NDPW is mutually exclusive with BDU.

DDND Display Destination old Name and Date. The destination diskette's old name and date are prompted to the display, allowing the operator to decide whether or not to proceed with the copy. DDND is mutually exclusive with Y, N, and NDMW.

ODN=namel Old Destination Name. If the destination diskette's old name is not equal to namel, then the system prompts, allowing the operator to decide whether to proceed with the copy. ODN is mutually exclusive with Y, N and NDMW.

KDN Keep Destination diskette Name. The destination diskette keeps its old name rather than receive the source diskette's name. KDN is mutually exclusive with Y, N, BDU and NDN.

KDD Keep Destination diskette Date. The destination diskette keeps its old date rather than receive the mm/dd/yy parameter from the COPY command. KDD is mutually exclusive with Y, N, BDU and USD.

NDN=name2 New Destination Name. The destination diskette takes name2 as its name, rather than receive the source diskette's name. Name2 must conform to the specification for diskette names. NDN is mutually exclusive with BDU and KDN.

USD Use Source Date. The destination diskette uses as its date the source diskette's date, rather than receive the mm/dd/yy parameter from the COPY command. USD is mutually exclusive with KDD and BDU.

SN=name3 Source diskette Name. If the source diskette's name is not equal to name3, a prompt is issued, allowing the operator to decide whether or not to proceed with the copy.

BDU Bypass destination Directory Update. Aside for simply copying the source sectors onto the destination diskette, the format 5 COPY also updates the boot and PDRIVE data in the destination file BOOT/SYS and, as necessary, the name, date, password and extra granule information into file DIR/SYS. There are times, however, when this file updating is not wanted, and by specifying option BDU these updates are bypassed. BDU is useful when the source diskette has a bad directory, has a non-standard directory (such as a TRSDOS Model III directory) or has no directory at all or when the user wants a full diskette copy with no alterations. BDU is mutually exclusive with KDN, NDN, NDPW and USD.

UBB Use Big Buffer In NEWDOS/21 and NEWDOS/80 version 1, COPY was restricted to using main memory below 70000H unless it was a two diskette, single drive COPY, in which case all of memory to HIMEM was used. If a user wanted to force the usage of all memory to HIMEM, the UBB parameter had to be specified. However, in NEWDOS/80 version 2, all of main memory to HIMEM is used unless the COPY was invoked under DOS-CALL (i.e., from BASIC), in which case only main memory below 70000H is used. Thus, in NEWDOS/80 version 2, UBB is a useless parameter left in existence only for upward compatibility from Version 1.

Format 6 is the multiple file COPY and is distinguished from format 5 by the inclusion of the CBF (Copy By File) option. Though format 5 is the faster way to backup a diskette, format 6 offers more flexibility, allowing files to be copied between diskettes and drives of widely varying characteristics. The choice of files to be copied can be limited by the combined effect of options USR, /ext, UPD, ILF, XLF and CFWO; if one or more criteria are specified, only those files satisfying all the criteria are copied. Format 5's options, except BDU, are used in format 6 as well as the following additional options.

If NFMT is specified, then none of Y, N, KDN, KDD, NDN, BDU, USD, NDPW, DDSL, DDGA or tc2 may be specified, ODPW may be required, and system files are not copied unless already existent in the destination file directory.

COPY

If NFMT is not specified, then the destination file is formatted as if the command was FORMAT, including establishing BOOT/SYS and DIR/SYS. Then, before any files are copied, all files to be copied are entered into the destination diskette's directory. This is necessary as system files must occupy the same directory FPDEs in order for DOS to work at all.

CBF Copy By File CBF, required for and used only in format 6, indicates the copy will be done by files rather than in straight sequential order of diskette sectors.

USR copy user files. Only user files are copied; system and invisible files are excluded.

/ext copy files having name extension ext. Only files with name extension ext are copied. ext is a 0 to 3 character name extension. Examples of this parameter are /CMD, /, /BAS, /X.

UPD copy updated files Only files that have the updated flag on in the source diskette directory are copied. This flag is turned on by the standard DOS sector write routine to indicate that at least one sector has been written or re-written to this file since the last time the updated flag was cleared. This flag is turned off by specific request via the PROT or ATTRIB commands and is NOT turned off by COPY. Since the standard DOS sector write routine is used to write the file's sectors to the destination diskette, the updated flag is turned on for the copied destination files.

ILF=filespec3 Include List File Filespec3 specifies a file containing a list of files to be copied. If a file is not in the list, it is not copied. It is not an error if an included file is not on the source diskette. Within the list, each file to be copied is specified by its name/ext followed by a EOL char (0DH). If a specification begins with a semi-colon, it is bypassed as a comment. Each specification, except comment, is limited to a maximum of 13 characters, including the EOL. On reading, the file's bytes are modulated into the ASCII range 0 to 127. The file can be made using SCRIPSIT, but the user must assure that no characters other than null (00H) follow the last EOL character; SCRIPSIT tends to leave extraneous characters so a delete-to-end-of-text should be done. ILF is mutually exclusive with XLF.

XLF=filespec4 Exclusion List File. The file filespec4 is the same structure as specified for ILF above and specifies the files to be excluded from the COPY. It is not an error if an excluded file is not on the source diskette. XLF is mutually exclusive with ILF.

CFWO Check File With Operator. For the qualifying files, DOS asks the operator, one file at a time, if the file is to be copied to the destination diskette. Reply Y if the file is to be copied, reply N if not to be copied, reply R if to restart entire CFWO query sequence, or reply Q if no more files to be copied. No files are copied until the querying is completed.

ODPW=password2 Old Destination diskette Password. If NFMT is specified, if passwords are enabled and if system option AR = N, then copy requires a destination diskette password match. If password2 does not match

the destination diskette's password, the copy is terminated.

DDSL=lnl Destination diskette Directory Starting Lump. Formatting will start the directory on the 1st sector of lump lnl if DDSL is specified; otherwise the default starting lump number for the drive (see PDRIVE command) will be used. DDSL is mutually exclusive with NFMT.

DDGA=gcl Destination diskette Directory Granule Allocation. Formatting will allocate gcl (value 2 - 6) granules to the directory if DDGA is specified; otherwise it will assign the default # of granules for that drive (see PDRIVE command). DDGA is mutually exclusive with NFMT.

If during a format 6 COPY, the destination diskette has insufficient space to contain a file, "DISKETTE FULL = name/ext" is displayed and the destination file's EOF is set to 0. Though EOF is set to 0, any space the file may have allocated to it is not deallocated.

A single drive format 5 or 6 COPY cannot be executed under DOS-CALL (i.e., from BASIC) since COPY under DOS-CALL restricts itself to main memory below 7000H and this would necessitate too many diskette swaps.

During a COPY or FORMAT where NDMW was not specified, pressing right arrow at any time will cause the function to pause, awaiting ENTER to continue or up-arrow to cancel. Pressing up-arrow at any time will terminate the function; however, be careful as the state of the destination diskette will be unknown, especially if the cancel comes during the actual formatting.

The COPY command and standard 40 track, double density, single sided, 5 inch TRSDOS Model III diskettes may be used to transfer TRSDOS Model III diskette files into or out of the NEWDOS/80 system. There are a number of restrictions to this operation.

NEWDOS/80 cannot be used to format a TRSDOS Model III diskette; however, once the user has a formatted empty TRSDOS Model III diskette, he/she may duplicate it repeatedly under NEWDOS/80 using format 5 COPY with the NFMT and BDU options, thus obtaining a stock of formatted, empty TRSDOS Model III diskettes.

The user must assure that where the source and/or destination is a TRSDOS Model III diskette the proper PDRIVE specs are invoked, either implicitly or directly by the SPDN and/or DPDN parameter (see PDRIVE command example 3, section 2.37 for the exact PDRIVE specification).

A file need not previously exist on a TRSDOS Model III diskette in order for it to be copied. NEWDOS/80 will allocate the proper directory entry and diskette space.

Any of COPY formats 1, 2, 3, 4 or 6 may be used to copy files to or from TRSDOS Model III diskettes. Remember, FMT must not be specified. If format 6 is used and one of the source or destination is a TRSDOS Model III diskette, then files marked as SYSTEM files (FPDE 1st byte, bit 6 = 1) are NOT copied.

Files copied between NEWDOS/80 and TRSDOS Model III are always readable though not necessarily usable on the receiving system.

COPY

Examples of COPY:

1. COPY XXX:1 YYY:1 In this format 1 COPY, file XXX on the diskette already mounted on drive one is copied as file YYY on that same diskette.
2. COPY,AAA,BBB:2 In this format 1 COPY, the currently mounted diskettes are searched for the file AAA. If found, it is copied as file BBB to the diskette already mounted in drive 2.
3. .COPY SUPERZAP/CMD:Ø :3 In this format 1 COPY, the file named SUPERZAP/CMD is copied from diskette already mounted in drive Ø to the diskette already mounted in drive 3. Since the file name and name extension are the same for both files, they were dropped from the second file-spec.
4. COPY XXX:1 2 SPDN=9 In this format 1 COPY, SPDN=9 causes, for the duration of the COPY only, all source file I/O to assume that drive 1 has the characteristics specified for drive 9 in the PDRIVE specifications. If we assume that the PDRIVE drive 9 specifications were those for a Model III TRSDOS diskette (see PDRIVE example 3, section 2.37), this COPY will copy file XXX from the TRSDOS Model III diskette already mounted on drive 1 to the NEWDOS/8Ø diskette already mounted on drive 2.
5. COPY \$XXX:1,YYY:Ø In this format 2 COPY, the destination diskette to contain file YYY is not the same diskette as was mounted on drive Ø when the COPY command was initiated. DOS will ask for the mount of the destination and the system diskettes as it needs them.
6. COPY,\$XXX:Ø YYY:1 In this format 2 COPY, the source diskette containing file XXX is not the same diskette as was mounted on drive Ø when the COPY command was initiated. DOS will ask for the mount of the source and system diskettes as it needs them.
7. COPY 1 XXX YYY/DAT In this format 3 COPY, the diskette containing file XXX is not the same diskette as the one to contain file YYY/DAT yet both the source and destination diskettes are to use drive 1. DOS will ask for the mount of the source and destination diskettes as it needs them. Note that, as required for format 3 and 4, neither filespec contains a drive number.
8. COPY Ø XXX/DAT /DAT In this format 3 COPY, file XXX/DAT on one diskette is to be copied as file XXX/DAT on another. Both diskettes are to be mounted on drive Ø, and DOS will ask for them as needed. Since drive Ø is used and this is format 3 rather than format 4, both the source and destination diskettes must contain NEWDOS/8Ø systems identical to that mounted on drive Ø when the COPY command was initiated.
9. COPY Ø \$XXX/DAT /DAT This format 4 COPY accomplishes essentially the same thing as the previous example. The difference is that DOS assumes that neither the source nor the destination diskette contains the proper NEWDOS/8Ø system; so DOS will ask for the mount of the system, source and destination diskettes as it needs them.

10. COPY 0 \$XXX XXX SPDN=9 This format 4 COPY accomplishes the same thing as in example 4 above excepting that only drive 0 is used. For the duration of this COPY, drive 0 uses two sets of PDRIVE specifications. The standard drive 0 specifications are used for the system and destination diskette I/Os, and the system diskette's PDRIVE's drive 9 specifications are used for the source diskette I/Os. Note, in this example, the second filespec was not foreshortened as there was nothing to foreshorten.

11. COPY 0 1 06/01/80 FMT This format 5 COPY is an example of one of the simplest and most commonly used forms of the full diskette COPY. This COPY copies one diskette to another using drive 0 as the source drive and drive 1 as the destination drive. Default track counts for the associated drives are used as diskette track counts. Both drives, other than possibly having different track counts (destination must be greater than or equal to source), have the same characteristics. The operator will be prompted for diskette mounts and error choices, if errors occur. Default parameter Y is in effect, indicating the operator does not care if the destination diskette previously contained data or not. The destination diskette will be formatted before the entire source diskette is copied to it, and it will receive the source diskette's name and password. Its date will be set to 06/01/80. If the destination diskette is to have more tracks than the source, they will be formatted and properly accounted for in the directory such that the destination diskette will be ready for use.

12. COPY 0 1,,NFMT This format 4 COPY is an example of another form of the simplest and most common full diskette copy. The only difference between this example and the one above is (1) the destination diskette is assumed already formatted, and (2) the current system date will become the destination diskette's date.

13. COPY,0,0,06/01/80,NFMT,USD,KDN,ODN=WATCHDOG,SN=GOODDATA This format 5 COPY is somewhat the same as the previous example except (1) this is a single drive, two diskette copy, (2) a prompt will be given if the source diskette does not have the name specified, (3) a prompt will be given if the destination diskette does not have the name specified, (4) the destination diskette will retain its old name, (5) it will receive its date from the source diskette. Being a single drive, two diskette copy, more mount prompts will be necessary than for a two drive COPY. Also, because of the large number of diskette mounts that would be involved, this single drive COPY cannot be executed via DOS-CALL (i.e., from BASIC).

14. COPY 0,1,,FMT,CBF This format 6 COPY is an example of one of the simplest and most commonly used forms of multiple file COPY. The destination diskette (to be mounted on drive 1) is to be formatted, and it receives its name and password from the source diskette (to be mounted on drive 0) and its date from the system date. Next, all of the source diskette's files, excepting BOOT/SYS and DIR/SYS, are copied to the destination diskette.

15. COPY 0,1,,NFMT,CBF This format 6 COPY is an example of another of the simplest and mostly commonly used forms of multiple file COPY. The differences between this and example 14 are (1) the destination diskette is not to be formatted, (2) its name, password and date are not changed, and (3) any source diskette system files (other than BOOT and DIR) that did not already exist on the destination diskette are not copied.

COPY - CREATE

16. COPY 0 1,,NFMT,CBF,USR This format 6 COPY is similar to the previous example except that system and invisible files are not copied.
17. COPY,0,1,,NFMT,CBF,USR,UPD This format 6 COPY is similar to the previous example except that the only source files copied are those marked as updated as well as not being either a system or an invisible file. In this manner, only the files changed since the last backup are backed up now. Remember, COPY does not clear the updated flags on the source diskette; use DOS commands PROT or ATTRIB to do this.
18. COPY,2,3=60,06/01/80,FMT,NDMW,CBF,DDSL=29,DDGA=4
During this format 6 COPY no diskette mount prompts or error choices are to be displayed; the system is to assume the diskettes are already properly mounted. The destination diskette is to be formatted with 60 tracks. The directory will start on lump 29, and will be allocated 4 granules. All source diskette files, except BOOT/SYS and DIR/SYS, will be copied to the destination diskette.
19. COPY 2 3 06/01/80,CBF,CFWO,NFMT
For this format 6 COPY, the destination diskette is assumed previously properly formatted and may contain existing files. For each source diskette file, excluding BOOT/SYS and DIR/SYS, the operator will be asked if the file is to be copied to the destination diskette. When all queries are done, the selected files are copied, excepting that system files that did not previously exist on the destination diskette are not copied. If the file already existed on the destination diskette, the file's old data on the destination diskette is lost.

2.15. CREATE Pre-allocate a disk file.

The CREATE command allows a user to create a file and optionally to write to the file a specified number of null records, thereby allocating the file's space as contiguously as possible, given the layout of the free space on the diskette.

There are times when a user program expects one or more of the files it uses to already exist, even though the files may not have any usable data in them; therefore, the user must create the file prior to the program's first use. Also, there are times when the efficiency of a program is reduced if a file's diskette space is scattered all over the diskette; to avoid this, the user should preallocate the needed file space to reduce this scattering.

```
CREATE,filespec1[,LRL=lnl][,REC=count1][,ASE=yn][,ASC=yn]
```

The CREATE DOS command creates new file filespec1 or alters the state of existing file filespec1.

LRL=lnl specifies the length of each record of the file. lnl must be a value between 1 and 256; the default value is 256.

REC=count1 specifies the number of records to be initially assigned to a file.

ASE=yn This parameter indicates whether, subsequent to the CREATE command, DOS may automatically allocate more diskette space to this file as necessary. ASE=Y allows this; ASE=N disallows this. The default is ASE=Y.

ASC=yn This parameter indicates whether the DOS close function will be allowed to automatically deallocate excess diskette space. ASC=Y allows this; ASC=N disallows it. The default is ASC=Y.

Enough diskette space is allocated to the file to provide for count1 records each of length lnl. lnl records of all zeroes are then written to the file, establishing the file EOF at the end of those records. If ASE=N is specified, the file is inhibited against further diskette space allocation, and if ASC=N the file is inhibited against automatic deallocation of excess diskette space.

CREATE command examples:

1. CREATE,XXX:1,LRL=30,REC=2000 File XXX is created, if it did not already exist, on the drive 1 diskette. The record length is 30 and 2000 of these records, containing all 00H bytes, are written to the file. The EOF is left at 60000. Subsequent DOS automatic space allocation and deallocation for this file are allowed.
2. CREATE,YYY:2,200,ASE=N,ASC=N File YYY is created, if it did not already exist, on the drive 2 diskette. The record length is 256 and 200 of these records, containing all 00H bytes, are written to the file. The EOF is left at 51200. Subsequent DOS automatic space allocation and deallocation for this file are not allowed.
3. CREATE,ZZZ:0 File ZZZ is created, if it did not already exist, on the drive 0 diskette. The record length is 256, and the EOF is set to 0. Subsequent DOS automatic space allocation and deallocation for this file are allowed.

2.16. DATE Set computer's current date.

DATE[,mm/dd/yy]

If no parameters are specified, the DATE command displays the current system date in mm/dd/yy format.

If mm/dd/yy is specified, the date mm/dd/yy becomes the system date and is set into the real time clock. mm is the month (value 01 - 12). dd is the day (value 01 - 31). yy is the year (value 00 - 99). No check is made on the validity of the 3 values except to limit them to 2 decimal digits. As the clock reaches 24:00:00, it is reset to 00:00:00 and the date's day within month value is incremented. For the Model I, no adjustment is made for end of month or end of year. For the Model III, end of month and end of year adjustments are done by the ROM.

At reset time, the date is set according to SYSTEM options AY or AZ.

DATE command examples:

1. DATE display the system date.
2. DATE,08/01/81 set system date to August 1, 1981.

2.17. **DEBUG** enable or disable the DEBUG facility.

DEBUG[,yn]

DEBUG or DEBUG,Y DEBUG is enabled (but not entered). This enabling causes a DEBUG entry whenever a user program (such as BASIC, SCRIPSIT, PROFILE, EDIT, etc.) is activated. The DEBUG entry occurs after the program load is completed but just before its first instruction is executed. The purpose of this pre-execution DEBUG entry is to allow the debugging programmer to change the state of a program or its initialization parameters before the program commences execution.

DEBUG,N The above enabling is disabled. At reset/power-on time, DEBUG is disabled.

This command has no effect on the operation of '123' (the simultaneous depressing of the 1, 2 and 3 keys) to enter the DEBUG facility.

Refer to the section 4.1 for the DEBUG facility specifications.

2.18. **DIR** Display a diskette's directory information.

DIR[:][dnl][,A][,S][,I][,U][,/ext][,P]

This command displays directory information for the diskette mounted on drive dnl or if dnl not specified, on the drive specified by system option AN.

The first display line contains the drive number, the diskette name, its date, the number of tracks, the number of free FDEs and the number of free granules. The values for track count and free granules are based on the current active PDRIVE specification for that drive and if those specifications are not proper, these displayed values may be in error.

The rest of the display contains file information.

If A is not specified, the files are displayed four to a line, giving for each its name and name extension, if any.

If A is specified, DIR will list one file per display line with the display line containing:

1. The file's name.
2. The file's name extension, if any.

3. The file's EOF value in xxx/yyy format where xxx is the relative sector number within the file and yyy is the relative byte number within that sector.
4. The file's logical record size (LRL) in bytes.
5. The number of logical records (RECS) in the file including any partial last record.
6. The number of granules (GRANS) allocated to the file.
7. the number of diskette space extents (EXT) allocated where that number divided by four and rounded up gives the number of directory entries used by the file.
8. 12 flags providing file information, defined as follows:

1. S = system file.
2. I = invisible file, see ATTRIB DOS command.
3. U = file updated since last time update flags cleared by PROT DOS command.
4. E = file will not be allowed to allocate more space that it already has.
5. C = excess file space beyond EOF is not automatically released during DOS close.
6. - 9. Reserved for future definition.
10. U = non-blank update password exists.
11. A = non-blank access password exists.
12. L = protection Level, see ATTRIB DOS command.

System files are not displayed unless S is specified.

Invisible files are not displayed unless I is specified.

If U is specified, only files marked as updated are displayed. Files marked as updated are those files changed via the standard DOS I/O write routine since the last time the update flags were cleared on the target diskette by the PROT or ATTRIB DOS command.

If /ext is specified, only those files having the name extension ext are displayed. ext is 0 to 3 characters. Example: DIR,1,/CMD will list all files having extension CMD such as EDTASM/CMD.

If both U and /ext are specified, then only files satisfying both conditions are listed.

When the display screen is full, DIR displays a '?' and waits for the user to respond ENTER to continue or BREAK to terminate the DIR function.

If P is specified, the directory information is sent to the printer rather than to the display. Caution, if the printer is not ready, the system will hang waiting for it.

If \$ is specified, DIR will ask for the mount of the target diskette before the listing and will ask for the remount of the system diskette before exiting. \$ should only be used when drive dnl = 0. There is no provision for changing the PDRIVE specifications internal to the DIR command.

DIR - DO - DUMP

The user must remember that if dnl is not specified, the default drive number is that specified by SYSTEM option AN which is not necessarily 0.

DIR command examples:

1. DIR 0 Display the name and name extension of all non-system, non-invisible files on the diskette currently mounted in drive 0. The files will be listed four per display line.
2. DIR 0,S,I,P Same as the previous example except that system and invisible files are also listed and that the listing is sent to the printer instead of the display.
3. DIR 1,/DAT,U Display the name and name extension of all of the current drive 1 files that are marked as updated and have name extension DAT.
4. DIR 2,A All of drive 2's non-system, non-invisible files are displayed, one file per display line. This display will usually involve more than one display page with the user stepping from one page to the next by pressing ENTER and, if desired, terminating the DIR function by pressing BREAK.
5. DIR \$0 Same as example 1 except the system will ask for the mount of the target diskette on drive 0 and when DIR is done, it will ask for the remount of the system diskette.

2.19 DO Shift to keyboard input from disk.

DO,filespec[,sectionid]

The DO command executes exactly the same as the DOS command CHAIN (see section 2.9).

2.20 DUMP Dump memory contents to disk.

DUMP,filespec[,start-addr,end-addr[,entry-addr[,reloc-addr]]]

The DUMP command writes main memory image data from main memory to the file file-spec, starting with the byte at start-addr and ending with the byte at end-addr.

Start-addr, end-addr, entry-addr and reloc-addr are each numeric values less than 65536 decimal or 10000 hex. If the value is hexadecimal it must be suffixed with a H (i.e. 8000H); otherwise the value is considered decimal. Start-addr and reloc-addr may be any value 0 - 0FFFFH.

This command operates in two modes, depending on the entry-addr value. If the entry-addr value = 65535 (0FFFFH), then an exact image of memory is dumped.

The start-addr value is stored in the file's first 2 bytes, and the rest of the file is the memory dump without any interspersed control bytes. This memory dump file may be displayed or printed via SUPERZAP's DMDB feature, thus allowing debugging to occur later or on another TRS-80 computer.

If entry-addr is less than 65535 (0FFFFH) or is not specified, then the specified area of memory is assumed to be machine executable code and is sent to the file in loader format so that it can be later read back in by the NEWDOS/80 loader, either for execution or simply for load (see LOAD command). If entry-addr is not specified, a value of 402DH (causing return to DOS READY) is used. CAUTION!! If the user attempts to run or load a file whose start-addr is less than 5200H, DOS will be clobbered.

reloc-addr specifies where the start-addr to end-addr range of bytes is to be loaded to by the LOAD command or when the program file is executed. During write of the object file, the value (reloc-addr) - (start-addr) is added to every load address placed in the object file. This value is also added to the entry-addr if entry-addr is within the start-addr to end-addr range. The actual object code is NOT altered; only the loader control information is.

If filespec1 does not specify an name extension, one is not automatically supplied as is done in TRSDOS.

DUMP command examples:

1. DUMP,PROGRAM/CMD:1,5200H,9ABCH,54EDH dumps the contents of memory from and including 5200H to and including 9ABCH to the file PROGRAM/CMD to exist on drive 1's current diskette. The dump will be in loader format with entry address equal to 54EDH. Subsequently, the file may be loaded back into memory via the DOS command:

LOAD,PROGRAM/CMD

or executed via DOS command:

PROGRAM[,parameters]

2. For this next example, assume that a user program is looping for some reason or has crashed, the personnel to debug the problem are not immediately available, and it is necessary to continue using the computer for other purposes. If a spare formatted diskette is available with sufficient free space, and if 'DFG' can activate MINI-DOS or if the computer is already at DOS READY, then issue the following command:

DUMP,TROUBLE/MEM:2,0,65535,65535

which will dump 65536 bytes of main memory, including ROM, the display, and all of RAM to file TROUBLE/MEM. The first 2 bytes of the file will contain 0000H which is the dump start address; the rest of the file is the memory contents with no interspersed control characters. Once the dump is completed, the operator should set aside the dump diskette for later use by the debugging personnel, optionally press reset, and go on with other tasks. At some later time, debugging personnel can inspect the problem using SUPERZAP's DMDB feature to display or print the contents of file TROUBLE/MEM as if it were actually in memory at the current time. The

DUMP - ERROR - FORMAT

debugger must remember that the DOS areas 4000H - 51FFH were altered by DOS actions, including DUMP, after the error occurred and before the dump actually occurred.

2.21. ERROR Display DOS error message.

ERROR,xx

displays the DOS error msg associated with the error number xx where xx is an integer between 0 and 63. Example:

ERROR,24 will display 'FILE NOT IN DIRECTORY'.

2.22 FORMAT Format a diskette for use with the NEWDOS/80 system.

Diskettes as they are received from the manufacturer cannot be used with NEWDOS/80. They must first be magnetically divided into tracks with each track divided into sectors of 256 bytes each. Between 15 and 30 percent of the diskette's bytes are used as format control information and are not available to contain user data.

The DOS command FORMAT does this diskette formatting, setting up the tracks and sectors properly and building the two system files, BOOT/SYS and DIR/SYS, required on every diskette. When done, the diskette is ready to be used as a data diskette with NEWDOS/80.

Formatting can also be done as part of the COPY command, formats 5 and 6 (see section 2.14).

```
FORMAT,dn2[=tc2],name2,mm/dd/yy,password3[,N][,Y][,NDMW]
      [,DDND][,ODN=namel][,KDN][,DDSL=lnl][,DDGA=gcl][,DPDN=dn4]
      [,PFST=tn3[,PFTC=tc3]]
```

FORMAT cannot be executed under MINI-DOS.

In NEWDOS/80 version 2, a track's sectors are read immediately after the track is formatted and before the disk arm is stepped to the next track. Then, after all tracks are formatted, if SYSTEM option BM = Y, the entire diskette is read during the VERIFYING phase. However, if BM=N, this verifying phase is skipped. The user can decide whether or not the verify-at-track format is sufficient and set option BM accordingly.

FORMAT does not allow the user to specify tracks to be locked out, and when an unverifiable sector is encountered, the associated track's lockout byte is not set to FF to indicate lockout. The lockout table is in the standard diskette directory only for compatibility with TRSDOS; NEWDOS/80 does not use it. Remember, NEWDOS/80 does not account for tracks in the directory, it accounts for lumps which can span tracks. NEWDOS/80 operates under the philosophy, however wrong, that if a diskette cannot be fully formatted it should be discarded.

FORMAT requires all parameters be specified in the command. It does not prompt the user for any.

dn2 is the number of the destination drive to be used during format. Name2 is the name to be assigned to the diskette unless KDN is specified to retain the old name, in which case name2 must still be specified but will be ignored. mm/dd/yy is the date to be assigned to the diskette unless KDD is specified as the diskette date, in which case mm/dd/yy must still be specified but will be ignored. Password3 is the password to be assigned to the diskette. Password3 must conform to the rules for passwords.

Null parameters may be used to invoke default values for diskette name, date and password, using the name NOTNAMED, the system date and the password PASSWORD respectively. Any combination of the 3 null values may be used but where used the null parameters must be delimited by commas, not spaces. See examples 2, 3 and 4 below.

Since FORMAT and COPY share the same NEWDOS/80 code wherever possible, the specifications for the optional parameters are nearly the same as those specified for COPY, formats 5 and 6, the main difference being that only a format is done rather than both a format and a copy. The reader should read the sections for COPY, formats 5 and 6 (see section 2.14) to basically understand FORMAT's optional parameters. Only the differences and two additional options will be given here.

N is the default if neither it nor any of its mutually exclusive keywords are specified.

If =tc2 specified, the diskette will be formatted with tc2 number of tracks; otherwise the diskette will be formatted with the default number of tracks for that drive (see PDRIVE command). If =tc2 value is greater than the number of tracks the drive can handle, format will probably hang trying to step to the non-existent track.

PFST=tn3 and **PFTC=tc3** optional parameters are added to allow the formatting of a range of tracks rather than the entire diskette. If PFST is specified, =tc2 must not be specified, and if PFTC is specified, PFST must be specified. PFST means Partial Format Starting Track, and tn3 specifies the first track to format. If PDRIVE TI flags J or K are applicable for drive dn1, DOS will add one to tn3. PFTC means Partial Format Track Count, and tc3 specifies the number of consecutive ascendingly numbered tracks to format. If PFTC is not specified and PFST is specified, tc3 is assumed equal to 1. After tc3 number of tracks have been formatted and if SYSTEM option BM = Y, the entire diskette will be verified. If this full diskette verify is a problem, cancel the format after verify starts (by pressing up-arrow); remember, each track's sectors were already verified once immediately after the track was formatted.

FORMAT command examples:

1. `FORMAT,0,AAA0,08/01/81,PSWD,Y` The diskette to be mounted, at DOS's request, on drive 0 will be formatted according to the PDRIVE specifications current for that drive. DOS does not care whether the format diskette previously contained data or not. The diskette is named AAA0, dated August 1, 1981, and receives PSWD as its master password.

2. `FORMAT,0,,,Y` This example is identical to the previous example except that default values are used for the diskette name, date and password. The diskette is named NOTNAMED, is dated with the current system date and is assigned PASSWORD as its password.
3. `FORMAT,1,XXX,,PSWD,N,NDMW,DPDN=4,DDSL=40,DDGA=6` The diskette already mounted on drive 1 must not contain recognizable data. It is formatted according to the system diskette's PDRIVE drive 4 specifications (and not according to the existing drive 1 specifications). It is assigned name XXX and password PSWD; its date is taken from the current system date. The directory starts at the beginning of lump 40 and consists of 6 granules (allows for a maximum of 222 files). Due to NDMW, DOS does not ask for the mount of the format diskette nor does it allow error retry.
4. `FORMAT,1,,,Y,PFST=22,PFTC=2` Suppose a power failure destroyed the format of tracks 22 and 23 on a diskette. Using SUPERZAP, you have verified that indeed SECTOR NOT FOUND error occurs on at least one sector on each of those tracks and, using the CDS or SCOPY functions of SUPERZAP, you have saved in free sectors elsewhere, either on this diskette or another, the readable sectors of those two tracks. Executing this FORMAT command will cause only those two tracks to be reformatted; the rest of the information on the diskette is not affected. When done, you can now move back the saved sectors and recreate the ones that were not savable.

2.23. FORMS (Model III only) Set printer parameters.

`FORMS[,WIDTH=xxx][,LINES=yyy]`

The FORMS command optionally changes some printer parameters and always lists out the printer parameters.

WIDTH=xxx specifies the number of characters per line where xxx must be a value between 9 and 255. If WIDTH is not specified, the number of characters per line is not changed.

LINES=xxx specifies the number of lines per page, and must be a value between 1 and 254, where 254 indicates no limit on the lines per page. If LINES is not specified, the lines per page value is not changed.

FORMS command examples:

1. `FORMS,WIDTH=80,LINES=60` character per line is set to 80 and lines per page to 60.
2. `FORMS,WIDTH=255,LINES=254` Unlimited characters per line and lines per page.
3. `FORMS` Displays current values for characters per line and lines per page.

2.24. FREE Display number of free granules and free FDEs for each diskette currently mounted.

FREE[,P]

For each drive with a diskette mounted, FREE will display the drive number, the diskette name, the diskette date, the number of tracks for the diskette, the number of free FDEs and the number of free granules.

If P is specified, the information will be sent to the printer instead of the display.

FREE command examples:

1. FREE For each diskette currently mount the number of free granules and free directory entries is listed on the display.
2. FREE,P Same as above except the listing is sent to the printer.

2.25. HIMEM Set DOS's high memory value.

HIMEM[,addr1]

DOS maintains a high memory address in the two bytes at Model I location 4049H (Model III location 4411H). This high memory value is used by COPY, BASIC, EDTASM, DISASSEM and LMOFFSET as the upper limit of the memory they can use. User programs should also use this 2 byte HIMEM value as their upper limits. Caution! The loader does not use HIMEM as its upper limit during program load.

If no parameters are specified, the HIMEM command displays in hexadecimal the current high memory value.

If addr1 is specified, the DOS high memory address is set to addr1 which must be an integer between 28672 and 65535 decimal (7000H - 0FFFFH hexadecimal).

HIMEM command examples:

1. HIMEM Displays the current DOS high memory address.
2. HIMEM,49000 Set DOS's high memory value to 49000 (0BF68H).

2.26. JKL Send the current contents of the display to the printer.

JKL has no parameters. This command uses the same routine used by the 'JKL' triple key function (see section 4.5). JKL simply dumps the display contents to the printer. If system option AK=Y, hex codes $\geq 80H$ (which includes the graphics) will be transmitted unchanged; otherwise a period will be substituted for them. Hex codes $< 20H$ will be displayed as periods. Pressing BREAK during JKL print will terminate the JKL function.

JKL - KILL

JKL's main use will be either via CMD"JKL" from BASIC or via DOS-CALL from a user program.

2.27. KILL delete a file.

This command deletes a file from a diskette. The file is no longer accessible by normal methods and is no longer known to DOS.

KILL,filespec1

The file filespec1 is deleted from the current diskette mounted on the specified drive. If a drive number was not specified, then all mounted diskettes are searched, starting with the diskette on drive 0, and the delete is done on the 1st file found having the specified name and name extension.

KILL action is as follows:

1. If the file was allocated file space on the diskette, the space is released, and becomes available for subsequent assignment to other files. The file's data, if any, on the diskette is not altered by the KILL. This data, though no longer accessible, is not written over until the associated file space is reassigned to another file and those sectors actually written to.
2. The file's FPDE and any owned FXDEs are freed by zeroing bit 4 of the 1st byte of each and by zeroing the associated HIT sector byte for each. Except for that bit 4, none of the associated FPDE and FXDEs are altered by normal DOS operation until that FDE is reassigned to another file by DOS.

If the user has inadvertently killed a file that shouldn't have been, since neither the associated FDE's or the diskette space used by the file is changed by DOS until DOS has a need to, it is possible to reconstruct the FPDE and FXDEs and reallocate the space. To do this, you must be extremely familiar with the workings of the directories; do not call Apparatus as this is a major undertaking and not something that can be quickly taught. If you don't know how to do it, forget it!

If you have more than a few files to delete at one time from a diskette, use the PURGE command.

KILL command examples:

1. KILL XXX/BAS:1 The file XXX/BAS on the diskette mounted on drive 1 is killed.
2. KILL YYY Starting with drive 0, mounted diskettes are searched until file YYY is found on one of them. That file is then killed. If other mounted diskettes also contain a YYY file, the other YYY files are not killed.

2.28. LC Set keyboard a - z toggle switch to the specified state.

LC[,yn]

LC or LC,Y sets the keyboard lower case a - z toggle switch to accept a - z without change.

LC,N sets the keyboard lower case a - z toggle switch to change lower case a - z to upper case A - Z.

For the Model I, the LC command has no effect unless the lower case driver is active (see LCDVR command).

2.29. LCDVR (Model I only) Lower case driver.

LCDVR[,x[,s]]

In NEWDOS/80 version 1, the lower case driver that processed keyboard lower case alphabetic characters and which sent lower case displayed characters to the display was a separate program that executed from high memory. In version 2, the lower case driver is an integral part of the Model I NEWDOS/80.

If x = Y, the lower case driver routine is activated, and if x = N, the routine is deactivated. When the lower case driver routine is active:

1. Keyboard input a - z characters are processed according to the a - z toggle switch.
2. ASCII codes 96 - 127 (60H - 7FH) are displayed as their proper characters and are not changed to 64 - 95 (40H - 5FH) by the ROM display routine.

The second parameter is meaningful only when x = Y, performs the same as the first parameter of LC command, initially setting the a - z toggle switch to accept a - z (if s = Y) or convert a - z to A - Z (if s = N).

Once the lower case driver is activated, pressing shift 0 will switch the driver back and forth between accepting lower case letters and converting lower case letters to upper case. Further, DOS command LC may be used to explicitly set one or the other of those states.

To use the lower case driver, NEWDOS/80's keyboard and display intercept routines must be enabled. Other routines (excluding ROUTE) that disable these NEWDOS/80 functions will also disable the lower case driver (one example is using the circular buffer in the spooler).

If no parameters are specified, the command is assumed to be LCDVR,Y,N.

This lower case driver operates somewhat differently than the LCDVR program supplied with Version 1. In Version 1, if lower case a - z was being converted to upper case A - Z, then upper case A - Z was also being converted to lower case a - z. Version 2 does not convert upper case A - Z to lower case a - z; instead a true capital letter lock is done.

LCDVR command examples:

1. LCDVR The lower case driver routine is activated and the lower case switch is set to convert lower case a - z to upper case A - Z.
2. LCDVR,Y,Y The lower case driver routine is activated, and the lower case switch is set to accept lower case a - z without modification.
3. LCDVR,N The lower case driver routine is deactivated.

2.30. LIB Display NEWDOS/80 library commands.

LIB requires no parameters. It displays the library commands of NEWDOS/80. Commands FORMAT, COPY and APPEND execute in memory 5200H and up, and, along with CHAIN, cannot be executed in MINI-DOS. The other commands execute from the DOS overlay area, 4D00H-51FFH, and, except for CHAIN, can be executed under MINI-DOS.

2.31. LIST List a text file on the display.

LIST,file-spec[,start-line[,line-count]]

This command sends the contents of file file-spec to the display. Though file file-spec need not be a text file, if it is not, the resulting display will not be very meaningful. Examples of text files are BASIC programs saved with the A option, BASIC files written using PRINT, assembler, FORTRAN and COBOL source text files, SCRIPSIT files saved with the A option and Electric Pencil files. To list a non-text file, use SUPERZAP.

No check is made on the character representations except to modulate characters whose hexadecimal values are between 80H and FFH into the range 00H to 7FH and to replace with a period all characters whose hexadecimal value is less than 20H or greater than the high ASCII character value specified by the SYSTEM option AX.

If start-line (decimal value 1 - 65535) is specified, listing will start with that line where a line is considered to end with the ENTER or EOL character 0DH.

If line-count is specified, then the number of lines displayed is limited to either line-count or the number of lines in the file from the start point, whichever is less. If line-count is specified, start-line must also be specified.

Pressing right arrow will cause a display pause when hex char 0DH is encountered or after 256 bytes have been displayed, whichever comes first. Pressing ENTER will continue the displaying. Pressing up-arrow will terminate LIST.

Aside from just listing a file, LIST is useful where text files maintain a

date/time stamp near the beginning. If the user has multiple copies of a text file, it may be necessary to look at the file beginning to determine which copy is the most recent.

LIST command examples:

1. LIST,BASEPROG/BAS displays the entire contents of file BASEPROG/BAS.
2. LIST,XXX,1,6 displays the first 6 lines of file XXX.
3. LIST,YYY:1,200 displays the contents of file YYY from the 200th line to the end of the file.

2.32. LOAD Load a Z-80 machine language file into RAM.

LOAD,filespec1

This command loads the Z-80 machine language file filespec1 into RAM, and stores its entry address into the two bytes at 4403H (17411 decimal). The file must be in proper loader format, such as created by DUMP or EDTASM. The load proceeds using control data from the file. If the file loads over any part of the resident DOS (4000H - 4CFFH) or its overlay area (4D00H - 51FFH), serious and maybe file damaging trouble will occur; with luck, the system will hang.

LOAD is used when a program or data is to be loaded into RAM for later use by other programs. An example is loading programs which will be invoked via BASIC's USR function. Remember, the entry address is stored in the two bytes at 4403H (17411 decimal); this is not done in TRSDOS.

LOAD command examples:

1. LOAD,OVERLAY/OBJ:1 The object code module OVERLAY/OBJ is loaded into main memory from the diskette mounted on drive 1. The load control information within file OVERLAY/OBJ determines what is to be loaded and where in main memory it is to be loaded.
2. Suppose that BASIC does not use all of high memory and that a BASIC program wishes to load the program USR3PGM/OBJ into high memory and later execute it as the BASIC USR3 function. Executing the BASIC statements:

```
CMD"LOAD,USR3PGM/OBJ"
DEFUSR3 = (PEEK(17411) + 256 * PEEK(17412) - 65536
```

will set this up.

2.33. MDBORT Terminate MINI-DOS and go to DOS READY.

MDBORT has no parameters. It should only be executed when NEWDOS/80 is in MINI-DOS state. MINI-DOS state is terminated, the pre-MINI-DOS state purged and the system goes to DOS READY.

The purpose of MDBORT is to provide for the situation where the operator does not want to continue the main program which was interrupted by the simultaneous depression of the D, F and G keys (which invoked MINI-DOS).

2.34. MDCOPY Copy a file while under MINI-DOS.

MDCOPY,filespec1[,TO],filespec2

The regular COPY command cannot be executed under MINI-DOS. MDCOPY gives the user a restricted and quite slow form of file copy which does execute under MINI-DOS.

MDCOPY copies the contents of file filespec1 to the new or existing file filespec2. File filespec1 is not altered, and the previous contents of file filespec2, if any, are lost. Filespec2 may not be foreshortened as is allowed for COPY.

MDCOPY command example:

MDCOPY XXX/DAT:0 YYY/DAT:1

The contents of file XXX/DAT on the diskette currently mounted on drive 0 is copied as file YYY/DAT onto the diskette currently mounted on drive 1.

2.35. MDRET Exit from MINI-DOS and return to main program.

MDRET has no parameters. The system exits MINI-DOS state and continues the main program at the point where it was interrupted by the invocation of MINI-DOS (simultaneous depression of the D, F and G keys). If the cursor was displayed before 'DFG', it will be redisplayed. If the 'DFG' interruption occurred while the key input buffer contained a partial input record, that partial record is still there even though it is no longer displayed. The user should continue keying exactly where he/she left off.

If the invocation of MINI-DOS occurred during the timer interrupt rather than the key intercept, one or more of D, F or G may appear as spurious input keys after MDRET is executed. The user should backspace over them. The user and DOS have no control over these spurious input chars; therefore DFG should not be pressed when a program is in text overwrite mode, such as SCRIPSIT or Electric Pencil; instead go into command mode where the spurious characters can be backspaced over without damage to the text.

2.36. PAUSE Display message and pause waiting on ENTER.

PAUSE,msg

The message msg is not redisplayed if the PAUSE command itself was displayed. If the PAUSE command was not displayed, as occurs if it is executed under DOS-CALL, the message msg is displayed. In any event, the message PRESS "ENTER" WHEN READY TO CONTINUE is displayed on the next line. DOS then waits for the user to press the ENTER key. The PAUSE command is one of the four ways of causing a pause in chaining, and can also be used when a series of commands in main memory are being executed by a series of DOS-CALLs.

PAUSE command example:

PAUSE,MOUNT DISKETTE LABELED "PRIMARY" ON DRIVE 1.

This message will appear on the display and will be followed on the next display line by the message PRESS "ENTER" WHEN READY TO CONTINUE. DOS waits for the user to press ENTER which presumably he/she will do after the proper diskette has been mounted in drive 1. DOS doesn't check to see if the user has done what was requested; all DOS does is wait for the ENTER.

2.37. PDRIVE Assign default attributes to a physical drive.

```
PDRIVE[,password1:|dn1,[dn2[=dn3]][,TI=type1][,TD=type2][,TC=tc1]
[,SPT=sc1][,TSR=rc1][,GPL=gc2][,DDSL=ln1][,DDGA=gc1][,A]
```

NEWDOS/80 has limited capabilities for operating with a mixture of 5 inch disk drives and to a lesser extent 8 inch disk drives. PDRIVE is the command method used to inform NEWDOS/80 of a particular physical drive's characteristics.

Each PDRIVE command lists the resulting specifications for 10 drives even though the actual number of drives eligible for I/O is limited by the SYSTEM option AL and in no case exceeds 4. Those drives within the range of SYSTEM option AL are flagged on the PDRIVE display by an asterisk suffixed to the drive number. The specifications for the 10 drives is maintained on the system diskette mounted on drive dn1. For efficiency reasons, DOS normally uses drive specifications from a table it has in main memory. This main memory PDRIVE table contains specifications for 1 to 4 drives, depending upon the SYSTEM option AL value, and is automatically reloaded from the drive 0 diskette at power on and reset if and only if the specifications for all 10 drives are error free (otherwise the reset hangs). This table is also immediately reloaded by a PDRIVE command specifying the A parameter (see below).

Drive dn1 is the drive containing the system diskette whose control information (in the 3rd sector) is being updated. Drive dn2 indicates which physical drive of the 10 represented in the control information sector on drive dn1 is having its control information updated.

For example, if the PDRIVE command is PDRIVE,1,4,TC=80 then the diskette on drive 1 is read to obtain the PDRIVE control information and is updated

PDRIVE

to contain the new drive 4 specification. Drive 1's PDRIVE control information contains the specifications for ten drives, dn2 values 0 through 9, and it is the fifth drive's information (for dn2 = 4) that is changed. The specifications for the other nine drives are not changed.

If passwords are enabled, then password1 must be specified and be the master password for the diskette on drive dn1. Otherwise password1 may be left out of the command.

Control data is changed only for the parameters specified; parameters not specified are not changed. If any errors are displayed, the dn1 diskette must NOT be used as the system diskette during a reset/power-on until the errors are corrected.

PDRIVE,dn1 will list the 10 PDRIVE specifications contained in the control data on the system diskette mounted on drive dn1.

dn2 must be specified if any other optional parameters except A are specified. If dn2 is specified, it must be the 1st parameter following dn1.

dn2=dn3 causes drive dn2 to assume the PDRIVE specifications of drive dn3. This is done before any other optional parameters are interpreted.

TI=typel specifies the type of disk drive interface. typel consists of one or more alphabetic letter flags chosen from the list below. For the Model I, one and only one of flags A, B, C or E must be chosen. For the Model III, one and only one of flags A or D must be chosen. The other flags are optional depending upon the interface. Certain flags are inter-drive mutually exclusive meaning that for a given drive dn1, if one dn2 drive specifies a flag that is interdrive mutually exclusive with another flag, then another dn2 drive may not specify the excluded flag. For now, flags B, C and E are interdrive mutually exclusive for the Model I.

Flag A means the standard disk interface is to be used for diskette I/O for this drive. For the Model I this interface supports drive types A and C. For the Model III this interface supports drive types A, C, E and G.

Flag B (Model I only) means that an OMIKRON mapper type interface is installed and is to be used for I/O for this drive. This interface supports drive types A, B, C and D.

Flag C (Model I only) means that a PERCOM doubler type interface is installed and is to be used for I/O for this drive. This interface supports drive types A, C, E and G.

Flag D (Model III only) means that an Apparat disk controller type interface is installed and is to be used for I/O for this drive. This interface supports drive types A through H (drive types F and H require a Model III speed up modification).

Flag E (Model I only) means that an LNW type interface is installed and is to be used for I/O for this drive. This interface supports drive types A through H.

Flag **H** means head settle delay is to be done whenever DOS changes from another drive to this drive. For Model I and Model III 5 inch drives, the heads for all 5 inch drives are loaded when the motors go on, and this extra time delay is NOT needed. Flag **H** is needed for 8" drives.

Flag **I** means the lowest numbered sector on each track is sector 1. This is the normal state for Model III TRSDOS diskettes. If flag **I** is not specified, the lowest numbered sector on each track is assumed to be 0, which is the state for the Model I and for NEWDOS/80 on the Model III.

Flag **J** means the track numbers start from 1. If flag **J** is not specified, track numbers are assumed to start from 0, which is the standard state for the Model I and the Model III.

Flag **K** means track 0 is formatted (or is to be formatted) in density opposite to that of the diskette's other tracks. This makes track 0 unavailable for normal I/O. Flag **J** is implicitly set by flag **K**. The purpose of formatting track 0 in opposite density is to allow a double density (Model I) or single density (Model III) SYSTEM diskette to be booted up. The Model I ROM must be able to read the boot sector in single density, and the Model III ROM must be able to read the boot sector in double density. Setting flag **K** causes FORMAT and COPY with format to format track 0 in the opposite density and to store the required boot sector onto that track for the ROMs to use. With flag **K** set, normal DOS I/O to track 0 actually goes to track 1, 1 to 2, etc. Flag **K** must be specified for a drive that is to read a double density diskette created by the PERCOM type doubler interface under NEWDOS/80 version 1 or any other DOS except NEWDOS/80 version 2 or higher. For NEWDOS/80 version 2 Model I, double density data diskettes do not have to reserve track 0 for opposite density if those diskettes will never be used on a drive 0 whose PDRIVE specifies double density. Flag **K** must NOT be specified for standard Model III diskettes, unless for some reason the user wants a single density system diskette on the Model III or is making a double density diskette to be read on the Model I that does not have NEWDOS/80 version 2. When flag **K** is specified, then TC must specify one less track than would be specified if flag were not specified. Further, due to the differing sequence in which consecutive sectors are stored on the diskettes, double sided, double density diskettes created under the patched NEWDOS/80 version 1 are not readable under NEWDOS/80 version 2. To transfer files on those diskettes to Version 2, they must first be moved (using Version 1) to either single sided (either density) or double sided, single density diskettes.

Flag **L** means two step pulses between tracks. This allows a 35 or 40 track diskette to be read on an 80 track drive. Writing can also be done in this manner, but the 35 or 40 track drives have trouble reading some of the sectors so writing is not recommended.

Flag **M** means the diskettes are standard TRSDOS Model III diskettes. Flag **M** implies flag **I**. The COPY DOS command is the only function within NEWDOS/80 that will honor or even notice a TRSDOS Model III diskette as distinct from a NEWDOS/80 diskette, and even this will not occur unless flag **M** is set.

Flags **F** through **G** and **N** through **Z** are reserved for future definition.

TD is the Type of Drive specification. The definitions are:

1. TD=A 5 inch, single density, single sided drive.
2. TD=B 8 inch, single density, single sided drive.
3. TD=C 5 inch, single density, double sided drive.
4. TD=D 8 inch, single density, double sided drive.
5. TD=E 5 inch, double density, single sided drive.
6. TD=F 8 inch, double density, single sided drive.
7. TD=G 5 inch, double density, double sided drive.
8. TD=H 8 inch, double density, double sided drive.

If a CPU speed up module is installed in the computer that reverts to normal CPU during disk I/O, this reversion must not slow the CPU speed to less than the original rated CPU speed for that model. NEWDOS/80's disk I/O loops, especially for the Model I for drive types B, D, E and G, cannot tolerate any reduced CPU speed below the original speed. In limited testing and with SYSTEM option BJ properly set, NEWDOS/80 Version 2 has run disk I/O successfully without the need to turn off the CPU speed; however, Apparat does not guarantee such performance.

TD=F and TD=H require a CPU speed up module installed in the computer which at least doubles the CPU's speed during disk I/O.

For drive types C, D, G and H, the current NEWDOS/80 interfaces (TI flags A, B, C, D or E) consider a double sided diskette as a single volume (i.e., only one directory) with each track having its lower numbered sectors on the first side and the higher numbered sectors on the second side. Pin 32 is used to select the 2nd side (special cables required), and any drive on the cable that shunts pin 32 over as a drive 3 select must have that shunt wire cut to prevent that drive from being selected when another drive's 2nd side is being selected. Double sided, double density 40 and 80 track drives have been used on the Models I and III under NEWDOS/80 Version 2.

One of the reasons Apparat never supported double density in Version I was that most drives did not work reliably in double density. Whether this was the fault of the drives, the diskettes, the data separator or the controller was never really ascertained. Over the last nine months things have improved somewhat, but double density is still not as reliable as single density and probably never will be. Apparat was informed that the two byte pattern 6DB6 is a much better "worst case" double density pattern than the E5's used in single density, and indeed the 6DB6 pattern is such. In fact, it is such a good "worst case" condition that a good percentage of certified double sided, double density diskettes will fail format. To many users, this will prove intolerable and they will want to apply the ZAP that goes back to the E5 pattern, if it is not already applied. However, using the E5 pattern in double density means that the user will increase the probability that a diskette that formats successfully will at some future time fail.

TC=tcl specifies the number of tracks on the disk, excluding track 0 if TI flag K is set. If flag K is not set, TC=35 for a 35 track drive, TC=40 for a 40 track, etc. If flag K is set, then TC=34 for a 35 track drive, TC=39 for a 40 track, etc.

SPT=scl specifies the number of sectors per track. For double sided, single volume diskettes (TD = C, D, G or H), scl must be twice what it would be if single sided diskettes. scl may be any value from 1 to the maximum number of 256 bytes sectors the track can physically hold. For each of the above specified drive types, the maximum number of sectors per track is: A=10, B=17, C=20, D=34, E=18, F=26, G=36 and H=52.

TSR=rcl specifies the track stepping pulse time code the controller uses for this drive. rcl is a value from 0 to 3 and becomes part of the SEEK, STEP and RESTORE commands sent to the controller. For the Model I and III standard controllers, TSR=0 gives 5 ms stepping, TSR=1 gives 10ms stepping, TSR=2 gives 20ms stepping and TSR=3 gives 40ms stepping. TSR=3 was the original standard for the Model I, with some users using TSR=2 or TSR=1 for certain drives. The Model III appears to use TSR=0 as standard. If you are having drive trouble, the safest setting is TSR=3 (fastest stepping rate for the Model I is 12ms).

GPL=gc2 specifies the number of granules per lump where gc2 is a value between 2 and 8. In TRSDOS for the Model I and III and the older versions of NEWDOS, disk space allocation was done via granules (5 sectors per granule on the Model I and 3 per granule on the Model III) and tracks (2 granules per track on the Model I and 6 granules per track on the Model III). In NEWDOS/80 version 2, for both the Models I and III, there are still 5 sectors per granule, and 2 to 8 granules per lump (not track). Wherever a track number appeared in the directory (in the GAT sector and in the FDE two byte extent elements), it has been replaced with a lump number. Doing so allows a granule to start in one track and end in another and allows double density and 8 inch diskettes to maximize the number of sectors per track while keeping the same directory format. GPL=2 maintains compatibility with the old 35 track single density diskettes, as the directories will be exactly the same and transferable back and forth between the Model I TRSDOS and NEWDOS versions before NEWDOS/80 version 2. However, by going to GPL=8 the directory can now accommodate $192 \times 8 \times 5 = 7680$ sectors or 1,966,000 bytes.

DDSL=lnl is the logical equivalent of and replacement for the DDST parameter used in NEWDOS/80 version 1. lnl specifies the number of the lump at whose first sector is to contain the directory's 1st sector. This value is stored in the boot sector 3rd byte during diskette format and is used when necessary to find the directory. It is also used during diskette format to determine where to put the directory. In the older systems, the 3rd byte of the boot sector contained the track number in whose 1st sector the directory started. Since tracks are not used in space allocation and control in NEWDOS/80 version 2, the 3rd byte of the boot now contains the number of the lump in whose 1st sector the directory starts. To determine the relative sector number of the directory's 1st sector (the GAT sector), access the boot sector's 3rd byte and multiply that value by 5 times GPL. DDSL=17 maintains compatibility with the standard 35 track, single sided, single density diskettes. DDSL should be set to the value used for the DDST parameter in NEWDOS/80 version 1.

DDGA=gcl specifies the default number of granules to be allocated to the directory when it is created during format, where gcl is a value between 2 and 6. DDGA=2 should be specified for standard 35 track, single density, single sided compatibility. $gcl > 2$ allows the user to have more than 62 files on a data diskette with the maximum being 222 files.

A specifies that if and only if no errors were found during the checking of

PDRIVE

the specifications for all the drives, then the specifications for SYSTEM option AL number of drives is loaded into the main memory PDRIVE table to immediately become the controlling data for those drives; this eliminates the need for a reset. If parameter A is specified, dnl must = 0.

PDRIVE is executeable under MINI-DOS.

PDRIVE command examples:

1. PDRIVE,dnl,dn2,TI=A,TD=A,TC=35,SPT=10,TSR=3,GPL=2,DDSL=17,DDGA=2 is the PDRIVE specification for a standard 5 inch, 35 track, single density, single sided diskette used for communication in the Model I world. This specification can also be used on the Model III to read the diskette providing the directory address marks are correct (see SYSTEM option AN).
2. PDRIVE,dnl,dn2,TI=A,TD=E,TC=40,SPT=18,TSR=3,GPL=2,DDSL=17,DDGA=2 is the Model III specification (Model I, use TI=C) for a standard 5 inch, 40 track, double density, single sided diskette used for communication through out the NEWDOS/80 Model III world. Using this specification, this diskette can also be read on the Model I in a drive other than 0 if a double density modification is installed in the expansion interface.
3. PDRIVE,dnl,dn2,TI=AM,TD=E,TC=40,SPT=18,TSR=3,GPL=6,DDSL=17,DDGA=2 is the Model III specification (Model I, use TI=CM or EM) for reading or writing to a TRSDOS Model III standard 5 inch, double density, single sided diskette. A 40 track, double density, single sided 5 inch diskette is the only type TRSDOS Model III diskette that NEWDOS/80 can handle. GPL=6 is mandatory. Since a TRSDOS Model III diskette cannot be formatted by NEWDOS/80, DDSL and DDGA are meaningless. In NEWDOS/80 (double density mod must be installed for Model I), only the COPY DOS command can be used with TRSDOS Model III diskettes excepting that diskette sectors can be read/written via SUPERZAP by using the DD, DM, DTS, VDS, CDS, CDD, etc. functions that do not refer to files (i.e., don't use DFS).
4. PDRIVE,dnl,dn2,TI=A,TD=C,TC=80,SPT=20,TSR=2,GPL=8,DDSL=20,DDGA=6 is the specification for a 5 inch, 80 track, single density, double sided, single volume diskette with 20ms stepping, 8 granules per lump, with the directory positioned at the diskette halfway point and maximum size directory. For the Model III, the single density drive 0 restriction applies.
5. PDRIVE,dnl,dn2,TI=A,TD=G,TC=80,SPT=36,TSR=2,GPL=8,DDSL=35,DDGA=6 is the Model III specification (Model I, use TI=C or E) for a 5 inch, 80 track, double density, double sided, single volume diskette to use 20ms stepping, 8 granules per lump, maximum size directory positioned at the diskette halfway point. For the Model I, the double density drive 0 restriction applies.
6. PDRIVE,dnl,dn2,TI=CK,TD=E,TC=39,SPT=18,TSR=3,GPL=2,DDSL=17,DDGA=2 is the Model I specification (Model III, use TI=AK) for 5 inch, 40 track, double density, single sided diskette that has track 0 formatted in single density, hence only 39 tracks available for regular use. This specification will handle double density diskettes formatted by TRSDOS and NEWDOS/80 version 1 running under the PERCOM doubler. This specification will also be used when generating a double density diskette to be the system diskette in drive 0 for the Model I. For LNW Model I interface, use TI=EK.

7. PDRIVE,dn1,dn2,TI=CK,TD=G,TC=79,SPT=36,TSR=3,GPL=8,DDSL=35,DDGA=6 is the Model I specification (Model III, use TI=AK) for a 5 inch, 80 track, double density, double sided, single volume diskette that has track 0 formatted single density. For the LNW Model I interface, use TI=EK.

Warning!!! Double sided, double density diskettes used on the patched NEWDOS/80, version 1 are not usable on Version 2 (see TI flag K discussion).

8. PDRIVE,dn1,dn2,TI=AL,TD=A,TC=35,SPT=10,TSR=3,GPL=2,DDSL=17,DDGA=2 is the specification for a 5 inch, 35 track, single sided, single density diskette that is to be read on an 80 track drive. The 80 track drives step only half as far as the 35 and 40s for each data track; setting flag L causes 2 steps to be taken for each data track stepped.

9. PDRIVE,dn1,dn2,TI=BH,TD=B,TC=77,SPT=17,TSR=3,GPL=3,DDSL=17,DDGA=6 is the Model I specification for an 8 inch, 77 track, single sided, single density diskette. Note, NEWDOS/80 version 1 used SPT=15 and an implied GPL=3, and to read those diskettes, SPT=15 and GPL=3 must be used. It is recommended that a COPY be done to convert those diskettes to SPT=17, thus gaining 12% more diskette space. Flag H causes head load settle delay to be used, required for most 8 inch drives.

10. PDRIVE,dn1,dn2,TI=BH,TD=D,TC=77,SPT=34,TSR=3,GPL=8,DDSL=17,DDGA=6 is the Model I specification for an 8 inch, 77 track, single density, double sided, single volume diskette with head load settle delay required.

11. PDRIVE,dn1,dn2=dn3 is the specification to cause drive dn2 to receive as its specifications those of drive dn3.

12. PDRIVE,dn1,dn2=dn3,TC=40,TSR=2 is the specification to cause drive dn2 to receive as its specifications those of drive dn3 and then to apply new values for TC and TSR.

13. PDRIVE,0,A causes the PDRIVE data for SYSTEM option AL number of drives to be loaded into the main memory PDRIVE table if and only if the full display of the specifications shows no error.

14. PDRIVE,0,dn2=dn3,A changes drive 0's specifications for dn2 to be those of dn3, and then performs as in the above example.

2.38. PRINT List a text file on the printer.

PRINT,filespec[,start-line[,line-count]]

PRINT executes identical to LIST, excepting the listing goes to the printer instead of the display. Refer to DOS command LIST for specifications and examples.

2.39. PROT Alter some diskette control data.

```
PROT,[password1:]dnl[,NAME=namel][,DATE=mm/dd/yy][,RUF]
    [,PW=password2][,LOCK][,UNLOCK]
```

At least one optional parameter must be specified. The target diskette is mounted on drive dnl. If passwords are enabled, password1 must be specified and must equal the diskette's master password.

NAME=namel The diskette is given the name namel.

DATE=mm/dd/yy The diskette is given the date mm/dd/yy.

RUF Reset Udated Flags. This option turns off the updated flags for all files on the diskette. If a user backs up only those files having the updated flag on (see UPD option of COPY) off, executing PROT with the RUF option after the copying is completed turns off the updated flags so the files will not be eligible for a subsequent backup until the file is subsequently updated. Simply writing or rewriting one sector of the file, whether or not anything was actu- ally changed, causes DOS to turn on a file's updated flag.

PW=password2 Password2 must conform to the rules for passwords, with null set as all blanks. The diskette receives password2 as its password.

LOCK All files of the diskette, except system and invisible files, are given the diskette master password as both their access and update passwords. If password2 specified, it is used. This feature used to be the only way a user, in a password enabled system, could get to a file whose password(s) he/she had forgotten, if the user did know the diskette master password. It has the unfortunate drawback in that it changes the passwords for all, except system and invisible, files on the diskette; thus causing the user to reassign passwords to all the others as well as to the file whose passwords he/she forgot. An easier way is available if the user knows the password of at least one NEWDOS/80 system diskette or better still, has a NEWDOS/80 system diskette with passwords disabled (system option AA = N). With passwords disabled, the user can use ATTRIB to directly reassign new passwords to the file whose passwords are forgotten without having to affect other user files on the diskette. Then passwords can be reenabled.

UNLOCK The access and update passwords of all of the diskette's files, except system and invisible files, are set to all blanks, meaning no passwords for those files.

PROT command examples:

1. PROT,2,RUF The updated flag is cleared for each file on the diskette currently mounted on drive 2.

2. PROT,OLDPSWD:1,NAME=AAB3,DATE=07/15/81,PW=NEWPSWD

In this example, passwords are enabled; therefore the diskette's master password OLDPSWD was required. The diskette control information for the diskette mounted on drive 1 is changed such that its name is AAB3, its date is July 15, 1981 and its new master password is NEWPSWD.

2.40. PURGE Selectively kill files from a diskette.

PURGE,[password1:]dn1[,/ext][,USR]

The diskette mounted on drive dn1 is used for this command. If passwords are enabled, password1 must be specified and must be equal to the diskette's master password.

For each file, except BOOT/SYS and DIR/SYS, on the diskette, DOS asks the operator if the file is to be killed. If the file is to be killed, respond Y; the file will be immediately killed, as if a KILL command has been issued. If the file is NOT to be killed, respond N. Respond Q if you wish to quit the PURGE function.

/ext If this option is specified, the purge queries are limited to only those files having name extension ext where ext is 0 to 3 characters.

USR If this option is specified, system and invisible files are not included in the PURGE function.

PURGE command examples:

1. PURGE,1 For each file, except BOOT/SYS and DIR/SYS, on the diskette currently mounted on drive 1, DOS asks if the file is to be killed. If the response is Y, the file is killed.
2. PURGE,0,/DAT For each file on the diskette currently mounted on drive 0 that has name extension DAT, DOS asks if the file is to be killed and does so if the response is Y.
3. PURGE,0,USR For each non-system, non-invisible file on the diskette currently mounted on drive 0, DOS asks if the file is to be killed and does so if the response is Y.

2.41. R Repeat the previous DOS command.

This command causes the re-execution of the previous DOS command, excluding the command R. Example:

```
DIR 1            followed by:
R
```

will execute the same as if the two DOS commands had been:

```
DIR 1
DIR 1
```

The R command can not be executed from BASIC via CMD"doscnd" as that function requires that the command, excluding ENTER, must be 2 or more characters long.

R - RENAME - ROUTE

The **R** command has no parameters and must be keyed exactly as **R** followed by **ENTER**. If more than 2 characters are keyed into the buffer and then backspaced so that DOS only sees the **R** and the **ENTER**, the previous DOS command that was residing in the command buffer will still have been altered and the **R** command will either fail or in rare circumstances, execute something different than what the operator expected.

If the previous DOS command is no longer intact in the DOS command buffer, the results of the **R** command are unpredictable.

If **SYSTEM** option **BE = N**, the **R** command does not execute the previous DOS command but instead simply returns to **DOS READY**.

2.42. RENAME Rename a file.

RENAME,filespec1[,TO],filespec2

The file **filespec1** is renamed to **filespec2**, where **filespec2** consists of only a name and optionally a name extension. If **filespec1** does not specify a drive number, then all mounted diskettes are searched, and the first file encountered matching **filespec1**'s name and name extension is renamed. **RENAME** change only the file's name and name extension; nothing else is changed.

RENAME command example:

1. **RENAME XXX/DAT:1 YYY/OBJ** The file **XXX/DAT** on the diskette currently mounted on drive 1 has its name changed to **YYY** and its extension changed to **OBJ**.

2.43. ROUTE

1. **ROUTE**
2. **ROUTE,CLEAR**
3. **ROUTE,dev1[,dev2][,dev3]....**

The purpose of the **ROUTE** command is to allow some flexibility from where the keyboard and/or **RS-232** input is received and to where display, printer and **RS-232** output is sent.

At the conclusion of a **ROUTE** command, any existing routes are displayed; if none, nothing is displayed. **ROUTE** with no parameters does nothing except display the existing routes.

ROUTE,CLEAR clears all routes.

dev1 specifies the device being routed. **dev2**, **dev3**, etc. specify the device(s) being routed to (the routed-to devices) when **dev1** is an output device or routed from (the routed-from devices) when **dev1** is an input device. For the Model I,

the device codes are KB for the keyboard, DO for the display, PR for the printer and NL for null (meaning nothing is transferred). For the Model III, RI for the RS-232 input and RO for the RS-232 output are added to the above 3 codes. An input device (KB or RI) may not be routed to an output device (DO, PR or RO), and an output device may not be routed to an input device.

Whenever dev1 is specified, ROUTE initially clears any previously existing routes for that device and then establishes the routes specified by dev2, dev3, etc., if any.

Any of the devices dev2, dev3, etc. may also be of the form MM=addr where addr specifies the main memory location of a user routine to which dev1 is to be routed. The first 12 bytes of the routine are reserved for use by DOS and must not be altered by the user. Upon routing, the user routine is entered via a CALL at the 13th byte, and it is the user's responsibility to save and restore all registers, except AF, used by the routine and routines it calls. If dev1 is an input device, the routine returns the new byte in register A with a zero indicating there is no new input byte from that routine. If dev1 is an output device, upon entry to the routine, register C contains the byte being outputted.

If dev1 is an output device, the output byte is sent to all routed-to devices in the order given in the ROUTE command.

If dev1 is an input device, each routed-from device is queried in the order given in the ROUTE command. If that device supplies a non-zero byte, the queries stop and the byte is used as the input byte for the dev1. If no routed-from device has an input byte, a zero is considered dev1's current byte.

The maximum number of routes-to and routes-from, excluding MM=addr types, in existence at one time is four for the Model I and six for the Model III.

WARNING!!! No editing of input or output characters is done during routing. This may cause problems (i.e., display control characters causing the printers to do unpredictable things).

ROUTE command examples:

1. ROUTE,PR,DO Printer output does not go to the printer but instead goes to the display.
2. ROUTE,DO,DO,PR Display output goes to both the display and the printer.
3. ROUTE,PR,DO,PR Printer output goes to both the display and the printer. If the routes of both example 2 and 3 are active, the routing is equivalent to the Model III TRSDOS function DUAL.
4. ROUTE,KB,RI (Model III only) Keyboard input characters come from the RS-232 input device and not from the keyboard.
5. ROUTE,DO,RO (Model III only) Display output is sent to the RS-232 output device and not to the display.
6. ROUTE,PR,MM=0FE80H Printer output is sent to the routine at main

ROUTE -- SETCOM

memory location 0FE80H (the routine's actual entry point is 0FE8CH).

7. ROUTE,KB,KB,MM=0F800H Keyboard input comes from either the keyboard or the routine at main memory location 0F800H. Input from the keyboard has precedence.
8. ROUTE,PR,NL Printer output is discarded.
9. ROUTE,PR All routing for the printer is dissolved. Printer output goes to the printer.
10. ROUTE,CLEAR All routes are dissolved, and all devices are returned to their normal paths.

2.44. SETCOM (Model III only) Set RS-232 interface parameters.

SETCOM[,OFF][,WORD=w1][,BAUD=br][,STOP=sb][,PARITY=pp][,WAIT][,NOWAIT]

The SETCOM command optionally changes the state of the RS-232 interface and always displays the state. For RS-232 discussion, see chapter 8 of the Model III Operation and BASIC Language Reference Manual. The SETCOM command affects only the standard RS-232 control blocks and routines.

If OFF is specified, the RS-232 interface is turned off. No other optional parameters may be specified.

If any of WORD, BAUD, STOP or PARITY is not specified, the state for that keyword is not changed.

WORD=w1 specifies the number of bits per transmission byte. w1 must be one of 5, 6, 7 or 8.

BAUD=br specifies the transmission rate (the baud rate) for both sending and receiving. The 16 allowable values for br are 50, 75, 110, 134, 150, 300, 600, 1200, 1800, 2000, 2400, 3600, 4800, 7200, 9600 and 19200.

STOP=sb specifies the number of stop bits to be used for each byte transmitted. sb is either 1 or 2.

PARITY=pp specifies the parity to be used in the transmission where 1 = odd parity, 2 = even parity and 3 = no parity.

WAIT or **NOWAIT** are mutually exclusive and specify whether or not the RS-232 input routine is to wait until an input byte is received and the output routine is to wait until the current byte has been sent. If neither WAIT nor NOWAIT is specified, the previous wait or no wait state remains.

SETCOM command examples:

1. SETCOM,WORD=8,BAUD=300,STOP=1,PARITY=1,WAIT Activates the RS-232

interface, if not already active, and sets the interface for 8 bit bytes, 300 baud rate, one stop bit, odd parity and forces the RS-232 routines, when called, to wait until an input byte is ready or until the RS-232 output device will accept an output byte.

2. SETCOM,NOWAIT,PARITY=3,WORD=7 Activates the RS-232 interface, if not already active, and sets the interface for 7 bit bytes, no parity and causes the RS-232 routines not to wait until an input byte is ready or the RS-232 output device will accept an output byte. The TRS-80 interrupt routines will handle the actual byte input or output with the RS-232 device. The other parameters not mentioned in the command are not changed.

3. SETCOM,OFF The RS-232 interface is deactivated. The current interface specification is remembered.

2.45. STMT Display specified message.

STMT,msg

Since normal DOS commands are always displayed, this command normally has nothing to do since its function, to display the message msg, has already been done. However, if this command was invoked via DOS-CALL (which does not display the DOS command), the message msg is displayed.

STMT is one of 3 ways in chaining to display a message without a pause. This allows multiple line instructions to be displayed, with the last line being a PAUSE and the others being STMTs.

STMT command examples:

1. STMT PHASE ONE COMPLETED This is simply an announcement to the terminal operator that phase one (whatever that was) has been completed. DOS does not pause.
2. STMT DISMOUNT AND STORE AWAY DISKETTE XXX
PAUSE AND MOUNT DISKETTE YYY ON DRIVE 2.

This example illustrates the combined use of the STMT and PAUSE commands to give instructions and wait until they are carried out.

2.46. SYSTEM Change system options.

```
SYSTEM,[password1:]dnl[,AA=yn][,AB=yn][,AC=yn][,AD=yn][,AE=yn]
[,AF=yn][,AG=yn][,AI=yn][,AJ=yn][,AL=al][,AM=am][,AN=an]
[,AO=ao][,AP=ap][,AQ=yn][,AR=yn][,AS=yn][,AT=yn][,AU=yn]
[,AV=av][,AW=aw][,AX=ax][,AY=yn][,AZ=yn][,BA=yn][,BB=yn]
[,BC=yn][,BD=yn][,BE=yn][,BF=yn][,BG=yn][,BH=yn][,BI=bi]
[,BJ=bj][,BK=yn][,BM=yn][,BN=yn]
```

SYSTEM

The NEWDOS/80 system diskette whose control information is being updated/ displayed by this command is mounted on drive dnl. If passwords are enabled, password1 must be specified and be equal to the diskette's master password. If no optional parameters are specified, then only a display of existing options is given. The optional parameters may be specified in any order, and only those parameters specified have their values changed in the diskette's control data (3rd sector on the diskette). Parameters not specified are not changed.

If many options are being changed, it may be necessary to perform multiple SYSTEM commands as the DOS buffer is limited to 79 characters per command.

It is anticipated that additional options will be specified as time proceeds.

Changes to a system diskette's system options do not affect the computer operations until that system diskette is mounted on drive 0 and a reset done.

AA=yn If AA=Y, passwords are enabled. If AA=N, passwords are disabled.

AB=yn If AB=Y, the system is to operate in RUN-ONLY mode. SYSTEM options AD=N, AE=N and AF=N are forced at reset time, and the pressing of ENTER to override the auto command is disallowed. The user must have a proper auto command (see AUTO, section 2.4) that will either invoke a user program or execute a CHAIN file that will eventually invoke a user program. In RUN-ONLY mode, if the system finds itself at normal DOS READY or MINI-DOS READY, it will go into an endless loop after displaying 'RUN ONLY STOPPED!! PRESS 'R' FOR RESET'. Upon receiving R, the DOS command BOOT (see section 2.7) will be executed. BASIC honors RUN-ONLY by disabling BREAK, treating LOAD without R or V as an error, and by not allowing any direct statements. If AB=N, the system is in normal command mode.

AC=yn (Model I only) If AC=Y and if SYSTEM option AJ=Y, the NEWDOS/80's debounce routine is used. If AC=N or SYSTEM option AJ=N, the NEWDOS/80's debounce routine is bypassed.

AD=yn If AD=Y, 'JKL' is enabled, and if AD=N, 'JKL' is disabled.

AE=yn If AE=Y, '123' is enabled as the method to invoke DEBUG (see section 4.1). If AE=N, '123' is disabled.

AF=yn If AF=Y, 'DFG' is enabled as the method of invoking MINI-DOS (see section 4.2). If AF=N, 'DFG' is disabled.

AG=yn If AG=Y, BREAK is considered a normal input key with code = 01. If AG=N, the BREAK key is not considered a normal input key and its occurrence is changed to the null key code 00. The state of the BREAK key is set according to option AG at reset and then again everytime the system returns to normal DOS READY. DOS command BREAK may be used to enable or disable the BREAK key until the next normal DOS READY. Also, programs may enable the BREAK key by storing a 0C9H byte in Model I location 4312H (Model III location 4478H) or disable the BREAK key by storing a 0C3H byte in that location.

AH=yn Not defined in NEWDOS/80, version 2. Formerly, this dealt with delaying the disabling of timer interrupts during disk I/O to gain better clock accuracy. This is no longer done.

AI=yn (Model I only) If AI=Y, lower case modification has been installed in the computer and AI=N if it is not. User programs may test for bit 4 of 436CH for this state, 1 if AI=Y and 0 if AI=N. Currently, DEBUG and SUPERZAP use this flag to decide whether memory displays can display lower case.

AJ=yn If AJ=Y, NEWDOS/80's keyboard intercept routine is active. This routine contains repeat key function, 'debounce' (Model I only) and one of the methods used to spot 'JKL', '123' and 'DFG' (the other being off the timer interrupts). If AJ=N, NEWDOS/80 does not intercept the keyboard two byte address vector at 4016H and

1. The repeat key function for the Model I is not active regardless of the SYSTEM option AU. The Model III reverts to the ROM repeat key function.
2. 'debounce' (Model I only) is not active regardless of SYSTEM option AC setting.
3. 'JKL', '123' and 'DFG' can only be triggered via the interrupts, resulting in many more spurious key input characters.

If the up-arrow key is depressed all during the reset/power-on sequence, AJ = N is forced; this is necessary for those programs that eventually overlay the DOS in main memory.

AK=yn Not defined in NEWDOS/80, version 2. Formerly, this option dealt with allowing 'JKL' to pass graphic characters to the printer. This has been incorporated into SYSTEM option AX.

AL=al al (value 1 - 4) specifies the number of physical drives in the system. If your system only has one drive, setting al = 1 will limit the system to only checking for that one drive. Though al can be set to 255, it should never exceed 4.

AM=am am (value 0 - 255 where 0 = 256) is the number of tries allowed for a disk I/O before it is declared in error. The original DOSs used a value of 10.

AN=an an = the default drive number for the DIR command.

AO=ao When creating a file and when the user lets the system choose the diskette to contain the file by not specifying a drive number in the filespec, the system will first search all the drives for an existing copy of the file. If it does not find an existing copy, the system will start searching at drive ao, and will search that and higher numbered drives until a free FDE is found. It will not search a drive whose number is less than ao.

AP=ap ap is a memory address, which if other than 0 and is within the range of existing memory, is stored as DOS's HIMEM address value in the two bytes at Model I location 4049H (Model III location 4411H).

AQ=yn If AQ=Y, the CLEAR key is enabled, and if AQ=N, the CLEAR is disabled if SYSTEM option AJ=Y.

AR=yn If AR=Y, COPY, formats 5 and 6, are allowed without diskette password checking even though passwords are enabled. If AR=N, passwords are required if passwords enabled.

SYSTEM

AS=yn (Model I only) If AS=Y, BASIC will convert input text character strings from lower to upper case. This is useful when lower case hardware is not installed or when lower case drivers are not used as it is very possible to input lower case characters (using the shift key) and have BASIC display them as upper case even though they are really lower case. The user can stare forever at a compare that looks equal on the display, but BASIC computes as unequal. If as = N, BASIC will leave the text character strings alone. This option does not affect string characters input as data rather than as part of text.

AT=yn AT=N puts chaining into record mode, meaning that only requests for full records come from the chain file; single char key input request are honored from the keyboard. AT=Y puts chaining in single character mode meaning that all requests for an input key come from the chain file.

AU=yn AU=Y turns on the clock driven repeat key function. The first repeat will delay option AV number of 25 ms intervals. Subsequent repeats will enter as fast as the program asks for them but not more than 12 per second. AU=N turns off the repeat key function, eliminating repeat keys on the Model I and shifting to the ROM repeat key function on the Model III.

AV=av AV is used when AU=Y. av is the number of 25 ms intervals to pass between the key depression and the acceptance of the 1st repeat of that character. Subsequent repeats are as fast as the program wants them but not more than 12 per second.

AW=aw is the number of write-with-verify disk I/O tries allowed. This I/O retry count works in conjunction with option AM=am with each retry under AW taking place only after the sector verify read has failed am number of times. Formerly, if sector write encountered no error and the verify read did result in an error, it was left to the user to retry the write. Now, if aw is greater than 1, the write will automatically be retried in the cases where the write was apparently good but the verify read failed.

AX=ax This is ASCII code of the highest printable character for the printer. It is used by system routines to determine when to substitute blanks or periods in place of ASCII codes higher than this value. This value must not exceed 255. This high ASCII code is stored in the one byte at Model I location 4370H (Model III location 4290H).

AY=yn is used only during resets wherein DOS senses that it was not active immediately prior to the reset (i.e., reset after power-on or after execution of non-disk BASIC). AY=Y causes the operator to be asked for date and time. AY=N bypasses this query and causes date and time to be set to zeroes.

AZ=yn is used only during resets wherein DOS senses that it was active immediately prior to the reset. AZ=Y causes the operator to be asked for date and time. AZ=N causes date and time to be left as they were prior to the reset.

BA=yn BA=Y causes a reset to activate 'ROUTE,DO,NL', thus causing all display output, including the DOS and BASIC banners, to be lost until the operator or a user program executes either 'ROUTE,CLEAR' or 'ROUTE,DO'. BA=N disables this reset action.

BB=yn (Model III only) BB=N informs the system that the clock interrupts

occur 60 times a second. BB=Y informs the system that the clock interrupts occur 50 times a second. This option does not set the clock to perform as such, but only acknowledges that it does.

BC=yn BC=Y means the operator can manually pause or cancel chaining. BC=N means the operator is not allowed to manually pause or cancel chaining. RUN ONLY forces BC=N.

BD=yn BD=Y means the operator can override the AUTO command at reset by holding down the ENTER key. BD=N means he/she can't. RUN ONLY forces BD=N.

BE=yn BE=Y enables the DOS command R to repeat the previous DOS command (see section 2.41). BE=N causes the R command to simply return to DOS READY.

BF=yn (Model I only) BF=Y performs at reset/power-on time the equivalent of the DOS command LCDVR,Y (see section 2.29). BF=N performs the equivalent of LCDVR,N. However, if DOS senses that the lower case hardware is either not installed or is not operating, BF=N is forced.

BG=yn BG=Y performs at reset/power-on time the equivalent of the DOS command LC,Y (see section 2.28). BG=N performs the equivalent of LC,N.

BH=yn At reset/power-on time BH=Y enables cursor blinking, and BH=N inhibits it.

BI=bi At reset/power-on time, the numeric value bi is set as the cursor character's value, excepting that if bi = 0, then the standard cursor character value is used (95 for the Model I and 176 for the Model III).

BJ=bj Option BJ provides a minimal control for NEWDOS/80 when a CPU speed up modification is installed that is to continue operation during disk operations. This option multiplies (roughly) by bj the number of 2-80 instructions executed during certain timing loops used internal to NEWDOS/80. bj must be an integer greater than 0 and equals the number of times the CPU has been speeded up. Set bj = 1 if the loops are not to be lengthened. If the loops are to be lengthened, bj must always be rounded up in the cases where the new CPU speed is not an even multiple of the original Model I or Model III speed. Option BJ does NOT perform the actual CPU speed switching.

BK=yn BK=Y allows the DOS command WRDIRP and the W and C functions of DIRCHECK to be executed. BK=N causes these functions to be rejected with 'DISK ACCESS DENIED'.

BM=yn BM=Y causes diskette formatting to verify read sectors in a separate VERIFYING phase after all tracks have been formatted. This verify read is in addition to the verify read done on a track's sectors immediately after the individual track was formatted. BM=N bypasses this VERIFYING phase, deeming as sufficient the verify sector read done when the individual track was formatted.

BN=yn (Model I only) BN=N causes the write of single density diskette directory sectors to use the address mark readable by Model I TRSDOS. BN=Y causes the write of single density diskette sectors to use the address mark readable by Model III NEWDOS/80. BN=Y should only be used where it is required that single density diskettes be NEWDOS/80 version 2 exchangeable between the Model I and the Model III.

SYSTEM - TIME

Though the information contained in the directories used by Model I TRSDOS, Model I NEWDOS/80 and Model III NEWDOS/80 is the same (except for some additions by NEWDOS/80), the address mark byte (part of the magnetic format and identification bytes that surround each 256 bytes of user data on the soft sector diskettes) used to indicate the directory sectors are 'protected' is different on the Model III than it is on the Model I for single density diskettes.

The changing of SYSTEM option BN does not in itself change the address mark of any directory sectors. All this does is set the protected sector write routine in DOS to write the specified address mark whenever a protected sector is written or rewritten to disk. To set all sectors of a single density diskette directory to the proper address mark, use either DOS command WRDIRP or DIRCHECK with the W option. Warning!!! If a single density diskette has been used on the Model III or has been used on the Model I where BN=Y and the diskette must now be used with Model I TRSDOS, the user must set BN=N and rewrite the directory sector address marks using WRDIRP or DIRCHECK with option W. This must be done even though, with BN=N, SUPERZAP under NEWDOS/80 on the Model I shows the directory sectors protected; this is because Model I NEWDOS/80 accepts either address mark value as 'protected' though it only writes the one value specified by option BN.

System option codes B0 and up are reserved for future definition.

SYSTEM command examples:

1. SYSTEM,0,AL=4,AA=Y,AU=Y,AV=20,AT=Y The SYSTEM control parameters AL, AA, AU, AV and AT are changed on the current system diskette mounted on drive 0. All the other SYSTEM parameters are left unchanged. The full SYSTEM specification is then displayed. These changes are not used to control NEWDOS/80 until the next reset/power-on.
2. SYSTEM,2,AP=0FF00H,AN=1,AX=126 The SYSTEM control parameters AP, AN and AX are changed in the control sector of the diskette currently mounted on drive 2. No other SYSTEM parameters are changed. The full system specification contained on that diskette is then displayed. For the SYSTEM parameters contained on that diskette to control NEWDOS/80, that diskette must be a NEWDOS/80 version 2 system diskette, must be dismounted from drive 2 and remounted on drive 0, and a reset/power-on must be done.

2.47. TIME Set the real time clock.

TIME[,hh:mm:ss]

If no parameters are specified, the current times is displayed in hh:mm:ss format.

If hh:mm:ss is specified, the clock is set to time hh:mm:ss where hh is a 2 digit hour value, 00 - 23, mm is a two digit minute and ss is a two digit

seconds value. No check is made on the validity of the values. Each of the three values is converted to a single byte value and stored into its byte of the clock. The clock three bytes start at model I location 4041H (model III location 4217H) and are in seconds, minutes, hours order.

At reset/power-on the clock is set according to SYSTEM option AY or AZ. The clock is updated once a second. The user should not rely upon the clock for an accurate value as disk I/O frequently and interrupt routines infrequently run so long with interrupts disabled that one or more timer interrupts will be missed, causing the clock to run slow. The real time clock is not a hardware clock, but instead is maintained by software that is not aware of the lost timer interrupts.

TIME command examples:

1. TIME,15:23:00 The clock is set to 3:23 PM.
2. TIME The current time is displayed.

2.48. VERIFY Require verify read after every disk write.

VERIFY[,yn]

NEWDOS/80 performs verify read after all of its directory writes and after all sector writes when logical record or single byte I/O is used. It does not perform verify reads when full sector writes are done via the 4439H vector.

VERIFY or VERIFY,Y Diskette writes done via the 4439H vector are verify read. A verify read means the sector is read after it is written. If the sector was written illegible or with bad parity, an error will be triggered. A byte for byte data compare is not done. However, if the verify read detects an error and SYSTEM option AW is not equal to 1, the write and verify read will be done again since the system still has access to the data that should have been placed into the diskette sector.

VERIFY,N Diskette full sector writes done via the 4439H vector are not verify read.

COPY, EDTASM and BASIC SAVE's write the file completely without validity read, but then read back the entire file as a verify read. All BASIC disk data writes to print/input files, marked item files, fixed item files or field item files (where record length is not 256) perform verify read due to the fact that byte rather than sector I/O is used. Field item files with record length 256 use sector I/O and are not verify read unless VERIFY is on.

WRDIRP

2.49. WRDIRP Write directory sectors protected.

WRDIRP,dnl

WRDIRP causes the directory sectors for the diskette in drive dnl to be read and rewritten in the currently defined protected state for the current computer (see SYSTEM options BN and BK).

This command is used where single density diskettes are to be exchanged under NEWDOS/86 version 2 between the model I and III.

This command enables the user to set the directory to the proper read protect state while under MINI-DOS, since it is most likely he/she will find out about the problem when in the middle of doing something else (and thus can't get to DIRCHECK). CAUTION!!! This command uses the directory starting granule number from the 3rd byte of the boot sector to find the directory. It then checks to see if the FPDE's for BOOT/SYS and DIR/SYS are present. If these checks pass, it then changes what it thinks are the directory sectors all to protected status. Do NOT use this command unless you are sure the only problem is the different protection status between the model I and model III; if you have doubts, use the W function of DIRCHECK.

If SYSTEM option BK = N, the DOS command WRDIRP is disabled.

WRDIRP command example:

1. WRDIRP,1 For the diskette mounted on drive 1, the directory address marks are set for the current computer and, if Model I, for the setting specified by SYSTEM option BN.

3. DOS ROUTINES.

3.1. This chapter specifies the DOS routines that are available for use by machine language programs. If you are neither a Z-80 programmer nor interested in Z-80 machine code, you should bypass this chapter. Readers of this chapter are assumed to be knowledgeable of Z-80 machine code and at least one assembly language for the Z-80.

These DOS routines have entry and exit conditions, and rather than repeat them in each routine's specification, some of the conditions are defined here with the using routine's specification simply referring to the condition's code.

A. Only register AF is altered by the routine. Any other registers used by the routine are saved on entry and restored on exit.

B. On exit, Z state is set if no error is encountered during the routine's execution. NZ state is set if a DOS error is encountered, and register A contains a DOS error code. The setting of Z and NZ takes precedence over the setting of other flags such as C and NC.

C. On entry, DE points to an open FCB.

There are incompatibilities with TRSDOS in the use of some of these routines. They are discussed briefly in the routines where they occur, so study them carefully. The reader should also be aware of the differences in the way the FCB fields NEXT and EOF are maintained (see FCB specification, section 5.9).

The discussion of each routine gives its entry address (the address to be used in the CALL or JP Z-80 instruction), then its title (if one is appropriate), and then its specification.

Unless otherwise specified, the DOS routine uses the invoker's stack. Unless specified as a dead end routine, the DOS routine exits to the caller.

Many of these routines use a FCB (see section 5.9). NEWDOS/80 on both the Models I and III and Model I TRSDOS all use a 32 byte FCB while Model III TRSDOS uses a 50 byte FCB. NEWDOS/80 will run with user programs having the 50 bytes FCB but will only use the first 32 bytes of those FCBs. Programs using a 32 byte FCB with Model III TRSDOS will have problems.

The routines listed below are not necessarily in ascending numeric order.

3.2. 402DH. No-Error Exit. Dead end routine. Programs concluding with no error jump to 402DH. DOS checks its own state in the following order.

If either MINI-DOS or DOS-CALL, the stack pointer is set to where it was before the last DOS command; otherwise it is set to DOS's stack area and the BREAK key is enabled/disabled according to system option AG.

If DOS-CALL and if either not chaining or chaining is not to be continued at the current DOS level, all registers except AF are restored to as they existed on DOS-CALL entry, Z state is set, and a return is made to the DOS-CALL invoker. If this was the outermost DOS-CALL level, DOS is taken out of DOS-CALL state.

If RUN-ONLY and if chaining is not active, the message 'RUN ONLY STOPPED!! KEY 'R' FOR RESET.' is displayed, DOS loops waiting on the reply, and then executes DOS command BOOT (see section 2.7).

If DOS-CALL and if chaining is to continue at the current DOS-CALL level, DOS waits for the next command from the chain file.

If MINI-DOS, then MINI-NEWDOS/80 READY is displayed, and DOS waits for the next command.

If chaining is active, DOS waits for the next command from the chain file.

NEWDOS/80 READY is displayed and DOS waits for the next input command.

3.3. 4030H Error-already-displayed DOS Error Exit. Dead end routine. Programs concluding with an error that is either already displayed or not to be displayed jump to 4030H. DOS action is the same as for 402DH except as follows:

If CHAINING, chaining is aborted.

If DOS-CALL, the current DOS-CALL level is exited in the same manner as for 402DH, except that C state is set.

3.4. 4400H Performs identical to 402DH.

3.5. 4405H Enter DOS and execute a command. Dead-end routine. DOS is entered, and the stack pointer is set to DOS's own area. HL points to a command, terminated by a 0DH byte, that DOS is to use as its next command. DOS moves this command to its own 80 byte command buffer and then executes it.

3.6. 4409H DOS Error Exit. Dead end routine if bit 7 of register A equals 0. Programs terminating with a DOS error jump to 4409H with the DOS error code in register A and bit 7 of register A equal 0. Depending upon DOS's state, the following actions occur:

If CHAINING, chaining is aborted.

If DOS-CALL, the current DOS-CALL level is exited in the same manner as for 402DH exit, except NZ and NC state is set and the DOS error code is in register A. The error msg is not displayed.

Otherwise the DOS error message is displayed, and an exit is taken to 402DH.

A program may CALL 4409H to display an error msg by placing the error code in A and setting bit 7 of register A equal to 1. The appropriate DOS error message will be displayed. On return, only the F register has been altered.

The Model I TRSDOS will print diagnostics if bit 6 of register A equals 0. The Model III TRSDOS displays only the error number if that bit equals 0 and the error message if that bit equals 1. NEWDOS/80 ignores the value of that bit.

Debugging hint. By setting the 4 bytes at 4409H equal to CD 0D 44 C9, the error display routine can be made to invoke DEBUG instead of displaying the error message.

3.7. 440DH Enter DEBUG. User programs have two methods of entering the DEBUG facility: (1) by use of Z-80 instruction RST 30H and (2) by the Z-80 instruction CALL 440DH. When done with the DEBUG facility, DEBUG command G will return to the instruction following the RST 30H or the CALL, provided the PC register was not changed.

3.8. 4410H (447BH in Model III) Enqueue a user timer interrupt routine. Registers AF, BC, DE and HL are altered by this routine. On entry, DE points to the user interrupt routine which must conform to the following format:

1st 2 bytes. Used by DOS as a forward chain pointer. On entry, the two bytes can be any value.

3rd byte. The number of 25ms intervals to pass between invocations of the user's routine. Example, if the routine is to be invoked every second, the 3rd byte must be set = 40 (28H). DOS does not alter this byte.

4th byte. Count down value to the next invocation. On entry, this byte should be properly initialized to a value greater than 0 but less than or equal to the value in the 3rd byte. Every 25ms interrupt, DOS decrements this value. If the result is non-zero, this routine is bypassed for this 25ms interrupt. If the result = 0, the value from the 3rd byte is moved into the fourth byte, registers HL, DE, BC and AF are saved, and the user routine is called at its 5th byte. Any other registers used by the routine must be saved/restored by it. Interrupts are disabled, and the user routine must not re-enable them.

While a user interrupt routine is in the interrupt chain, it must not be al-

tered in any way except by a routine that runs with interrupts disabled; the first two bytes must never be altered.

Model I TRSDOS uses the 4 vectors, 4410H, 4413H, 4416H and 4419H, for its user interrupt routine handling. NEWDOS/80 uses only 4410H and 4413H for non-compatible handling of these routines. Any program using a 25ms interrupt user routine in TRSDOS must be modified to work under NEWDOS/80. This is a major incompatibility between the two Model I systems.

Model III TRSDOS has not yet made any provision for user timer routines, using 4410H - 441BH for other purposes, including HIMEM.

Model III NEWDOS/80 continues with the user timer interrupt routine mechanism used on the the Model I, except that 447BH is the routine enqueue vector instead of 4410H, and in order to continue with 25 ms counting where the Model III clock actually counts in either 30ths or 25ths of a second, a second pass through the user routine check and invocation sequence is done when necessary to bring 25ms counting up with the real clock. If a user routine is being invoked every 25 ms, the routine must be prepared to accept two invocations within the same timer interrupt.

3.9. 4413H Dequeue a user timer interrupt routine. Registers AF, BC, DE and HL are altered. The user interrupt routine (as described in section 3.7) pointed to by register DE is taken out of the 25ms interrupt chain, if it is in the chain. The routine no longer participates in the interrupts and may now be altered at will by the user.

See section 3.8 for TRSDOS incompatibility.

3.10. 4416H Keep drives rotating. If the disk drives are rotating, reselect the current drive, thereby keeping the drives rotating for approximately 2.4 seconds more. Register AF is altered.

This routine does not exist in TRSDOS; see section 3.8 for incompatibility.

3.11. 4419H DOS-CALL. Execute a DOS command and return. This routine is DOS-CALL. DOS does not shift to its own stack area, but instead remains with the user's stack. All registers except AF are saved in the stack and will be restored on return. The command to be executed is pointed to by HL, must be less than 80 characters, must terminate with byte 0DH, and can be anything legal for the current state DOS is in. DOS sets DOS-CALL state, if not already set, saves the current stack pointer, and executes the command. The command can be the invocation of a user program.

DOS-CALL is now legal under CHAINING where it was not in NEWDOS/80 Version 1.

DOS-CALL is the way BASIC executes the DOS command contained within the BASIC statement `CMD"xx"` where `xx` is the DOS command.

The DOS-CALL caller is responsible for assuring that memory conflicts do not arise and that sufficient stack space is available.

Nested calls to DOS-CALL may be executed. Upon exiting from a DOS-CALL level, the return is made to the next outer level. When the outermost level is exited, DOS leaves DOS-CALL state.

If the DOS command invokes a program, that program may use its own stack area, and it must exit using one of the three exits: `402DH`, `4030H` or `4409H`. On exiting, the program may store a 2 byte parameter in `4403H`, `4404H` (17411, 17412 decimal) for use by the caller.

The `4419H` vector is used differently in TRSDOS; see section 3.8 for incompatibility.

See section 4.4 for further discussion of DOS-CALL.

3.12. 441CH Extract a filespec. From the text pointed to by HL, extract a filespec, place it in the area pointed to by DE and terminate it with the byte `03H`. Registers AF, BC and HL are altered.

If the first text character is A - Z or `0 - 9`, or if the first text character is `*` and the next character is A - Z or `0 - 9`, text is moved from the HL area to the DE area until a character that is not `/`, `.`, `:`, A - Z, or `0 - 9` is encountered or until 32 bytes have been transferred. If less than 32 bytes, a `03H` byte is placed after the last byte in the DE area to indicate end of filespec, and a return is made with Z state set. If the filespec is more than 31 characters it is considered improper as discussed in the following paragraph.

If the first character was improper, or if the first character was `*` but the 2nd was improper, a return is made with NZ state set.

On exit, if the terminator/improper byte equals `03` or `0DH`, then HL points to that byte; otherwise HL points to the next byte.

The user will notice that NEWDOS/80 doesn't check for an exact filespec; it leaves this to be done by the OPEN routines, `4420H` and `4424H`.

3.13. 4420H Open a FCB to a new or existing disk file. Conditions 3.1.A and B hold. The entry requirements are the same as for `4424H`, which is executed immediately as a subroutine to this routine. If `4424H` is successful in opening an existing file, no further action is required here, and an exit is taken with Z and NC states set. If the file was not found, this routine proceeds to create the file.

If the filespec in the FCB pointed to by register DE specifies an explicit

drive number and the diskette mounted on that drive has a free FDE, the file is created on that diskette whether or not the diskette actually has any free space. If the filespec did not specify a drive number, the system starts searching mounted diskettes, starting with the drive number specified by SYSTEM option AO and preceding through higher numbered drives until a diskette with a free FDE is found. If a free FDE is not available, the file cannot be created, and the error exit is taken.

Creating a file consists of converting a free FDE to a FPDE. This entails inserting the name and name extension (if any), encoding the password (if any) as both the update and access passwords, storing the LRECL (0 means 256) from register B, setting the EOF equal to 0, setting access level as FULL, and marking the file non-system, non-invisible. No diskette file space is assigned to the file at this time; in fact, DOS doesn't even look to see if the diskette has any free space. Note, though the LRECL is stored in the FPDE during file creation, it is never used. Each subsequent open of the file uses the LRECL provided in register B.

After the file is created, the DOS routine at 4424H is called to perform the OPEN. On exit after a successful file create and open, Z and C states are set.

3.14. 4424H OPEN a FCB to an existing file. Conditions 3.1.A and B hold. On entry, register DE points to a FCB containing the filespec for the file to be opened, HL points to a 256 byte buffer to be used during disk sector reads and writes for this FCB, and B contains the LRECL (0 = 256). If an explicit drive number was specified in the filespec, the search for the file is limited to that drive; otherwise the search starts with drive 0 and proceeds to higher drives until a file with the specified name and name extension is found. If no file is found, the error exit is taken.

If passwords are enabled and the file has non-null passwords, then an error exit is taken if the filespec does not contain either the update or the access password. If passwords are disabled or the file has no passwords or the update password is specified, the FCB's access level is set to FULL; otherwise the access level from the FPDE is placed into the FCB to limit the type of access for this file.

The FCB is converted from containing the filespec to containing information about the file, which will be used while the FCB is open to reduce the amount of directory I/O which would otherwise be required. The conversion entails copying the EOF and the 1st 4 extents from the FPDE, storing the LRECL from register B, setting bit 7 of the FCB's 2nd byte equal to 1 if LRECL is not equal to 0 (to indicate logical record processing), setting NEXT equal to 0, storing the drive number and the FPDE's DEC code, storing the 256 byte buffer pointer from register HL, setting the access level, setting bit 5 of the FCB's 2nd byte equal to 1 to indicate that the buffer does not contain the current, sector and setting bit 7 of the FCB's 1st byte equal to 1 to indicate that the FCB is open.

3.15. 4428H CLOSE a FCB. Conditions 3.1.A, B and C hold. This routine dissolves the connection between the FCB and the file. If bit 4 of the FCB's 2nd byte equals 1, the FCB's buffer is written to disk like a 4439H call. If the FCB's EOF is different from that in the FPDE, the FPDE is updated for the new EOF. If the file has excess granules beyond EOF and if automatic space deallocation is allowed, the excess granules are released. The FCB is then converted back to contain a filespec consisting of the file name, name extension (if non-blank) and the drive number. This filespec can be used later to re-open the file, provided a password is not required.

3.16. 442CH Kill the FCB's associated file. Conditions 3.1.A, B and C hold. The file associated with the FCB is killed in the same manner as for DOS library command KILL (see section 2.27). The FCB is set to all zeroes.

3.17. 4430H Load a program file. Conditions 3.1.A and B hold except the registers AF, BC and HL are altered and on exit HL (and 4403H - 4404H (17411 - 17412 decimal)) contain the program's entry address. On entry, register DE points to a FCB containing the program file's filespec. The load is done the same as for DOS library command LOAD (see section 2.32).

3.18. 4433H Load and commence execution of a program file. Dead end routine. On entry, DE points to a FCB containing the program file's filespec. Registers AF and BC are altered; all other registers are passed on unchanged to the program when its execution begins. The file open, load and commence execution are done the same as when DOS executes a command that is not a library command, excepting that there is no default name extension. If an error occurs during the open or load, DOS exits to 4409H. If DEBUG is active (see section 2.17), DEBUG is entered just before the program commences execution.

3.19. 4436H READ a disk sector or move a logical record from the FCB's buffer to the caller's buffer. Conditions 3.1.A, B and C hold.

If bit 7 of the FCB's 2nd byte equals 0, the sector represented by the high two bytes of the NEXT field is read into the FCB's buffer and, if no error or if error code 6 (sector read protected), the NEXT field is advanced 256 bytes. If an error other than code 6 occurs, the NEXT field is not advanced, meaning the user can retry to read the same sector.

If bit 7 of the FCB's 2nd byte equals 1, then a logical record of length equal to the FCB's LRECL (where 0 means 256) is moved from the FCB's buffer to the buffer pointed to by register HL on entry. As each byte is moved, the NEXT field is incremented. When the FCB's buffer is empty, the next file sector is automatically read into it and byte movement continues. If an error occurs,

including error code 6, the logical record move terminates, leaving NEXT advanced for the number of bytes moved.

If bit 1 of the FCB's 1st byte equals 1, the NEXT and EOF fields are considered RBA's within the diskette rather than within a file, thus giving the user the capability to read a diskette, rather than a file. The use of bit 0 of the FCB's first byte is defined in section 3.20 below. DOS routines 0013H, 001BH, 4439H, 443CH and other routines that indirectly read or write sectors also operate as such if any of these two bits are on. The use of these 2 bits is incompatible with TRSDOS.

One incompatibility between NEWDOS and TRSDOS occurs when the program reads the EOF from the FCB to determine the number of bytes in the file. However, in many cases the user does not have to know what the EOF is. Instead, for both TRSDOS and NEWDOS, the user can read the file sector by sector, waiting for either of the two EOF errors. If the error code is 1CH (END OF FILE ENCOUNTERED), then the file ends on a sector boundary and the last sector read successfully was the file's last. If the error code was 1DH (PAST END OF FILE), then the last sector successfully read was also the file's last, but was only a partial sector with the value in FCB+8 equaling the number of bytes in that sector belonging to the file. Remember, this is true for both TRSDOS and NEWDOS; thus the same code can work for both.

3.20. 4439H WRITE without verify a sector to disk or move a logical record from the caller's buffer to the FCB's buffer. Conditions 3.1.A, B and C hold.

If bit 7 of the FCB's 2nd byte equals 0, the disk sector as defined by the NEXT field is written with the contents of the FCB's buffer. Unless VERIFY is on (see section 2.48), verify read is not done. If no error, and if the lower order byte of NEXT equals 0, the NEXT field is advanced 256 bytes. Whether or not NEXT was advanced, if NEXT now exceeds EOF or if bit 6 of the FCB's 2nd byte equals 0, EOF is set equal to NEXT. If an error occurred, NEXT is not altered, thus allowing the user to retry to write the same sector.

If bit 7 of the FCB's 2nd byte equals 1, a logical record of length equal to the FCB's LRECL (0 means 256) is moved from the caller's buffer, pointed to by register HL on entry, to the FCB's buffer. With each byte's move, NEXT is incremented, and if NEXT now exceeds EOF or if bit 6 of the FCB's 2nd byte equals 0, EOF is set equal to NEXT. When the FCB's buffer fills, the buffer is written to the appropriate disk sector with verify read and then the logical record move continues, filling in the FCB's buffer for the next file sector. Whenever an error occurs, the logical record move terminates, leaving NEXT advanced for the number of bytes moved.

Bit 1 of the FCB's 1st byte functions as described in section 3.19. If bit 0 of that byte equals 1, then sectors are written protected (error code 6 on sector read).

If a verify read is done after the write of a protected sector, error code 6 is not returned to the caller as an error.

A significant incompatibility with TRSDOS lies in the fact that when a sector

is written to disk in NEWDOS/80 and the low order byte of NEXT is non-zero, NEXT is not advanced by 256 bytes. In this case, NEWDOS/80 assumes that the caller is writing the last sector of the file (though it need not be) that is only partially full, and that NEXT already is the proper RBA value for EOF (if EOF is to be updated by the write).

One incompatibility between NEWDOS and TRSDOS is in setting the final EOF for a file that is written sector by sector but usually does not end on a sector boundary. However, if the program knows when it is about to write the last sector, whether partial or full, and can store the desired low EOF byte value in FCB+5 just before writing that last sector, both TRSDOS and NEWDOS will exit from that write with the same EOF. Thus, in this instance, the same program code will work for both TRSDOS and NEWDOS, and no incompatibility exists.

3.21. 443CH This routine is identical to 4439H, except that a verify read is always done after a sector write.

3.22. 443FH Position FCB to start of file. Conditions 3.1.A, B and C hold. If the FCB has a sector awaiting write (bit 4 of FCB 2nd byte = 1), it is written as a 4439H call. The FCB NEXT field is set = 0. Bit 5 of FCB 2nd byte is set = 0 to indicate the buffer does not contain the current sector.

3.23. 4442H Position FCB to a specified file record. Conditions 3.1.A, B and C hold. The NEXT field is set to the RBA of the logical record whose relative record number (0 = the first record) is in register BC upon entry. If the new NEXT is in the same sector as the old NEXT, the status of the current sector is not changed (i.e., the sector is not written to disk if bit 4 of the FCB 2nd byte equals 1). If the new NEXT is not in the same sector as the old NEXT, then (1) if bit 4 of the FCB 2nd byte equals 1, the old sector is written back to disk, and (2) bit 5 of the FCB 2nd byte is set to 1 to indicate that new sector has not yet been read into the buffer.

3.24. 4445H Position FCB back one record. Conditions and performance are the same as 4442H except that the NEXT field is reduced by the LRECL.

3.25. 4448H Position FCB to EOF. Conditions and performance are the same as 4442H except that the NEXT field is set equal to the EOF field.

3.26. 444BH Allocate file space. Conditions 3.1.A, B and C hold. If the file sector represented by the two high order bytes of the FCB's NEXT field is not already allocated to the file, the granule containing it is allocated along with the granules for any lower sectors for the file that are not yet allocated. This allows the programmer to allocate file space before it is actually needed, and is especially valuable when it is necessary to know that a sector can be written before any data is placed in the buffer. If a file's size can be predetermined before being written (such as is done in COPY), pre-allocating the necessary granules saves considerable time over allocating the granules as the file write proceeds.

This address is defined differently in TRSDOS.

3.27 444EH Position FCB to the specified XBA. Conditions and performance are the same as for the 4442H call except the new NEXT position value is taken from the registers H, L and C where H contains the high order and C the low order values.

This address is defined differently in TRSDOS.

3.28 4451H Write the EOF value from the FCB to the directory. Conditions 3.1.A, B and C hold. If the EOF value in the FCB differs from that in the file's FPDE, the FCB's EOF value is written into the FPDE on disk.

This address is defined differently in TRSDOS.

3.29. 445BH Select and power up the specified drive. Conditions 3.1.A and B hold. On entry, register A contains a drive number. That drive becomes the current drive, is selected and, if necessary, powered up.

3.30. 445EH Test for mounted diskette. Conditions and performances is the same as for 445BH excepting that, in addition, the drive is tested to determine if a diskette is mounted and is rotating. If this rotation test fails, error code 08, DEVICE NOT AVAILABLE, is returned.

3.31. 4461H *name routine enqueue. Register HL points to a user routine in main memory to be chained in the chain of user logical routines. The first 12 bytes of the routine are defined as follows:

4 bytes reserved for use by DOS only.

8 byte logical routine name field containing the 1 - 8 character name of the routine, padded on the right with blanks.

If a routine with the same name already exists in the queue, FILE ALREADY EXISTS error code is returned with NZ set. Otherwise the routine is enqueued, and exit taken with Z state set. HL, DE, BC and AF are altered by this function. This function is new with NEWDOS/80.

Subsequently, whenever a DOS command of the form *name1 or *name1,parameters is executed, DOS searches its queue for a routine named name1, sets HL pointing to the parameters, if any, and jumps to the routine's 13th byte. When the routine concludes, it should exit via 402DH, 4409H, or 4030H. The routine may use all registers, and can use the two bytes at 4403H - 4404H to receive or pass back a parameter. If the logical routine name1 does not exist in the queue, FILE NOT IN DIRECTORY error code is returned with NZ set.

3.32. 4464H *name routine dequeue. HL points to a logical routine as defined in section 3.31. If the routine is not in DOS's logical routine queue, this function exits with FILE NOT IN DIRECTORY error code in register A and with NZ set. Otherwise, the routine is dequeued, meaning that subsequent *name1 commands naming it will abort, displaying FILE NOT IN DIRECTORY. Registers HL, DE, BC and AF are altered by this function. This function is new with NEWDOS/80.

3.33. 4467H Send message to the display. Condition 3.1.A holds. The message bytes pointed to by HL up to and including a 0DH byte (EOL) or up to but not including a 03H byte (EOM) are sent to the display.

3.34. 446AH Send message to the printer. The same as 4467H except the message is sent to the printer.

3.35. 446DH Convert clock time to HH:MM:SS character format. The current clock value at Model I locations 4041H - 4043H (Model III locations 4217H - 4219H) is converted to HH:MM:SS character format and stored in the 8 bytes pointed to by HL. Registers AF, BC, DE and HL are altered. On exit, HL points to the next byte after the HH:MM:SS field.

3.36. 4470H Convert the date to MM/DD/YY character format. This routine is the same as 446DH, except the date value at Model I locations 4044H - 4046H (Model III locations 421AH - 421CH) is converted to MM/DD/YY format.

3.37. 4473H Insert default name extension into filespec. If the file-spec pointed to by register DE has no name extension, insert the 3 characters pointed to by HL as its name extension. The resulting filespec cannot exceed 31 characters. Registers AF and HL are altered.

3.38. 0013H Read a byte from a disk file. This is DOS's single byte read routine even though it starts in ROM. Conditions 3.1.A, B and C hold. If the disk sector containing the NEXT byte of the file is not in the FCB's buffer, it is read into there. The byte is then placed into register A for use by the caller. The FCB's NEXT field is incremented.

3.39. 001BH Write a byte to a disk file. This is DOS's single byte write routine, even though it starts in ROM. Conditions 3.1.A, B and C hold. If the disk sector corresponding to the FCB's NEXT position is not in the FCB's buffer, it is read into the buffer, unless NEXT is on a sector boundary and is equal to EOF. The byte in register A on entry is placed into the buffer, and NEXT is incremented. If the buffer is now full, the sector is written to disk as if a 443CH call.

3.40. 447BH For Model III only, performs the same function as call 4410H does for the Model I (see section 3.8). For the Model III, 4410H must not be used.

4. DOS FEATURES.

This chapter discusses DEBUG, MINI-DOS, CHAINING, DOS-CALL, JKL and asynchronous execution. DEBUG, DOS-CALL and asynchronous execution are primarily of interest to machine language programmers and those interested in Z-80 code. Other users should make a quick reading of DEBUG and DOS-CALL as they are frequently referred to elsewhere in the manual. MINI-DOS and JKL can be used immediately by everyone. CHAINING can be very complex; novice users will want to test out the chaining concept by using the BASIC program CHAINBLD/BAS to first inspect the sample chain file CHAINTST/JCL and then to create some elementary chain files.

4.1. DEBUG Facility.

As an aid primarily for the machine language programmer but also for use by higher level language programmers, NEWDOS/80 has the DEBUG facility for interrupting current execution, inspecting memory, altering memory, inspecting disk, altering disk, single step execution, etc.

DEBUG can be entered in three ways:

1. Simultaneously depressing the three keyboard keys 1, 2 and 3. In order for this 123 action to work the follow conditions must be met.
 1. SYSTEM option AB = N.
 2. SYSTEM option AE = Y.
 3. Either (1) interrupts are enabled or (2) the main program is awaiting keyboard input via the standard keyboard input routine and SYSTEM option AJ = N.
 4. DOS must not be currently using its overlay area (main memory locations 4D00H - 51FFH).
 5. DOS must not have its overlay inhibit enabled.
2. Executing either a RST 30H or a JP 440DH or a CALL 440DH Z-80 instruction.
3. Automatically at, but before, a machine code program commences execution if DEBUG has been turned on via DOS command DEBUG (see section 2.17).

Upon entry, the DEBUG facility will (1) save all registers in the interrupted program's stack, (2) use the next stack locations for its own operations, (3) disable any stops that may have been set on its last exit, (4) display memory using mode and locations as remembered from its last exit, and (5) display the cursor in the lower right hand corner of the display to indicate that the DEBUG facility is awaiting an input command.

All commands, even the single character commands, to the DEBUG facility must terminate with ENTER. If an error is made in keying in a command but before ENTER is depressed, simply backspace over the incorrect characters and type in the correct ones. If desired, the command may be purged before ENTER by keying

shift left arrow.

Both the X and S displays display memory 16 bytes per display line, both in hexadecimal and in character format. If SYSTEM option AI = Y, character formats will include lower case letters.

When DEBUG encounters an error condition, it displays 'ERROR' and waits for the user to acknowledge the error which is done by pressing ENTER to clear the error state.

The DEBUG facility commands are as follows. Wherever numeric values are used, they are always hexadecimal values without the suffixed H unless otherwise specified.

X The DEBUG facility shifts to X display mode, if not already there. The X display contains 15 lines. The 1st through 4th lines contain the 1st 64 byte memory area display. The 5th line displays the interrupted/replaced contents of Z-80 registers AF, BC, DE and HL. The 6th through 9th lines contain the 2nd 64 byte memory area display. The 10th line contains the interrupted/replaced contents of Z-80 registers AF', BC', DE' and HL'. The 11th through 14th lines contain the 3rd 64 byte memory area display. The 15th line contains the interrupted/replaced contents of Z-80 registers PC, SP, IX and IY. The displays for registers AF and AF' also include a bit mask for the associated F register, with an alphabetic character if the bit equals 1 (state set) and a - if the bit equals 0 (state not set). The meanings of the bits (7 - 0) are:

7. S = minus sign
6. Z = zero
5. I = unused bit
4. H = half-carry
3. I = unused bit
2. P = even parity or overflow
1. N = subtraction
0. C = carry

Using the X display allows the user to track the registers and three separate memory areas at one time.

S The DEBUG facility shifts to S display mode, if not already there, using X display's 1st memory area's base address rounded down to a 256 byte page boundary as the S display's base address. The S display displays 256 bytes of memory, using 16 display lines.

[n]Daddr1 If in S display mode, the 256 byte block containing addr1 is displayed; if n is specified, the base address of the the specified area is changed, but the display won't change since DEBUG is in the S display mode. If in the X display mode, addr1 becomes the base address for the specified area: 1 if n not specified, 2 if n equals 2, and 3 if n equals 3. Examples:

1. D7080 displays the contents of locations 7000H - 70FFH if DEBUG is in S display mode. If in X display mode, display area 1 will display the contents of locations 7080H - 70BFH.

2. **3DFFC0** If **DEBUG** is in **X** display mode, display area 3 will display the contents of locations **FFC0H - FFFFH**. If in **S** mode, the new area 3 address is remembered, but the display is not changed.

[n]; If in **S** display mode and **n** not specified, the **S** display is advanced to the next 256 byte block. If in **X** display mode, the specified 64 byte display area is advanced 64 bytes: area 1 if **n** not specified, area 2 if **n** equals 2, and area 3 if **n** equals 3.

[n]- If in **S** display mode and **n** not specified, the **S** display is retarded to the next lower 256 byte block. If in **X** display mode, the specified 64 byte display area is retarded 64 bytes: area 1 if not specified, area 2 if **n** equals 2 and area 3 if **n** equals 3.

Maddr1 The **DEBUG** facility shifts to **S** display mode, if not already there, displays the 256 byte block containing **addr1**, enters modify mode and displays a blinking cursor over the hex digit next to be changed. Pressing a key **0 - 9** or **A - F** causes that hex digit to be replaced in memory and the cursor advanced one position. Pressing right arrow or space advances the cursor one position without memory change. Pressing left arrow retards the cursor one position without memory change. Pressing shift left arrow retards the cursor 4 hex digits without memory change, and pressing shift right arrow advances the cursor 4 hex digits without memory change. Pressing up arrow moves the cursor up one display line without memory change, and pressing down arrow moves the cursor down one line without memory change. The cursor cannot be advanced or retarded outside the current 256 byte page. Pressing **ENTER** terminates modify mode. Any other key terminates modify mode and raises **ERROR** state.
Example:

M6314 **DEBUG** is shifted to **S** mode, if not already there. The contents of **6300H - 63FFH** are displayed, and a blinking cursor is displayed over the first hexadecimal digit of byte **6314H**. The operator may now key in replacement hexadecimal digits and/or move the cursor around within the displayed 256 byte page.

F[addr1][,hb1][,hb2][,hb3][,hb4] Starting at main memory location **addr1**, find an occurrence of the specified series of hexadecimal bytes. **hb1**, **hb2**, **hb3** and **hb4** are each 2 hex digits representing a hexadecimal byte. If any of **hb1**, **hb2**, **hb3** or **hb4** are specified, **addr1** must also be specified. If none of **hb1**, **hb2**, **hb3** or **hb4** is specified, then the series of hexadecimal bytes last used by an **F** command is used. If **addr1** is not specified, then the memory location +1 of the last **F** command match is used, thus allowing the user to find successive occurrences of the initially specified byte string. Main memory is searched for an occurrence of the search string of bytes. If found, the address of the first of the matching bytes less **20H** is made the **X** display's 1st area's base address. This causes the matching byte string to appear at the start of line 3 of the **X** display. If not found, **X** display's 1st area's base address is set = **0FFE0H**. Example:

F5200,CD,24,44 will start at main memory location **5200H** and search for the first occurrence of the three bytes mentioned. Subsequently, the command **F** will search for the next occurrence of the same three bytes.

If a match takes place in the current stack area, it is possible that the matching bytes will be gone from the stack before they can be displayed, thus causing the user to think DEBUG has stopped erroneously. Further, DEBUG stores the comparison copy of the bytes in the 51xxH region of memory; so if that area is searched, a match will be found upon the compare bytes themselves.

I Execute the interrupted program's current instruction and then re-enter the DEBUG facility. This allows the user to single step execute the interrupted program. The user may then observe the changes (or havoc) wrought by each instruction. Single stepping has some pitfalls however:

1. A full timer interrupt sequence may also execute during the single step.
2. Single stepping is not allowed if the instruction location is less than 5200H or jumps to or returns to a location less than 5200H.
3. The DEBUG facility uses the 2-80 instruction RST 30H to trap for the return to DEBUG after the single instruction has been executed. Therefore, the single stepped instruction should not branch upon itself and should not refer to the next byte following itself as the source or destination of data.

C Performs identical to I except that if the single stepped instruction is a CALL, the entire called routine is executed during the so called single step.

Rdreg,value1 Replaces the interrupted contents of double register dreg with the value value1. Examples:

RDE,C000 replaces the previous contents of register DE with the hexadecimal value C000.

RHL',7100 replaces the previous contents of register HL' with the hexadecimal value 7100.

Ldnl,drrl Relative sector drrl of the diskette mounted on drive dnl is read into DOS's system sector buffer (Model I locations 4200H - 42FFH; Model III locations 4300H-43FFH). DEBUG then shifts into S mode and displays the sector's contents in that buffer. drrl is a decimal (yes, decimal) value. The user is responsible for providing correct values for dnl and drrl as DEBUG makes no checks. Once the sector's contents are in the buffer, the user may treat those bytes as normal main memory, may search them using the F command and may alter them by using the M command. However, altering the sector in the buffer does not alter it on the diskette; the WR command must be executed to store the sector back onto the diskette. Since almost all NEWDOS/80 system programs use the system sector buffer for their diskette reads and writes, the user should not use the L or WR commands if the interrupt took place in DOS (in this case the interrupt address is usually below 5200H but be careful of COPY, FORMAT, etc.) and he/she intends to continue the interrupted program's execution. Warning !!! If passwords are enabled, commands L and WR will be rejected and ERROR state entered. Example:

Li,150 loads the 151st sector of the diskette currently mounted

on drive 1 into the system sector buffer.

WRdnl,drsl The contents of the system sector buffer (4200H-42FFH on the Model I; 4300H-43FFH on the Model III) are written to relative sector drsl of the diskette mounted on drive dnl. The parameter definitions and restrictions in the use of command L also apply to command WR. If the specified diskette sector is read protected, it is written read protected. Warning!!! If you specify the wrong values for dnl and drsl, you will write the buffer's data to the wrong sector and create for yourself a lot of trouble. Be sure you know what you are doing!!! Example:

WR1,150 writes the current contents of the system sector buffer to the 151st sector of the diskette currently mounted on drive 1.

Q Exit DEBUG to DOS READY. The previous program is forgotten. If the system was in DOS-CALL or MINI-DOS, that state is purged.

G[addr1][,addr2][,addr3] Restore the registers and resume program execution. If addr1 is specified, execution resumes at that location; otherwise it resumes at the memory address specified in the PC register. If addr2 is specified, a breakpoint is set for that location by replacing the byte at that location with the single byte 2-80 instruction RST 30H which when executed will cause the DEBUG facility to be reentered. The replaced byte is not lost (it is restored upon DEBUG re-entry), but it is unavailable during the period from DEBUG exit until DEBUG entry. Addr3 is a 2nd breakpoint address. When addr2 is specified, it is not required that addr1 be specified. Addr2 and addr3 must not be less than 5200H. Examples:

G7000,8400,8425 will set a breakpoint at main memory locations 8400H and 8425H, and will restore the registers and commence program execution at main memory location 7000H.

G will restore the registers and commence program execution at the main memory location saved in the PC register. If the interrupted program was awaiting input (such as DOS READY or BASIC READY) at the time of interrupt, it is still awaiting input. Even though no cursor is re-displayed (as DEBUG does not remember the cursor state), the user may proceed with key input.

4.2. MINI-DOS.

There are many times when, during the execution of a main program, the operator would like to interrupt the main program, execute one or more of the DOS library commands and then resume main program execution without any change having occurred to the main program's state during the interruption. NEWDOS/80 provides such a facility, called MINI-DOS.

In order to use MINI-DOS the following conditions must be met:

1. SYSTEM option AB = N.
2. SYSTEM option AF = Y.
3. Either (1) interrupts are enabled or (2) the main program is awaiting keyboard input via the standard keyboard input routine and SYSTEM option AJ = Y.

With these conditions satisfied, the simultaneous depression of the keys D, F and G will cause the main program to be interrupted, its register state saved, and MINI-DOS state to be entered. MINI-NEWDOS/80 READY will be displayed. CAUTION, pressing DFG is not recommended while disk I/O is in progress as a fatal error to the diskette is possible; if exit from MINI-DOS is via MDBORT, then there's no problem.

From MINI-DOS state, the operator may execute any of the DOS library commands except APPEND, CHAIN, COPY and FORMAT. Non-library commands or programs may not be executed under MINI-DOS.

When ready to return to the main program, enter the DOS library command MDRET. If the cursor was displayed before DFG, it will be redisplayed. The main program's register state is restored, and the main program resumes its execution. If the main program was awaiting keyboard record input and a partial record was already inputted, that partial record is still in the buffer even though it is not displayed. If the main program was awaiting keyboard input, whether or not any characters had been entered, upon exit from MINI-DOS, the main program is still waiting. Don't be timid; start keying. If the main program was not awaiting keyboard input, it will go on about its business.

If the main program is not to be resumed, entering the DOS library command MDBORT will terminate both MINI-DOS and the main program, with the system going to normal DOS READY.

Though COPY may not be used under MINI-DOS, simple file copies can be done using DOS library command MDCOPY.

NEWDOS/80 is unable to eliminate all cases where the triple key depression results in one or more of the keys being transmitted as input to the main program. This is especially so when system option AJ = N. These spurious keys usually show up on exit from MINI-DOS. The user should back space over them, and should not use triple key depression when the main program is in text overwrite mode.

As an example of MINI-DOS use, start at DOS READY and execute the following:

```
BASIC
10 PRINT "HELLO": GOTO 10
RUN
```

The BASIC program is now in an endless loop printing the word HELLO on the display. Simultaneously press the D, F and G keys. The BASIC program's execution is interrupted, and the message MINI-NEWDOS/80 READY appears on the display. Now execute the following DOS commands:

```

DIR 0
FREE
CLOCK
CLOCK,N
LIB
SYSTEM,0
PDRIVE,0
MDRET

```

The MDRET command caused the exit from MINI-DOS, and the BASIC program continued execution where it was interrupted. Now, while we have a test program executing, let's try out the entry to DEBUG. Simultaneously depress the 1, 2 and 3 keys. Once again, the BASIC program's execution is interrupted. The DEBUG routine is now active, and the display is loaded with either the X or the S DEBUG display format. Now type in G followed by ENTER. DEBUG is exited, and the BASIC program continues execution. Now, press DFG again to get back into MINI-DOS. Once there, execute DOS command MDBORT. This causes DOS to forget about the interrupted program, to exit MINI-DOS and go to normal DOS READY.

4.3. CHAINING.

The DOS commands CHAIN and DO are simply different spellings of the same command; therefore, in this section, only the command word CHAIN will be used where in reality either one can be used.

For most TRS-80 users there are functions which use the same series of DOS commands and/or program responses, and for each of these functions it would save a lot of key stroking, operator time and errors if this keyboard character sequence could be saved in a disk file to be called upon when the operator wishes to execute a specific function.

For example, suppose that each time a reset/power-on is done, the operator keys in the following commands and program responses:

HIMEM,0E800H	Execute DOS command HIMEM
PROGRAM1	Execute program named PROGRAM1
Y	Response to PROGRAM1's 1st query.
50	Response to PROGRAM1's 2nd query.
PROGRAM2	Upon PROGRAM1'S completion, execute program PROGRAM2
1	Response to PROGRAM2's 1st query
WORKF1	Response to PROGRAM2's 2nd query
WORKF2	Response to PROGRAM2's 3rd query
BASIC,RUN"BASPGM1/BAS"	Upon PROGRAM2's completion, enter BASIC and run BASIC program BASPGM1.
Y	Response to BASPGM1's 1st query.

Subsequent input to BASPGM1 is assumed to vary from run to run, is therefore not part of the standard sequence and of no concern here. What is of concern is that this same sequence of keyboard input must be keyed in each time.

However, if this keyboard character sequence was placed in a disk file named, for example, XXX/JCL, then this keyboard input sequence can be triggered to occur by executing the DOS command:

```
CHAIN,XXX/JCL
```

The execution of this CHAIN command (see section 2.9) causes keyboard input to come from the file XXX/JCL, starting at the file beginning and transmitting characters as keyboard input when requested by DOS or the executing program. The characters are transmitted upon request until the end of the file is reached, at which time keyboard input is switched back to the normal keyboard. Thus, having keyed in the CHAIN command, the operator may sit back and wait until after BASPGM1 has received its first response instead of having to key in the various commands and responses as needed.

Further, since this keyboard sequence is to be invoked at reset/power-on, the operator may avoid even the keying in of the CHAIN command by setting that command up beforehand as the AUTO command (see section 2.4). This is done by executing the DOS command:

```
AUTO,CHAIN,XXX/JCL
```

Now, when reset/power-on is done, the CHAIN command is automatically executed, and the operator has nothing to do until after program BASPGM1 has received its first response.

Both this process of causing keyboard input to be taken from a disk file and the associated operational mode that NEWDOS/80 is in during that time is called chaining. The files that contain the keyboard character sequences are called chain files.

NEWDOS/80 is not concerned with the creation of chain files; NEWDOS/80 only uses them in response to a CHAIN command (see section 2.9). It is up to the user to decide what keyboard character sequence is to be contained in a chain file, and it is left to the user to build the chain files he/she needs. Probably the simplest way is to use either SCRIPSIT or PENCIL and store the resulting file in ASCII mode. For users that do not have either SCRIPSIT or PENCIL, a BASIC program named CHAINBLD/BAS has been included on the NEWDOS/80 diskette to create and edit simple chain files. To build chain files having other than printable keyboard characters, some other chain file build program must be used.

Chain file creators must remember that, except for any ./ type chaining control records (discussed below), the chain file must contain exactly the keyboard character sequence that DOS or the current executing program expects. Chaining does not guess for you.

During the processing of a chain file, NEWDOS/80 operates in one of two modes, depending upon the setting of SYSTEM option AT.

If SYSTEM option AT = Y, then all requests for keyboard input via the standard keyboard routine are honored from the chain file. This applies to both a request for a record (such as INPUT or LINEINPUT in BASIC) and

for a single character (such as INKEY\$ in BASIC).

If SYSTEM option AT = N, then only requests for full records (such as INPUT or LINEINPUT in BASIC) via the standard keyboard routine at ROM location 0040H are honored from the chain file. Requests for a single byte (such as INKEY\$ in BASIC) are honored from the keyboard.

On the NEWDOS/80 Version 2 diskette the user has been provided with (1) the BASIC program CHAINBLD/BAS with which the user can build simple chain files and (2) a sample chain file named CHAINTST/JCL. The instructions for using CHAINBLD/BAS are given in section 6.6. Here, all we want to do is use CHAINBLD/BAS to look at the chain file CHAINTST/JCL. With computer at DOS READY, enter the follow responses:

BASIC RUN "CHAINBLD/BAS:0"	start CHAINBLD/BAS executing
2	chooses file load option
CHAINTST/JCL:0	filespec of file to be loaded into memory
L ;	list first page of chain file
;	list next page of file
U	return to edit menu
Q	return to main menu
5	exit from the program

At each step, study carefully what is displayed. This chain file contains a good example of commands, program responses, and chaining control records. **Don't be alarmed at CHAINBLD's 10 second initialization time.** Once you have carefully studied the chain file, exit back to DOS and execute the chain file using the DOS command:

CHAIN,CHAINTST:0

Since most chain character sequences are short, usually less than 100 characters, it is a shame to allocate a full granule of 1280 bytes for each such sequence. Therefore, NEWDOS/80 allows a chain file to be divided into sections with the keyboard character sequence making up each section preceded by a section identification record (see ./0 discussion below) excepting that the first section of a chain file need not have a section ID record. If the chain file section that is to be accessed by a CHAIN command is preceded by a section ID record, the CHAIN command must specify the section ID as well as the file.

During chaining, when either end of file or end of section is encountered, NEWDOS/80 terminates chaining without notification and sets keyboard input back to the normal keyboard routine. This also happens if either DOS command CHRON,N or the chaining ./5N function (see ./ below) is executed. If the current program was awaiting input, the operator will have no indication of this change except that all activity will stop. Usually, the operator knows what will be the first display after chaining terminates; so he/she is ready for it.

If a DOS recognized error occurs during chaining, chaining will be terminated with the message CHAINING ABORT displayed to inform the operator.

If the DOS command CHAIN is executed while chaining, chaining simply forgets the previous file and starts chaining within the new file, which may well be the same file and section as the previous one. CHAIN commands are not nested, and there is no RETURN function in chaining.

DOS-CALL is legal during chaining.

During chaining, there are five ways to alter the sequence of keyboard characters.

1. The current executing program may decide to execute a CHAIN or CHNON command via DOS-CALL (CMD"doscnd" in BASIC).
2. A CHAIN command itself may be part of the chain file. However, for the command to be executed, either DOS must be awaiting its next command or the current program executing must be clever enough to detect the CHAIN command record in its normal record processing and execute the CHAIN command via DOS-CALL (CMD"doscnd" in BASIC).
3. An easier method is by having the chain file contain a ./4 type chaining control record (discussed below) at the point where the change of sequence is to occur. Using the ./ allows the chaining sequence to be changed regardless of whether DOS or a user program is in control and the sequence change takes place without notification on the display. The limitation of this type of sequence changes is that chaining cannot shift to a different file.
4. The DOS command CHNON (see section 2.10) may be part of a chain file. Remember, DOS must be awaiting its next command. If CHNON,N is specified, chaining is deactivated (though the chain file is not closed and file position is remembered for a subsequent CHNON,Y or CHNON,D command), and keyboard input next comes from the keyboard. If CHNON,Y is specified and DOS-CALL is active, chaining continues but the current DOS-CALL level is exited.
5. A ./5 type chaining control record (defined below) may be used in the chain file instead of DOS command CHNON. The ./5 record function is executed even if DOS is not awaiting its next command.

If the CHAIN command is executed via DOS-CALL (CMD"doscnd" in BASIC), the programmer must remember that DOS remains in DOS-CALL executing DOS commands from the CHAIN file until either end of file, end of section, command CHNON,N or command CHNON,Y (see section 2.10) is encountered. Thus, if a program wishes to activate chaining but wants to process subsequent chain input itself, then the first characters of that chain file or chain file section must be either CHNON,Y or CHNON,N.

Chaining has six control records that may be placed within a chain file. Each of these records must start with either a one character or a 4 character identification sequence and must end with the EOL (ENTER) character. In NEWDOS/80 Version 1, only the one character record identification was used; in Version 2, it is recommended that the four character record identification be used, as the four characters are all printable and thus visible during chain file create or edit. The record ID characters are not displayed during chaining. These control records cause chaining to perform the action described for each. For each special record defined below, the four character record ID is given first followed by the alternative one character ID value.

1. ./0 or one byte = 128 (80 hex). This identifies a section ID

record, which must be the first record of a chain section, unless the first section within a file is to be unnamed. The rest of the record is the section's ID which is used to match against a CHAIN command's section ID, if it specifies one, or against the section ID specified in a /.4 chain control record. Subsequent file characters until EOF or until but not including the next section ID record are all considered part of this new section. Example:

./0XXXXXX identifies subsequent characters as belonging to chain section XXXXXX.

2. /.1 or one byte = 129 (81 hex). This causes the rest of the record to be displayed, and then the system waits for the user to press ENTER before continuing. This is a built in pause function. Example:

./1MOUNT WORK DISKETTE The message MOUNT WORK DISKETTE is displayed followed by PRESS "ENTER" WHEN READY TO CONTINUE. DOS then waits for the ENTER.

3. /.2 or one byte = 130 (82 hex). The rest of the record is bypassed without further action. This allows the chain file creator/maintainer to place comment records in the file for documentation without them being displayed.

4. /.3 or one byte = 131 (83 hex). The rest of the record is displayed, but no pause is done. This allows the creator/maintainer to display to the operator what is happening. Example:

./3PHASE TWO COMPLETED The message PHASE TWO COMPLETED is displayed. DOS does not wait but instead continues processing chain file input.

5. /.4 or one byte = 132 (84 hex). The rest of the record is a chain file section ID of 31 characters or less. The current chain file is searched for a chain section whose section ID matches that specified in the /.4 record. When found, chaining continues with the first character of that section. If the section is not found, END OF FILE ENCOUNTERED error is displayed and chaining is aborted. Example:

./4XXXXXX Sequential chain character processing shifts within the current chain file to the chain section named XXXXXX (see ./0 example above).

6. /.5 or the one byte = 133 (85 hex). The rest of the record is either the character Y, N or D. Using this one character parameter, a CHNON function is performed. The advantage of using the /.5 function rather than an actual CHNON command is that DOS does not have to be waiting for its next command. The disadvantage is that the chaining state change is more subtle. The /.5 function is not for the novice. Examples:

1. /.5N chaining is deactivated though the file is not closed.
2. /.5Y chaining remains active but the current DOS-CALL level, if any, is exited.

The novice chain file creator will find it easiest to use none of the chaining control records described above. As experience is gained, try using the `./3` record to display a comment and the `./1` record to display a message and wait for ENTER. Next, try using `./0` records to divide a chain file into sections and then the `./4` record to cause chaining to branch around within a chain file.

The chain file creator/maintainer is responsible for assuring that chaining does not create impossible situations for the system or user programs.

During chaining and if SYSTEM option BC = Y, the operator may terminate chaining by holding down the up arrow key, or the operator may force a chaining pause by holding the right arrow key, and may resume chaining by pressing ENTER.

4.4 DOS-CALL.

NEWDOS/80 allows any machine language program to call the DOS routine at 4419H (see section 3.11) to execute a DOS command or user program. This capability is called DOS-CALL. BASIC uses DOS-CALL to execute the `CMD"doscnd"` function.

The calling program builds a DOS command in a buffer and terminates it with a `0DH` byte. With HL pointing to the command, the DOS routine at 4419H (see section 3.11) is called to cause DOS to execute the command after moving it to its own buffer and converting lower case to upper.

If the DOS-CALL is executing a user program, DOS does not check for conflict between the calling program and the called program. It is the responsibility of both programs to avoid conflicts. An example of a user program executing under DOS-CALL is the execution of SUPERZAP under BASIC through the `CMD"SUPERZAP"` function.

Furthermore, the registers cannot be used to pass parameters back and forth between the calling and the called programs. On entry to the called program, however, register HL does point to the command parameters. Also, the two bytes at 4403H - 4404H may be used to pass a 2 byte parameter back and forth.

A user program activated under DOS-CALL may itself use DOS-CALL (be careful not to overflow the stack). DOS-CALLs can be nested, with each call activating a new DOS-CALL level.

Upon return from a DOS-CALL, the calling program must check for three states. If Carry is set, an error has occurred that has already been displayed. If the program is to continue execution, then it must decide what to do. If the program is to terminate, it should exit via a jump to 4030H in case this program was itself invoked by DOS-CALL, which will cause an exit to the next higher calling program with C state set.

However, if the returned state is NZ and NC, a DOS error has occurred that has not yet been displayed and the error code is in the right 6 bits of register A (bits 6 and 7 equal 0). If the calling program is to continue operation, it

can have the error message displayed by calling 4409H with bit 7 of register A = 1; otherwise it should exit via a jump to 4409H with bit 7 of register A = 0. This latter action will cause the error message to be displayed and the system goes to DOS READY unless the calling program was itself invoked by DOS-CALL, in which case the error msg will not be displayed and an exit will be taken to the next higher calling program with register A unchanged and NC and NZ states set.

If the returned state is NC and 2, then the called function completed normally. Since all registers except AF are saved at DOS-CALL entry and restored at DOS-CALL exit, the only way a parameter may be passed back is by using the two bytes at 4403H and 4404H (17411 and 17412 decimal). Actually, the higher unused bytes of the DOS command buffer, 4318H - 4367H, can be used for communication each way in DOS-CALL, but the programmer must understand that DOS moves all commands into that buffer before executing them.

4.5. JKL.

NEWDOS/80 has a small routine for dumping the contents of the display screen to the printer. This feature allows the operator to print information that would otherwise be lost as soon as the display is used for something else.

In order to use JKL, the following conditions must be met.

1. System option AD = Y.
2. Either (1) interrupts are enabled or (2) the main program is awaiting keyboard input via the standard keyboard input routine and system option AJ = Y.
3. DOS must not be currently using its overlay area (main memory locations 4D00H - 51FFH).
4. DOS must not have its overlay inhibit enabled.

With these conditions met, the simultaneous depression of the keys J, K and L will cause the main program to be interrupted, its state saved, and the contents of the display dumped to the printer without any editing except that implied by SYSTEM option AX. If the printer is not ready or drops ready, the system will loop waiting for it and no message will be displayed to the operator.

JKL will substitute a period for each display character that is non-printable as defined by SYSTEM option AX.

Pressing the BREAK key will terminate the JKL function, except if the CPU is hung waiting on the printer.

When the dump is completed, the interrupted program is resumed. The problem of spurious input characters discussed in section 4.2 exists here as well.

In earlier versions of NEWDOS, the JKL routine was always resident in main memory. In Version 2, the JKL routine was very reluctantly moved into a system overlay program, thus making it unusable in certain circumstances where it was usable before. For example, JKL can not be invoked from DEBUG.

4.6. Asynchronous Execution.

NEWDOS/86, like TRSDOS, allows for a very limited form of asynchronous execution. This is accomplished by inserting a user interrupt routine into DOS's 25ms interrupt chain. The DOS routine (see section 3.8) at Model I location 4410H (Model III location 447BH) must be used to insert the routine into the chain, and the DOS routine 4413H (see section 3.9) must be used to take the routine out of the chain. Refer to these two sections for the required format of the user interrupt routine and how it is invoked.

Again, the user is reminded that the use of user interrupt routines under NEWDOS/86 is incompatible with that under TRSDOS.

5. DOS MODULES, DATA STRUCTURES, AND MISCELLANEOUS INFORMATION.

This chapter gives information about the modules on the NEWDOS/80 diskette, about diskette directories and about File Control Blocks. The novice user should read sections 5.1 and 5.4 and leave the other sections for another time.

5.1. Files required on each diskette used with NEWDOS/80.

DIR/SYS 2 - 6 granules. Diskette directory. This file is required on every diskette used with NEWDOS/80 as it contains the control information about all files on the diskette. FORMAT or the format part of COPY creates this file automatically, and DOS updates this file as necessary to add, alter, or delete control information about files on that diskette. The structure of the directory is given in section 5.6. Also see section 5.6.2 for correction to HIT sector code for DIR/SYS.

BOOT/SYS 1 granule. Must occupy the first granule of every diskette. On data diskettes this file serves only to reject an attempt to boot using this diskette in drive 0. On system diskettes, the first sector contains the machine code for loading the DOS system from the drive 0 diskette when a power on, reset or jump to location 0 occurs. On NEWDOS/80 system diskettes, the 2nd sector is a duplicate of the first (required for booting on the Model III), and the 3rd sector contains system control information set up by the DOS commands SYSTEM and PDRIVE. FORMAT or the format part of COPY creates this file automatically.

5.2. NEWDOS/80 DOS System Modules.

The DOS system consists of 14 program modules which execute from three areas. The resident module SYS0/SYS resides in all the non-data areas from 4000H to 4CFFH. The modules SYS1/SYS through SYS5/SYS, SYS7/SYS through SYS9/SYS and SYS14/SYS through SYS17/SYS all share the DOS overlay area 4D00H - 51FFH (only one module at a time can be in that area). SYS6/SYS executes from both the overlay area and the 5200H - 6FFFH area.

SYS0/SYS 3 granules. DOS's resident module loaded by the bootstrap routine and remains permanently in main memory, except for the DOS initialization routines in the overlay area which are overlaid when no longer needed. SYS0/SYS handles DOS initialization, disk I/O, clock interrupts, load of other system modules, keyboard intercept, etc.

SYS1/SYS 1 granule. Interrogates DOS commands.

SYS2/SYS 1 granule. Creates files, opens FCBs, allocates file space, allocates FDEs, encodes passwords and loads users programs to be run. Executor for library commands RENAME and LOAD.

SYS3/SYS 1 granule. Closes FCBs, kills files, insert/deletes entries from 25ms chain. Executor for library commands BLINK, BREAK, CLOCK, DEBUG, JKL, LCDVR, LC, VERIFY and most of PURGE.

SYS4/SYS 1 granule. Displays DOS error messages.

SYS5/SYS 1 granule. DEBUG facility.

SYS6/SYS 7 granules. Executes in 4D00H - 6FFFH. Executor for library commands FORMAT, COPY and APPEND.

SYS7/SYS 1 granule. Executor for library commands TIME, DATE, AUTO, ATTRIB, PROT, DUMP, HIMEM and the 1st part of PURGE, SYSTEM and PDRIVE.

SYS8/SYS 1 granule. Executor for library commands DIR and FREE.

SYS9/SYS 1 granule. Executor for library commands BASIC2, BOOT, CHAIN, CHNON, MDCOPY, PAUSE and STMT. Enqueues and dequeues user logical routines and routes each invocation (see DOS routines 4461H and 4464H in chapter 3).

SYS14/SYS 1 granule. Executor for CLEAR, CREATE, ERROR, LIST, PRINT and ROUTE.

SYS15/SYS 1 granule. Executor for FORMS and SETCOM.

SYS16/SYS 1 granule. Executor for most of PDRIVE.

SYS17/SYS 1 granule. Executor for WRDIRP and most of SYSTEM.

5.3. NEWDOS/80 BASIC Modules.

NEWDOS/80's Disk BASIC enhancements to the TRS-80's ROM BASIC consists of a main resident module and 8 overlay modules. The modules SYS10/SYS through SYS13/SYS and SYS21/SYS execute from DOS's overlay area, 4D00H - 51FFH. The modules SYS18/SYS through SYS20/SYS execute from BASIC's overlay area, 5200H - 56FFH. All of BASIC's modules, except BASIC/CMD, are loaded as needed and must be on the system diskette when needed.

BASIC/CMD 4 granules. Resident module residing in 5700H and up. Executes Disk BASIC's functions. This module need not reside on the system diskette as it may be invoked from a data diskette (like any other program), and once invoked, it is not needed again until BASIC is next invoked.

SYS13/SYS 1 granule. Displays BASIC's error messages and executes 1st part of RENUM. Must be on the system diskette whenever BASIC is active.

SYS12/SYS 1 granule. Executes BASIC direct command REF. Must be on the system diskette if REF will be executed.

SYS11/SYS 1 granule. Executes BASIC direct command RENUM. Must be on the system diskette if RENUM will be executed.

SYS10/SYS 1 granule. Executes BASIC statement's GET and PUT, and must be on the system diskette if either statement is to be executed.

SYS18/SYS 1 granule. BASIC direct statement executor. Must be on the system diskette whenever BASIC is active.

SYS19/SYS 1 granule. Executor for BASIC statements LOAD, RUN, MERGE, SAVE and CMD"F"DELETE. Must be on the system diskette whenever BASIC is active.

SYS20/SYS 1 granule. Executor for a number of disk BASIC statements and usually is the module resident when BASIC is executing a program. Must be on the system diskette whenever BASIC is active.

SYS21/SYS 1 granule. Executor for CMD"O" and must be on the system diskette if CMD"O" will be executed.

5.4. Other Modules on the NEWDOS/80 diskette.

DIRCHECK/CMD A program that checks the directory for errors and list or prints the directory contents. See section 6.4.

EDTASM/CMD An editor/assembler for Z-80 code-source and object code from/to disk or tape. See section 6.5.

DISASSEM/CMD A program that disassembles Z-80 machine code. See section 6.2.

LMOFFSET/CMD A program that reads load modules from disk or tape and writes them to disk or tape. The program optionally (1) assigns new load addresses, (2) appends a pre-execution move-program-to-execution-location appendage and (3) prepares the program to run without DOS. See section 6.3.

SUPERZAP/CMD A program that allows inspection and modification of either disk or main memory. Disk operations are diskette or file oriented. See section 6.1.

CHAINST/JCL A sample chain file created by CHAINBLD/BAS.

CHAINBLD/BAS A BASIC program that creates and edits simple record oriented chain files for subsequent use via the DOS commands CHAIN or DO. See section 6.6.

ASPOOL/MAS H. S. Gentry's automatic spooler program as modified by Apparat for NEWDOS/80. See section 6.7.

5.5. Reduced Sized Systems.

Reduced sized systems can be created, if passwords are disabled, by COPYING the full NEWDOS/80 diskette onto a new diskette and then KILLING the unwanted files. A minimum system to handle open's and close's will consist of 10 granules (BOOT, DIR, SYS0-SYS4). If the DEBUG facility is to be used (including BASIC's CMD"D"), add SYS5. Section 5.2 indicates which additional modules must be added for the various DOS library commands. If BASIC is to be used, section 5.3 indicates which BASIC modules must be added, and section 5.2 indicates which DOS modules must be added if DOS library commands are to be executed via BASIC's CMD"xx" statement.

If the system module loader finds the module's directory entry inactive or encounters an error during loading, then one of the following occurs:

If SYS4 is an active module in the system, then SYSTEM PROGRAM NOT FOUND error will be displayed via a jump to 4409H.

If the jump to SYS4 via 4409H finds SYS4 not in the system, then the Z-80 HALT instruction is executed which on the Model I causes reset and on the Model III stops the computer (the operator must manually press reset).

Modules included in this category are SYS1/SYS thru SYS21/SYS. If any of BASIC overlay modules fail load, the user must carefully execute BASIC * to get back the basic program text.

CAUTION!!! Once a system file has been killed from a system diskette, it cannot be restored by simply copying it from another system diskette. The DOS system loader requires that system file FPDEs be in specific FDE slots in the directory and that all of a system file's space be accounted for in the first extent element. Further, SYS0/SYS must occupy the same granules as it did before kill, and it is recommended for efficient system operation that all other system files also occupy the same granules. Once the FPDE has been properly reconstructed, DOS command COPY can then be used to copy the file's contents.

5.6. Diskette Directory Structure.

For the Model I, NEWDOS/80 and TRSDOS diskettes are interchangeable provided the NEWDOS/80 diskette's directory consists of only 2 granules (see DDGA parameter of FORMAT, section 2.22, and COPY, section 2.14), and is set up for 10 sectors/track, 2 granules/lump and 5 sectors/granule operations (5 sectors per granule is standard for NEWDOS/80). The files on the diskettes may not be operationally interchangeable between the two systems; system modules, BASIC, ELECTRIC PENCIL, SCRIPSIT, etc., definitely are not though the files they manipulate are.

For the Model III, the directories of NEWDOS/80 and TRSDOS diskettes are NOT compatible; a TRSDOS Model III diskette may not be used directly with NEWDOS/80 and NEWDOS/80 diskettes may not be used directly with TRSDOS Model III. If the NEWDOS/80 single density diskette has a directory of Model I standard position

and size, the Model III TRSDOS has a conversion program to copy the data to a Model III diskette. The COPY function of NEWDOS/80, Version 2, also has a way of copying one, some or all files of a Model III TRSDOS Version 1.3 or higher diskette to or from a NEWDOS/80 diskette (see sections 12.1 and 2.14).

NEWDOS/80 makes all FDE's of a diskette, except those for BOOT/SYS and DIR/SYS, available for use; thus, a 2 granule directory on a newly formatted data diskette has 62 FDEs available. NEWDOS/80 allows the directory to be allocated with up to 6 granules during diskette formatting (see DDGA parameter of PDRIVE, FORMAT and COPY), thereby providing for a maximum of 222 available FDEs.

A diskette's directory always starts on a lump boundary and contains the GAT sector followed by the HIT sector followed by 8, 13, 18, 23 or 28 FDE sectors, depending upon the number of 5 sector granules allocated to the directory (see the DDGA parameter of PDRIVE, FORMAT and COPY). The user is encouraged to study the directory structure by use of program SUPERZAP (see section 6.1). The starting lump number of the directory is always contained as a hexadecimal value in the 3rd byte of each diskette's 1st sector; this value is used by DOS to find the directory.

5.6.1. The GAT (Granule Allocation Table) Sector.

The GAT sector is the first sector in the directory and contains the following information:

Granule free/allocated table. Each of relative bytes 00H - 5FH corresponds to a lump and contains the free/allocate status bits for all of that lump's granules. The number of granules per lump is specified by the GPL parameter of PDRIVE and is a value between 2 and 8. The lump's 1st granule's bit is bit 0 (counting from the right), the 2nd granule's bit is bit 1, and so on up to the 8th granule. If the bit equals 0, the granule is free. If the bit equals 1, the granule is allocated or non-existent.

Granule existence table. Relative bytes 60H - BFH correspond to relative bytes 00 - 5FH. If a bit within a byte equals 0, then the corresponding granule for that lump exists and is usable. If the bit equals 1, the corresponding granule does not exist, must not be used and the corresponding bit in 00 - 5FH must equal 1. Actually, though NEWDOS/80 creates these existence bytes during format, it does so only for compatibility with the old style TRSDOS diskettes (where in these bytes were known as lockout bytes). Actually, NEWDOS/80 never sets a granule non-existent. When necessary, the granule existence table is discarded altogether to make additional GAT sector bytes available to the granule free/allocated table.

In order to maximize the amount of diskette space controlled by the GAT sector, NEWDOS/80 Version 2 allows the free/allocated section of the GAT to extend through, and thereby replace, the existence (or lockout) portion of the GAT. In this case, the free/allocated status bytes are GAT relative bytes 00H through BFH instead of 00H through 5FH as discussed above. This extension is automatically done during format if the number of lumps for the diskette exceeds 60H (96 decimal).

The diskette's encoded password is in relative bytes CEH - CFH.

The diskette name is in relative bytes D0H - D7H.

The diskette date is in relative bytes D8H - DFH.

If a system diskette, the AUTO command to be used at reset is contained in relative bytes E0H - FFH. If the first byte of this area is 0DH (EOL), then no AUTO command exists for this system diskette.

5.6.2. The HIT (Hash code Index Table) Sector.

The HIT sector is the 2nd sector in the directory. It serves as an index into the FPDEs for the diskette's files and also serves to indicate which FDEs are free and which are in use. If a HIT sector byte equals 0, the corresponding FDE either doesn't exist or is free. If a HIT sector byte is non-zero, the corresponding FDE is in use, and if in use as a FPDE, the HIT sector byte's value is a hash code formed from the contents of the FPDE's 6th through 16th bytes (the name and name extension). Thus, when it is necessary to look up a file in the directory, the hash code is computed and the HIT sector searched for a match. If a match is found, the corresponding FDE sector is read and the corresponding FPDE tested for matching name and name extension. If this match fails, the HIT sector search is continued.

The relative position of the HIT byte within the HIT sector is exactly equal to the corresponding FDE's DEC code; for it is by using the DEC code as an index into the HIT sector that the system knows which HIT byte to set non-zero when a FDE is allocated and to set to zero when a FDE is freed.

The HIT sector's 32nd byte is used differently in NEWDOS/80 than all the other HIT sector bytes. This byte contains the count of extra FDE sectors allocated to the directory; the legal values are 0, 5, 10, 15 and 20. This value is set up when the diskette is formatted.

On old Model I diskettes the value of the HIT sector byte for DIR/SYS (2nd byte of the HIT sector) was 2CH which is not the correct value. This incorrect value causes FILE NOT IN DIRECTORY error to appear when the directory file itself is being accessed. For such diskettes, use SUPERZAP to put the correct value of C4H into the HIT sector 2nd byte.

5.6.3. The FDE (File Directory Entry) Sectors.

The rest of the directory's sectors are FDE sectors, with each 256 byte sector containing eight 32 byte FDEs. A FDE is free if bit 4 of its 1st byte equals 0 and in use if the bit equals 1. An in-use FDE is a FPDE if bit 7 of its 1st byte equals 0 and a FXDE if the bit equals 1. When an FDE is freed, only the 4th bit of the 1st byte is zeroed and the corresponding HIT sector byte is zeroed. Nothing else is changed. However, the user may zero the entire 32 bytes of each unused FDE by using the C function of DIRCHECK, thus obtaining a cleaner looking directory.

5.7. FPDE File Primary Directory Entry. Each file, when created, is assigned a directory entry somewhere in the FDE sectors. This entry contains:

1st byte:

Bit 7 = 0. Indicates FPDE, vice FXDE.
Bit 6 = 1. If a system file.
Bit 5 = 0. Undefined.
Bit 4 = 1. Indicates FDE allocated to a file.
Bit 3 = 1. If the file has the invisible attribute.
Bits 2 - 0. Access level code (see PROT parameter of ATTRIB, section 2.3).

2 byte:

Bit 7 = 0. The file may be allocated more space when necessary.
Bit 7 = 1 prohibits this. DIR, ATTRIB, CREATE and the DOS file space allocation routine use this bit.

Bit 6 = 0. The DOS file close function may deallocate any excess granules above the EOF (i.e., apparently not being used by the file).
Bit 6 = 1 prohibits this. DIR, ATTRIB, CREATE and DOS file close use this bit.

Bit 5 = 1. At least one sector of the file has been written to, either new data or updated data, since the last time this bit was set to 0. DIR, ATTRIB, CREATE, PROT, COPY and the DOS sector write routine use this bit.

Bits 4 to 0. Undefined and reserved for future definition.

3rd byte = 0. Currently undefined and reserved for future definition.

4th byte. The lower order byte of the file's EOF. This value is the EOF position within the EOF sector. See FCB 20th byte below.

5th byte. The logical record length (LRECL) (0 = 256) in bytes. When a file is created via a 4420H vector call, the value from register B is stored here. When an existing file is opened, even as a new output file, this value is not updated. This value is never used in NEWDOS/80. The value stored in FCB+9 at open time is that from register B, not from the FPDE.

6th-13th bytes. The file name, padded on right with blanks if necessary.

14th-16th bytes. The file name extension, padded on right with blanks as necessary.

17th-18th bytes. The encode of the update password.

19th-20th bytes. The encode of the access password.

21st byte. The middle order byte of the EOF.

22nd byte. The high order byte of the EOF. The 4th, 21st and 22nd

bytes are a 3 byte EOF value. This EOF value, instead of being in RBA format as are the EOF and NEXT fields of the FCB, is maintained in the old TRSDOS format which has the following rules:

If the lower order byte of the EOF equals 0, the EOF is in RBA format.

If the lower order EOF byte is not 0, then the EOF value in the FPDE is equal to the actual RBA value plus 256 (the high two byte value of the EOF is incremented by 1).

NEWDOS/80 maintains the directory FPDE EOF field in this manner in order to maintain compatibility with the old Model 1 TRSDOS 2.3 diskettes (see section 12.1). New EOF values for a file are placed into the FPDE only during file-create, write-EOF and DOS close. Thus, if the system fails requiring reset, the user can expect that any file open for output at the time of failure will contain the new data but usually not the new EOF.

See section 12.1 for EOF and NEXT incompatibility with other DOSs.

23-30th bytes. Four 2 byte pairs (extent elements), each specifying a contiguous area of the diskette assigned to this file. The format of an extent element is:

1st byte:

255 (0FFH) means the end of the extent elements for this file.

254 (0FEH) means the next byte contains the DEC for the first or next FXDE assigned to this file.

0 - 253 (0 - 0FDH) equals the number of the diskette's lump in which the area starts. Other considerations including the number of lumps the GAT sector can handle limit this value to the range 0 - 191. This value is also the relative location within the GAT sector of the byte associated with this lump.

2nd byte (when the 1st byte is less than 254)

left 3 bits equals the number of granules (0-7) from the start of the lump to the start of the area.

right 5 bits equals the number less one of contiguous granules assigned to this area.

31-32nd bytes. An extent element whose 1st byte is either 255 or 254.

5.8. **FXDE** **File Extended Directory Entry.**

When a file has more than 4 space areas assigned, the additional extent elements are contained in FXDE's assigned to the file. The format of a FXDE is:

1st byte. Bits 7 and 4 are both 1 to indicate a FXDE; all other bits of the byte equal 0.

2nd byte. The DEC for previous FXDE or FPDE of this file. This is a backward chain. The previous entry's 31st byte will be 254, and the 32nd byte will contain the DEC of this FXDE.

Bytes 3-22. Unused and should equal 0.

Bytes 23-32. Are as defined for the FPDE.

5.9. **FCB** **File Control Block.** Also known as a DCB (Data Control Block) or an IOB (input/output block).

In order that file information be read from or written to a diskette, a link must be created between that file and the user program. The link is created by the DOS open function (see sections 3.13 and 3.14) and dissolved by the DOS close function (see section 3.15). During the time the link is in existence, the control information for that link is maintained in a 32 byte area of main memory known as a File Control Block. At open time, the user specifies where in user memory this FCB is to be. While this link is in existence, the FCB's area of main memory must not be used for any other purpose. DOS does not remember where the FCBs are. The user informs DOS of which FCB to use for each function that is to use a FCB. Thus, the link is effectively dissolved by simply never using the FCB again in a function call or by using the FCB in the open of a new link. Remember though, if writing to a file where the EOF is being changed, either a a DOS close or DOS write-EOF (see section 3.28) function must be done to assure the EOF is properly placed in the FPDE.

At open time (a call to DOS 4420H or 4424H), the caller provides in register DE the address of a 32 byte main memory area for use by the system as a FCB while the file is open. The user must have placed the filespec (terminated by a 0DH or 03H byte) for the desired file into the FCB's 1st bytes, and the DOS close function will attempt to put it back there when done. NEWDOS/80 will accept the Model III TRSDOS 50 bytes area but only uses the first 32 bytes. While the FCB is open, the format for the 32 byte FCB is:

1st byte:

Bit 7 = 1. The link is in existence (i.e., an open has been done).

Bit 7 = 0. The link is not in existence (i.e., either an open has not been done or a close has been subsequently done).

Bits 6-2 = 0. Undefined.

Bit 1 = 1. The value in the FCB's NEXT and EOF fields are RBAs within the diskette, rather than the file. This allows the user to I/O directly to diskette sectors, bypassing the file concept altogether. This bit should never be 1 during byte I/O via the 0013H or 001BH calls.

Bit 0 = 1. Sectors written to the file are written read protected in the same manner as DOS writes directory sectors. This bit should never be 1 during byte I/O via the 0013H or 001BH calls.

2nd byte:

Bit 7 = 1. Either single byte operations or logical record operations (record length in FCB's 10th byte) are being done via this FCB. NEXT value is maintained at the next byte to be read or written. This bit is set to 1 at open time if register B is not 0. It is also set to 1 whenever byte I/O is done via the 0013H or 001BH ROM calls.

Bit 7 = 0. Read and write operations are by full 256 byte sectors with the FCB's NEXT value incremented 256 bytes upon the completion of each successful I/O.

Bit 6 = 0. The FCB's EOF value is to be set equal to the FCB's resulting NEXT value on every successful write operation.

Bit 6 = 1. The FCB's EOF value is to be set equal to the FCB's resulting NEXT value only for those successful write operations resulting in the NEXT value exceeding the current EOF value.

Bit 5 = 0. The FCB's buffer contains the current file sector's data. If bit 5 = 1, the buffer does not contain the current file sector's data; if needed, that sector's data must be read into the buffer.

Bit 4 = 0. The FCB's buffer does not contain updated data not yet sent to the file. If bit 4 = 1, the buffer does contain updated data not yet sent to the file. During DOS close, if this bit is 1, the sector data in the buffer is automatically written to disk. This updated data is also written on every 443FH and 4451H call and on every 4442H, 4445H, 4448H and 444EH call that positions the file within a different sector.

Bit 3 = 1. This FCB is in the NEWDOS/80 Version 2 format for the 18th - 32nd bytes. This bit is set to 1 by DOS open. If bit 3 = 0, the FCB is in the old format and is illegal in NEWDOS/80 Version 2.

Bits 2 - 0. Access level code (see PROT parameter of ATTRIB, section 2.3).

3rd byte:

Bits 7 - 5. These bits are defined the same as those in the FPDE 2nd byte (see section 5.7). If bit 5 equals 0, the DOS sector write routine sets the bit to 1 in both the FCB and the FPDE just before it actually writes the current sector to disk.

Bits 4 - 0. Undefined and reserved for future definition.

4-5th bytes. The main memory address of the FCB's buffer. The user determines where the buffer is to be and puts this address into register HL before the call to the DOS open routine. Sectors are read from disk into this buffer and written to disk from this buffer.

6th byte. The low order byte of the FCB's NEXT field. This is the relative position within sector value. See discussion for FCB 12th byte below.

7th byte. The relative number of the drive containing the diskette containing the file.

8th byte. The DEC code of file's FPDE. After the FCB is opened, this DEC code is the link between the open FCB and the file's directory information as the FCB itself no longer contains the filespec.

9th byte. The low order byte of EOF. This is the relative position within the EOF sector. See discussion of FCB 14th byte below.

10th byte. The logical record length (LRECL) ($\emptyset = 256$) for records of this file. This value is supplied in register B by the caller at open time. If not \emptyset at open time, bit 7 of the FCB's 2nd byte is set to 1, and subsequent DOS sector read or write calls must contain, in register HL, the address of the logical record to be moved to the FCB's buffer (write) or filled from the FCB's buffer (read).

11th byte. Middle order byte of the NEXT field.

12th byte. High order byte of the NEXT field. The 12th, 11th and 5th bytes form a 3 byte RBA within the file of the next byte to be processed, either input or output.

For single byte and logical record I/O, DOS maintains the FCB NEXT field in exact RBA format.

For full sector I/O, DOS also maintains the NEXT field as an exact RBA, but there are subtle actions by DOS that can give trouble if the user is not aware of them. DOS does not change the lower order byte of the NEXT field during full sector I/O. Normally, this byte is zero, and that's fine. However, the user can set this byte non-zero or if the previous I/O done was in single byte or logical record mode the lower order byte will probably be non-zero. The user must be aware of the following rules:

During full sector reads, all three bytes of NEXT participate the EOF check just as for single byte and logical record reads.

During full sector write, when the low order byte of the NEXT field is non-zero, the NEXT field is not advanced 256 bytes upon the successful completion of the write and EOF, if it is updated, assumes that non-advanced NEXT value. The rationale here is that if the NEXT field's lower order byte is zero, the value of NEXT after the successful write is to be at the first

byte of the next sector, but if the NEXT field's lower order byte is non-zero, the value of NEXT after the successful write is to remain within the sector just written.

See section 12.1 for discussion of NEXT and EOF field incompatibility with other DOSs.

13th byte. Middle byte of the EOF field.

14th byte. The 14th, 13th and 8th bytes form 3 byte RBA within the file of the end-of-file (the 1st byte beyond the file's last data byte). This value is initialized from the FPDE at open time, and is updated at sector, logical record or byte write time under control of the FCB 2nd byte, bit 6. See section 12.1 for discussion of NEXT and EOF field incompatibility with other DOSs.

15-22th bytes. Identical to 23-30th bytes of FPDE.

23-24th bytes. For the current FXDE whose 4 extent elements are in the FCB 25th - 32nd bytes, the number in this field represents the relative granule number of that FXDE's 1st extent's 1st granule. If that value equals 0FFFFH, then no FXDE is represented in the 25th-32th bytes.

25-32nd bytes. Identical to 23-30th bytes of the current FXDE, if any.

Discussion of FCB bytes 17-32:

The definition for FCB bytes 17 to 32 has changed from what it was in NEWDOS/80 Version 1 and Model I TRSDOS. It was assumed that very few user programs ever referred to these bytes as they serve only to reduce the number of directory accesses done by the resident DOS. However, some users (such as the old SUPERZAP coded in BASIC) have made use of the old definitions to get around having to open a file when diskette, rather than file, I/O was wanted. NEWDOS/80 Versions 1 and 2 have provided a diskette, as opposed to file, I/O method (see FCB 1st byte, bit 1 definition); that method should be used and those old pseudo FCB methods MUST be discarded to run with NEWDOS/80 Version 2. Failure to do so could be catastrophic; NEWDOS/80 Version 2 has activated bit 3 of FCB 2nd byte in an attempt to head off these bad pseudo FCBs.

This change to the FCB 17-32nd bytes allows the FCB to contain all of a file's extent information for any file having 8 or less extents (DIR with the A option will display how many extents a file has). If the file occupies contiguous diskette space, 8 extents is enough for approximately 300,000 bytes (or 270,000 bytes if the directory is spanned by the file's space).

If the file has more than 8 extents, meaning that more than one directory FXDE is assigned to the file, then the FCB contains space information for the file's 1st 4 extents and the 1 to 4 extents of the FXDE last having a sector read or written. It is quite possible for large randomly accessed files to require a lot more directory accesses than was done under NEWDOS/80, Version 1.

6. ADDITIONAL PROGRAMS SUPPLIED ON NEWDOS/80 DISKETTE.

6.1. SUPERZAP.

Program SUPERZAP/CMD provides the user with the means to read and write standard 256 byte diskette sectors or any part of main memory, except writing to ROM. Learning to use SUPERZAP is strongly recommended for all NEWDOS/80 owners. If corrections (known as zaps or patches) are to be made to your NEWDOS/80, Apparat will distribute them in written form for application using SUPERZAP. You must know how to use DFS and MODxx. In learning to use SUPERZAP, do your learning on a diskette having data that you can afford to lose!!!!

Certain diskettes are written in non-standard sector formats and are thus inaccessible to SUPERZAP. There exist other programs that read anything that is on a diskette, but do not have some of the other SUPERZAP features. The user, at some time, will probably want to buy one of these other programs from the vendors that sell them.

SUPERZAP operates in both upper and lower case.

Where numeric values are inputted and unless otherwise specified, SUPERZAP assumes DECIMAL unless the value is suffixed with the character H to indicate hexadecimal.

6.1.1. Function Modes. The menu displays the functions available. The user keys in the selected function's characters and then presses ENTER. The SUPERZAP functions are as follows:

DD Display a Disk sector. SUPERZAP will ask for the drive number and the number of the relative sector within the diskette, read the sector and display it.

DM Display a 256 byte page of main memory. SUPERZAP will ask for a memory address, truncate it to a 256 byte boundary and display the page.

DFS Display a File's Sector. SUPERZAP will ask for the file's file-spec. Next, SUPERZAP will ask for the relative sector number within the file and will display that sector.

DTS Display track's sector. SUPERZAP will ask for the drive number, track number and the number of the relative sector on the track. It will then read the sector and display it.

DMDB Display Memory Dump Block. SUPERZAP will ask for the filespec of the memory dump file (created by DUMP, see section 2.20). It will display the dump's base address. Next it will ask for a main memory address within the range of the dump, truncate it to a 256 byte boundary and display the memory page.

VDS Verify Disk Sectors. SUPERZAP will ask if the operator wants a pause when a read protected sector is encountered. Next, SUPERZAP will ask for the drive number and the number of the relative sector on the

diskette of the 1st sector to be verified. Lastly, it will ask for the number of sectors to be verified. It will then proceed with the verify which consists simply of reading each sector within the range specified. When a protected sector is encountered and if a pause was requested, SUPERZAP will display the sector's location and wait for the operator to press ENTER before continuing. VDS is a fast way of finding bad sectors on a diskette that the user suspects have gone bad. While verifying is being done, VDS may be cancelled by pressing up-arrow.

ZDS Zero Disk Sectors. SUPERZAP will ask for the drive number and the number of the relative sector on the diskette of the first sector to be zeroed. Next, it asks for the number of sectors to be zeroed. The zeroing is then done. The read protection status of each sector is not changed.

CDS Copy Disk Sectors. SUPERZAP will ask for the drive number and the number of the relative sector on the diskette of the source (where the data is coming from) range's 1st sector. Next, it will ask for the same data for the destination (where the data is going to) range's 1st sector. Lastly, it will ask the number of sectors to be copied. The copy is then done. Destination sectors are each assigned the read protection status of the corresponding source sector.

CDD Copy Disk Data. This function differs from CDS in that any string of diskette bytes may be copied. SUPERZAP will ask for the drive number and the number of the relative sector on the diskette of the sector containing the source range's 1st byte and then ask for that byte's offset within the sector. It will ask for the same information for the destination range's 1st byte. Lastly, it will ask for the number of bytes (65535 is the maximum allowed) to be copied. The copy is then done. The read protection status of the destination sectors is not changed.

DPWE Display PassWord Encode. SUPERZAP will ask for the password, encode it and display the resulting encode in hexadecimal as it would appear in a directory FPDE.

DNTH Display Name/Type hashcode. SUPERZAP will ask first for the filename and next for the type (name extension). It will then hash them and display the resulting hashcode in hexadecimal as it would appear in the directory HIT sector.

EXIT End SUPERZAP and exit to 440DH (DOS READY).

Since ZDS, CDS and CDD change diskette data, the user is first asked if he/she is sure this function is wanted, just in case the wrong function was keyed.

For CDS and CDD, the copy normally proceeds in ascending byte order for both the source and destination. However, if the highest source byte is within the destination range, the copy is in descending byte order to avoid destructive overlap.

All disk I/O's are done through the normal DOS sector I/O routines. Thus, if an error occurs, system option AM and AW I/O try counts are in effect.

For VDS, ZDS, CDS and CDD, if a disk I/O error results, the operator will be

offered the choice of retrying, skipping the sector or terminating the function. In many cases, repeated retrying will eventually work. If the error sector was a source sector, skip will cause the associated destination bytes to receive whatever happens to be in the source's buffer; this should be no problem as the user is faced with a reclaim job anyway.

When SUPERZAP is waiting for a numeric value, keying an X as the value will cause SUPERZAP to terminate the function and return to the menu. If SUPERZAP is waiting for a filespec, a null parameter will terminate the function.

When any of DD, DM, DFS, DTS or DMDB is suffixed with ',P', the sectors or memory pages will be printed as well as displayed. For DD,P, DFS,P or DTS,P, the user will be asked for the number of sectors to be printed. For DM,P or DMDB,P the user will be asked for the number of bytes. If the printer is not ready or drops ready, SUPERZAP will loop waiting on it without operator notification. Pressing the P key will cause printing to pause; press ENTER to continue. Pressing the H key will terminate printing.

6.1.2. Display Mode. For DD, DM, DFS, DTS and DMDB, while a sector or memory page is displayed, SUPERZAP is in the display mode and waits for a display mode command. Except for the F and L commands, the keyed command bytes are not displayed and do not require termination with ENTER; the command is executed as soon as all characters of a display mode command have been keyed. The display mode commands are:

- X The current function is terminated and SUPERZAP returns to the menu.
- R Redisplay the same sector or memory page.
- + or ; Display the next higher sector or memory page.
- Display the next lower sector or memory page.
- J Restart the same function.
- K Restart the same function, retaining the 1st parameter unchanged.

SCOPY DD and DTS only. The current sector is to be copied to a specified sector. SUPERZAP will ask for the destination sector's drive number and relative sector number. The destination sector may be the same as the source sector. SUPERZAP will read the destination sector and report its status. Then the source sector's contents are written to the destination sector. SCOPY is useful when a sector is found to have bad parity but, with the exception of a few bytes, is intact; by SCOPYing upon itself, new parity will be generated, and the sector can then be repaired. It is also useful for altering a sector's read protect status.

When SUPERZAP is in the display mode, it has a diskette, file, main memory or memory dump file search capability. The match is on 1 to 4 hexadecimal bytes (without the suffixed H) which are represented by aa,bb,cc,dd. When the search finds a match, the sector or memory block containing the first byte of the match is displayed with a thin vertical blinking cursor to mark its position. That cursor will disappear as soon as a key is depressed.

sed; however, the associated 'find' position is remembered in case the search is to be continued. When SUPERZAP is in display mode, the following commands to perform searching may be keyed in, terminated by ENTER.

F,aa,bb,cc,dd The 1 to 4 hexadecimal match bytes are stored, and the search starts at the first byte of the diskette (if DD or DTS mode) or file (if DFS or DMDB mode) or main memory (if DM mode).

F, The same as above except the previously established match bytes are used.

Fxx,aa,bb,cc,dd The 1 to 4 hexadecimal match bytes are stored, and the search starts within the current sector or block at the xxth relative byte where xx is a 2 digit hexadecimal number without the suffixed H.

Fxx or **Fxx,** The same as above except the previously established match bytes are used.

F The search continues at the first byte following the position of the first byte of the last match, and the search uses the previously established match bytes.

L,aa,bb,cc,dd This command is to be used instead of F,aa,bb,cc,dd when, in DFS mode, the file being searched is standard load module (i.e., SUPERZAP/CMD, LMOFFSET/CMD, etc.) and the user wants SUPERZAP to purge out all except actual object code bytes from the search. This allows a load module file search for two or more bytes without the imbedded loader control information interfering with the match. The resulting display will still contain the loader control information; the user must be prepared to occasionally see this control information imbedded within the matching bytes. Usually, but not always, this control information is 4 bytes long with the first byte being a hexadecimal 01. Except for purging this control information from the match, L,aa,bb,cc,dd works the same as F,aa,bb,cc,dd. The F command may be used to continue an L type search.

L, The same as above except the previously established match bytes are used.

MODxx DD, DM, DFS and DTS only. SUPERZAP enters modify mode and positions the cursor to the first hex digit of relative byte xx (value 00H - FFH) of the current page or sector.

EXIT End SUPERZAP and exit to 402DH (DOS READY).

If an error occurs during the keying in of a display mode command, the partial command is ignored and the sector or block is redisplayed again.

6.1.3. Modify Mode. SUPERZAP enters modify mode upon execution of the display mode command MODxx. This mode allows the changing of individual bytes within the current disk sector or memory page. Responses while in modify mode are defined as follows:

Hexadecimal digit character 0 - 9 or A - F. The hex digit at the current cursor position is replaced by the new hex digit, and the cursor is advanced one position. If the cursor wraps around, an error will occur if the next character inputted is a hex digit character. Replacements in a main memory page are for real while replacements in a sector are buffered until the sector is written or a 'Q' command cancels the pending update.

Space or right arrow.	The cursor is advanced one position.
Left arrow.	The cursor is retarded one position.
Shift right arrow.	The cursor is advanced 4 positions.
Shift left arrow.	The cursor is retarded 4 positions.
Down arrow.	The cursor is advanced one display line.
Up arrow.	The cursor is retarded one display line.

ZTxx This sequence is displayed vertically in display column 7 and must terminate with ENTER. All hex digits from and including the cursor position to and including the 2nd hex digit of relative byte xx are zeroed. The cursor is left positioned to the 1st hex digit following relative byte xx, and if wrap around occurs, the next input char may not be a hex digit.

RTxx,jk This command is similar to ZTxx except that each byte's 1st digit is replaced with the hex digit j, and each byte's 2nd digit is replaced with the hex digit k.

Q For sector operations only. Modify mode is terminated, any changes in the buffer are discarded, and SUPERZAP returns to display mode.

ENTER For memory page operations, modify mode is terminated, and SUPERZAP returns to display mode. For sector operations, the operator is asked if he/she really wants to update the sector now. If not, SUPERZAP continues in modify mode. If so, the sector (with any changes) is written back to disk, modify mode is terminated, and SUPERZAP returns to display mode.

When modify mode encounters an error, it will display 'INVALID MODIFICATION MODE CHAR. REPLY '*' TO CONTINUE'. Upon receiving *, SUPERZAP returns to modify mode.

6.2. DISASSEM.

Program DISASSEM/CMD disassembles Z-80 object code from a standard TRS-80 load module or from main memory. The disassembled code is sent to the display or to the printer. Generated source text may be sent to disk and a location cross reference may be produced.

Responses to the query 'OBJECT FROM MAIN MEMORY OR DISK?' (M OR D):

1. **null or D** Object is a disk load module.

1. Respond to the query 'FILESPEC?' with the filespec of the load module to be disassembled.

2. Respond to the query 'OFFSET OBJECT VIRTUAL ADDRESSES BY? (HEX)' with either null (meaning 0) or a 1 to 4 digit hexadecimal number (without suffixed H) which when added to the load addresses within the load module will give the proper address where the instructions being disassembled would be during normal execution of that code. This parameter is needed when an object module loads to one place in main memory, but actually executes from another. Wraparound is allowed. Example:

If the object module loads into C000H - FFFFH but is to execute in 7000H - AFFFH, applying an offset of B000 will cause the disassembler to disassemble as if the load was actually done to 7000H - AFFFH.

3. Respond to the query 'VIRTUAL RESTART LOCATION? (HEX)' with either null (meaning start at the file beginning) or a 1 to 4 digit hexadecimal number (without the suffixed H) which is the listed location of any instruction of the disassembly. This allows restart of a large disassembly within the instruction print portion of the listing, and the location chosen is usually the location value for the first instruction on the page where printing was interrupted.

2. **M** The object code is in main memory.

1. Respond to the query 'OBJECT VIRTUAL BASE ADDRESS? (HEX)' with the 1 to 4 digit hexadecimal location value (without suffixed H) where the object code is considered to execute from, whether or not it is actually there now. In the listing, this value will be the first instruction's printed location value.

2. Respond to the query 'OBJECT REAL BASE ADDRESS (HEX)?' with null (meaning the real and virtual locations are the same) or with the 1 - 4 digit hexadecimal main memory location (without suffixed H) where the disassembler will actually find the object code.

Responses to the query 'ANY OPTIONS?':

1. **null** No more options to be specified.

2. **PTR** The output is sent to the printer instead of the display.

3. **BFSP** Bypass Full Screen Pauses. In normal operation the disassembler pauses whenever the display screen is full or whenever a break occurs in the sequential locations of the disassembled file. The disassembler waits for (1) ENTER to continue, (2) X to terminate the disassembly or (3) V (object from main memory only) to restart the disassembly at a new location. The BFSP option bypasses this pausing, causing display to occur as fast as the disassembly can proceed. This option is automatically invoked if option PTR is specified.

The remainder of the options are legal only when the object code is from disk:

4. **NCR** The location reference table is not to be built and no display or listing done of it.
5. **NIP** Do not print or display the disassembled instructions.
6. **STD** Source To Disk The disassembled code is to be sent to disk in the format of an EDTASM source text file. See discussion below.
7. **FGN-xxx** First Generated Name xxx is the 3 alphabetic character name of the first name to be assigned during the STP action described below. The default name is AAA.
8. **RTD** The location reference table is to be stored onto disk. After the reference table is built, the program will ask for the 'REFERENCE TABLE FILESPEC?'. Respond with the filespec of the file to contain the reference table. Reference table files can be used (by a user-created program) to merge the reference tables of two or more programs. See below for file format.
9. **REA** Enable listing of all types of references; this is the default.
10. **RE&** Enable list of the specified reference type where '&' is one of L, P, R, S, T, U, V, W or X. Reference types are defined at the beginning of each location table listing.
11. **RIA** Disable list of all types of references.
12. **RI&** Disable listing of the specified reference type where '&' is one of L, P, R, S, T, U, V, W or X.

The disassembler operates through four phases:

1. If object code from disk and option NCR not specified, DISASSEM displays 'BUILDING CROSS REFERENCE TABLE' and passes through the object code building the location reference table. For a large disassembly this will take some time. If insufficient main memory for the table, the disassembly will terminate.
2. If RTD option specified, this phase writes the location reference table to disk.
3. List disassembled instructions to display or printer. If STD specified, the resulting text is also written to disk. On the disassembled instruction print lines, column 1 indicates the number of references to bytes of the instruction; the value is hexadecimal with blank meaning 0 and F meaning 15 or more references. Column 2 indicates which bytes of the instruction have been referenced. If blank and column 1 non-blank, then only the instruction's 1st byte is referenced; otherwise the hex digit represents a 4 bit binary mask of which bytes, from the left, are referenced.

4. If object is from disk and NCR is not specified, the location reference table is displayed or printed. The definitions of the reference type codes are given first. Then, in ascending numeric order, every referenced location is listed with the location of every referencing instruction. Suffixed to each referencing location value is the reference type code for the Z-80 instruction making the reference.

If the disassembler finds something wrong with the object module, either 'DISK OBJECT FILE FORMAT NOT AS EXPECTED' or 'PAST END OF FILE' will be displayed and the disassembly will terminate.

While the disassembled instructions are being displayed or printed, holding down P will cause a pause; press ENTER to continue. Holding down X will terminate the disassembly. At most other times when DISASSEM is awaiting a user response, the disassembly may be terminated by holding down up-arrow and pressing ENTER.

For main memory disassemblies, the operator may shift the disassembly point at will. When the disassembly is paused, keying V will display the query 'VIRTUAL RESTART LOCATION? (HEX)'. The operator responds a 1 to 4 hexadecimal digit value which is the main memory location where the disassembly is to restart.

If the PTR option is specified and after all options have been specified, the following occurs:

Respond to the query '# LINES PER PAGE, EXCLUDING TOP AND BOTTOM MARGINS? (1-255)' with the number of printable lines per page.

Respond to the query '# LINES EACH FOR TOP AND BOTTOM MARGIN? (0-10)' with the number of lines the disassembler is to skip at both the top and bottom of each page. If 0, the disassembler does no paging action. What the disassembler does for top and bottom margins is completely independent and in addition to anything a printer driver may be doing.

Respond ENTER to the query 'REPLY "ENTER" WHEN PRINTER AT TOP OF PAGE' when the printer is on and at top of page.

Respond to the query 'HIGH ASCII CODE FOR PRINTER? (5A - 7F)' with the 2 hexadecimal digit value (between 5AH and 7FH) for the highest printer code for your printer.

The STD option causes the disassembled code to be converted into EDTASM type source text code. The resulting STD output (if not too large) can be loaded and assembled by EDTASM. The outputting of source text via the STD option works as follows:

After the cross reference table build phase and the RTD phase, respond to the query 'ASSEMBLER SOURCE TEXT OUTPUT FILESPEC?' with the filespec of the file to contain this generated source code. The file will be opened, and the generated text sent to it during the main disassembly phase.

All numeric values within the disassembled code are replaced with a 3 character alphabetic name unique to that value. The names are assigned arbitrarily in ascending alphabetic order with the first name assigned either AAA or the name specified by the FGN option.

If a numeric value does correspond to a disassembled location, the name assigned to that value is placed in the location name field of that location's instruction when it is sent to disk and displayed or printed.

If a numeric value does not correspond to a disassembled location, an EQU statement is generated at the end of the source text to equate the name with the value.

ORG statements are generated as necessary, and the END statement is generated as the last text statement.

The format of the reference table file created by the RTD option is:

1. 1 byte = C0H. Backward EOF. Ignore it.
2. 1 or more entries of the form:
 1. 2 byte memory location value, 1st byte = low value, 2nd = high.
 2. Control byte, bits 7 - 0 (7 is left most):

7-6 = 11. Dummy last entry in table. Ignore all other bits and bytes of the entry.

7-6 = 01. Referencee entry. Bits 5-0 = 0. The location is referenced by one or more of the subsequent referencer entries.

7-6 = 00. Referencor entry. The instruction at this location referenced the location of the previous reference entry. Bits 5-0 contain the referencer instruction type: 0 = S, 1 = T, 2 = U, 3 = V, 4 = W, 5 = X, 8 = P, 9 = L, and 10 = R. See a reference listing for definitions.

6.3. LMOFFSET.

Program LMOFFSET/CMD reads a tape or disk load module, displays its load information, optionally changes the program's load area, optionally attaches an appendage enabling the program at execution time to move itself from its load area to its execution area, optionally prepares the module to run under non-disk BASIC via SYSTEM, and stores the module onto disk or tape with a new name.

LMOFFSET functions as follows:

1. Reads either a tape-type assembly load module from tape or a disk-type assembly load module from disk.

If from disk, LMOFFSET asks for the source filespec.

When reading from tape, a single * will be displayed when LMOFFSET is ready for the tape. Do rewind (if necessary) fast forward positioning (if necessary) and press PLAY. *** appears when tape read synchronization has completed. The character C will be displayed

when a bad checksum is encountered. The character P will be displayed if leading extraneous data bytes encountered. The character I will be displayed if imbedded extraneous bytes are encountered.

2. Displays (1) the area into which the module will load, (2) possible conflicts with system storage and (3) the module entry point. If an appendage is scheduled to be applied, the entry point will be into the appendage.

3. Asks for a new load point. Reply either with a new load point or simply reply ENTER if satisfied with the current load point. If the user is simply transferring the load module without change, respond ENTER to the first request for a new load point and LMOFFSET will go directly to step 7 below.

4. If a new load point specified, LMOFFSET asks if the appendage is to be suppressed.

If the appendage is to be suppressed, the resulting module can only be used via the DOS library command LOAD as there is no appendage to move the program to its execution area and the entry point is forced equal to 0. The resulting output load module can be used via LOAD where two or more load modules are loaded into main memory and then stored as one load module via DOS library command DUMP.

If the appendage is not to be suppressed, then LMOFFSET will append to the user program either a DOS enabled appendage or a DOS disabled appendage, depending on whether DOS is to be disabled or not.

5. If a new load point was specified, LMOFFSET goes back to 3 above to display the resulting load information and ask for a new load point. If another load point is given, it cancels the one specified earlier, including its scheduled appendage, if any.

6. Finally, when the response to 3 above is a null, then if a new load point was specified and the appendage is not suppressed, LMOFFSET asks if DOS is to be disabled. If so, the DOS disabled appendage is selected; if not, the DOS enabled appendage is selected.

7. LMOFFSET next asks if the destination is disk or tape.

If the destination is disk, LMOFFSET asks for the filespec of the load module file to be created.

If the destination is to tape, LMOFFSET asks for the tape module name and then which tape speed (L or H). Next it asks for ENTER when the tape is positioned and in record mode.

8. The resulting load module is then written to disk or tape. If a new load point was specified, (1) the load address for each object code record is altered, (2) if the appendage was not suppressed, an extra object code record (the appendage) is inserted before the entry point record and the entry point is set to the appendage's 1st byte, and (3) the entry point is set to 0000 if a new load address was specified and the appendage was suppressed.

9. When the destination file write is completed or if an error or other type of termination occurs during step 7 or 8 above, LMOFFSET asks if the same module is to be written to another file (which may be the same file). If so, steps 7 and 8 above are repeated.

10. When all done or if an error or other type of termination occurs while not in steps 7 or 8, LMOFFSET asks if another source load module is to be processed. If so, execution returns to step 1 above; if not, LMOFFSET exits back to DOS.

The up-arrow key may be used at any time to terminate the current LMOFFSET function. If LMOFFSET is waiting for a response, hold down the up-arrow key and press ENTER.

A module can end up with multiple appendages if the output from one LMOFFSET run is made the input to another, but doing this is strongly discouraged; in the case where one appendage is a DOS disable appendage, it must never be done. LMOFFSET knows nothing of a previously existing appendage appended by a previous execution of LMOFFSET.

LMOFFSET does not perform any object code relocation!!!! It only assigns code to new load locations so that DOS can load the module from disk without damage to DOS.

If the source program loads into the display area (3C00H - 3FFFH) without overflowing it, those object code records will not have their load addresses modified.

The appendage added to a module by LMOFFSET starts with 64 bytes of zeroes. This area is available to users to patch in special code. The load address of this patch area is the same as the module's resulting entry address, providing there is only one appendage. Z-80 code patched into this area will be the first executed when that program commences execution. This will be done before the program is moved to its execution locations and before DOS is disabled, if DOS is to be disabled.

When a program is to run in any part of the DOS area, a DOS disabling appendage must be specified. The DOS disabling appendage causes the user program to execute as if it was loaded from tape under the non-disk BASIC SYSTEM function.

When the resulting user program module is executed, the action is as follows:

For a DOS enabled appendage:

1. Executes any user supplied code in the 64 byte patch area.
2. Moves the main program to its execution locations.
3. Commences execution of the main program.

For a DOS disable appendage:

1. Executes any user supplied code in the 64 byte patch area.
2. Moves the display screen contents to high memory.

3. Displays the following:

RECORD AND THEN PERFORM THE FOLLOWING INSTRUCTIONS

1. HOLD DOWN BREAK KEY AND PRESS RESET TO ACTIVATE NON-DISK BASIC.
2. RELEASE BREAK KEY AND ENTER BASIC INITIALIZATION RESPONSES.
3. ENTER "SYSTEM".
4. ENTER "."

3. When the operator has done the above, the appendage continues execution.

4. Restores the screen contents from high memory.

5. Moves the main program to its execution locations.

6. Commences execution of the main program.

6.4. DIRCHECK.

The DIRCHECK/CMD module tests and lists the target diskette's directory. If errors are found in checking the directory, they are listed before the directory listing. DIRCHECK also allows the option of cleaning up (not repairing) the directory, and, as an aid to moving single density diskettes back and forth between the Models I and III under NEWDOS/80, allows the option of writing the directory protected.

To the query 'OUTPUT TO PRINTER', reply Y if output to go to printer and N if to go to the display.

To the query 'WHICH DRIVE CONTAINS TARGET DISKETTE', reply the target drive number, in decimal.

DIRCHECK reads the BOOT sector (the diskette's 1st sector), and tests that the first 2 bytes are 00H and FEH respectively. If they are, DIRCHECK uses the 3rd byte as the number of the lump at whose first sector the directory starts. If the first 2 bytes are not correct, DIRCHECK displays '***** DISKETTE 1ST SECTOR NOT "BOOT". ASSUMING DIRECTORY STARTS ON LUMP 17 DECIMAL.'.

DIRCHECK proceeds to read the directory. In previous NEWDOS versions, DIRCHECK refused to process a directory that was not write protected. Because of the problem of moving single density diskettes between the Model I and Model III under NEWDOS/80, an unprotected directory will now be accepted, with two error messages displayed, one at this time and one after the files have been listed. The error message is '***** AT LEAST ONE DIRECTORY SECTOR UNPROTECTED'. If this message appears along with many other errors, the user can assume that DIRCHECK has not found the directory and should NOT execute the W function described later.

DIRCHECK uses the drive's PDRIVE (see section 2.37) data to determine the

number of lumps and granules accounted for by the directory. If the PDRIVE data is not correct for the diskette, it is very probable DIRCHECK will list errors that are not actually present.

Complaints, if any, about the directory are next listed. If a number is given, it is in hexadecimal for use in directory repair via SUPERZAP. Do not try to repair a bad directory unless you know what you are doing!!!!!! The next best thing is to try to extract valued files via COPY and then re-format the diskette having the bad directory.

If the complaint is about a directory entry for a file, either the primary or an extended entry, the hexadecimal code is the DEC for the file's FPDE. When the complaint deals with a file extended directory entry but does not specify the file name/type, the hexadecimal code is the DEC for the FXDE itself. When the complaint deals with a HIT sector byte, the hexadecimal code is the relative location of that byte in the HIT sector. When the complaint deals with a GAT sector byte, the hexadecimal code is the relative location of that byte in the GAT sector. When the complaint deals with a granule, the hexadecimal value is expressed in bb,r format where bb is both the lump number and the relative byte location of the lump's byte within the GAT sector and x is both the relative granule within the lump and the bit number, counting from zero from the right, within that GAT byte.

The diskette's name and date are next listed.

The files are next listed, with numeric values in decimal and the following definitions:

S System file.

I File has invisible attribute.

P=nnn File has access level nnn, and both update and access passwords are non-blank.

EOF=sss/bbb End Of File value. sss = the relative sector within the file. bbb = the relative byte within the sector.

nnn EXTs nnn is the number of extent elements, maximum of four per FDE, used to account for this file's disk space.

nnn SECTORS The number of sectors allocated to this file.

Lastly, the number of free granules and locked out granules for the diskette are displayed. If the diskette contains more than 60H (96 decimal) lumps or if GAT relative byte 60H equals 0FFH, DIRCHECK assumes that there is no lock-out (existence) table. Note, NEWDOS/80 does not mark granules as locked out; the lockout table is maintained only for compatibility with Model I TRSDOS.

If at least one directory sector is unprotected, another error message indicating such is displayed.

'FUNCTION COMPLETED' message is displayed followed by the query:

REPLY

N TO EXIT PROGRAM
Y IF ANOTHER DISKETTE FOR SAME SPECS
I FOR PROGRAM RE-INITIALIZATION
W TO WRITE DIRECTORY SECTORS PROTECTED
C TO CLEAN UP (NOT REPAIR) THE DIRECTORY

Reply with one of the following:

N Program exits to DOS at 402DH.

Y Another diskette to be checked but with same response to the printer query.

I Another diskette to be checked but with different response to the printer query.

W The directory sectors are read and re-written in protected state. Refer to specifications for DOS command WRDIRP (section 2.49) and option SYSTEM option BN (section 2.46). This function is only meaningful for single density diskettes that are going from Model I to Model III or vice versa or used interchangeably.

C All unused FDEs within the directory are zeroed. This is a cosmetic function only that clears out residual information from no longer used FDEs. Normally, when DOS releases FDEs via KILL or automatic space deallocation, it only zeroes bit 4 of the first byte of the FDE, leaving the rest of the information for the remote possibility that the sophisticated user will attempt to reclaim the file or the sectors it used to own.

During display or printing, pressing:

BREAK - processing will pause at end of current line or line group.

ENTER - continues processing.

UP-ARROW - terminates displaying or printing.

6.5. EDTASH Disk Oriented Editor/Assembler.

35 months ago Apparat converted the TRS-80's tape oriented editor/assembler to:

1. Read text from disk as well as cassette.
2. Write text and/or object to disk as well as cassette. Disk files are validity read after all sectors written.
3. Allow down-arrow scrolling to display up to 15 text lines.
4. Prevent the confusing printer output associated with DEFM. Only the 1st byte of associated object code is listed.
5. List symbols in alphabetical order with reference list.

6. Accept and convert lower case alpha to upper.

It was anticipated that Radio Shack would soon come out with a disk oriented editor/assembler that would eliminate any need for the Apparat enhancements. To a degree that has come to pass, but not sufficiently to bury the Apparat enhanced version. Since the Apparat enhanced version is based on the copy-righted tape editor/assembler, Apparat has always required and still requires, as a pre-condition of use of its enhanced version, that the user purchase a copy of the TRS-80 tape editor/assembler and thereby pay the royalty due. In an effort to enforce this, Apparat has always refused, and will continue to refuse, to supply any documentation for the editor/assembler beyond that dealing explicitly with Apparat's enhancements.

This EDTASM is essentially the same as that offered with NEWDOS/21 and NEWDOS/80 Version 1 except:

1. EDTASM will now display, as part of the 'A' CMD, after the TOTAL ERRORS display, the number of bytes left in the text area so the user can judge his approach to symbol table overflow or text buffer overflow.
2. (Model III only) Object code cannot be outputted to tape. The user must output the object code to disk and then use LMOFFSET to copy it to tape.

Supplemental instructions for the editor-assembler.

1. To load a text module into the text buffer, enter one of the following commands:

1. L D=filespec1 if text from disk
2. L T=nnnnnn if text from cassette

where filespec1 is the filespec for the assembler text module to be loaded into the text buffer from disk and nnnnnn is the name of the assembler text module to be loaded into the text buffer from tape.
Examples:

1. L D=OLDTEXT/SRC:1 loads the assembler text file OLDTEXT/SRC into the text buffer from the diskette currently mounted on drive 1.
2. L T=OLDTXT loads the assembler text file OLDTXT into the text buffer from tape.

If the text buffer already contains text, the query 'TEXT IN BUFFER. ARE YOU CONCATENATING???' appears. If you are not concatenating, reply N; the buffer is marked empty before loading the specified text module. If you are concatenating, reply Y to cause the new text to be appended onto the end of the old. No concern is shown for overlapping sequence numbers; therefore you should execute a N EDTASM command upon completion of the load to assure a valid set of ascending sequence numbers.

2. To store a text module:

1. W D=filespec2 if text going to disk
2. W T=nnnnnn if text going to cassette

where filespec 2 is the filespec of the disk file to receive the assembler text from the buffer and nnnnnn is the one to six character name given to the text file written to tape. Examples:

1. W D=NEWTEXT/SRC:1 The assembler text (not the object code) currently in the text buffer is written to file NEWTEXT/SRC on the current diskette mounted on drive 1.
 2. W T=NEWTXT The assembler text currently in the text buffer is written to tape and named NEWTXT.
3. For A commands with NO option not specified, respond to the query 'OBJECT FILE TO DISK OR TAPE? REPLY D OR T?':
1. T (Model I only) Object code going to cassette. The program name will come from the A command.
 2. D Object code going to disk. Respond to the query 'OBJECT FILESPEC?' with the nnnnnnnn/ttt.pppppppp:d filespec of the object module. The file will be opened immediately, but not written until end of assembly listing. The name in the A command is ignored.
4. When an output text or object disk file is opened, one of the following is displayed:
1. 'FILE ALREADY EXISTS. USE IT????'. Reply Y if this is your intention. Otherwise reply BREAK to terminate the W or A command.
 2. '***** FILE NON-EXISTENT. REPLY 'C' TO CREATE IT'. Reply C if this is your intention. Otherwise reply BREAK to terminate the W or A command.
5. Due to an error in the original DOS, EDTASM runs with interrupts disabled (except when re-enabled by disk I/O) in order that use of BREAK will function properly.
6. This EDTASM can execute in a regular TRSDOS Model I environment.
7. This EDTASM uses the standard keyboard, display and printer routines and control blocks. Users altering the system beware!!!!

6.6. CHAINBLD.

The BASIC program CHAINBLD/BAS is a simple program to allow users to create and modify chain files (chaining is discussed in section 4.3).

CHAINBLD operates in record mode, requiring that an EOL character (ENTER character) appear in the file at least every 240 bytes, and it treats each occurrence of the EOL character as both the end of a BASIC input line and the end of

a record within a chain file. All inserts, deletions, replacements, moves and copies are done in terms of records.

Furthermore, CHAINBLD makes no provision (except for the old Version 1 hex codes 80 - 83) for the file to contain special non-printable characters. The rule is that if the string resulting from the BASIC statement `LINEINPUT C$` does not contain a given character, then that character cannot become part of the chain file. The exception is the EOL character which is automatically supplied by CHAINBLD. If the user needs special characters in his/her chain file, some other program must be used to build the chain file. As a last resort, there is always SUPERZAP.

The CHAINBLD program starts off with a 16 second initialization period while it allocates maximum space to the string area. Users are warned that if `BREAK` is used to interrupt or terminate the CHAINBLD program, they must remember that all available space has been assigned to the string area and that due to this lack of space, some functions will not work. If a `CLEAR` is done to free up some space, be sure to specify a string area size.

After initialization, the main menu is displayed (not to be confused with the edit menu). The choices are:

1. **DELETE ALL TEXT LINES** All the text lines in the string area are deleted and the edit menu is displayed. When CHAINBLD starts execution, there are no text lines in the string area.
2. **LOAD EXISTING TEXT FROM DISK** Use this option to edit an existing chain file. If the string area already contains text lines, CHAINBLD will ask if those lines are to be deleted. If not, CHAINBLD returns to the main menu as it assumes the user wants to do more with the previous text. Otherwise the old text lines are deleted.

CHAINBLD will then ask for the existing chain file's filespec. If the filespec does not contain a name extension, the name extension `JCL` is assumed. The file is then loaded into the string area. The file cannot exceed the string area capacity and cannot have more than 1000 lines. The file must be segmented into records as discussed above. After the load, CHAINBLD displays the edit menu.

3. **SAVE TEXT TO DISK** The user has completed the creation and/or editing of the chain file text and now wants to write it to disk. If there are no text lines, the CHAINBLD will ask if a null file is to be written; if not, CHAINBLD goes back to the main menu.

Next, CHAINBLD asks if the file is to be written so that it can be processed by `NEWDOS/80` Version 1. If so, any `./0` through `./3` chain control records are changed as they are outputted by substituting the corresponding single byte control code (80H - 83H) in place of the `./x` character sequence. The text in the string area is not changed.

CHAINBLD then asks for the output file filespec. If the filespec does not contain a name extension, the name extension `JCL` is used. The file is then written to disk. When done, CHAINBLD goes back to the main menu.

4. **EDIT TEXT** This option does nothing except display the edit menu.

5. EXIT PROGRAM If the string area contains text that has not yet been written to disk, CHAINBLD asks if the user really wants to exit the program; if not, CHAINBLD goes back to the main menu. Otherwise CHAINBLD deletes all text lines and releases all string space except 50 bytes. The program then ends in the normal manner.

When the edit menu is displayed the user has a number of choices:

1. List text lines. The text lines are implicitly numbered in sequential order regardless of the changes that take place in the text. Line numbers do not belong to individual text lines. Instead a line number indicates the line's position at the current time within the file. This means that insert, delete, copy and move all change the line numbers of some or all of the text lines. The L and ; edit commands allow the user to display the text lines. L; displays the first line. L/ displays the last. L52 displays the 52nd line. In each case, if any text lines follow the target line in the text, they are also displayed. The ; edit command allows forward text paging.
2. The I edit command allows for a one or more text lines to be inserted in the text after the specified line. I0 does inserting at the start of the text. I/ does inserting at the end of the text. I23 does inserting after line 23. Lines are inserted into the text until, but not including, a line containing the /.// character sequence is encountered. That character sequence terminates the line insert mode.
3. The R edit command allows a new line to replace an old line. R43 causes text line 43 to be replaced with the new line that CHAINBLD will ask for.
4. The D edit command allows one or more text lines to be deleted. D34 deletes text line 34. D 20 41 deletes text lines 20 through 41.
5. The X edit command allows the specified text line to be added onto. Note that CHAINBLD does not actually allow a line to be edited. The edit mode really refers to editing the entire text.
6. The C edit command allows the specified lines to be duplicated to another part of the text. C 20 30 5 causes a copy of text lines 20 through 30 to be inserted after text line 5. Please note that the old lines 20 through 40 will now have line numbers 31 through 42.
7. The M edit command allows the specified lines to be moved to another position in the text. M 20 30 5 causes the text lines 20 through 30 to be deleted from the text and reinserted after text line 5.
8. The U edit command redisplay the edit menu.
9. The Q edit command redisplay the main menu.

The best way to learn CHAINBLD is to use it. The NEWDOS/80 distribution diskette comes with a sample chain file named CHAINTST/JCL. Load it in and look at it. Once in the string area, you may modify the text as desired, but do not store it back out as CHAINTST/JCL; use some other name.

6.7. ASPOOL.

1. The object module ASPOOL contained on the NEWDOS/80 diskette is H. S. Gentry's automatic Spooler Program, modified by Apparat to operate with NEWDOS/80 and to self-relocate. This program will automatically direct your printer output to the disk, and then automatically print it on the printer. This spooler program will print in the background while your foreground main program is executing provided the main program every second or so either sends a byte to be spooled or checks the keyboard for a new input character.

This spooler program is included on the NEWDOS/80 diskette as a free program to NEWDOS/80 owners. It is NOT a fully supported part of NEWDOS/80.

The basic operation of NEWDOS/80 DOS assumes that output that DOS sends to the printer will not involve disk I/O enroute to the printer. Therefore, the spooler discards all printer output it senses coming from DOS (such as PRINT, JKL, DIR with P option) with the warning message CAN'T SPOOL FROM DOS being displayed once for each spooled file.

This spooler program does NOT allow a spool file to be printed multiple times; once printed, the file EOF is set to 0 and the file closed to reclaim the file space. This spooler program does NOT remember spool contents from one spool activation to the next (this includes a reset). The user is warned that while the spooler is active, do NOT use reset or DOS library command BOOT to get to DOS ready. Instead, if another way is not available, use DFG to get to MINIDOS and then DOS library command MDBORT to get to DOS READY or use '123' to get to the DEBUG facility and then use DEBUG command Q to get to DOS READY.

2. INITIAL SETUP. Create a working spool module. Before the spool system can be used, working program module copy(s) of ASPOOL must be set up. You should set up a working program module for each different configuration you intend to use. When making a working program module, the input module 'filespec1' must ALWAYS be ASPOOL/MAS or a copy of it, and the output module 'filespec2' must NEVER be ASPOOL/MAS. To create a working spool program module (as opposed to the master), enter the DOS command filespec1,I (example: ASPOOL/MAS:0,I). The program will then ask for parameter specifications:

The program asks if the software printer driver whose address in is 4026H - 4027H at the time of spooler activation is to be used to drive the printer. Reply Y for yes or N for no (the spooler will drive the printer). If N, then:

The program asks if the printer is parallel or serial. Answer P for parallel or S for serial. If serial, then:

The program asks if the printer is an H14 type. Respond Y for yes and N for no.

The program asks if the printer output is to be formed into pages with a form feed between pages. Reply Y for yes and N for no. If Y, then:

The user will be asked for the number of print lines per page. Enter a number between 10 and 99.

The program asks if the printer uses a soft or hard form feed. A soft form feed is done by counting the number of lines printed and then printing carriage returns (0DH) (with or without line feeds (0AH)) until the end of the page is reached. A hard form feed is a single control character that causes a form feed function. If your printer will recognize a hard form feed answer H, otherwise answer S. If soft form, then:

The program asks for the total number of lines per page. Answer with a number between 10 and 99.

The program asks if a form feed is to be done at the end of each print file. Reply Y for yes and N for no.

The next question concerns automatic linefeed on each carriage return. Some printers linefeed on carriage returns and the computer should not output linefeeds. If your printer is of this type (Radio Shack standard) answer the question with N. If you want the software to generate linefeeds then answer with Y.

The program asks for the number of the disk drive that will be used to spool the print data. Answer with a number from 0 to 3.

The program asks for the number of seconds to transpire after the last keyboard key inputted until the spool program can start printing again. Respond with a 2 digit value 00 - 59. The purpose of a non-zero delay is to allow the keyboard to have primacy over the printer. When a keyboard key is depressed and if the spool program is printing a file, printer action will pause while keys are being inputted and until the required number of seconds have passed since the last key.

The program asks if the printer is to be driven by the timer interrupts (every 25ms on the Model I; every 33 or 25ms on the Model III) as well as via keyboard input and spooler output. Reply Y for yes if the interrupts are to be used; reply N for no. Allowing the interrupts to be used enables the spooler program to print while a foreground program is executing that does not frequently check the keyboard or send output to the spooler. The disadvantage of using the interrupts is that for a buffered printer, interrupts are disabled during the entire outputting of a line to the printer. However, the time delay will probably be no worse than that associated with disk I/O. If the interrupts are used, printing will nevertheless stop if the foreground program never sends anything to the spooler or tests the keyboard for input. This is because the disk I/O to read the next sector is done only during keyboard checking or main program output to the spooler. See circular buffer discussion for an additional disadvantage when the interrupts are used.

The program asks if the circular buffer is to be used to buffer keyboard input characters. Reply Y if yes; N if no. The circular buffer helps prevent lost keyboard input. If the 25ms interrupt is enabled to drive the printer (see above option), the circular buffer uses the ROM keyboard character input routine and therefore disables any drivers (such as

NEWDOS/80's keyboard intercept routine, lower case driver, etc.) activated before the spooler is activated. If the 25ms interrupt is not used to send spooled output to the printer, then that does not frequently check the keyboard or send output to the spooler. The disadvantage of using the interrupts is that, for a buffered printer, interrupts are disabled during the entire outputting of a line to the printer. However, the time delay will probably be no worse than that associated with disk I/O. If the interrupts are used, printing will nevertheless stop if the foreground program never sends anything to the spooler or tests the keyboard for input. This is because the disk I/O to read the next sector is done only during keyboard checking or main program output to the spooler. See circular buffer discussion for an additional disadvantage when the interrupts are used.

The program asks if the circular buffer is to be used to buffer keyboard input characters. Reply Y if yes; N if no. The circular buffer helps prevent lost keyboard input. If the 25ms interrupt is enabled to drive the printer (see above option), the circular buffer uses the ROM keyboard character input routine and therefore disables any drivers (such as NEWDOS/80's keyboard intercept routine, lower case driver, etc.) activated before the spooler is activated. If the 25ms interrupt is not used to send spooled output to the printer, then the regular keyboard routine(s) (as existed in the 4016H - 4017H vector at spool activation) is used. This latter also holds if the circular buffer is not used, regardless of whether or not the 25ms interrupt is used.

Now that the spooler has all the initialization parameters, the in-main-memory program is altered. The program then asks for the filespec of the working program module to be stored on disk. Respond with the filespec you will use in the filespec2,A DOS command discussed below; do NOT respond ASPOOL/MAS!!!!!! The working program module will be written to disk, and the spool program exits to DOS via 402DH.

3. ACTIVATE SPOOLING.

When spooling is to be used, enter the DOS command "filespec2,A" (example: SPOOLER,A) where filespec2 is the filespec of one of the working spool program modules you have created. filespec2 must **NEVER** be ASPOOL/MAS. If the spooler is already active, 'FILE ALREADY EXISTS' error message is displayed.

The module will load into the 5200H - 5FFFH region, relocate itself to HIMEM - areasize+1, and sets HIMEM = HIMEM - areasize where HIMEM is the DOS high memory address contained in Model I locations 4049H - 404AH (Model III locations 4411H - 4412H) and areasize is the amount of memory required by the spooler. Then the keyboard vector at 4016H - 4017H and the printer vector at 4026H - 4027H are intercepted to vector to the spooler. If interrupts are to be used, a routine is entered into NEWDOS/80's 25ms interrupt chain of user interrupt routines. 'SPOOLER ACTIVE' is displayed, and the 402DH exit is taken to DOS.

The spooler is now active. All data intended for the printer will be directed to one of five disk files (POOL1, POOL2, POOL3, POOL4, POOL5). Why five files you may ask? Well, when you have "printed" as much data as you wish and would like that data to be actually printed on the real printer, you send an end-of-file to ASPOOL. This is done either via DOS command *ASP,W (CMD"*ASP,W" from BASIC) or by outputting to the spooler a 03 byte in the normal print stream

(LPRINT CHR\$(3) from BASIC). The file that was spooling will be closed and scheduled for printing. You may now spool to another file by just "printing" more data. The data will be placed on the disk while the first data file is being printed. This procedure may be repeated five times. If you try to spool a sixth file before the first has been printed on the real printer, the system will display 'SPOOL FULL. WAITING ON PRINTER' and will hang until a file is printed. All data is printed on the real printer in the background while the current or another main task is executing or simply while the system is waiting for the user to tell it what to do next. Whenever *ASP,W is executed or a 03 byte is seen in the output to the spooler, the spooler program considers this an end of file (performing top-of-form if specified) even though you may be sectioning your spooled output for one report to keep the printer going and avoid running out of space.

Warning!!! The Model III ROM routine, normally used by the spooler, will discard the current character being sent to the printer if it senses the printer is not ready (including busy) and the BREAK key is pressed. Since the executing foreground program may be using the BREAK key while the spooler is printing in the background, there will be times when printer characters will be lost, unknown to the spooler. This can seriously limit the usefulness of any spooler on the Model III that uses the ROM printer driver routine.

You may bring the spool system down gracefully at any time by the DOS command *ASP,S (CMD"*ASP,S" from BASIC) or by sending a 04 byte in the normal output to the spooler (LPRINT CHR\$(4) from BASIC). This procedure will purge the current spool file, will prevent any new files from being created, and will display 'SPOOL STOPPING'. Main program execution then continues, any characters sent to the spooler will be ignored and the spooler continues to print any files that have been scheduled. When all files have been printed, the *ASP,P function is performed. NOTE, if the spooler appears to hang, it is probably waiting for the main program to check the keyboard. If the main program can't do this, try DFG, but wait till the drives stop.

You may bring the spool system down abruptly at any time by entering DOS command *ASP,P (CMD"*ASP,P" from BASIC). All remaining spooled data is lost. If an interrupt routine was active, it is purged. The keyboard and printer vectors are restored to what values they were when the spooler activated. If DOS's HIMEM value is the same as that set by the spooler when activated, HIMEM is set back to what it was before the spooler was activated, thus reclaiming the spooler's main memory. However, if the HIMEM is not the same, HIMEM is not changed, and the spooler memory remains lost to subsequent main programs. 'SPOOLER PURGED' is displayed, and the DOS 402DH exit taken to DOS.

You may flush the print queue at any time by entering DOS command *ASP,C (CMD"*ASP,C" from BASIC). The spooler will respond with "CLEAR BACKLOG OR PRINT (B/P)?". Respond with a B and Enter if you wish to clear the backlog, or a P and Enter to stop printing the current print file. Clearing the backlog does not purge the current print file, and clearing the current print file does not purge the backlog.

The status of the spool system may be determined at any time by entering the DOS command *ASP (CMD"*ASP" from BASIC). The system will print a list of all files waiting to be printed (BACKLOG) and any file that is open for printing or spooling. If the system has been stopped but not yet purged, "SPOOL STOPPING" will be displayed. If the spooler has been purged or not activated, 'FILE NOT IN DIRECTORY' is displayed.

7. DISK BASIC, NON-I/O ENHANCEMENTS.

7.1. For NEWDOS/80 most, but by no means all, of the interface specifications between BASIC and the BASIC programmer remain the same as for DISK BASIC under TRSDOS 2.3 on the Model I and for TRSDOS 1.3 on the Model III. The NEWDOS/80 BASIC user is expected to have and be knowledgeable of both the non disk BASIC manual and the disk BASIC portions of the TRSDOS manual for whichever of the two TRS-80 models is being used. The current and next chapters of this NEWDOS/80 version 2 documentation discuss only the differences from the TRS versions. Both the Tandy manuals are excellent; if they didn't come with your TRS-80 when you bought it, buy them!!!! Apparat does not, in this manual, duplicate their contents.

7.2. General Comments

1. When a BASIC syntax error occurs, BASIC does not automatically enter EDIT on the offending text line, but it does set that line as the current line. If the operator wishes to edit the line, press comma. This change is to make it more difficult for the operator to inadvertently clear variables that he/she would otherwise want to see to assist in debugging.
2. BASIC programs may disable the BREAK key via CMD"BREAK,N", and reen-able it by CMD"BREAK,Y".
3. Because CLOAD does a NEW function between consecutive bytes from tape, it will lose synchronization if BASIC is running with more than 3 file areas.
4. When a DOS error is encountered by BASIC and if no ON-ERROR routine is active, both the DOS error message and the BASIC error message are displayed.
5. BASIC now has a total of 8 overlays that it uses. The user will notice that disk I/O occurs whenever RUN is executed and whenever execution is interrupted (STOP, error or BREAK) or terminated (END); this is done to bring in BASIC routines needed for the current or anticipated next function.
6. NEWDOS/80 DISK BASIC does NOT allow text line deletion to be done by simply typing in the line number. The explicit delete command, DELETE or D, must be used.

7.3. DISK BASIC is activated by keying in one of the following commands to DOS:

1. BASIC
2. BASIC *
3. BASIC n
4. BASIC m
5. BASIC cmd
6. BASIC n,m,cmd
7. BASIC m,n,cmd
8. BASIC n,m
9. BASIC m,n
10. BASIC n,cmd
11. BASIC m,cmd

where:

***** means the user wants BASIC to reinstitute the program in the text buffer, using the same values for m and n as appear to exist in main memory. This allows the user to recover from an unwanted 'reset' or to get back to the same program after a CMD"S". If BASIC is able to accomplish this, it forces 'LIST' as its first command. If BASIC is unable to reinstitute the program, it exits to DOS READY. BASIC * will not work if n was less than 2 or if the program was less than 3 lines.

n = the number of fileareas that BASIC is to allocate, default = 3, maximum = 15. This is the highest fan (filearea number) that will be used in any statement during this invocation of BASIC. If the BASIC program is to use field item files with standard record length not equal to 256, then n must be specified and must be suffixed with the character V (see example 4 below).

m = memory size. The value m minus 1 is the highest memory location that BASIC is allowed to use. If m is not specified, the current DOS HIMEM value is used. All memory m and above is not used by BASIC and can be used for other routines such as printer drivers, special code USR routines, etc.

cmd = one line of BASIC text, consisting of one or more BASIC statements. This text line is considered direct keyboard input and will be executed as soon as initialization is completed.

Remember, the DOS command activating BASIC is limited by DOS to a maximum of 80 characters, including ENTER, and it is further limited to 32 characters, including ENTER if invoked via 'AUTO'.

Any error encountered during initialization causes a return to DOS.

If DOS is in RUN-ONLY state, the DOS command activating BASIC must contain a RUN or a LOAD (option R) statement.

Examples:

1. BASIC Brings up BASIC with 3 file areas, high memory set to the current value for HIMEM in DOS and displays 'READY', waiting for the operator's command.

2. BASIC,RUN"XXX/BAS" Brings up BASIC with 3 file areas, high memory set to the current DOS HIMEM value, loads BASIC program XXX/BAS into the text area and starts its execution.
3. BASIC,9,48152,LOAD"XXX/BAS" Brings up BASIC with 9 file areas, high memory set to 48151 (1 less than 48152), loads BASIC program XXX/BAS into the text area and displays 'READY', waiting for the operator's command.
4. BASIC,3V This works the same as example 1 above, except that each of the 3 file areas is assigned an extra 256 byte buffer. This extra buffer per filearea is needed if the program will be using field item files with a record length other than 256.
5. BASIC,CLEAR3000:A=1:RUN"XXX",V Brings up BASIC with 3 fileareas, sets its high memory value to DOS's current HIMEM value, performs CLEAR reserving 3000 bytes for the string area, sets numeric variable A equal to 1, loads BASIC program XXX and commences its execution without clearing the variables, thus leaving variable A intact for the program to inspect.

7.4. NEWDOS/80 DISK BASIC allows the following 'direct' commands:

. (period) LIST the current text line.

down-arrow LIST the next text line. If there is no next text line, performs as / .

up-arrow LIST the text line before the current line. If none, performs as ; .

; or **shift-up-arrow** LIST the first text line.

/ or **shift-down-arrow** LIST the last line in text. Users having the newer ROM will find that shift-down-arrow is no longer a usable key; hence the need for / .

: Scroll one display page toward the start of the text. When done, the previous current text line is now at the bottom of the display excepting that if the previous command was : or @ , the previous display's top line is now the new display's bottom line. The new current text line is the bottom line on the new display.

@ Scroll one display page toward the end of text. When done, the previous current text line is now at the top of the display, and the new current text line is the bottom text line on the new display.

, (comma) EDIT the current text line.

Only 1 such command per direct statement line, and the command, to be seen, must be the first character of the input line (no line number or backspacing allowed).

7.5. NEWDOS/80 DISK BASIC allows the truncation of the commands AUTO, DELETE, EDIT and LIST to A, D, E and L respectively when the following conditions are met:

1. 1st character of the input line.
2. Followed by either a period or a decimal digit.
3. The input line does not contain an =.

7.6. DI and DU Two additional BASIC text editing functions are implemented using the following forms of direct command:

1. DI aaaaa,bbbb
2. DI .,bbbb
3. DU aaaaa,bbbb
4. DU .,bbbb

where:

aaaaa is the line number of the text line to be moved or duplicated, and **bbbb** is the line number to be given the moved text line or the duplicate of the text line.

DI means to delete the line at aaaaa and insert it at bbbb.

DU means insert at bbbb a duplicate of the text line at aaaaa, but do not delete the line at aaaaa.

Text referring to aaaaa is not altered to refer to bbbb. If this is desirable, then use RENUM to move the text line.

The use of a period in place of aaaaa causes aaaaa to default to the last line listed, edited or deleted.

7.7. RUN and LOAD may now optionally retain all variables and open fileareas by using the V option in the following formats:

```
RUN"filespec",V
LOAD"filespec",V
```

where filespec is the filespec of the program file being executed. The LOAD with the V option executes exactly the same as the RUN with V option. The RUN with V option preserves all the variables, excepting DEFFN variables, during the execution of RUN; thus the variables existing before the RUN statement can be used after the RUN statement. Any fileareas open prior to the RUN are left open for use after the RUN statement. If the V option is specified, the R option may not be. See example 5 in section 7.3.

7.8. The **MERGE** statement has been expanded:

MERGE will merge either an ASCII or a packed text file.

MERGE may be executed as a direct statement or as a program statement.

If **MERGE** is executed as a program statement, the **MERGE** statement must not be part of a **DEFFN** statement, a subroutine or a **FOR-NEXT** loop (as a **POPS** function is implicitly performed), must be the last statement of the text line, must be followed by the text line where execution will continue after the **MERGE**, and the merge file must not contain a line whose number is the same as the number of a text line existing at the start of the execution of the merge (use **CMD"F",DELETE** to delete conflicting text lines before executing the **MERGE**). The merge protects all variables. The user must assure enough main memory space is available for the merge as error recovery is not possible if the merge fails once actual merging commences. Example:

```
100 MERGE"XXX/BAS"  
110 X=1          execution continues here after the MERGE is completed
```

7.9. **RENUM** Renumber the Current BASIC Program.

```
RENUM sssss,iiiii,ppppp,qqqqq[,U][,X]  
RENUM ,  
RENUM U  
RENUM X  
RENUM U,X
```

The current BASIC program or a part of it may be renumbered while it resides in the text area. Via the **U** option, the **RENUM** does not actually perform renumber but only does its text error checking, thus allowing the undefined line numbers and some, but not all, syntax errors to be found. The user may, by proper choice of the new line number values, move a portion of the program to a different place in the program with all references to any of the moved lines changed to the new lines numbers. Lastly, via the **X** option, **RENUM** will not declare as an error any undefined line number if that line number lies outside of the range of lines being renumbered, thus allowing a program to have references within it to lines that are intentionally not part of the program.

The basic renumber command causes all text lines whose line numbers are greater than or equal to **ppppp** and less than or equal to **qqqqq** to be assigned new line numbers. **sssss** is the first new line number assigned with subsequent numbers generated by adding **iiiii** to the line number of the previous text line. **sssss** and **iiiii** must be in the range 1 - 65529 and have default value 10. **ppppp** must be in the range 1 - 65529, has default value 0. **qqqqq** must be in the range 1 - 65529, greater than or equal to **sssss**, and has default value 65529. The range of newly generated line numbers must not encompass any old text lines that are not part of the resequenced range **ppppp** - **qqqqq** inclusive. So long as this rule is observed, the newly generated line number range may be placed anywhere in the text with the renumbered text moved to the proper new text location.

At least one parameter must be specified. If the user wants to specify all defaults and neither X nor U, then use a comma as the only parameter.

For the series sssss,iiii,ppppp,qqqqq, if one or more of the 4 numbers are to use the default values, then commas must appear in the proper place to indicate which of the 4 values a given line number is for. See example 4 below.

If the U option is specified, the text is not altered in any way and RENUM simply searches text for undefined line numbers and for some errors associated with BASIC statements that use line numbers. These errors are displayed in the following format:

```
sssss/U - there is no text line sssss.  
sssss/X - text line sssss has syntax error.  
sssss/S - text line sssss has a bad line number.
```

If the X option is specified, references to non-existent text lines are not displayed as errors if that line number is also outside of the ppppp to qqqqq range. The X option is intended as aid to programmers who use a base program and overlay programs which refer to text lines in each other.

If any error is encountered before text is altered, the command reverts to performing as if the U option had been specified and displays all the errors it can find. If an error is encountered after text alteration begins, 'FATAL ERROR. TEXT NOW BAD' is displayed and the 4030H exit taken to DOS. The BASIC text must not be reclaimed (don't use BASIC *).

If either SYS11/SYS or SYS13/SYS are not in the system when RENUM is executed, the system will exit to DOS READY (see section 5.5).

RENUM will refuse to renumber a program whose first text line's number equals 0. Use 'DI' to assign the line a number other than 0. Examples:

1. RENUM U The BASIC text is checked for undefined line numbers and other errors that would normally be encountered in an actual renumber. The BASIC text is not altered.
2. RENUM , The entire BASIC text is renumbered using an increment of 10. The first text line is assigned line number 10, the 2nd assigned line number 20, and so on.
3. RENUM 100,100 The entire BASIC text is renumbered using an increment of 100. The first text line is assigned line number 100, the 2nd is assigned 200, and so on.
4. RENUM 2050,,2050,3160 All text lines from and including any line numbered 2050 to and including any line numbered 3160 are renumbered using an increment of 10. The first renumbered line is assigned line number 2050, the second is assigned 2060, and so on.
5. RENUM 30000,5,15365,18112 All text lines from and including any line numbered 15365 to and including any line numbered 18112 are renumbered using an increment of 5. The first renumbered line is assigned line number 30000, the 2nd is assigned 30005, and so on. The renumbered text lines are moved to the new positions in the text.

7.10. REF The BASIC statement REF allows the BASIC programmer to find all places in the program where a line number, an integer, a variable, a string, a function code, a packed sequence of characters or an unpacked sequence of characters is referenced. REF has the following formats:

1. REF* Display full reference list for all line numbers, integers and variables.
2. REF\$ Print on the printer a full reference list for all line numbers, integers and variables.
3. REFnn Display all references to the variable(s) named nn. If nn is only 1 character, a blank is assumed for the second. nn may not be more than 2 chars and must not have a type suffix.
4. REFsssss Display all references to the line number and/or integer sssss where sssss is a 1-5 decimal digit number between 0 and 99999. Hexadecimal or octal references within the text are not listed.
5. REF*nn
6. REF\$nn
7. REF*sssss
8. REF\$sssss
9. REF Display the next text line containing at least one reference to the variable or number specified by the last REFnn or REFsssss statement executed. If there are no more referencing text lines, 'TEXT END' will be displayed. If 'REF' entered again, the first referencing text line will be listed. Remembrance of the search variable name or number and the current search line number within the text is usually (but not always) lost when any command involving DOS is executed.
10. REF=xxx The character sequence xxx is packed by the standard BASIC text packing routine. The BASIC text is then searched for a match on the packed xxx value and the line numbers listed for all lines containing the packed xxx value. If the packed value xxx is more than 16 bytes long, only the first 16 packed bytes participate in the compare. This format of REF is to be used when the user wants to know where in the text a BASIC function code (i.e., PRINT, LPRINT, GOTO, etc) is used. The text lines containing xxx can be displayed one at a time by repeated issuance of the format 9 REF command.
11. REF"xxx This format operates similar to format 10 except that xxx is not packed. xxx is considered a string unless xxx itself contains a ". This format allows xxx to be found in strings and comments.
12. REF@sssss This statement is similar to format 9 except that the search will start with 1st text line whose line number is greater than or equal to sssss.

Press BREAK to pause, ENTER to continue, and up-arrow to terminate the REF function. Formats 5-8 are the same as 1 and 2, except listing/printing starts

with the specified variable name or decimal number, if it exists, or the next higher existing name or number, if not.

If SYS12/SYS is not in the system when the REF statement is executed, the system will exit to DOS (see section 5.5).

7.11. Text String Lower Case Suppression (Model I only) Users who do not have the hardware lower case modification or those that do but don't use a lower case driver to bypass the ROM display routine will occasionally be puzzled why some string compares fail and syntax errors appear in perfect appearing statements. This is due to the acceptance of lower case letters into strings which display as upper, and the acceptance of lower case @ into text statements. Remember the ROM swaps lower case to upper and vice versa before BASIC sees the characters. In the case of data, there is nothing that can be done about this problem except to remember that if it appears equal on the display, there still may be a lower case/upper case mismatch in memory. For text input, if system option AS = Y, text string lower case letters, but not lower case @, will be forced to upper case, eliminating many of these problems.

7.12. RUN-ONLY For DISK BASIC there are two ways BASIC can be forced to run in RUN-ONLY mode: (1) if system option AB = Y, and (2) if the BASIC program file is password protected, passwords are enabled, the access password specified in the RUN or LOAD (option R) statement and the access level = EXEC.

If system option AB = Y, the DOS command activating BASIC must contain the necessary RUN or LOAD (option R) statement to start a program executing as the operator is not allowed to input any direct command statements.

In RUN-ONLY, the BREAK key is disabled and BASIC is inhibited from accepting direct statements (data is OK) from the operator. The program has full control, and must exercise it. A menu program can issue RUN or LOAD (option R) statements for other BASIC programs, and those programs can do the same to return to the MENU program or go on to the next program of a sequence. Optionally, a base program may remain in memory at all times, and via CMD"F", DELETE and MERGE, bring in overlay programs as necessary. Programmers should carefully study available options under RUN, MERGE, LOAD, and CMD"F" functions.

7.13. Comparisons in the use of the function CMD between NEWDOS/80 and TRSDOS.

1. **CMD"A"** Not implemented; use CMD"S".
2. **CMD"B"** Not used on the Model I by NEWDOS/80 nor TRSDOS. TRSDOS' Model III use is not implemented in NEWDOS/80; use CMD"BREAK,Y/N"
3. **CMD"C"** This command (1) compresses out all spaces from the program text, excepting for those within strings, and (2) deletes all remarks from

the text, including entirely those lines which are entirely remarks. The statement `CMD"C",S` compresses out all spaces from the program text, excepting those within strings and remarks. The statement `CMD"C",R` deletes all remarks from the text, including deleting entirely those lines which were entirely remarks.

In some cases, `GOTO`, `GOSUB`, etc. refer to a text line that is entirely remarks and the deletion of remarks from the text will cause these referenced lines to disappear. The programs should be altered to have these `GOTOs` and `GOSUBs` refer to text lines that are not entirely remarks. After remarks have been deleted from a program, execute `RENUM U` to determine if there are any undefined line numbers resulting.

Though BASIC is designed to ignore spaces that are not in text remarks or character strings, the removal of spaces from text can still cause confusing situations. For example, compressing

```
10 FIELD 1, 20 AS C$
20 IF F OR D THEN 10
to
10 FIELD1,20ASC$
20 IFFORDTHEN10
```

will cause syntax errors to occur for both lines during execution after either (1) the program has been stored in ASCII and then read back in or (2) the lines have been edited. To avoid these problems that may exist for weeks or months before either of the above two conditions occur, the `CMD"C"` function automatically unpacks each compressed text line, packs it again and compares the new packing with the old that existed before the spaces were compressed out. For any text line where the two packings are different in any way, the spaces are restored into that text line (remarks, if deleted, remain deleted) and the line's number is listed on the display. The user may then inspect these lines and remove spaces that won't affect the program. For any given program, there should be very few lines rejected by `CMD"C"`.

4. **CMD"D** TRSDOS' meaning is not implemented on the Model III under NEWDOS/80; use `CMD"doscnd`. On the Model I, `CMD"D` still invokes `DEBUG` though 123 is the preferable method.
5. **CMD"E** Displays the DOS error message associated the latest DOS error encountered by BASIC.
6. **CMD"F** Not used in TRSDOS. In NEWDOS/80, there are two formats:
 1. `CMD"F",fc` used when the function code `fc` must be findable by `REF`, `RENUM` and others.
 2. `CMD"F=fc` used when the function code `fc` is not to be seen by `REF`, `RENUM`, etc. or where the specially defined function code could be confused by the normal text packing routine.

These `CMD"F` functions are specified in sections 7.15. thru 7.20.

7. **CMD"I"** Not used on the Model I by either NEWDOS/80 or TRSDOS. TRSDOS' Model III use is not implemented in NEWDOS/80; use **CMD"dos-cmd"**.

8. **CMD"J"** Calendar Date Conversion.

CMD"J",date1,date2

converts the expression date1 to the appropriate format and stores the result in the string variable date2. If date1 is in mm/dd/yy format, date2 is stored in ddd format and if date1 is in -yy/ddd format, date2 is stored in mm/dd/yy format where:

mm is a two digit month value between 01 and 12.
dd is a two digit day-of-the-month value between 01 and 31.
ddd is a three digit day-of-the-year value between 001 and 366.
yy is a two digit relative year-within-century value between 00 and 99. For leap year conversions, yy is assumed to be in the 20th century, i.e., from 1900 to 1999.

9. **CMD"L"** TRSDOS Model III meaning not implemented in NEWDOS/80; use **CMD"LOAD,filespec"**. This function is not used on the Model I.

10. **CMD"O"** Array Sort; see discussion below (section 7.21.) for **CMD"O"**.

11. **CMD"P"** Not used on the Model I. TRSDOS' Model III meaning is not implemented in NEWDOS/80; use **PEEK(&H37E8)** to obtain the 0 - 255 value for the current printer status.

12. **CMD"R"** TRSDOS' Model III meaning is not implemented in NEWDOS/80; use **CMD"CLOCK,Y"**. On the Model I, **CMD"R"** still reenables the interrupts as before.

13. **CMD"S"** Exit BASIC and return to DOS READY state. However, if the command is of the form **CMD"S=doscmd"**, then the following occur:

1. The DOS command doscmd is moved into the DOS command buffer.
2. BASIC exited.
3. The DOS command placed into the DOS buffer is executed immediately without an intervening DOS READY.
4. When that command is completed, control returns to DOS READY and not to BASIC.

14. **CMD"T"** TRSDOS' Model III meaning is not implemented in NEWDOS/80; use **CMD"CLOCK,N"**. On the Model I, **CMD"T"** still disables the interrupts as before.

15. **CMD"X"** Not used on the Model I by NEWDOS/80. TRSDOS' Model III meaning is not implemented; use the **REF** command.

16. **CMD"Z"** Not used on the Model I by NEWDOS/80. TRSDOS' Model III meaning is not implemented; use **CMD"ROUTE,..."**.

7.14 CMD"doscnd"

If the string expression associated with the CMD function has two or more characters and does not start with either "S=" or "F=", then the string is assumed to be a command to be executed by DOS. BASIC moves the command to DOS' command buffer, sets DOS to MINI-DOS mode, and calls DOS to execute the command via 4419H, DOS-CALL. Upon return, BASIC turns off DOS' MINI-DOS mode. If DOS has rejected the command because it was not legal under MINI-DOS, BASIC then attempts to reissue the command to DOS under normal mode by doing the following:

If approximately 8,000 bytes are not available between the top of BASIC's array areas and the bottom of BASIC's stack (which is immediately below the string area), BASIC declares OM ('OUT OF MEMORY') error and terminates the current statement. If the space is available, BASIC moves all of memory from 5200H to 70FFH to that free area, sets itself to use stack area 7000H-71FFH and computes a checksum over the region from 7100H to the top of BASIC's memory (takes about 2 seconds). Then it calls DOS to execute the DOS command. Upon return from DOS, BASIC moves the saved region back to 5200H-70FFH and recomputes the checksum (again, another 2 seconds). If the check fails, this means that the DOS command executed has altered some of BASIC's bytes; BASIC cannot continue and exits to DOS with 'BAD MEMORY' error.

Whichever way the command was executed, BASIC now checks the return code from DOS. If an error occurred and the error message has already been displayed, BASIC terminates the CMD"doscnd" statement with 'PREVIOUSLY DISPLAYED ERROR' error state. If a DOS error occurred, BASIC calls 4409H to display the DOS error message and terminates the CMD"doscnd" statement with 'DOS ERROR' error state. If no error occurred, BASIC continues with normal processing.

Any DOS library command or assembly language program (that will execute using only the 5200H - 6FFFH region and/or a non-BASIC, non-DOS region of main memory) can be executed in this fashion. SUPERZAP and DIRCHECK are two programs that may be executed through CMD"doscnd". FORMAT and most forms of COPY can be done; however, single drive, two diskette copies cannot be done as they require the maximum amount of memory. Also, don't specify the UBB parameter in COPY.

Remember, DOS commands are limited to 80 characters, including the ENTER character that BASIC will append to the doscnd string when moved to the DOS command buffer.

User programs are warned to leave the Model I memory area 4080H - 41FFH (Model III area 4080H - 41E2H) alone except where alteration is in conformance with BASIC's current uses.

CMD"BASIC" should never be executed. If for some reason the programmer wants to exit BASIC and return, use CMD"S=BASIC".

Almost all DOS commands may be executed via CMD"doscnd". Examples:

1. CMD"DIR 1" list a directory
2. CMD"COPY XXX:0 YYY:1" copy a file
3. CMD"COPY 0 1 07/10/81 FMT" full diskette copy, with format
4. CMD"SUPERZAP" executes program SUPERZAP and return to BASIC
5. CMD"DO CHAINFIL" perform chain file functions and return

7.15 **CMD"F=POPS", CMD"F=POPR" and CMD"F=POPN":**

If the statement is **CMD"F=POPS"**, then all returns and FOR-next controls are purged, leaving BASIC with no outstanding returns or nexts. When done, execution continues with the next statement. The purpose of this statement is to allow the programmer to 'bail-out' of complex coding and return to BASIC's first level. This avoids leaving residual information in BASIC's control stack which on recursive returns to the high level without **CMD"F=POPS"** will eventually cause program failure.

If the statement was **CMD"F=POPR"**, then the current GOSUB level is purged along with any outstanding FOR-NEXTs for that level. This is the same as return except control does not pass to the statement following the associated GOSUB, but instead passes to the statement following the **CMD"F=POPR"** statement.

If the statement is **CMD"F=POPN"**, then the most recently established FOR-NEXT's control data is purged. This is the same as 'NEXT' where the loop limit is exceeded. Execution continues with the statement following the **CMD"F=POPN"** statement.

If the statement is **CMD"F=POPN" vn** where vn is a variable name, the FOR-NEXT loop associated with vn is purged along with any other FOR-NEXT loops established while vn's loop was outstanding. Execution is the same as for 'NEXT vn' when the loop is to end. Execution continues with the statement following the **CMD"F=POPN" vn** statement. The purpose of **CMD"F=POPN"** is to allow breaking out of a loop while not leaving residual loop control information that can confuse the programmer if he/she subsequently uses FOR-NEXT variables in reverse order.

7.16. **CMD"F=SASZ"** Change BASIC's string area size without affecting or clearing the variables.

CMD"F=SASZ",expl

allows the string area size to be changed without clearing the variables. expl must be a value large enough allow the string area to contain the strings that it contains when the statement is executed. An error will be generated if expl is too small or is too large (i.e., will cause overlap with the text, scalar and array areas). Example:

CMD"F=SASZ",4000

7.17. **CMD"F=ERASE" and CMD"F=KEEP"** Selective clearing of BASIC variables.

CMD"F=ERASE",vn1,vn2,vn3... allows the specified variables to be cleared. If a specified variable is within an array, the entire array is cleared. The size of the string area is not changed. This statement should be used when an array is no longer needed or the user wishes to redimension it by a subsequent DIM statement. This statement may be

multi-text lines as described for CMD"F=KEEP" below.

CMD"F=KEEP",vn1,vn2,vn3... causes all variables to be cleared except those specified and except specially defined variables such as those defined by a DEFFN statement. The size of the string area is not changed. If no variable names are specified, all variables are cleared, except the special ones. If a specified variable name is within an array, the entire array is exempted from the clear. The statement may specify as many variable names as desired with overflow from one text line to the next non-comment text line taking place whenever the last variable name of a text line is followed by a comma. Example:

```
CMD"F=KEEP",A$,B$,C,D$, 'statement first line
E!,F,G$, 'statement 2nd line
REM this line is bypassed
H!,I 'statement last line
```

7.18. CMD"F",DELETE Dynamic deletion of text lines:

CMD"F",DELETE ln1-ln2

This statement allows the text lines from and including any line numbered ln1 to and including any line numbered ln2 to be deleted during program execution. All variables are retained, excepting that DEFFN variables for DEFFN statements in the delete range are cleared. The string area size is not changed. Any string variable whose current string was actually in the deleted text area has that string moved to the string area. CMD"F",DELETE must not be executed as a direct statement, must not be contained in a DEFFN statement, a subroutine or a FOR-NEXT loop (as a POPS function is implicitly performed), must be the last statement on its text line and must be followed by the text line where execution will continue after the delete. Example:

```
1000 CMD"F",DELETE 10500-15000
110 X=1 execution continues here after the DELETE is completed
```

7.19. CMD"F=SWAP" Swapping of variable contents:

CMD"F=SWAP",vn1,vn2

This function swaps the value of variable vn1 with that of variable vn2. Both variables must be of the same type, i.e., both strings, both single precision floating point, etc. Example:

```
CMD"F=SWAP",A$,B$
```

7.20. **CMD"F=SS"** BASIC single stepping:

1. **CMD"F=SS"** turn on single stepping
2. **CMD"F=SS",ln1** single stepping starts at line ln1.
3. **CMD"F=SS",N** turn off single stepping.

The BASIC programmer may now single step through program execution. Using either format 1 or 2 above sets BASIC into single step mode, though for format 2, actual single stepping does not start until text line ln1 is the next line to be executed. A single BASIC text line is executed for each step, and between steps the line number for the next line to be executed is displayed in '@nnnnn' format in the display upper right corner to indicate that BASIC is waiting for the operator to respond. Responding ENTER causes line nnnnn to be executed and then BASIC waits for user response again. Responding BREAK causes execution to be broken in the normal manner though it should be noted that the line number the BREAK shows is for the line just executed or being executed while the '@nnnnn' display is for the next line to be executed. If the user does not change text during BREAK, the program may be continued via CONT; in this case, the '@nnnnn' display will immediately reappear without execution of a line. Pressing ENTER will then execute the line. While in BREAK, the operator may turn single stepping on or off as desired without affecting the ability to CONT. If the BREAK occurs before RUN or LOAD,R executes one text line, CONT will not work.

Single stepping or the scheduling of the single stepping to start when a particular text line is encountered remains in effect until either **CMD"F=SS",N** is executed to turn it off or until a format 2 type stepping command is executed, wherein stepping goes off until the specified line is encountered. The execution of RUN, LOAD, NEW, etc. does affect single stepping state.

7.21. **CMD"O"** The main memory BASIC array sort has 2 formats:

1. **CMD"O",n,av1[,av2,....]** (direct sort)
2. **CMD"O",n,*iav1,av2[,av3,...]** (indirect sort)

In explaining this sort, the term REN is used and is defined to mean a Relative Element Number identifying an array element. The elements within any BASIC array, regardless of dimension, are integer numbered from 0 up. If an array has only one dimension, then an element's REN is simply the value of its subscript and if you use only single dimensioned arrays, you can ignore the rest of this paragraph. However, if you use multi-dimensional arrays, then you should know which method to use to increment array subscript values in order to extract elements in the sorted order. **CMD"O"** does not care what dimension the arrays have; it simply counts off the array elements in the order BASIC stores them in main memory. You, the programmer, do care as you must use subscripts in order to access the array elements. For multi-dimensional arrays, the rule for computing the REN is complex and can best be illustrated by a three dimension array example using two statements:

```
DIM A(R1,R2,R3)
Y = A(X1,X2,X3)
```

where the REN of this element is computed as $X1+X2*(R1+1)+X3*(R1+1)*(R2+1)$. If the array had only two dimensions, then the REN would be $X1+X2*(R1+1)$, and, of course, if the array had only one dimension, the REN would simply be $X1$.

If the CMD"O" statement specifies more than one array, excluding iavl, then the RENs for the first sort item in each array, excluding iavl, must be equal.

The sorting order used has one level for each array specified, excluding the iavl array, with highest to lowest level in the order, left to right, of the array variables in the CMD statement. Within each level, the normal sort order is ascending ASCII (actually hexadecimal) numeric value for character string arrays and most negative to most positive value for numeric arrays. However, if the array variable in the CMD statement is prefixed with a minus sign (example: -A#(0)), then the order of sort within that level is descending ASCII (actually hexadecimal) numeric value for character string arrays and most positive to most negative value for numeric arrays. A null compare string character is considered to have a numeric value less than 0.

Normally in character compares, the entire string is used in the compare. However, if the array variable in the CMD statement is suffixed with a field of the form (x,y) (Example: A\$(1)(5,4)), then the compare starts with the xth character of the string and compares using only y characters.

n is the number of elements in each of the arrays participating in the sort. Only n elements from each array participate in the sort. Elements of an array below or above the n elements specified do not participate. If n is a zero value, then for the sort, n is set to the number of elements in first array specified from and including the element specified through and including the last element of the array.

If the number of elements in any array from and including the specified element to and including the array's last element is less than n, FC error is declared.

A maximum of 9 arrays may be specified. All array variable subscripts, except for the indirect array if specified, must evaluate to the same REN value.

Format 1 is a direct sort meaning that the elements of all 1 to 9 arrays are moved around to conform to the desired sort order.

av1 must be specified; av2 and up are optional.

The resulting order of the n elements in each array is the same for each array (i.e., the arrays are not sorted independently). Thus, if the jth element of array 1 is sorted into the kth element slot, then for each of the other arrays, if any, the jth element is also placed into the kth element slot.

Format 1 is compatible with TRSDOS Model III BASIC CMD"O" if and only if only one array variable is specified, it is for a string array and n is an integer variable.

Format 2 is an indirect sort. In this sort, only the n elements of array iavl are altered; the other arrays are not changed in any way. The intent of format 2 is to allow a sorted sequence to be determined without actually changing the

arrays supplying the sort values. A user may have a group of data records spread across a number of arrays such that a record consists of one element from each array, with the REN of each of those elements making up the record equalling the record number. By using format 2 with the indirect array, the user may effectively sort the records using a subset of the items as the sort criteria and without actually rearranging the order of the records, thus leaving them in record number order.

Format 2, as opposed to format 1, is indicated by specifying the iavl array variable, prefixed by an *.

iavl must be an integer array variable.

av2 must be specified; av3 and up are optional.

The n consecutive elements starting at iavl are initialized with the RENs corresponding to the n consecutive elements of array av2 (which also correspond to the RENs for the other arrays, if any).

During sorting only array iavl is altered; , arrays av2 and up are not altered.

Upon completion, the n elements of array iavl are in the desired sorted order such that by using successive values out of array iavl as subscripts, the user may access elements from any of the other arrays (that are single dimensioned) in that sorted order. Accessing multi-dimensioned arrays is more complex and is left as an exercise for the more advanced user.

Example program using a number of sorts:

```
10 DIM NM$(200), AM!(100), LN$(100), IX$(100), ZC!(50), L$(50)
30 X=150
40 CMD"0",X,NM$(0)
60 CMD"0",X,-NM$(25)
70 CMD"0",0,-AM!(1),LN$(1)(5,3)
80 CMD"0",100,*IX$(0),ZC!(1),L$(1)
```

At line 40 the first 150 elements of array NM\$ (elements NM\$(0) to NM\$(149)) are sorted in ascending order. If any of the strings are null, they will appear first in the resulting array. The last 51 elements of array NM\$ (elements NM\$(150) to NM\$(200)) do not participate in the sort and are left unchanged.

At line 60 elements NM\$(25) through NM\$(174) are sorted into descending order, with null strings, if any, appearing as the end elements of those 150 elements. The first 25 and the last 26 elements of the array do not participate in the sort.

At line 70 the AM! and LN\$ arrays are both sorted, both in the same order which is first by descending order of AM! array values and then, where AM! array values are equal, by ascending order of LN\$ array values where only the 5th, 6th and 7th characters of the LN\$ array elements participate in the sort determination. If a LN\$ array element has less than 5 characters, it is considered a null for sort determination purposes. AM!(0) and

CAREFULLY STUDY chapter 11 of NEWDOS/80 documentation for instructions on how to apply zaps.

Some modules have multiple versions with the zaps different in each version. Use the verify to determine which version you have and apply the appropriate zap(s). If you have a version different from any listed (i.e., the verify(s) do not match, contact the program's distributor or Apparat). Apparat is trying to get the program creator/maintainer/distributor to create and distribute the necessary zaps to run with NEWDOS/80, Version 2, but where this does not occur and for widely used programs, Apparat will generate any necessary zaps. If Apparat decides to generate the zaps and does not have your particular version, you will be asked to send the version you have on a diskette (as a gift to Apparat, see chapter 11) to Apparat so that Apparat may determine the appropriate zaps; Apparat will not seek out your version from another source, and will not create a zap from a paper listing.

***** ZAP 001 ***** 08/04/81 ***** V2M1 *****

Mandatory zaps to Microsoft's EDIT/CMD to enable it to run with NEWDOS/80. You must maintain separate copies of this module for each of TRSDOS and NEWDOS as the module for one system is incompatible with the that for other though the files they manipulate are compatible. These changes are due to the FCB's NEXT and EOF fields being defined in NEWDOS differently than in TRSDOS.

EDIT/CMD,38,E8 change
7E E6 7F 7E 21 FE FF CA 58 78 EE 80 87 DA 5D 78 to
7E 60 69 D6 01 30 01 2B 29 07 30 01 23 18 04 78

EDIT/CMD,32,A2 change
78 E6 7F C2 28 72 78 EE to 78 D6 01 30 08 18 04 EE

***** ZAP 002 ***** 08/04/81 ***** V2M1 *****

Mandatory zap for PENCIL/CMD to disable the alteration of a DOS location by PENCIL. This alteration of DOS by PENCIL is not needed in either NEWDOS/80 or NEWDOS/21.

PENCIL/CMD,00,AE change F3 32 9B 46 C3 to F3 00 00 00 C3

Apparat has been advised that the following two zaps to PENCIL/CMD will (1) allow PENCIL/CMD to read the directory properly and (2) enable the use of MINI-DOS under PENCIL/CMD.

PENCIL/CMD,05,60 change 58 23 22 to 58 00 22

PENCIL/CMD,00,61 change 54 22 16 40 21 to 54 00 00 00 21
This latter zap prevents PENCIL/CMD from using its own keyboard routine,

thereby defaulting back to NEWDOS/80's wherein 'DFG' invoking MINI-DOS can be spotted.

***** ZAP 003 ***** 08/04/81 ***** V2M1 *****

Mandatory zap to Radio Shack's programs SCRIPSIT/UC and SCRIPSIT/LC to run under NEWDOS/80 (and NEWDOS/21). The user should maintain separate copies for NEWDOS and for TRSDOS as the programs for each system are incompatible with the other system even though the files they manipulate are compatible. The first 3 changes are necessary because of the different way the FCB's NEXT and EOF fields are maintained. If you are running NEWDOS and files appear to load short one sector, check to make sure these zaps are in. The 4th zap causes DOS' HIMEM address value in 4049H - 404AH to be used as SCRIPSIT's high memory. The 5th zap re-enables the interrupts so MINI-DOS can be invoked from SCRIPSIT.

SCRIPSIT/UC,11,75 and SCRIPSIT/LC,11,75
change 47 00 CD 6E 7A 4F to 47 00 3A B9 7C 4F

SCRIPSIT/UC,11,FB and SCRIPSIT/LC,11,FB
change B7 C4 EF 5D 79 to B7 32 B6 7C C4

SCRIPSIT/UC,12,00 and SCRIPSIT/LC,12,00
change 32 B9 7C 11 to EF 5D 00 11

SCRIPSIT/UC,00,63 and SCRIPSIT/LC,00,63 change
7C 21 FF 00 25 7E 2F 77 AE 20 F9 22 to
7C 2A 49 40 00 00 00 00 00 00 22

SCRIPSIT/UC,00,C3 and SCRIPSIT/LC,00,C3
change 57 F3 ED to 57 00 ED

***** ZAP 004 ***** 08/04/81 ***** V2M1 *****

Optional zap to increase drive power on delay to the full one second used in older DOSs. NEWDOS/80 waits only 1/2 second for the the drives to attain rotational speed during power on select. If you feel the drives would perform better with the longer delay, apply this zap.

SYS0/SYS,04,C3 change 06 80 CB to 06 FF CB

***** ZAP 005 ***** 08/04/81 ***** V2M1 *****

Mandatory zap for APL80/CMD to enable it to run with NEWDOS/80. APL80/CMD references a routine internal to DOS that is in a different location in NEWDOS/80 than it was for TRSDOS and NEWDOS/21.

APL80/CMD,12,74 change 21 A2 4B to 21 B4 4B

APL80/CMD,14,52 change 21 A2 4B to 21 B4 4B

***** ZAP 006 ***** 08/04/81 ***** V2M1 *****

Optional zap to EDTASM/CMD to disable the lower case to upper case conversion done by EDTASM's keyboard input routine. Most functions within EDTASM will still require upper case; but comments and operands enclosed in single quotes (for DEFM and DEFB) will accept lower case.

EDTASM/CMD,28,E1 change FE 61 D8 to FE 80 D8

***** ZAP 007 ***** 08/04/81 ***** V2M1 *****

This is information rather than an actual zap.

1. Where possible, the NEWDOS/80 modules have reserved zap areas. Apparat purposely did not mention them in its documentation as it did not want to draw attention to them. Users are hereby warned that Apparat will preempt these areas without preliminary notice and in its zap verifies will expect these areas to contain zeroes. Users who apply non-Apparat zaps into these areas should carefully maintain logs of what they have done to compare against future NEWDOS/80 zaps for area conflicts.
2. The DOS command ATTRIB (see section 2.3) has an additional optional parameter, LRL=xxx, not specified in that section. LRL=xxx specifies the new logical record length of records in the file where xxx is an integer between 1 and 256. This record length is used now only by DIR, but if user processing assumes a file has a given record length, some users may want the DIR display to reflect it.
3. MINI-DOS (see section 4.2) is illegal under DOS-CALL (see section 4.4). If the DFG keys are depressed while DOS is under DOS-CALL, the triple key depression will be ignored.
4. DOS command ROUTE (see section 2.43) has been altered such that existing routes are displayed only if the ROUTE command has no parameters.
5. DOS command COPY (see section 2.14), format 6 (CBF) has a new optional parameter DFO (Destination Files Only). If DFO is specified, then file contents are copied if and only if the file previously existed on both the destination and source diskettes. DFO is mutually exclusive with FMT.
6. DOS command FORMAT (see section 2.22) has a new optional parameter RWF (Raw Format). If RWF is specified, all errors are ignored and each track is formatted once, whether or not the format actually takes. RWF is used when the user wishes to obliterate the information on a damaged diskette and doesn't have a magnet. RWF is mutually exclusive with KDN, KDD, DDSL, DDGA and PFST.

***** ZAP 008 ***** 08/04/81 ***** V2M1 *****

Mandatory zap to PROFILE's module INIT to correct for a different error code returned by NEWDOS/80 and to allow for NZ error state to take precedence over C or NC state on return from 4420H call. With this change, the zapped module

will still run under TRSDOS. This zap is for 3 different versions of the same module.

INIT,00,54 change
44 38 09 28 0F FE 1A 28 13 C3 3F 52 CD to
44 20 19 00 00 00 00 00 00 00 30 08 CD

If the above doesn't verify, then try one or the other locations below.

INIT,00,63 or INIT,00,64 change
44 38 11 28 07 FE 1A 28 13 C3 47 52 CD to
44 20 19 00 00 00 00 00 00 00 38 08 CD

For those interested and for some PROFILE modules, the following optional zap will reenable the interrupts so '123' and 'DFG' can be used under PROFILE and NEWDOS/80.

PROFILE/CMD,11,45 change F3 CD to 00 CD

***** ZAP 009 ***** 08/04/81 ***** V2M1 *****

Mandatory zap to Racet's Infinite Basic IBLOAD/CMD module to enable it to run under NEWDOS/80 as well as TRSDOS.

IBLOAD/CMD/CMD,08,15 change
15 21 B6 79 11 F4 79 CD 36 44 28 to 15 11 F4 79 CD 13 00 32 B6 79 28

***** ZAP 010 ***** 08/04/81 ***** V2M1 *****

Mandatory zap to Racet's DSM module DSMB/CMD to adjust for NEWDOS/80's requirement that a filespec's type have a maximum of 3 chars and that a filespec end with a terminator. This corrects only for the filespec DSMC/CMDPATCHPATCHPATCH such that if a user patches in a different filespec, he/she will have to apply the 03 byte at the end of that filespec.

DSMB/CMD,03,C2 change 44 50 41 to 44 03 41

***** ZAP 011 ***** 08/04/81 ***** V2M1 *****

Mandatory zap to allow VISICALC to operate with NEWDOS/80. The resulting zapped module will not run with TRSDOS or NEWDOS21; so maintain 2 different versions. This zap deals with the different handling by NEWDOS/80 of the user 25ms interrupt routines (see sections 3.8 and 3.9).

VC/CMD,03,2B change
09 3E 00 21 20 03 22 51 9F C9 79 to 09 18 BB 00 00 08 08 C3 EF 9B 79

VC/CMD,75,15 change 11 28 9C 22 to 11 1E 55 22

VC/CMD,75,24 change
C9 3E 03 C3 13 44 CD 4E 53 F5 CD 16 9C 28 0E 3E to
C9 11 1E 55 C3 13 44 CD 4E 53 CD 16 9C C8 00 3E

Mandatory zap to VISICALC to adjust for NEWDOS/80's difference from TRSDOS on a returned error code causing VISICALC's directory search to hang if any of the 4 drives are not present or have no diskette mounted. This zap is not incompatible with TRSDOS.

VC/CMD,73,01 change C9 FE 18 20 to C9 37 C9 20

***** ZAP 012 ***** 08/04/81 ***** V2M1 *****

Optional zap to increase or decrease the sensitivity of double density diskette formatting. One of three byte patterns can be chosen, depending on the reliability of your interface, drive and diskettes. The more sensitive the byte pattern, the greater the probability a marginal diskette will fail format and the lesser the probability that having formatted successfully, the diskette will fail later (under normal careful handling). The less sensitive the byte pattern, the lesser the probability a marginal diskette will fail format and the greater the probability that having formatted successfully, the diskette will fail later. The byte patterns are:

1. E5 E5 = least sensitive during formatting. This was and is the single density standard pattern.
2. 5B 5B = intermediate sensitivity during formatting. This is the TRSDOS Model III pattern.
3. 6D B6 = most sensitive during formatting. This pattern strains the disk formatting and if the interface, drives and diskettes are not in first class condition, 30% or more of the diskettes will fail formatting.

Depending upon the frequency of format failures to diskette failures at other times, the user chooses which of the three 2 byte patterns to use and inserts them in the following locations, first checking that one of the three patterns is already at those locations. Each location receives both bytes, and as a check on each location, the preceding byte is F5.

SYS6/SYS,31,D9

SYS6/SYS,31,F3

***** ZAP 013 ***** 08/03/81 ***** V2M1 *****

Optional zap to allow the COPY function to use Model III diskettes in the TRSDOS 1.2 or earlier directory format instead of the TRSDOS 1.3 format the COPY command is prepared to handle. The zap must be backed off when the user wants to re-enable COPY to handle TRSDOS 1.3 format Model III diskettes.

SYS6/SYS,14,75 change 01 00 7B to 01 01 7B
 SYS6/SYS,14,C8 change 01 00 40 4E 01 13 00 to 01 13 40 4E 01 00 00
 SYS6/SYS,20,EA change 61 C8 5E to 61 C9 5E

***** ZAP 014 ***** 08/08/81 ***** V2M1 *****

Mandatory zap to correct an error in BASIC that was causing SYNTAX error to occur when the short editing codes A, D, E and L were being used. This error was introduced into BASIC just before Version 2 release in the correction of another but more trivial error.

SYS18/SYS,02,31 change
 2C D7 28 06 FE 3D 20 F9 18 23 E1 to 2C CD CF 65 28 27 FE 0D 20 F7 E1
 BASIC/CMD,14,D8 change 00 00 00 00 00 to 23 7E FE 3D C9

***** ZAP 015 ***** 08/18/81 ***** V2M1 *****

Mandatory zap to correct error in format 5 COPY where the BOOT sector was not receiving the correct directory starting lump number if this differed from the PDRIVE specification. The error would manifest itself by directory read error in DIR.

SYS6/SYS,05,96 change 64 01 00 01 18 to 64 CD 80 5C 18
 SYS6/SYS,15,46 change
 00 00 00 00 00 00 00 00 00 00 00 00 00 00 to
 01 00 01 B7 C0 13 13 1A 32 BC 64 1B 1B C9

***** ZAP 016 ***** 08/18/81 ***** V2M1 *****

Correct error in PDRIVE causing SYSTEM PROGRAM NOT FOUND error when the second drive number is specified wrongly as greater than 9.

SYS16/SYS,00,6A change C3 1A 52 CB to C3 4B 50 CB

***** ZAP 017 ***** 08/18/81 ***** V2M1 *****

Mandatory zap to correct error in COPY and FORMAT where DDSL parameter was being erroneously rejected.

SYS6/SYS,01,FA change CB 70 20 to CB 52 20

***** ZAP 018 ***** 08/25/81 ***** V2M1 *****

Mandatory zap to SUPERZAP to correct an error where the DM,P functions was not sending the correct memory contents to the printer.

SUPERZAP/CMD,00,04 change
00 00 00 00 00 00 00 00 00 00 00 00 to
3A 91 54 CB 5F C0 2A B4 54 22 95 54 C9

SUPERZAP/CMD,03,43 change 54 3A 91 54 CB to 54 CD 00 52 CB

***** ZAP 019 ***** 08/25/81 ***** V2M1 *****

Mandatory zap to correct next-without-for error occuring when CHAINBLD is saving a file in version 1 format and the last line starts with a /. sequence.

Add to the end of line 126 of CHAINBLD/BAS the following eight characters:
:GOTO130

***** ZAP 020 ***** 08/28/81 ***** V2M1 *****

Mandatory zap to DOS to allow ROUTE of the display to cause the BASIC PRINT of a numeric value to not output the value twice.

SYS0/SYS,07,E6 change 28 39 CD to 28 5D CD

SYS0/SYS,08,1F change
23 7E 23 66 6F 7C B5 C8 7E BB 23 20 02 7E BA 23
20 EE E5 D5 C5 7E A0 23 23 23 5E 23 56 D5 DD E1
7A B3 C4 D4 03 C1 D1 E1 CB 40 28 D4 B7 28 D1 C9
CD

to

7E BB 23 20 02 7E BA 23 20 1A E5 D5 C5 7E A0 23
23 23 5E 23 56 D5 DD E1 CD D4 03 C1 D1 E1 CB 40
28 02 B7 C0 23 7E 23 66 6F 7C B5 20 D3 C3 F8 4C
CD

SYS0/SYS,10,08 change
C9 00 00 00 00 00 00 00 00 to C9 CB 40 C0 79 C9 A4 4B 00

SYS14/SYS,02,74 change 43 00 00 43 to 43 FC 4C 43

***** ZAP 021 ***** 08/28/81 ***** V2M1 *****

Mandatory zap to BASIC to correct error during marked item and fixed item file processing causing strings greater than 127 characters to be written erroneously and IGEL expressions of the form (len)# and (len)\$ to malfunction.

BASIC/CMD,11,18 change CD E1 61 79 DD to CD D4 65 00 DD

BASIC/CMD,14,DD change
00 00 00 00 00 00 00 to C5 CD E1 61 79 C1 C9

***** ZAP 022 ***** 08/28/81 ***** V2M1 *****

Mandatory zap to EDTASM to cause the cursor display to be forced every time the * prompt is displayed, waiting for the next command. This allows the cursor to be turned back on after a return from the DEBUG 123 function, which turns it off.

EDTASM/CMD,05,12 change CD 39 59 0E to CD 00 57 0E

EDTASM/CMD,03,1A change
40 7D E6 3F C0 11 C0 FF 19 C9 to 40 CD 39 59 3E 0E C3 39 59 C9

***** ZAP 023 ***** 08/28/81 ***** V2M1 *****

Mandatory zap to DOS to ease some of the problems caused by the fact that NEWDOS/80 Version 1 always used a granule lockout table in the directory GAT sector whereas Version 2 many times does not, leaving that part of the GAT sector for use by the extension for the free/allocated table. Early in the development of Version 2, the rule was that if the PDRIVE specification for GPL was greater than 2, then the lockout table was not used. Later on, the rule was changed to be if the number of lumps is greater than 60H (96 decimal) or if relative byte 60H of the GAT sector = 0FFH, then the lockout table is not used. Some code in SYS6 was not changed to reflect this rule change, causing either a lock out table to not be created or to not be properly extended when the destination diskette has more granules than the source diskette. This change corrects this. However, users are warned that diskettes with GPL greater than 2 (such as 8 inch or double sided, single density 5 inch diskettes coming from Version 1) converted previous to this zap may have trouble with DIRCHECK, on either Version 1 or 2, complaining that one or more granules are locked out but free or locked out but allocated to a file. The diskettes can still be used as it is only DIRCHECK that has the problem, but sooner or later the diskettes should be re-copied using CBF with FMT so this lockout table conflict will be straightened out and DIRCHECK will stop complaining.

SYS6/SYS,10,0A change
3A CA 59 FE 02 C0 7D to 3A C6 59 FE 61 D0 7D

***** ZAP 024 ***** 08/30/81 ***** V2M1 *****

Mandatory zap to DOS to:

1. Correct error in format 5 and 6 COPY where destination verify error was causing erroneous END OF FILE ENCOUNTERED or INPUT PAST END error to be triggered for the next sector.

4. When the COPY command completes successfully and the system has returned to NEWDOS/80 READY, mount the destination diskette on drive 0 and press RESET. The NEWDOS/80 system on that double density, single sided diskette is now the system.

5. Perform a DIR 0 command to ascertain the extra granules are available. Then execute PDRIVE,0 to observe that the specifications for drive 0 are now single sided, double density with track 0 reserved for opposite density. Please note that the specifications for drives 1 through 9 have not been changed. If they are to be changed, you must do it, studying carefully the PDRIVE command, see section 2.37

2. To make a double sided, single density NEWDOS/80 Version 2 system diskette.

1. Make a copy of the NEWDOS/80 Version 2 master diskette. When done, mount that copy of the NEWDOS/80 Version 2 system in drive 0 and press RESET.

2. Execute the following DOS command:

```
PDRIVE,0,6,TI=A,TD=C,TC=40,SPT=20
```

This changes the specifications for drive 6 to be 5 inch, single sided, single density, 40 tracks. If you wish other than 40 tracks, change the TC parameter above to the desired track count.

3. Place a write protect tab on the system diskette you have just changed.

4. Execute the following command

```
COPY,0,0,,USD,FMT,DPDN=6
```

The source and system diskettes are the same and are the one with the write protect tab. The destination diskette is the one to contain the double sided, single density NEWDOS/80 Version 2 system. If you have two drives available, you may use COPY,0,1,,USD,FMT,DPDN=6 instead. The destination must be on drive 1 if it is to have more than 40 tracks (when the COPY is finished, that drive can be made drive 0).

5. When the COPY command has completed successfully and returns to NEWDOS/80 READY, mount the destination diskette in drive 0 and press RESET to bring up the double sided, single density system. Perform DIR 0 and PDRIVE,0 as discussed above to observe the changed system. Proceed with additional PDRIVE re-specifications, if necessary.

3. To make a double sided, double density NEWDOS/80 Version 2 system diskette.

1. You must have an excellent working Percom or LNW double density interface in your expansion interface.

2. Proceed as for single sided, single density discussed above excepting that the PDRIVE command is

PDRIVE,0,6,TI=CK,TD=G,TC=39,SPT=36,GPL=2,DDGA=2

This is for a 40 track drive, for 35 use TC=34, for 80 use TC=79.
Further:

1. For a destination drive more than 40 tracks use GPL=8 and you will probably want an expanded directory, say DDGA=6 for maximum size, giving 224 directory entries. However, if any of GPL, DDSL or DDGA are different between the source and destination drives during COPY or if the number of sectors, granules or tracks for the destination diskette is less than the source diskette, the CBF (Copy By File) parameter must be specified in the COPY command (example: COPY,0,0,,USD,FMT,DPDN=6,CBF). So, in the case here for drives over 40 tracks, since the GPL is different (the source's GPL is 2 and the destination's GPL is now 8), you must use the CBF parameter. Actually, you could have used the CBF option in any of the COPY's mentioned above in this zap, but CBF runs slower and should only be used where necessary.

2. For LNW interface, you can specify TI flag E instead of flag C (example, TI=EK instead of TI=CK)(if any 8 inch drives are to be used with the LNW, E must be specified instead of C). However, remember, flags E and C are interdrive mutually exclusive; so if you change one of the 10 drive specs from using flag C to using flag E, you must change any of the others that use flag B or C (see next section).

4. Users setting up their systems to use the 8 inch drives through the OMIKRON interface (TI=BH) are experiencing trouble with the PDRIVE error code **** TI= SPEC BETWEEN DRIVES INCOMPATIBLE. Please refer to the last two sentences of the TI=typel paragraph in the middle of page 2-34. If any drive's TI specifies flag B, then no other can specify either flag C or E. You must change the PDRIVE specifications for drives 4, 6, 8 and 9 as they conflict with flag B. To do this, simply execute the DOS commands

```
PDRIVE,0,4=0
PDRIVE,0,6=0
PDRIVE,0,8=0
PDRIVE,0,9=0
```

Remember, you should not make any PDRIVE changes to the NEWDOS/80 Version 2 master diskette; perform the changes on working copies of it.

***** ZAP 030 ***** 09/02/81 ***** V2M1 *****

Information only.

1. Chapter 12 failed to make it clear that though diskettes are content interchangeable under NEWDOS/80 Version 2 between the Model I and Model III, there is a problem dealing with a format control byte for directory sectors of single density diskettes. Carefully read SYSTEM options BK and BN (even though you have only Model III) on page 2-49, WRDIRP command on page 2-52 and the W function of DIRCHECK on page 6-14.

1. For Model III NEWDOS/80 Version 2 users, single density diskettes coming from the model I can be processed on the Model III by setting SYSTEM option BK=Y, setting up the proper single density PDRIVE and then for each such diskette, execute once either the DOS command WRDIRP or the W function of DIRCHECK. After this is done, the diskette can be used as any other diskette under Model III NEWDOS/80 Version 2. Subsequently, this diskette can not be processed by the Model I TRSDOS 2.3, but it can be processed by the Model I NEWDOS/80 Version 1 provided the format of the diskette is not changed to one of the variety of formats available on Version 2 but not available on Version 1). However, once this diskette is used back on the Model I NEWDOS/80 Version 1 and a directory sector is updated, the diskette cannot be reused on the Model III without performing again the WRDIRP or DIRCHECK function on that diskette on the Model III (remember, NEWDOS/80 Version 1 does not have either of these two functions).

2. For users that have NEWDOS/80 Version 2 for both the Model I and III and wish to use single density 5 inch diskettes interchangeably between the model I and model III, set SYSTEM options BK=Y and BN=Y on the Model I and BK=Y on the Model III. Then, for each such single density diskette, execute once either WRDIRP or the W function of DIRCHECK. This can be done on either the Model I or III and all such diskettes do not have to be done at the same session. Each such diskette can now be used interchangeably between the Model I and Model III under NEWDOS/80 Version 2 (don't forget the proper PDRIVE specifications), but the diskette cannot be processed by TRSDOS 2.3

2. For BASIC function RENUM (see section 7.9 on page 7-5) the 4th and 5th formats listed (RENUM X and RENUM U,X) are not valid and should be deleted from the middle of page 7-5. If the X parameter is to be used, it must be done via the 1st format listed as X is meaningless unless specific values for ppppp and/or qqqqq are also specified.

3. Some users have asked for more distinctions between full diskette COPY (format 5) or Copy By File COPY (format 6), both specified in section 2.14.

1. Format 5 copies a full diskette sector by sector and is generally faster than format 6, which copies files individually. However, if the source diskette is relatively empty, format 6 may be faster.

2. In format 5 the source directory becomes the destination directory, including the same size and relative sector position on the diskette, while in format 6, the two directories are considered separate just as in a format 1 through format 4 COPY.

3. Generally, if format 5 is used, both the source and destination PDRIVE specifications for GPL, DDSL and DDGA must be the same (though only the restriction on GPL is enforced, but not if BDU is specified); the other PDRIVE parameters may be different provided the destination diskette is to have at least as many sectors as the source diskette (though the format 5 specifications say that sectors per track must be the same; this is not so in Version 2 where it was in Version 1).

4. Format 5 with the BDU option allows some alien diskettes to be copied that otherwise could not be copied.

5. Format 6 allows a diskette's contents to be copied between diskettes having a different number of granules per lump (GPL), the directories positioned differently on the diskettes, the directories of different sizes, or the destination diskette having less sectors than the source.

6. Format 6 copies all of a source diskette's files or a selected subset of those files.

7. Both format 5 and 6 allow the option of formatting the destination diskette (FMT) or not (NFMT). Formatting a diskette magnetically initializes the entire diskette including the inter-sector control bytes used only by the drives and the controller. Many users prefer to do this everytime a back up is done. Of course, formatting a diskette destroys the previous contents.

8. If format 6 is being used to copy a NEWDOS/80 Version 2 system diskette, the FMT option must be specified. This assures the correct BOOT, SYSTEM and PDRIVE control informat is stored on the destination diskette, and the correct positioning of SYSTEM files which, excepting for BOOT/SYS and SYS0/SYS, are all positioned on the destination diskette in same position relative to the directory that they are on the source diskette.

9. In format 6 where NFMT is specified, system files are NOT copied to the destination diskette if they are not already existing in the destination directory. This is because system files usually use specific FDEs in the directory, and only FMT can assure that these FDEs are available.

10. Format 5 without BDU and format 6 with FMT both assume the possibility of the destination diskette being used later as the system diskette and the destination drive or one like it being used later as drive 0; therefore both initialize the BOOT/SYS file to contain the proper BOOT code and drive 0 PDRIVE specifications.

***** ZAP 031 ***** 09/06/81 ***** V2M1 *****

Mandatory zap to DOS to allow files to be copied from and to diskettes used by Model I TRSDOS 2.3B and higher as well as from and to diskettes used by Model III TRSDOS 1.3 or higher. After applying the documentation changes given below, see section 12.5.1 on page 12-7, the 'flag M' paragraph on page 2-35 and the bottom half of page 2-15.

This enhancement expands the definition of PDRIVE TI flag M (see page 2-35). When the M flag is specified and the TD field specifies double density (i.e., TD=E), the PDRIVE specification is assumed for a Model III TRSDOS diskette and TI flag I is implied (see example 3 on page 2-38). When the M flag is specified and the TD field specifies single density (i.e., TD=A), the PDRIVE specification is assumed for Model I TRSDOS 2.3B or higher diskette, and TI flag I is not implied and must not be specified (see example 1 on page 2-38 with TI=AM).

Radio Shack has started distributing certain new programs (i.e., COBOL) with or on Model I TRSDOS 2.3B or higher diskettes with that system being somewhat different than Model I TRSDOS 2.3, including the use of RBAs as discussed in section 12.1 for the Model III. These diskettes are NOT compatible with NEWDOS/80 diskettes, and, as with Model III TRSDOS diskettes, COPY is the only function of NEWDOS/80 that can be used with the Model I TRSDOS 2.3B diskettes (though FREE and DIR (except EOF and special flags) appear to work).

Files on either Model III TRSDOS or Model I TRSDOS 2.3B diskettes that are to be used either by NEWDOS/80 or user programs executing with NEWDOS/80 must be copied to NEWDOS/80 diskettes. FORMAT or COPY with FMT option cannot be used to format a diskette in either the Model III TRSDOS or the Model I TRSDOS 2.3B format; however, format 5 COPY with the BDU option can be used to make copies of those diskettes.

ZAP 013 must NOT be installed in a NEWDOS/80 to be used to copy Model I TRSDOS 2.3B files. ZAP 013 must be used for Model III TRSDOS 1.1 & 1.2 diskettes.

Insert the following notes in the outside margin of the specified paragraph:

1. Page 2-9, next to last paragraph: "For Model III TRSDOS and Model I TRSDOS 2.3B diskettes, see ZAP 031."
2. Page 2-15, "The COPY command" paragraph: "This section applies also to standard 35 track, single sided, single density diskettes for Model I TRSDOS 2.3B or higher."
3. Page 2-15, "The user must" para: "See examples 1 and 3, section 2.37".
4. Page 2-35, "Flag M" paragraph: "Expanded to include Model I TRSDOS 2.3B or higher diskettes. See ZAP 031
5. Page 2-38, example 1: "For Model I TRSDOS 2.3B diskettes, use TI=AM (see ZAP 031)." Also in this same paragraph, change the last two words to read "option BN" instead of AN.
6. Page 12-7, paragraph 12.5.1: "See ZAP 031."

SYS6/SYS,00,7D change CD B3 63 21 to CD 96 5C 21

SYS6/SYS,15,5C change

```

                                00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00

```

to

```

                                CD B3 63 3A
BE 59 47 3A B9 59 4F 3A CC 59 57 3A C7 59 5F 79
A3 CB 6F 28 06 78 AA 0F DA 47 67 78 CB 69 20 04
CB 6B C8 7A 0F D8 21 5B 5B 22 F7 55 21 B1 5B 22
5D 5B 21 00 5C 22 61 5B AF 32 7F 61 67 6F 22 BF
61 22 B5 5B 3E 18 32 2D 61 C9

```

SYS6/SYS,22,6B change CD B3 63 CD to CD 96 5C CD

SYS16/SYS,01,F8 change 05 28 02 3E 03 CD to 05 00 C4 8D 51 CD

SYS16/SYS,02,AF change
CB E3 DD 7E 05 FE 06 C0 to CB 43 3E 06 C4 87 51 C0

SYS16/SYS,04,9A change
00 00 00 00 00 00 00 00 00 00 00 00 00 00 to
00 CB E3 DD BE 05 C9 DD CB 0F 56 C8 3E 03 C9

***** ZAP 032 ***** 09/10/81 ***** V2M1 *****

Mandatory zap to DOS to:

1. prevent COPY from setting file update flag on in Model I TRSDOS 2.3B and Model III TRSDOS diskettes when that bit is used differently in those systems.

2. enable /ext type CBF file selection when the source is a Model I TRSDos 2.3B or Model III TRSDOS diskette.

SYS6/SYS,10,83 change C3 39 44 DD to C3 E4 5C DD

SYS6/SYS,15,AA change
00 00 00 00 00 00 01 00 EA 5C 00 00 00 00 00 00 00 to
3A 0C 43 CB 6F 28 01 00 EA 5C 04 DD CB 02 EE C3 39 44

SYS6/SYS,16,F0 change 61 20 0D 3A 96 59 CB to 61 3A 96 59 20 0A CB

***** ZAP 033 ***** 09/10/81 ***** V2M1 *****

Mandatory zap to correct error in SUPERZAP during the DM function and during the F, find function.

SUPERZAP/CMD,00,11 change
00 00 00 00 00 00 00 to 6B 63 4B 22 C3 54 C9

SUPERZAP/CMD,05,0B change 00 6B 63 4B CB to 00 CD 0D 52 CB

***** ZAP 034 ***** 09/11/81 ***** V2M1 *****

Mandatory zap to the Ryan-McFarland Corp's COBOL version 1.3B distributed by Radio Shack to allow it to run with NEWDOS/80 Version 2 for the Model I and Model III. This zapped version will not run under TRSDOS. Users must copy the COBOL multiple files onto NEWDOS/80 diskettes (see zap 031).

RSCOBOL/CMD,99,7D change 44 24 3E 40 49 to 44 82 27 44 49

RSCOBOL/CMD,99,CF change 44 13 1F 44 to 44 82 27 44

RUNCOBOL/CMD,115,82 change
44 3E 40 49 40 24 17 to 44 27 44 49 40 82 17

RUNCOBOL/CMD,115,99 change
02 1F 44 11 44 13 0A to 02 27 44 11 44 82 0A

***** ZAP 035 ***** 09/13/81 ***** V2M1 *****

Mandatory zap to DOS to correct a directory clobbering error that occurs when either CLOSE or KILL frees up a FPDE or FXDE that occupies the first FDE slot in a directory sector. This error was missed during BETA testing as it was caused by a late adjustment to handle the TRSDOS Model III diskettes. A few persons were complaining about directories being clobbered, but only on September 12th was an error report made that lead to the discovery. Though the problem would appear to affect many users, apparently to date it has not.

SYS3/SYS,01,CC change
00 7D D6 17 BB 30 1D to 00 7B C6 16 BD 38 1D

***** ZAP 036 ***** 09/13/81 ***** V2M1 *****

Information zap.

1. Documentation correction for EDTASM. Tape I/O is NOT available for the Model III. If it is attempted, BAD PARAMETER(S) error will be given.

1. Place in the outside margin of the "2. L T=nnnnnn" paragraph of page 6-15 the following restriction: "Model I only"

2. Place in the outside margin of the 2nd line of page 6-16 of page 6-16 the following restriction: "Model I only"

2. Correct the "A list of all" paragraph on page 1-3 to read "NWD80V2/ILF and NWD80V2/XLF" instead of "NWD82V2/ILF and NWD82V2/XLF".

3. Delete the words "sectors per track, " from the "Format 5 is a full" paragraph of page 2-11.

4. The MM=addrl function of ROUTE requires the main memory location addrl to be greater than 51FFH. In the "Any of the devices" paragraph of page 2-43, insert the words "greater than 51FFH" after the word "location" in the phrase "memory location of a user".

***** ZAP 037 ***** 09/14/81 ***** V2M1 *****

Mandatory zap to BIONIC BASIC to make it compatible with NEWDOS/80 Version 2 for the Model I. These zaps were provided to Apparat and have not been checked out by Apparat. One or more of the zaps may already be installed in your modules. When these zaps are applied, the BIONIC BASIC must not be used with any other version of NEWDOS/80.

FIREUP/CMD,02,51	change	3A 31 0D	to	3A 30 0D
" ,04,90	change	21 86 63 22	to	21 FC 61 22
" ,05,3C	change	40 09 58 01	to	40 FF 57 01
" ,05,40	change	05 28 65	to	05 86 65
" ,05,4E	change	05 30 5F	to	05 8E 5F
" ,05,55	change	05 60 5F	to	05 BE 5F
" ,05,5C	change	05 CF 64 21	to	05 2D 65 21
" ,05,63	change	05 BE 64 21	to	05 1C 65 21
" ,05,6A	change	05 95 64	to	05 F3 64

INSTALL/CMD,01,0D	change	3A 31 0D	to	3A 30 0D
" ,01,4F	change	44 C8 FE	to	44 C9 FE

REMOVE/CMD,01,12	change	3A 31 0D	to	3A 30 0D
" ,01,54	change	44 C8 FE	to	44 C9 FE

***** ZAP 038 ***** 09/14/81 ***** V2M1 *****

Optional zap to Model I SCRIPSIT to eliminate the 'hang' occurring when the END function is executed and the last disk I/O was to a double density drive. SCRIPSIT executes the END function by jumping to location 0, causing a software but not a hardware RESET. The double density modifications to the expansion interface require a hardware RESET to reset them to the single density disk I/O assumed by the software RESET in the ROM. SCRIPSIT uses the RESET to restore the keyboard, display, printer and other interfaces it has changed. If the Z-80 HALT instruction is executed instead of a jump to location 0, the Model I (this does not hold for the Model III) hardware RESET is triggered which in turn triggers the software RESET. In both cases, either the jump to 0 or the HALT, the red lights on the disk drives must be off. The zap is applicable under TRSDOS as well as all versions of NEWDOS.

SCRIPSIT/LC,19,E3	and	SCRIPSIT/UC,19,E3
change	6F C3 00	to 6F 76 00

***** ZAP 039 ***** 09/24/81 ***** V1M1 *****

Mandatory zap to PENCIL to enable it to run with NEWDOS/80, version 2. This zap is an extension of zaps 002 and 026. We apologize for the large number of zaps to PENCIL, but Apparat doesn't use PENCIL and so must rely upon the users to find the discrepancies.

PENCIL/CMD,03,25	change	53 36 A0 C1	to	53 CB FE C1
------------------	--------	-------------	----	-------------

***** ZAP 040 ***** 09/29/81 ***** V2M1 *****

Mandatory zap to DOS to correct rare occurring error that could, if the same HIT code is used more than 31 times in a directory, cause file open to not find a file and to put two files with the same name/ext on the diskette.

SYS2/SYS,01,CB change FE CD 28 to FE CC 28

***** ZAP 041 ***** 09/29/81 ***** V2M1 *****

Information and manual corrections.

1. A number of users have had trouble with tape I/O under NEWDOS/80 Version 2. Some of the early copies of NEWDOS/80 Version 2 had errors due to undetected RAM errors during duplication and in maybe as many as 20 cases this affected the EDTASM or LMOFFSET module. However, if these modules were bad, they usually also had problems with disk I/O as well as cassette I/O and so if disk I/O works fine, we assume it is not a bad copy of NEWDOS/80. Tape I/O has long history of trouble, varying from computer to computer and especially from tape unit to tape unit such that any particular tape will fail on somebody's cassette unit. This has always been an exasperating problem and the main reason why cassettes are not used at Apparat (though we do act as a retailer/-distributor for products distributed on cassettes produced by others). Because cassettes are not used at Apparat, NEWDOS receives very little testing with cassettes, and in the future we are considering withdrawing all support (i.e., LMOFFSET and EDTASM) from cassettes. Cassette support for EDTASM for the Model III has already been withdrawn and will probably soon be withdrawn for the Model I (since the purpose of our EDTASM was to give disk support, not cassette). For now though, we will restrict our error study to those problems presented to us on a diskette containing the actual NEWDOS system used. If the user presents us with a cassette along with the diskette we will test that as well; otherwise we will test with simple programs from disk in-house. Neither the diskette nor the cassette will be returned to the user. Lastly, if you can avoid use of cassettes, DO!!!!

2. The specifications for ROUTE using the MM=addr1 operand are in error in the manual.

1. Page 2-43, 3rd paragraph, 3rd line, change "12" to "16".
2. Same paragraph, 5th line, change "13th" to "17th".
3. Page 2-44, top line, change "0FE8CH" to "0FE90H".

3. A number of users has asked why Automatic Density Recognition (ADR) was not used in NEWDOS/80 Version 2. We wanted to include ADR but found it impractical unless we limited or expanded other capabilities made available by PDRIIVE. Since we were already two months late in releasing Version 2, we decided to release without it. Part of the problem is in providing a second SPT parameter and an extra indicator for track 0 usage (remember, Version 2 operates with double density diskettes that may or may not have track 0 reserved for single density). We also felt that if we included ADR, we should

also include ASR (automatic side recognition). For now, we will remain without ADR and ASR, but will not rule it out for a subsequent NEWDOS/80 version.

4. For BASIC CMD "O" and multi-dimensional arrays, a few users have asked for clarification of term REN used in the documentation for on pages 7-14 through 7-17. CMD"O" does not care whether an array is single or multi-dimensional as CMD"O" only concerns itself with the relative positioning in main memory between array elements and not with the actual subscripts for a given element, except for determining the main memory position of the first element participating in the sort as specified in the CMD "O" statement. As an aide to the programmer to understand the sort order, a formula was given for two and three dimensional arrays to determine the REN of any array element given its subscripts. The following working BASIC program demonstrates the relationship between REN and subscripts for a three dimensional array, using R1, R2, R3, X1, X2 and X3 to correspond with the useage at the bottom of page 7-14 and top of page 7-15.

```
10 R1=3: R2=4: R3=2: DIM A(R1,R2,R3)
20 REN=0: FOR X3=0TOR3: FOR X2=0TOR2: FOR X1=0TOR1 'CREATE ARRAY IN REN
ORDER
30 IF REN <> X1+X2*(R1+1)+X3*(R1+1)*(R2+1) THEN PRINT"ERROR": STOP
35 ' THE ABOVE ASSURES THE FORMULA COMPUTES TO THE CURRENT REN NUMBER
40 A(X1,X2,X3)=REN: REN=REN+1: NEXT X1,X2,X3 'STORE THE REN NUMBER IN THAT
ELEMENT
50 CMD"O",0,A(0,0,0) 'SORT ARRAY IN ASCENDING NUMERIC ORDER
60 ' THE ARRAY ORDER SHOULD NOT HAVE BEEN CHANGED.
70 FOR X3=0TOR3: FOR X2=0TOR2: FOR X1=0TOR1 'LIST ARRAY IN SAME ORDER
STORED
80 PRINT A(X1,X2,X3);: NEXT X1,X2,X3 'AND THIS SHOULD BE ALSO THE SORTED
ORDER
```

Elements with one or more zero subscripts do participate in the sort if that element is within the main memory range of elements sorted, i.e., has a REN greater than or equal to the REN of the 1st sort element and less than or equal to the REN of the last sort element.

5. Correct the last paragraph of page 2-27 by deleting the 3rd sentence and changing the 4th sentence to read "Hex codes less than 20H or greater than the SYSTEM option AX value will be displayed as periods."

6. A number of users having CPU speed up modifications in their computers and setting the slow-down-during-I/O switch have complained that NEWDOS/80 continuously toggles the fast/normal CPU speed state (in many cases a light flickers on/off or red/green). Indeed this is true. In the original TRSDOS, there were 8 interrupts, 0 - 7, of which only 6 and 7 were used. Interrupt 6 only read the disk controller status register; so NEWDOS/80, to save resident DOS space which is critical, combined interrupt 6's function with interrupt 7, reading the controller status register every 25 ms interrupt. Though the fast/normal CPU toggling is interested only in the controller command register, the hardware connection actually toggles on both the read of the status register and the write of the command register. Normal disk I/O cannot operate without the status register read when the controller has interrupt status; so we cannot eliminate the interrupt 7's read of the status register without

re-enabling interrupt 6 and we don't have the patch space for that. Therefore, users must turn off the switch on their computers that allows the fast/normal toggling to take place, and simply use the fast speed all the time (be sure SYSTEM option BJ is set correctly). There is no guarantee that your computer will actually work at the faster speeds. Doubling the CPU speed seems OK; tripling appears NOT. The LNW computer at 2.5 times the TRS-80's normal speed is reported by LNW to work fine.

***** ZAP 042 ***** 09/30/81 ***** V2M1 *****

Mandatory zap to correct error in BASIC's RENUM function giving SEQ # OVERFLOW when large programs, say over 26,000 bytes of text, are renumbered. Though a number of users called on this problem, it wasn't until a user sent us a written error report with the problem program on a system diskette that we finally had enough to go on.

SYS11/SYS,03,BB change 0F ED 42 DF 38 to 0F CD 9D 51 38

SYS11/SYS,04,A5 change 00 00 00 00 00 to ED 42 D8 DF C9

***** ZAP 043 ***** 10/07/81 ***** V2M1 *****

Mandatory zap to DOS to correct omission from ZAP 020 (ROUTE) which caused SYSTEM option BA to cause hang on reset.

SYS0/SYS,00,BF change FF 00 00 00 to FF FC 4C 00

***** ZAP 044 ***** 10/07/81 ***** V2M1 *****

Mandatory zap to DOS to disable SYSTEM option BM. SYSTEM option BM=N caused the full diskette verify to be bypassed when the user felt the track verify that occurred immediately after a track was formatted was sufficient. However, if the user is formatting more tracks that the drive can physically handle, FORMAT with SYSTEM option BM=N will not detect the error whereas it will with SYSTEM option BM=Y. Therefore, SYSTEM option BM is dropped, and the full diskette verify will always be done.

On the outside margin of the BM=yn paragraph of page 2-49, write the following:
"eliminated by ZAP 044".

SYS6/SYS,10,35 change
E1 3A 6D 43 CB 5F C8 3E to E1 00 00 00 00 00 00 3E

SYS17/SYS,02,55 change FE 31 7A to FE FE 7A

***** ZAP 045 ***** 10/07/81 ***** V2M1 *****

Mandatory zap to correct BASIC function REF\$ to (1) avoid occasional misses of printer line advance and (2) disable printer operations after the function.

SYS12/SYS,04,BA change FE 38 30 to FE 35 30
SYS18/SYS,03,57 change D2 B5 57 3D to D2 59 55 3D
SYS18/SYS,03,69 change 00 00 00 00 00 to 11 45 64 D5 EF

***** ZAP 046 ***** 10/09/81 ***** V2M1 *****

Optional zap to DOS to allow 'JKL' to print graphics on the EPSOM printers that use graphic codes 0A0H - 0DFH. This is done by converting hex codes 80H through 0BFH to 0A0H through 0DFH.

SYS3/SYS,04,BF change 30 02 3E to 30 07 3E
SYS3/SYS,04,C8 change
00 00 00 00 00 00 00 00 to FE 80 38 F7 C6 20 18 F3

Use next zap if 0BFH rather than SYSTEM option AX is to govern as high ASCII for JKL.

SYS3/SYS,04,B9 change 47 3A 70 43 B8 to 47 00 3E BF B8

***** ZAP 047 ***** 10/21/81 ***** V2M1 *****

Mandatory zap to correct DOS handling of 8 inch, double density, single or double sided, single volume drives (PDRIVE TD=H) where the computer hardware is modified to handle double CPU speed and 8 inch, double density, single or double sided, single volume operations. The PDRIVE SPT maximum values are 30 for single sided and 60 for double sided. The PDRIVE GPL must be atleast 3 for single sided and atleast 5 for double sided; however 8 is recommended in both cases. This zap does NOT mean that your particular computer can handle this type of drive. However, LNW reports the LNDOUBLER 5/8 (CPU speed up modification required) and the LNW80 computer systems both support 8 inch double density under NEWDOS/80, Version 2 (also see zap 041 part 6).

SYS6/SYS,27,BD change E6 41 DD to E6 C1 DD
SYS6/SYS,31 F5 change
34 0A 26 0A 86 01 9C 27 44 00 to 13 0A 14 0A 53 01 BA 27 26 00
SYS16/SYS,04,2D change 12 1A 24 34 82 to 12 1E 24 3C 82

***** ZAP 048 ***** 10/21/81 ***** V2M1 *****

Mandatory zap to EDTASM to correct error occurring when shift-left-arrow is used to erase a filespec response.

EDTASM/CMD,31,00 change
58 C5 CD 2F 59 E1 E5 3A AA 53 F5 0E 01 CD 47 5B F1 32 AA to
58 D5 C5 CD 2F 59 E1 06 1F CD 40 00 DA D7 58 D1 7E C9 AA

***** ZAP 049 ***** 11/09/81 ***** V2M1 *****

Mandatory zap to DOS to correct error in DIR \$ or DIR \$0 command where DOS hangs if any response other than ENTER is given to the diskette mount requests.

SYS8/SYS,02,B8 change 20 FC C9 to 20 F9 C9

***** ZAP 050 ***** 11/09/81 ***** V2M1 *****

Optional zap to DOS to allow the DOS PRINT and LIST commands to accept all control characters in the hexadecimal range 00 to 1F instead of just 0D (end of line). If this zap is used, users must assure that files used with PRINT and LIST do not contain control characters the display or printer cannot handle. Remember, the high bit of all characters is zeroed, thus display graphic characters 80 - 9F will be transmitted as 00 - 1F.

SYS14/SYS,04,5A change 20 D0 FE to 20 C9 FE

***** ZAP 051 ***** 11/09/81 ***** V2M1 *****

Information zap.

1. Users must remember that the Model I TRSDOS 2.3B or higher and Model III TRSDOS 1.3 or higher, amongst other things, both went to using RBAs in the NEXT and EOF fields of the FCB, thus intentionally or unintentionally reestablishing compatibility with NEWDOS21 and NEWDOS/80 in the use of those two fields (which many user programs use), even though the EOF fields in the directories (which most user programs don't use) are now incompatible. Though files from those systems must be copied to NEWDOS diskettes, assembly language programs upgraded to run with those TRSDOS systems are more like to run with NEWDOS without change than they were before. For example, on the Model III, SCRIPSIT Version 3.2 has been found to work as-is. So, before calling Apparat to see if zaps exist for a given program, try it out, giving special attention to the file I/O.

2. The manual failed to explain that when SYSTEM option AJ=N or when the up-arrow key is held down during reset/power-on, DOS loses the ability use the lower case driver (Model I only) or to actually input keyboard characters from the chain file during chaining as these functions depend upon DOS's keyboard intercept routine being enabled. SYSTEM options AU=N and BF=N (Model I only)

and are also forced. DOS will think it is activating chaining, but actually the input characters will continue to come from the keyboard; the DOS READY prompts will not be seen as DOS thinks it is chaining. For LCDVR (Model I only), the command will execute but the key input functions for lower case drive will not be done. Insert the note "see ZAP 051, part 2" in the outside margin at the following places in the manual.

1. Page 2-7, the "CHAINING is discussed" paragraph.

2. Page 2-29, the "In NEWDOS/80" paragraph.

3. Page 2-47, the "AJ=yn" paragraph.

4. Page 4-9, the "If a DOS recognized" paragraph.

3. Chain files must always have a name-extension. When creating a CHAIN file, you must always specify a name-extension in the filespec, excepting that CHAINBLD/BAS will assume name extension /JCL if you don't give one. If the filespec given in a DO or CHAIN command does not specify a name-extension, then /JCL is assumed; therefore it is recommended that the name-extension /JCL be used on chain files when created. Place the note "See ZAP 051, part 3" in the outside margin in the following places in the manual.

1. Page 2-7, the "When the system" paragraph.

2. Page 4-8, the "Chain file creators" paragraph.

4. For Model I SCRIPSIT where the user wishes to use tape I/O, the user must back off the last zap of ZAP 003 (the SCRIPSIT/xx,00,C3 zap) in order that interrupts will remain disabled, a requirement for Model I tape I/O. This means the user cannot invoke MINI-DOS from SCRIPSIT.

***** ZAP 052 ***** 11/09/81 ***** V2M1 *****

Mandatory zap to BASIC to correct CLOSE without explicit fan(s) where filearea 2 and up was not being closed if filearea 1 was not open and the V parameter was specified in the BASIC invocation sequence.

BASIC/CMD,08,C8 change 66 11 2D 01 7E to 66 CD DB 65 7E

BASIC/CMD,14,E4 change 00 00 00 00 00 to ED 5B C5 64 C9

***** ZAP 053 ***** 11/09/81 ***** V2M1 *****

Part mandatory and part optional zap to MICROSOFT's BASIC compiler Version 5.23 (the release Version for a long time)(the first line a /LST file created by the compiler gives the compiler version number) to allow it to run with NEWDOS/80. This zap has been provided to Apparat by MICROSOFT and if there are questions with this zap, please contact MICROSOFT. Once these zaps are applied, this compiler and the compiled programs cannot be used with TRSDOS!!!

Future enhancements to the compiler may require the optional changes below to be backed off; therefore users should maintain copies of the compiler (1) as it existed before the mandatory changes below were applied, (2) after the

mandatory changes but before the optional changes below are applied and (3) the final result. Also, remember, the BASIC compiler's L80/CMD is not for use with FORTRAN, assembler, etc., but only with BASIC.

The production of this zap required a large amount of research and testing by MICROSOFT, and APPARAT sincerely thanks MICROSOFT for this extensive effort to make the BASIC compiler operate with NEWDOS/80, Version 2.

***** Mandatory section

BRUN/CMD,10,1D change 46 0B 70 to 46 00 70

***** Optional section

The following optional zaps are for:

1. The LOF function is changed to work like NEWDOS/80, rounding up the returned value if EOF is not integer divisible by the logical record length used in the OPEN statement. Further, if the result exceeds 32767, BAD RECORD NUMBER error results.
2. PUT and GET without explicit record number works correctly.
3. LOC functions correctly for the logical record length in the OPEN statement.

DIR/SYS,xx,yy Search the directory for BRUN/CMD's directory entry, the associated line on the SUPERZAP display should look something like this:

1020 0062 0042 52 55 4E20 2020 2043 4D44 ...b.BRUN....CMD

change the 62 (the 4th) byte to F6.

BRUN/CMD,40,4A change
21 0C 00 09 5E 23 56 EB D1 C1 C9 CD to
DD 21 6E 8A CB 23 DD 19 C3 2E 8A CD

BRUN/CMD,40,63 change 00 C3 AD 79 E1 to 00 C3 37 8A E1

BRUN/CMD,40,B3 change C5 21 0C 00 09 to C5 C3 00 8A 09

BRUN/CMD,40,CE change 1B 42 4B to CD 11 8A

BRUN/CMD,42,7F change CD 17 58 to CD 1B 8A

BRUN/CMD,56,84 change 02 02 00 52 (the rest is immaterial)
to

016D 008A CB23 DD21 6E8A DD19
DD5E 00DD 5601 C317 7ADD 7300 DD72 011B
424B C9C5 CB21 DD21 6E8A DD09 DD70 00DD
7001 C1C3 1758 DD6E 00DD 6601 D1C1 C9C5
DDE1 DD6E 0ADD 660E DD5E 0FDD 4E0B AFB9
281D AF06 18ED 6ACB 1317 9130 0181 3F10
F4ED 6AB7 2801 23D1 C1CB 7CC8 C39A 7D6C
6318 F402 0200 52

L80/CMD,00,7A change 00 8A 22 to 00 8B 22

Note, the above zap to L80/CMD changes the default data address for compiled BASIC programs from 8A00H to 8B00H to allow an extra 256 bytes for BASIC system use. If the -R switch is issued during the linking process, the -D switch must be reset to 8B00 instead of 8A00 as mentioned in the compiler manual.

***** ZAP 054 ***** 11/19/81 ***** V2M1 *****

Mandatory zap to EDTASM correct error in object code write to tape where checksums were being computed wrong. The NEWDOS/80 author apologizes to the ten or so persons who complained of this error over the last 4 months.

EDTASM/CMD,27,30 change CD A9 70 03 to CD 8B 72 03
EDTASM/CMD,31,12 change AA 53 36 00 E1 7E to F5 CD A9 70 F1 C9

***** ZAP 055 ***** 11/19/81 ***** V2M1 *****

Optional zap to DOS to allow the PATCH LC keyboard modification to work with NEWDOS/80 Version 2.

SYS0/SYS,02,34 change
 2E 36 01 01 38 16 FF 0A 5F AE 73 A3
20 0D 7A C6 08 57 2C CB 01 F2 4A 45 AF 18 0F 5F
 to
 2E 35 01 80 38 16 F7 7A C6 08 57 2C
CB 01 0A 5F AF CB 79 20 15 7B AE 73 A3 28 EC 5F

***** ZAP 056 ***** 11/29/81 ***** V2M1 *****

Mandatory zap to DOS to allow COPY with CBF option to allocate space on Model III TRSDOS diskettes beyond track 23.

SYS6/SYS,25,F0 change CD B2 4C DD to CD F2 5C DD

SYS6/SYS,15,BC change
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 to
DD CB 02 6E 28 04 DD CB 07 46 CA B2 4C 3E 03 C3 B4 4C

***** ZAP 057 ***** 11/29/81 ***** V2M1 *****

Mandatory zap to DOS to correct directory errors created during format 5 COPY when copying to a destination diskette that is to contain more granules than the source diskette and when the source diskette has less than 61H (97 decimal) lumps and the destination diskette is to have more than 60H (96 decimal) lumps. In NEWDOS/80 Version 2, in order to allow a maximum of 60H (96 decimal) lumps in the granule allocation table, that table (normally in 00 -5F of the GAT sector) expands into and supercedes the granule lockout table (normally in 60 -BF of the GAT sector. This error was leaving the GAT granule lockout table in

existence in the destination directory (remember, it is transferred over from the source diskette in format 5 COPY) when it should have been done away with to make room for the expanded granule allocation table. The error is immediately detectable by DIRCHECK after the format 5 COPY by the presence of one or more BAD "GAT" SECTOR BYTE errors. Otherwise, the error is not seen until TRACK # TOO HIGH error occurs when writing to the diskette and a granule beyond those allowed for the diskette is erroneously allocated; the file getting the error will NOT have had its EOF increased to include the erroneous sector. DIRCHECK will, in addition to the GAD "GAT" SECTOR BYTE errors, then display EXTENT SPACE OVERFLOWS DISKETTE for that file, but since EOF does not include that bad granule, single file COPY or format 6 COPY will still be able to copy the file. Therefore, any bad diskettes should be recoverable by using a format 6 COPY with FMT option to copy the contents of the bad diskette onto another diskette. You can then use either format 5 or 6 COPY with FMT option to copy it back.

This zap is large as part of SYS6/SYS is being moved to SYS17/SYS to make more patch area available in SYS6/SYS.

SYS6/SYS,07,79 change 52 CD 35 55 ED to 52 C3 1C 50 ED

SYS6/SYS,21,85 change 3E E6 28 to 3E F3 28

SYS17/SYS,00,0C change 2A C2 81 4E 78 to 2A C0 00 00 78

SYS17/SYS,03,2C through 9E was all zeroes, change to
CD 35 55 ED

5B C1 59 CD 84 57 ED 4B 94 59 CB 49 20 5E CD F9
56 1E 61 3A C6 59 BB 38 0E 3A B8 59 BB 30 08 1D
6B 36 FF 1D 23 20 FA CB 68 28 06 2A 81 59 22 CE
42 79 E6 0C 01 10 00 11 D0 42 21 83 59 20 07 21
8B 59 1E D8 0E 08 ED B0 2A D1 59 ED 5B C3 59 B7
ED 52 EB 38 11 28 0F 2A C3 59 3A BC 59 CD B4 4C
26 42 4F CD 62 57 CD 1F 49 C2 CB 54 C3 2D 55

***** ZAP 058 ***** 12/01/81 ***** V2M1 *****

Mandatory zap to LMOFFSET to correct error occurring when a object code block's load point is in the range 3F00 to 3FFFH.

LMOFFSET/CMD,01,36 change 78 05 85 to 78 3D 85

***** ZAP 059 ***** 12/28/81 ***** V2M1 *****

Mandatory zap to correct 3 bytes wrong in ZAP 054 (EDTASM), if not already corrected. The entire correct zap is given here. The corrections are to change to two occurrences of EB in the 1st part to 03 and the occurrence of 30 in the 2nd part to 31.

EDTASM/CMD,27,30 change CD A9 70 03 to CD 8B 72 03

EDTASM/CMD,31,12 change AA 53 36 00 E1 7E to F5 CD A9 70 F1 C9

***** ZAP 060 ***** 12/28/81 ***** V2M1 *****

Mandatory zap to DOS to eliminate disk status register read for all interrupts except the disk I/O (taking NEWDOS/80 back to the original TRSDOS way). NEWDOS/80 read the status on every interrupt in order to eliminate some code in the eternal quest to make more space available in SYS0. This worked fine until CPU speed up hardware modifications were devised that shift the CPU to slow speed for a number of milliseconds each time the status register was accessed. With NEWDOS/80 reading the status register every 25 ms, the CPU was spending most of its time at the slow speed if the user was using high speed and had set the switch enabling low speed to be temporarily switched. Most users just let the computer run always at the high speed and there was no problem; however, the 5MHZ speed is very marginal in supporting I/O thus requiring the slowdown. This zap does not eliminate other status reads done by NEWDOS/80 (such as to keep drives rotating if they are already rotating). This zap should eliminate most of the CPU slowdowns that were occurring. This zap was long delayed as it uses 7 of the last 10 zap bytes available in SYS0.

SYS0/SYS,00,33 change
00 00 00 00 00 00 00 to F5 07 DC E8 47 F1 C9

SYS0/SYS,02,E7 change
3A EC 37 3A E0 37 01 00 FC 45 07 DC to
3A E0 37 07 CD 53 01 00 FC 45 40 DC

***** ZAP 061 ***** 12/28/81 ***** V2M1 *****

Optional zap to DOS to cause DIR to actually read ENTER and BREAK from the keyboard rather than just look at the keyboard matrix. This zap allows BREAK to work for that function only if the BREAK key is enabled. This zap allows remote terminal operators of NEWDOS/80 to perform the DIR function when more than one display page will be involved. NEWDOS/80 was not designed to be run from remote terminals and at many places in its code looks directly at the keyboard matrix rather than actually accepting an input key when looking for BREAK, ENTER, UP or RIGHT ARROW. This zap changes only one of these situations, but a number of users have said they would be happy with that.

SYS8/SYS,02,94 change 0A 16 0F CD 6B 50 CB to 0A CD 6B 50 16 0F CB

SYS8/SYS,03,8A change
50 3A 40 38 E6 05 28 F9 0F D2 2D 40 3E to
50 CD 49 00 3D CA 2D 40 FE 0C 20 F5 3E

***** ZAP 062 ***** 01/12/82 ***** V2M1 *****

Mandatory zap to DOS force the 4445H call to DOS (back up one record) to set bit 6 of the FCB 2nd byte (disables EOF truncation).

SYS0/SYS,08,77 change 38 31 2B 18 1D CD to 38 10 2B 18 0D CD

Information zap.

1. NEWDOS/80 V2 BASIC functions LOAD, RUN and MERGE implicitly require that the text file being read be already in ascending sorted line number order whereas NEWDOS/80 Version 1, NEWDOS/21, TRSDOS, VTOS, LDOS, DOSPLUS and the other DOS's do not. Normally, the BASIC program files are in sorted line number order; so this difference was not noticed for some time into Version 2's release. Some users prefer to create text files in random line number order, relying on the implicit sort (not in NEWDOS/80 V2) done during LOAD, MERGE or RUN to sort the lines. These users must find some way of pre-sorting the text files, and since leading zeroes are suppressed from line numbers (causing line 5000 to sort before line 51), normal sorts won't work. The following sort program (known as CODESORT/BAS) will perform the sort, sorting the input text file into a different output text file.

```

10 CLEAR 2000: DEFINT A-Z: NR=0
20 PRINT"FILESPEC OF BASIC PROGRAM TO BE SORTED?": LINEINPUT FS$
30 OPEN"I",1,FS$: BC!=LOC(1)%
40 IF EOF(1)=0 THEN NR=NR+1: LINEINPUT #1,A$: GOTO 40
50 A$="": CLOSE
60 DIM CD$(NR), IX(NR), SN(NR): CMD"F=SASZ",BC!-NR+200
70 OPEN"I",1,FS$: X=1: K=1
80 IF X>NR THEN 170
90 LINEINPUT #1,CD$(X): Y=LEN(CD$(X)): Z=1: W=0: SN!=0: K=K+1
100 IF Y=0 THEN 160
110 IF Z>Y THEN 130 ELSE J=ASC(MID$(CD$(X),Z,1)): Z=Z+1: IF J=32 THEN 110
120 IF J>=48 AND J<58 THEN W=W+1: SN!=10*SN!+J-48: GOTO 110
130 IF W>0 AND SN!<65530 THEN SN(X)=SN!-32768: X=X+1: GOTO 80
140 PRINT K;"TH LINE HAS BAD OR MISSING LINE NUMBER. BYPASS IT? (Y/N) ";
145 INPUT A$
150 IF A$="N" THEN END ELSE IF A$<>"Y" THEN INPUT"BAD REPLY";A$: GOTO 150
160 NR=NR-1: GOTO 80
170 CLOSE: IF NR=0 THEN PRINT"NO RECORDS TO SORT": END
180 CMD"O",NR,*IX(1),SN(1)
190 PRINT"SORTED OUTPUT FILESPEC? ";: LINEINPUT FS$
200 OPEN"O",1,FS$
210 FOR X=1 TO NR: PRINT #1,CD$(IX(X)): NEXT
220 CLOSE: PRINT"DONE":END

```

2. In BASIC, RENUM does not renumber the CMD"F",DELETE statement properly. No zap will be issued to correct this.

3. The manual failed to inform programmers building programs to be executed that the command keyword or program name (filespec) is the first parameter of each DOS command and that, on entry to that program or DOS command function, register HL points to the parameters following the program name (filespec) in the DOS command statement that invoked the program. Examples:

1. XXXXXX This DOS command causes user program XXXXXX/CMD to be loaded from whichever drive it is found on into memory and program

execution commenced at its entry location. At that time, register HL points to the EOL character (ODH) since there are no parameters following the program's filespec. Note, in absence of a name-extension for the filespec XXXXXX, /CMD was substituted. Also, since no drive number was given, the drives were searched, starting with the drive 0, looking for the first occurrence of XXXXXX/CMD.

2. YYYY/OBJ:1,5,JJJ:1 This DOS command causes user program YYYY/OBJ:1 to be loaded into main memory from drive 1 and program execution commences at its entry location. At this time, register HL points the character 5 in the above command, as this is the first character of the first parameter following the program filespec. The user program may interrogate the parameter(s) with the EOL character (ODH) indicating the end of parameters.

3. ZZZ,Y,N,MYFILE This DOS command causes user program ZZZ/CMD to be loaded into main memory and execution started at its entry location with HL pointing to the character Y .

3. A number of users have asked why NEWDOS/80 Version 2 lacks features that other DOS's have. For the most part and for obscure reasons, we just elected to exclude them, but in many cases the main problem is that sufficient resident main memory space or overlay main memory space or both is not available.

1. In the DOS main memory region, 4000H thru 51FFH, NEWDOS/80 has 256 bytes less resident (always in memory) code/data than other DOS's have as it uses this 256 bytes to make the DOS overlay programs (i.e., SYS1/SYS) bigger.

2. Some DOS's have taken part of their resident code/data into high memory in order to gain more resident memory for DOS. For NEWDOS/80 Version 2, it was decided to remain out of high main memory, with the exception of the spooler, which was already there.

3. NEWDOS/80 has MINI-DOS which most other DOS's do not. This means that most of the DOS commands (DIR, FREE, LOAD, etc.) that execute in the 5200H thru 6FFFH region of main memory (and may call overlay routines that execute in the 4E00H thru 51FFH region) in other DOS's must execute in NEWDOS/80 entirely within the 4D00-51FFH DOS overlay region. This complicates the effort to extend the capabilities of any given DOS command.

4. A number of users have asked why SETCOM and FORMS were not included in Version 2 for the Model I like they were for the Model III. The author's excuses, weak as they are, are as follows:

1. For FORMS, of the two parameters, only LINES could have been accommodated as that is all the Model I ROM printer routine (used by NEWDOS/80) allows for. Most users that had to change the lines-per-page value at 4018H (16424 decimal) were already doing so, either via the POKE function of BASIC or the M function of DEBUG.

2. For SETCOM, this command changes the parameters in 3 control blocks for the RS-232C interface. NEWDOS/80 V1 and V2 for the Model I have no

main memory allocated for these three control blocks, and the Model I ROM does not have some of the routines used to change these control blocks, whereas the Model III does. Lastly, many excellent widely used RS-232C programs were already in existence handling the interface quite well without NEWDOS/80.

5. A number of users have asked why DIRECTORY READ ERROR or DIRECTORY WRITE ERROR appear as the DOS error message when an error occurs with a directory sector. Why not display the regular error code? We did this in order that normal file processing, the user would know that the directory, rather than his/her file, was the source of the error. At the time the error code substitution takes place, the system does not know whether or not the directory I/O was subsidiary to file I/O. We do apologize for the confusion created when the directory I/O was the main I/O (i.e., in DIR, FREE, etc.). The user can go to SUPERZAP and step through the directory (via DD, DTS or DFS (on DIR/SYS) to determine which sector is bad and what is the actual complaint. VDS mode can also be used.

6. LNW-80 users should be aware that that computer does not use the Z-80 instruction HALT to trigger the computers RESET line as does the TRS-80 Model I. Therefore, the BOOT DOS command and any other program that uses the Z-80 HALT instruction to RESET the computer will simply stop execution, which is what the normal Z-80 HALT instruction does. The user will have to actually press the RESET keys.

***** ZAP 064 ***** 02/15/82 ***** V2M1 *****

Mandatory zap to DOS to cause the /.5Y function of chaining (see page 4-11) to properly exit the current DOS-CALL level, if any, under certain circumstances where it was not. This problem can also be avoided by using CHNON,Y instead of /.5Y if DOS is awaiting its next command at that DOS level.

SYS9/SYS,01,97 change 43 B7 20 06 CB to 43 CD 3A 51 CB

SYS9/SYS,04,4E change
00 00 00 00 00 00 00 00 00 00 00 00 00 to
B7 C2 99 4E 78 E6 50 FE 40 CA 2D 40 C9

***** ZAP 065 ***** 02/15/82 ***** V2M1 *****

Information zap.

1. When COPY format 6 (CBF) is used to copy a system diskette and the system files are to be copied, the FMT parameter MUST be specified!!!! On page 2-14, last paragraph, is stated "If NFMT is specified, system files are not copied unless already existent in the destination file directory.". This is not true; if NFMT is specified or implied, the files are copied, but (1) SYS0/SYS will usually be in the wrong position causing BOOT to fail and (2) other system files may be in the wrong directory slots, eventually causing even worse trouble.

2. Some users have had GAT OVERFLOW error occur when using CBF with FMT to copy a system diskette. The system files SYS1/SYS through SYS21/SYS on a system diskette are positioned near the directory, some file above and some below, to enhance system efficiency. During the CBF COPY, the each system file is assigned space on the destination diskette in the same position relative to the directory as on the source diskette, and if that position is beyond either end of the diskette, GAT OVERFLOW error occurs. The solution to the problem is to cause the directory to be positioned nearer the center of the diskette. Two of the destination diskette's PDRIVE parameters are involved in the directory positioning: GPL and DDSL. Compute the number of lumps on the diskette and compare against DDSL to determine which end of the diskette the directory is too close to. You can take one of three actions to cause the directory to move closer to the diskette center: (1) change the DDSL value, (2) decrease the GPL value if the directory was too near the end of the diskette, or (3) increase the GPL value if the directory was too near track 0.

3. A number of users have complained that the LIST and PRINT commands do not allow for graphic characters. This was done so purposely as the intent with both LIST and PRINT was to provide a rudimentary, emergency method of listing or printing regular text files (files whose printable characters are between 20H and 7FH ASCII or that modulate to those values). These two commands were seldom used in NEWDOS+ or NEWDOS/80 Version 1, and we have been surprised by the increased useage in Version 2. For a subsequent release of NEWDOS80, we will try to add more capabilities to allow for graphics, but for now we simply apologize that the capability is not there.

4. For Model I users having CPU speed up modification installed that find that NEWDOS/80 Version 2 fails in double density I/O (or single density 8") where NEWDOS/80 Version 1 (using someone else's double density patches) worked, the user should ask the purveyor whether the speed up modification, when set to normal speed, actually causes the CPU to run slower than the standard Model I speed of 1.772 MHZ. Some of the earlier speed up mods did, and NEWDOS/80 Version 2 cannot tolerate any slowdown below 1.772 MHZ.

***** ZAP 066 ***** 03/16/82 ***** V2M1 *****

Mandatory zap to BASIC to correct error in dynamic MERGE occuring when the old text has lines within the range of the merging text (though not matching line numbers, which is not allowed). This is an unusual condition but nevertheless legal. This error was causing string variables whose strings are in the text area to not be properly repointed into the resulting text.

SYS19/SYS,00,DA change C5 21 3E 54 22 to C5 CD 20 56 22

SYS19/SYS,02,9D change C1 D1 E1 C9 2A to C1 C3 2A 56 2A

SYS19/SYS,02,E2 change CD F2 54 CD to CD 38 56 CD

SYS19/SYS,03,76 change
00 ED 52 38 2E 21 00 00 ED 52 30 27 AF to

00 00 CD 41 56 21 00 00 09 CD 49 56 AF

SYS19/SYS,04,34 change
0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 00

to

2100 0022 4256 213E 54C9 2A42
56ED 5B7A 5519 2242 56D1 E1C9 474F ED43
4256 C3F2 5401 0000 09ED 5218 03ED 523F
DOF1 C399 55

***** ZAP 067 ***** 03/25/82 ***** V2M1 *****

Mandatory zap to allow the TRSDOS 1.2 Model III VISICALC Version VC-150Y0-T83 to operate with Model I NEWDOS/80 Version 2. The 1st zap disables VISICALC's directory search feature. The 2nd and 3rd zaps insert the Model I HIMEM value. The 4th and 5th zaps disable the disabling of the Model III abort-on-BREAK RS-232 function which is not available on the Model I. The 6th zap performs a Model I check for the BREAK key. The 7th, 8th and 9th zaps disable VISICALC's direct printer interface (command /PR) with the RS-232 serial port which is not available on the Model I (the user may still use his/her own driver that takes /PP parallel printer output to the RS-232).

The directory search capability of VISICALC is disabled as NEWDOS/80 does not have the RAMDIR facility that Model III TRSDOS does. However, it is possible to use MINI-DOS to search the directory by (1) typing in the /SL command, (2) pressing DFG to enter MINI-DOS, (3) perform the MINI-DOS functions, (4) clear the display, (5) exit from MINI-DOS, (6) back in VISICALC, press three or more CLEARs to clear the command state, (7) execution one of the /T commands to restore the VISICALC display.

VC/CMD,86,CA change E5 CD 90 42 FD to E5 3E 08 B7 FD

VC/CMD,00,1E change 2A 11 44 7D to 2A 49 40 7D

VC/CMD,00,AA change 2A 11 44 11 to 2A 49 40 11

VC/CMD,84,CB change C9 32 03 42 CD to C9 00 00 00 CD

VC/CMD,85,25 change C9 32 03 42 CD to C9 00 00 00 CD

VC/CMD,83,9D change
F5 C5 D5 E5 CD 8D 02 28 0A CD 2D A4 E1 D1 C1 F1 to
F5 3A 40 38 E6 04 CC 35 A4 C4 2D A4 28 0B 00 F1

VC/CMD,84,C2 change E5 CD 5A 00 to E5 00 00 00

VC/CMD,85,05 change E5 CD 55 00 to E5 00 00 00

VC/CMD,84,BB change FF 32 FA 41 DD to FF 00 00 00 DD

***** ZAP 068 ***** 04/13/82 ***** V2M1 *****

Mandatory zap to DOS to correct an error in CREATE whereby the old file's (not the new) EOF was not being set = 0 when REC=0 parameter spec'ed or defaulted to.

SYS14/SYS,02,FE change 28 47 to 28 41

***** ZAP 069 ***** 04/13/82 ***** V2M1 *****

Mandatory zap to DOS to correct error in the DMDB function of SUPERZAP where the F, function was not displaying the correct dump location.

SUPERZAP/CMD,05,12 change 03 2A B2 54 CD to 03 CD 14 52 CD

SUPERZAP/CMD,00,18 change 00 00 00 00 00 00 to 3A B3 54 67 18 F6

***** ZAP 070 ***** 04/23/82 ***** V2M1 *****

Mandatory zap to BASIC to correct an error in CMD"0" sort of floating point values and, to a much lesser degree, of character strings. It is astonishing that this error was finally reported 8 months after Version 2 release; we simply refused to believe it as this meant virtually no one is using the floating point sort feature. The reporting user was persistent, however, sending in a very detailed problem report even so far as providing the zap! Well done!!! We thank this user and all others that persist in proving their point.

SYS21/SYS,03,1E change 18 29 B7 to 18 2B B7

***** ZAP 071 ***** 05/04/82 ***** V2M1 *****

Mandatory zap to VISICALC Version VC-160Y0-T83 for Model III TRSDOS 1.3 to operate with Model I NEWDOS/80 Version 2. Refer to ZAP 067 as this zap performs the same functions as that zap did for the TRSDOS 1.2 version.

VC/CMD,86,EB change E5 CD 90 42 FD to E5 3E 08 B7 FD

VC/CMD,00,1E change 2A 11 44 7D to 2A 49 40 7D

VC/CMD,00,B5 change 2A 11 44 11 to 2A 49 40 11

VC/CMD,84,EF change C9 32 03 42 CD to C9 00 00 00 CD

VC/CMD,85,46 change C9 32 03 42 CD to C9 00 00 00 CD

VC/CMD,83,BB change
F5 C5 D5 E5 CD 8D 02 28 0A CD 4B A4 E1 D1 C1 F1 to
F5 3A 40 38 E6 04 CC 53 A4 C4 4B A4 28 0B 00 F1

VC/CMD,84,E6 change E5 CD 5A 00 to E5 00 00 00

VC/CMD,85,26 change E5 CD 55 00 to E5 00 00 00

VC/CMD,84,DF change FF 32 FA 41 DD to FF 00 00 00 DD

***** ZAP 072 ***** 05/04/82 ***** V2M1 *****

Information zap on Model III TRSDOS diskettes.

Despite explicit and implicit statements in the manual and the zaps, users continue to think that Model III TRSDOS type diskettes are directly useable with NEWDOS/80 Version 2. NEWDOS/80 Version 2, with two exceptions, CANNOT, repeat, CANNOT operate with TRSDOS Model III system or data diskettes. Please believe us; this is so!!!! DO NOT ATTEMPT to use Model III type diskettes (data or system) with NEWDOS/80 except for the special conditions of COPY and SUPERZAP wherein PDRIVE TI flag M is used!!!!!! If you must use the DIR command to determine what is on a Model III TRSDOS type diskette, do so under TRSDOS, not NEWDOS.

The directory for Model III TRSDOS system and data diskettes is markedly different from the directory used on Model I TRSDOS 2.3 and all NEWDOS diskettes. For NEWDOS/80 Version 2 on the Model III, Apparat elected to remain with the old style directory so that data diskettes (once the address mark had been adjusted; see WRDIRP command and SYSTEM option BN) could be used interchangeably between the Model I and Model III under NEWDOS/80 Version 2 on both computers.

Realizing that data files and some program files must be transferable between TRSDOS Model III type diskettes and NEWDOS/80 Version 2 type diskettes, NEWDOS/80's COPY command, formats 1 - 4 and 6, allow, via special PDRIVE conditions, files to be copied from a Model III TRSDOS type diskette to a NEWDOS/80 Version 2 type diskette and from a NEWDOS/80 Version 2 type diskette to a Model III TRSDOS type diskette (note, COPY formats 1 and 2 filespecs for Model III TRSDOS files must have an explicit drive number). The special PDRIVE state is given in PDRIVE, example 3, page 2-38, and provides only for Model III TRSDOS type diskettes that are single sided, double density, 40 track. On your master Model III NEWDOS/80 system diskette, PDRIVE display slot # 4 was initialized to the correct value to use with these Model III TRSDOS 1.3 type diskettes (see zap 013 for TRSDOS 1.2 or 1.1 diskettes; see zap 031 for Model I TRSDOS 2.3B diskettes). For the remainder of this discussion, we will assume PDRIVE specification 4 contains the following values:

TI=xM,TD=E,TC=40,SPT=18,TSR=3,GPL=6,DDSL=17,DDGA=2
where x is C for PERCOM type double density interface and E for LNW type interface.

There are many variations available for copying to/from Model III TRSDOS diskettes which the more experienced NEWDOS user will adapt for his/her own

uses. The following examples are to get the novice through the first anxious moments. In each example, drive 0 is assumed a double density drive.

1. To copy file XXX/DAT from a Model III TRSDOS type diskette to a preformatted NEWDOS/80 Version 2 diskette, the following command will work:

`COPY,XXX/DAT:0,XXX/DAT:1,SPDN=4`

NEWDOS/80 will ask for the mount of the source diskette (the Model III TRSDOS type diskette) and the system diskette (the NEWDOS/80 system diskette) on drive 0 as necessary.

2. To copy multiple files from a Model III TRSDOS type diskette to a previously formatted NEWDOS/80 type diskette, the following command will work:

`COPY,0,1,,NFMT,CBF,CFO,SPDN=4`

NEWDOS/80 will ask for the mount of the source diskette (the Model III TRSDOS type diskette) and the system diskette (the NEWDOS/80 system diskette) on drive 0 as necessary. The user will be asked, one file at a time, which files are to be copied, except that files marked as system files are excluded automatically from the copy. To copy a system file, use the single file copy example above.

3. To copy file XXX/DAT from a NEWDOS/80 Version 2 diskette to Model III TRSDOS diskette, the following command will work:

`COPY,XXX/DAT:1,XXX/DAT:0,DPDN=4`

NEWDOS/80 will ask for the mount of the destination diskette (the Model III TRSDOS type diskette) and the system diskette (the NEWDOS/80 system diskette) on drive 0 as necessary.

4. To copy multiple files from a NEWDOS/80 type diskette to a previously formatted (under TRSDOS) Model III TRSDOS type diskette, the following command will work:

`COPY,1,0,,NFMT,CBF,CFO,DPDN=4`

NEWDOS/80 will ask for the mount of the destination diskette (the Model III TRSDOS type diskette) and the system diskette (the NEWDOS/80 system diskette) on drive 0 as necessary. The operator will be asked, one file at a time, to select which files are to be copied, excepting that any files marked as system files are automatically excluded from the copy. To copy a system file, use the single file copy example given above.

NEWDOS/80 Version 2 does not provide a method of copying to/from DOS's other than itself and TRSDOS. It is our intention that the TRSDOS diskette remain the common media for moving data between non-TRSDOS DOS's which is why we took the extra trouble to be able to copy TO a Model III TRSDOS diskette.

For the experienced user, SUPERZAP modes DD and DTS can be used to inspect Model III TRSDOS type diskettes provided the PDRIVE specifications are set correctly. The command

`PDRIVE,0,1=4,A`

will activate the drive #4 specifications as drive #1's specifications, thus allowing SUPERZAP to inspect a Model III TRSDOS type diskette on drive 1. When done, don't forget to change the PDRIVE specifications for drive 1 back. The Model III TRSDOS directory is 18 sectors long, starting at relative sector 306; remember, the directory format is different than that for NEWDOS/80.

***** ZAP 073 ***** 05/04/82 ***** V2M1 *****

Information zap on Model I TRSDOS 2.3B and higher diskettes. Refer also to ZAP 031.

Some time ago Radio Shack announced a double density modification to the Model I TRSDOS. To date, this modification is not available and Apparat does not know what zaps will have to be issued to operate with the new Model I TRSDOS 2.3B or higher double density diskettes. We assume that the new Model I TRSDOS will continue with the implementation of RBA format in the FCBs and the directories (which make the new TRSDOS diskettes incompatible with the old TRSDOS and with NEWDOS diskettes), and that like Model III TRSDOS diskettes, the new Model I TRSDOS diskettes will useable with NEWDOS/80 Version 2 only with COPY and SUPERZAP (see above zap) when the PDRIVE setting includes TI flag M. However, for now, use of flag M does not allow access to Model I TRSDOS double density diskettes as a TD code for double density implies Model III.

***** ZAP 074 ***** 05/12/82 ***** V2M1 *****

Mandatory zap to CHAINBLD/BAS to eliminate an unintended and non-displayed CLEAR character that causes trouble during PRINT of an ASCII copy of the program. This character is non-displayed but is the character in text immediately following the GOSUB36 of line 92. Load the program under BASIC, delete the character, and SAVE the CHAINBLD/BAS file back. Line 92 should display exactly the same after the character delete as before.

***** ZAP 075 ***** 05/12/82 ***** V2M1 *****

Mandatory zap to BASIC to correct memory-wipe-out error caused in certain circumstances by a REF= statement containing a ' character. The actual error is at 1A8B - 90 in the ROM and can be triggered in non-disk BASIC by keying in twice the direct command sss' where sss is three spaces. By making a change to NEWDOS/80's BASIC, the problem with REF is avoided.

SYS18/SYS,02,1A change
36 20 23 DF 38 FA 2B 36 FF 18 39 EB to
36 FF 23 DF 30 3E 36 20 23 18 F8 EB

***** ZAP 076 ***** 06/18/82 ***** V2M1 *****

Mandatory zap to DOS to allow NEWDOS/80 to run with the Radio Shack double density modification. This zap does NOT enable NEWDOS/80 to operate with Model I TRSDOS 2.7DD double density diskettes (see ZAP 078). PDRIVE TI flag D is hereby activated (please note this in the margin on page 2-34) for the Model I

to mean the Radio Shack double density interface, and all PDRIVE specifications for this interface must use TI flag A or D for single density diskettes and TI flag D for double density diskettes. If drive 0 is to be double density, TI=DK must be specified (with TC reduced by 1 (i.e., 34, 40, 76 or 79)). The Percom, LNW and Omikron double density interfaces for the Model I do not use write precompensation as does the Radio Shack interface. Since there is not enough resident DOS patch area to patch in precompensation and still retain system diskette interchangeability with other interfaces, it has been left out of this mandatory zap, but has been included as optional zap 077 below wherein the zapped NEWDOS/80 system diskette must only be run with an unmodified interface or with the Radio Shack DD interface.

***** Creating a system diskette to operate with a different I/O interface (i.e., the R. S. doubler) requires that the system diskette be created by format 5 or 6 COPY with FMT parameter specified.

***** TI flag D is interdrive mutually exclusive with flags B, C and E meaning that if D is specified in any drive's specification, then no other drive's specification may contain TI flags B, C or E. "TI= SPEC BETWEEN DRIVES INCOMPATIBLE" error will be given if this interdrive mutual exclusion is violated, requesting that you alter the various PDRIVE specs until atmost one of TI flags B, C, D or E is represented in the various PDRIVE specifications.

***** NEVER, NEVER, NEVER reset or boot the computer with PDRIVE showing an error. If this is done, the initialization routines will simply refuse to boot.

SYS6/SYS,07,7D change

ED 5BC1

59CD 8457 ED4B 9459 CB49 2047 CDF9 56CB
6828 062A 8159 22CE 42

to

DD 5604

DD4E 06DD 7E02 E61C FE08 C079 EE20 DD77
06C9 DD71 06DD 7307 C9

SYS6/SYS,27,C1 change 07 DD 56 04 DD to 07 CD D7 54 DD

SYS6/SYS,27,CD change

01 CD 59 69 20 03 CD AA 67 D1 DD E3 F5 DD 73 07 DD to
01 C5 CD 59 69 CC AA 67 C1 D1 DD E3 F5 CD EC 54 DD

SYS16/SYS,00,D6 change 05 7B 07 F6 FC 57 DD to 05 16 80 CD 95 51 DD

SYS16/SYS,02,56 change E6 68 C0 to E6 60 C0

SYS16/SYS,02,6A change 20 1D CB to 20 10 CB

SYS16/SYS,04,A9 change 00 00 00 00 00 00 to CB 43 C0 16 A0 C9

***** ZAP 077 ***** 06/18/82 ***** V2M1 *****

Optional zap to DOS to enable the Radio Shack double density write precompensation logic. When this zap is applied, the system diskette must only be used with either an expansion interface that has not been modified for disk double density or 8 inch drives or has been modified for the Radio Shack double density disk I/O. Once the diskette is modified, indicate on its label that this zap is installed.

SYS0/SYS,01,40 change
EF 00 00 00 3E 2A 18 AE C3 to EF 32 EE 37 C3 67 47 00 C3

SYS0/SYS,01,62 change
EF 00 00 00 00 00 00 18 D9 AF to EF 3E C0 30 DA 3E E0 18 D6 AF

SYS0/SYS,03,9A change CD 67 47 to CD B3 47

SYS0/SYS,04,A9 change
5E F3 3A 11 43 F6 FE 77 36 D0 FB 23 to
5E 18 08 3A 0D 43 0F BA C3 76 44 23

SYS6/SYS,29,5F change CD 67 47 to CD B3 47

***** ZAP 078 ***** 06/18/82 ***** V2M1 *****

Optional zap to allow COPY formats 1, 2, 3, 4 and 6 to copy files from or to Model I TRSDOS 2.7DD double density diskettes when the PDRIVE for that diskette is:

TI=xM,TD=E,TC=tc,SPT=18,TSR=3,GPL=6,DDSL=dt,DDGA=2

where:

x = C for Percom type double density modification, D for Radio Shack type modification and E for LNW type modification.

tc = diskette track count, 35, 40 or whatever. This track count includes the single density track 0.

dt = the directory track number (the standard is 17). NEWDOS/80 must be given the correct value as it does not obtain the value from the diskette's boot sector in the single density track 0.

See example 3, page 2-38. If ZAP 013 is applied to the diskette receiving this zap, ZAP 013 must be taken out before this zap is applied. Once this zap has been applied, the zapped diskette cannot be used to copy to/from Model III TRSDOS diskettes or to/from Model I TRSDOS 2.3B diskettes; this zap should only be applied to a special NEWDOS/80 system diskette whose sole function is to be used when copying files to/from Model I TRSDOS 2.7DD double density diskettes.

A Model I TRSDOS 2.7DD double density diskette cannot be formatted by NEWDOS/80, and it cannot be format 5 copied by NEWDOS/80, not even via the BDU option. Further, remember, format 6 (CBF) COPY does not copy system files to/from TRSDOS diskettes; formats 1 through 4 do, however.

Users must be aware that Model I TRSDOS 2.7DD double density diskettes are

written with track 0 in single density and all other tracks in double density; the directory information assumes track 0 is in double density and counts its information from track 0's 1st sector. Note, that track 0 is allocated on all diskettes to BOOT, a file that contains 10 sectors, not 18.

```

SYS6/SYS,14,25      change
00 3D 46 01 A8 41 46 01 A9 37 47 03 C3 0B 5C 37 48 01 0D 77 48 03 C3   to
00 A5 48 01 3E EE 48 01 00 F3 48 07 ED 5B 99 43 CD 0B 5C 8A 5B 00 C3

SYS6/SYS,14,67      change   01 50 D0   to   01 80 D0

SYS6/SYS,14,76      change   00 7B 4F 01 1A AF   to   00 38 50 01 C9 AF

SYS6/SYS,14,82      change
00 61 50 03 3E 1A B7 D6   to   00 67 50 03 36 80 23 D6

SYS6/SYS,14,8E      change
5C 12 51 01 1A 55 51 04 21 EF 5C C9   to   5C 0E 51 01 00 55 51 04 21 CD 40 C9

SYS6/SYS,14,A2      change   00 61 4E 01 0D 6C   to   00 8F 4E 01 80 6C

SYS6/SYS,14,B1      change
5B 18 EF 4E 02 35 56 DA 4E 01 2F 8B 4E 01 18 72   to
5B 28 EF 4E 02 35 56 E9 4F 02 36 00 00 5C 00 72

SYS6/SYS,14,D0      change
00 FB C1 20 0A 3A C4 46 E6   to   00 21 08 00 19 7E 12 C9 E6

SYS6/SYS,14,E9      change   3E 05 CD   to   3E 08 CD

SYS6/SYS,14,FB      change   3E 30 CD   to   3E 20 CD

SYS6/SYS,15,21      change   06 50 7E   to   06 80 7E

SYS6/SYS,20,11      change   01 EF 5C 23   to   01 CD 40 23

SYS6/SYS,20,97      change   3E 50 20   to   3E 80 20

```

***** ZAP 079 ***** 06/27/82 ***** V2M1 *****

Mandatory zap to DOS to correct error occurring when a file with EOF = 0 is copied (via single file COPY) to a NEWDOS/80 diskette from TRSDOS diskette other than the old TRSDOS 2.3 (or as now being called TRSDOS 2.3A) diskettes.

```

SYS6/SYS,05,C5      change
52 3A 14 53 B7 C8 CD 35 55 2A   to   52 CD 35 55 3A 14 53 B7 C8 2A

```

***** ZAP 080 ***** 07/19/82 ***** V2M1 *****

Mandatory zap to NEWDOS/80's ASPOOL program to correct error in the *ASP,S function where the computer is forced to DOS READY after the remaining spooled print completes printing. Instead, the delayed completion of the function should simply continue the interrupted program. To make room for this correction, the SPOOL PURGED message is no longer displayed. To determine that the spooler is gone, simply execute the *ASP command asking for spooler status. If the response is FILE NOT IN DIRECTORY, the spooler is gone.

ASPOOL/MAS,02,E8 change
44 C2 09 44 21 8B 58 CD 67 44 C3 2D 40 01 to
44 C1 21 08 44 B7 ED 42 C8 C3 15 55 00 01

***** ZAP 081 ***** 08/17/82 ***** V2M1 *****

Mandatory zap to LMOFFSET to correct error where the first program is stored with a disable-DOS appendage and the second program is stored with an appendage that does not disable DOS. This error causes the 2nd stored program to have a bad appendage.

LMOFFSET/CMD,00,34 change 53 21 3E 5A CD to 53 CD 15 5D CD

LMOFFSET/CMD,09,8F change
00 00 00 00 00 00 00 00 00 00 to 3E 50 32 C3 58 21 3E 5A C9

***** ZAP 082 ***** 08/31/82 ***** V2M1 *****

Information zap to allow BASIC and assembler programs to set the lower case state with the Model I NEWDOS/80 Version 2 DOS resident code. To execute the equivalent of the DOS command LC,N without causing disk I/O, BASIC programs execute POKE 17844,0 and assembler programs store 00 into 45B4H. To execute the equivalent of DOS command LC,Y without causing disk I/O, BASIC programs do POKE 17844,201 and assembler language programs store 0C9H into 45B4H. Remember, the lower case driver (see DOS command LCDVR) must be active for these POKES to work.

***** WARNING!!!!!! This 17844 (45B4H) location is NEWDOS/80 Version 2 dependent and definitely will be different in any subsequent NEWDOS/80 release. Users should mark this carefully in their programs. This is why we were so reluctant to release this information.

***** ZAP 083 ***** 09/02/82 ***** V2M1 *****

Mandatory zap to Radio Shack's Model I SuperSCRIPT for TRSDOS 2.3 (not 2.3B or 2.7DD) to enable it to run with the Model I NEWDOS/80 Version 2:

1. Allow the Main Menu Directory function to work. An actual NEWDOS/80 directory is executed via DOS-CALL; so the display will look different from that for TRSDOS. NOTE, the main menu display for the Model I does not show the "<D> Display disk directory" option as it does for the Model III, but a response of D will trigger it.

2. Allow the program to determine the number of 1024 byte page units of diskette space are available on the target drive. To do this, the DOS command DIR x,/Q9Q (where x is the drive #) is executed via DOS-CALL as NEWDOS/80 does not have the RAMDIR function. This causes an extra directory display to appear for during Main Memory function 0 that opens a document (appears after you have adjusted the document control data). This extra directory display may also appear at other times.

This zapped SuperSCRIPSIT must only be used with NEWDOS/80 Version 2 for the Model I.

With SuperSCRIPSIT, users may use DOS functions DFG (MINI-DOS) and 123 (DEBUG), but they must be very careful when pressing the three keys as SuperSCRIPSIT is likely to receive one or more of them. When a page of text is displayed, using the control-H command (HELP) puts the users where DFG or 123 may be pressed. Upon executing DOS command MDRET (to exit Mini-DOS back to SuperSCRIPT) or DEBUG command G (to exit DEBUG back to SuperSCRIPT), press BREAK to return to the page. If HELP was not available, you will additionally have to press control-T followed by BREAK to get back the full display. From the main menu, use option D to display a directory; then while the program is awaiting BREAK, you can press DFG or 123. WARNING!!!! Do not exit directly to DOS from Mini-DOS or DEBUG without giving SuperSCRIPSIT its chance to write data from memory and close its files; this can be disastrous to your document file.

```
SCRIPSIT/CMD,09,06      change
                        AB4F CDF0 4AC0 2100 4D01
2300 CB1E 3801 04CB 1E38 0104 0D23 20F2
0405 2801 0102 005B 0521 0500 CD71 6606
04CD 5166 7D32 227E AFC9 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000
```

to

```
                        ABC6 3032 225B 211E 5BCD
1944 C006 0411 333C 21DC AC1A 7713 D630
FE0A 3001 0102 005B 2310 F436 84CD B268
0605 CD71 6606 04CD 5166 7D24 2528 023E
FF32 227E AFC9 4449 5220 302C 2F51 3951
0D00
```

```
SCR17/CTL,02,3A      change
69 FE 30 38 F9 FE 34 30 F5 CD E5 75 0E 00 32 71 42 CD 19 44 3E 0F CD 33 00 21
69 32 70 8D 21 6C 8D CD 19 44 28 05 F6 C0 CD 09 44 18 06 44 49 52 20 30 0D 21
```

```
SCR17/CTL,04,AF      change  8E 00 4E  to  8E 44 4E
```

Information zap.

1. Most users are still puzzled about using multi-dimension arrays with BASIC's CMD"0". Please refer to section 7.21 in the manual and ZAP 41.4. CMD"0" was intended for single dimension arrays only, but it was found that a multi-dimension array could also be sorted if the user understands that the arrays items sorted (directly or indirectly) actually occupy consecutive memory locations (as assigned by BASIC during execution of the associated DIM statement) starting with the element specified in the CMD "0" statement. For single dimension arrays, this is the same order as ascending order of subscript, but for multi-dimension arrays, the order of elements used in the sort is COMPLEX and is given by the REN formulas. If you are going to sort a multi-dimension array, it is highly recommend that the sort start with the array's first element (i.e., the array's item specified in the CMD"0" statement should have all zero subscripts (i.e., A(0,0,0) for a 3 dimension array)). If you use anything other than zero subscripts for the sort of a multi-dimension array, you must be very clever to figure out which elements actually participate in the sort.

The REN formulas given on pages 7-14 and 7-15 show how to compute the REN for a given element in the array. Following are the formulas for computing the element subscripts corresponding to a given REN value (remember, the first REN value is zero).

1. For a single dimension array whose DIM statement is DIM A(R1) and for array element A(X1):

$$X1 = REN$$

2. For a two dimension array whose DIM statement is DIM A(R1,R2) and for array element A(X1,X2):

$REN/(R1+1)$ gives a quotient that is X2 and a remainder that is X1.

3. For a three dimension array whose DIM statement is DIM A(R1,R2,R3) and for array element A(X1,X2,X3):

$REN/((R1+1)*(R2+1))$ gives a quotient that is X3 and remainder M2 such that $M2/(R1+1)$ gives a quotient that is X2 and a remainder that is X1.

For an n dimension array (where n is not 1) the calculation involves REN being divided by product of all the ranges (a range is 1 greater than the value given in the DIM statement) except the nth, giving a quotient that is the nth subscript and a remainder that can be used as the REN value for calculating n-1th subscript as if the array had only n-1 dimensions. Continue this loop until n is reduced to 1.

2. Manual correction for ATTRIB, section 2-3, page 2-4. Place a note there to indicate that parameter LRL=lenl exists, allowing the user to alter the Logical Record Length of the file to the value lenl (1 to 256). This value, kept in the file's FPDE in the directory, is hardly ever used except by DIR, but some people want DIR to show the correct value. Remember, in NEWDOS/80 OPENs of a file, the LRL value is taken from register B rather than from the directory (in BASIC, it comes explicitly or implicitly from the OPEN statement).

***** ZAP 085 ***** 11/29/82 ***** V2M1 *****

Mandatory zap to DOS to correct error that was allowing a format 5 COPY to occur when both diskettes had the same number of sectors but different GPL values.

SYS6/SYS,22,36 change 5A 28 0E CB to 5A 00 00 CB

***** ZAP 086 ***** 12/17/82 ***** V2M1 *****

Mandatory zap to EDTASM to correct error where an error flag was not being reset after failure of a file open, thus causing the next file operation to fail to CLOSE a file properly.

EDTASM/CMD,30,61 change CA F8 01 CD to CA 08 57 CD

EDTASM/CMD,03,23 change C9 3A 28 52 F6 08 32 to AF 32 2E 76 C3 F8 01

***** ZAP 087 ***** 12/21/82 ***** V2M1 *****

Mandatory zap to BASIC to correct error in CMD"0" direct sort where an array is specified twice in the command sequence (i.e., two parts of a string supply independent sorting criteria.

SYS21/SYS,01,14 change 04 DD 77 04 D7 to 04 CD E0 65 D7

SYS21/SYS,01,7F change DF C2 4A 1E F1 to DF CD E5 65 F1

SYS21/SYS,01,8E change 01 32 02 4F F1 to 01 CD 17 66 F1

SYS21/SYS,02,88 change DD 7E 04 B7 28 to DD CB 04 7E 28

SYS21/SYS,03,EE change C9 DD 5E 13 DD to C9 CD 20 66 DD

SYS21/SYS,04,2C change 14 19 10 FD C9 to 14 C3 2B 66 C9

SYS21/SYS,04,B5 change
0C 28 05 2B 1B ED B8 13 DD 73 09 DD 72 0A DD to
0C EB B7 ED 42 DD 75 09 CD 34 66 20 22 00 DD

BASIC/CMD,14,E9 change
00 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
to
DD CB04 FEC9 C24A
1E3A 0251 B7FD 2100 4228 04FD 2117 42E5

BASIC/CMD,15,00 change
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
00
to
DD6E 05DD 6606 FD5E 05FD 5606 DF20 04DD
CB04 F611 1700 FD19 FD7E 00B9 38E8 E1C9
DDCB 0476 C032 024F C9DD 5E13 DDCB 0476
C8F1 09C9 DDCB 0476 C019 10FD C9DD 740A
09EB DDCB 0476 C078 B128 042B 1BED B8AF
C9

* * * NEWDOS/80 Version 2.0 Model I ZAP Index * * *
(Index listed in order of Filename)

ZAP#	Type	Area	Program	Reference
5	Mandatory	User	APL80/CMD	APL80/CMD
80	Mandatory	Utility	ASPOOL/MAS	*ASP,S function
14	Mandatory	BASIC	BASIC/CMD	Basic Editing
21	Mandatory	BASIC	BASIC/CMD	Marked & Fixed Item File Processing
52	Mandatory	BASIC	BASIC/CMD	CLOSE command
87	Mandatory	BASIC	BASIC/CMD	CMD"O" function
53	Mandatory	User	BRUN/CMD	Microsoft BASIC COMPILER v 5.23
19	Mandatory	Utility	CHAINBLD/BAS	Version 1 Format
74	Mandatory	Utility	CHAINBLD/BAS	Non-Displayed Character
53	Optional	User	DIR/SYS	Microsoft BASIC COMPILER v 5.23
27	Mandatory	Utility	DISASSEM/CMD	RTD Option
10	Mandatory	User	DSMB/CMD	Racet's DSM module DSMB/CMD
1	Mandatory	User	EDIT/CMD	Microsoft's EDIT/CMD
6	Optional	Utility	EDTASM/CMD	Disable LC to UC Conversion
22	Mandatory	Utility	EDTASM/CMD	Cursor Display
36	Information	Utility	EDTASM/CMD	Documentation errors
36	Information	Utility	EDTASM/CMD	Tape I/O for Mod III disabled
48	Mandatory	Utility	EDTASM/CMD	Filespec Response & <Sh-Lf-Arrow>
54	Mandatory	Utility	EDTASM/CMD	Object Code to Cassette
59	Mandatory	Utility	EDTASM/CMD	Correct & Restate ZAP #54
86	Mandatory	Utility	EDTASM/CMD	File Close Problem
37	Mandatory	User	FIREUP/CMD	BIONIC BASIC
9	Mandatory	User	IBLOAD/CMD	Racet's INFINITE BASIC
8	Mandatory	User	INIT	Radio Shack's Model I PROFILE
37	Mandatory	User	INSTALL/CMD	BIONIC BASIC
53	Optional	User	L80/CMD	Microsoft BASIC COMPILER v 5.23
58	Mandatory	Utility	LMOFFSET/CMD	Object Code Block Load
81	Mandatory	Utility	LMOFFSET/CMD	Appendage
2	Mandatory	User	PENCIL/CMD	ELECTRIC PENCIL
26	Mandatory	User	PENCIL/CMD	ELECTRIC PENCIL
39	Mandatory	User	PENCIL/CMD	ELECTRIC PENCIL
8	Optional	User	PROFILE/CMD	Reenable Interrupts
37	Mandatory	User	REMOVE/CMD	BIONIC BASIC
34	Mandatory	User	RSCOBOL/CMD	Ryan-McFarland Corp COBOL v 1.3B
34	Mandatory	User	RUNCOBOL/CMD	Ryan-McFarland Corp COBOL v 1.3B
83	Mandatory	User	SCR17/CTL	Radio Shack's Model I SUPERSCRIPSIT
51	Information	User	SCRIPSIT	Model I Cassette I/O
83	Mandatory	User	SCRIPSIT/CMD	Radio Shack's Model I SUPERSCRIPSIT
3	Mandatory	User	SCRIPSIT/LC	Radio Shack's Model I SCRIPSIT
38	Optional	User	SCRIPSIT/LC	Double Density & END command
3	Mandatory	User	SCRIPSIT/UC	Radio Shack's Model I SCRIPSIT
38	Optional	User	SCRIPSIT/UC	Double Density & END command
18	Mandatory	Utility	SUPERZAP/CMD	DM,P functions
33	Mandatory	Utility	SUPERZAP/CMD	DM & F functions
69	Mandatory	Utility	SUPERZAP/CMD	DMDB function

4	Optional	DOS	SYS0/SYS	Increase Drive Power-On Delay
20	Mandatory	DOS	SYS0/SYS	ROUTE command
43	Mandatory	DOS	SYS0/SYS	ROUTE command
55	Optional	DOS	SYS0/SYS	Patch LC Keyboard Modification
60	Mandatory	DOS	SYS0/SYS	Disk Status Register Reads
62	Mandatory	DOS	SYS0/SYS	4445H call to DOS
77	Optional	DOS	SYS0/SYS	Double Density Write Precomp Logic
40	Mandatory	DOS	SYS2/SYS	Directory Entries
35	Mandatory	DOS	SYS3/SYS	CLOSE & KILL commands
46	Optional	DOS	SYS3/SYS	'JKL': Graphics to Epson Printers
12	Optional	DOS	SYS6/SYS	Double Density Format Sensitivity
13	Optional	DOS	SYS6/SYS	To allow COPY of TRSDOS 1.2 (Mod 3)
15	Mandatory	DOS	SYS6/SYS	COPY Format 5
17	Mandatory	DOS	SYS6/SYS	COPY & FORMAT: DDSL parameter
23	Mandatory	DOS	SYS6/SYS	Granule Lockout Table in Directory
24	Mandatory	DOS	SYS6/SYS	FORMAT & COPY commands
28	Mandatory	DOS	SYS6/SYS	FORMAT: PFST parameter
31	Mandatory	DOS	SYS6/SYS	TRSDOS 2.3B (I) or TRSDOS 1.3 (III)
32	Mandatory	DOS	SYS6/SYS	TRSDOS 2.3B (I) or TRSDOS for Mod 3
44	Mandatory	DOS	SYS6/SYS	SYSTEM: BM parameter disabled
47	Mandatory	DOS	SYS6/SYS	PDRIVE: 8 Inch, Double Density
56	Mandatory	DOS	SYS6/SYS	COPY: CBF param & Model III TRSDOS
57	Mandatory	DOS	SYS6/SYS	COPY command
76	Mandatory	DOS	SYS6/SYS	Radio Shack's Double Density Board
77	Optional	DOS	SYS6/SYS	Double Density Write Precomp Logic
78	Optional	DOS	SYS6/SYS	Model I TRSDOS 2.7DD Diskettes
79	Mandatory	DOS	SYS6/SYS	COPY: TRSDOS 2.3B or Higher
85	Mandatory	DOS	SYS6/SYS	COPY Format 5
49	Mandatory	DOS	SYS8/SYS	DIR \$ or DIR \$0
61	Optional	DOS	SYS8/SYS	DIR: Remote Terminal Operators
64	Mandatory	DOS	SYS9/SYS	Chaining: ./5Y function
42	Mandatory	BASIC	SYS11/SYS	RENUM function
45	Mandatory	BASIC	SYS12/SYS	REF\$ function
20	Mandatory	DOS	SYS14/SYS	ROUTE command
50	Optional	DOS	SYS14/SYS	PRINT & LIST: Control Characters
68	Mandatory	DOS	SYS14/SYS	CREATE: Old File's EOF
16	Mandatory	DOS	SYS16/SYS	PDRIVE error
31	Mandatory	DOS	SYS16/SYS	TRSDOS 2.3B (I) or TRSDOS 1.3 (III)
47	Mandatory	DOS	SYS16/SYS	PDRIVE: 8 Inch, Double Density
76	Mandatory	DOS	SYS16/SYS	Radio Shack's Double Density Board
44	Mandatory	DOS	SYS17/SYS	SYSTEM: BM parameter disabled
57	Mandatory	DOS	SYS17/SYS	COPY command
14	Mandatory	BASIC	SYS18/SYS	Basic Editing
45	Mandatory	BASIC	SYS18/SYS	REF\$ function
75	Mandatory	BASIC	SYS18/SYS	REF= statement
66	Mandatory	BASIC	SYS19/SYS	Dynamic MERGE
70	Mandatory	BASIC	SYS21/SYS	CMD"O" function
87	Mandatory	BASIC	SYS21/SYS	CMD"O" function
11	Mandatory	User	VC/CMD	Radio Shack's Model I VISICALC
25	Mandatory	User	VC/CMD	Radio Shack's Model I VISICALC
67	Mandatory	User	VC/CMD	Model III VISICALC v VC-150Y0-T83
71	Mandatory	User	VC/CMD	Model III VISICALC v VC-160Y0-T83

7	Information DOS	Command	ATTRIB: LRL=xxx Parameter
7	Information DOS	Command	ROUTE: display of routes
7	Information DOS	Command	COPY: DFO parameter
7	Information DOS	Command	FORMAT: RWF parameter
29	Information DOS	Command	PDRIVE & COPY: Double Density
29	Information DOS	Command	PDRIVE: OMIKRON & 8 Inch Drives
30	Information DOS	Command	Model I & Model III Data Exchange
30	Information DOS	Command	COPY: Formats 5 & 6 discussed
36	Information DOS	Command	Documentation Correction
41	Information DOS	Command	ROUTE: Documentation Correction
41	Information DOS	Command	Automatic Density Recognition
41	Information BASIC	Command	CMD"O": explanation
41	Information DOS	Command	SYSTEM: AX parameter correction
51	Information DOS	Command	SYSTEM: AJ=N explanation expanded
63	Information DOS	Command	DIR & FREE Error Messages
63	Information User	Command	Program Parameters
65	Information DOS	Command	COPY: Format 6
65	Information DOS	Command	GAT Overflow & CBF with FMT COPY
65	Information DOS	Command	LIST & PRINT: no graphics
72	Information DOS	Command	Accessing files on Model III TRSDOS
73	Information DOS	Command	Accessing Model I TRSDOS 2.3B & Up
82	Information DOS	Command	LC,Y & LC,N without Disk I/O
84	Information BASIC	Command	CMD"O" & Multi-Dimension Arrays
63	Information BASIC	Commands	LOAD, RUN, MERGE & RENUM
63	Information DOS	Commands	FORMS & SETCOM omission in Model I
63	Information DOS	Features	Main Memory, High Memory, MINI-DOS
7	Information DOS	General	Reserved ZAP Areas in NEWDOS/80
41	Information DOS	General	Cassette I/O
51	Information DOS	General	TRSDOS 2.3B (I) & TRSDOS 1.3 (III)
51	Information DOS	General	Chain Filename & /JCL extension
41	Information DOS	Hardware	CPU Speed Up Modifications
63	Information DOS	Hardware	LNW-80 Computer Users
65	Information DOS	Hardware	CPU Speed Up Modifications
7	Information DOS	Mini-dos	Illegal under DOS-CALL
30	Information BASIC	Utility	RENUM usage

APPENDIX A

Understanding and learning to use the marked item and fixed item files specified in chapter 8 has proved difficult to the normal NEWDOS/80 user; therefore appendices A and B have been included to provide examples and more explanation in an effort to ease this difficulty. Nothing in appendix A or B is to be construed as overriding the specifications provided in chapter 8; the two appendices are provided simply and exclusively for examples and elaboration.

Appendix A was written by a user trying to cope with chapter 8 and is basically his understanding of marked item and fixed item files.

Appendix B is the NEWDOS/80 author's attempt to provide example programs of the 5 file sub-types: MF, MU, MI, FF and FI.

File Positioning

File Position (fp) is an operand in all NEWDOS/80 GETs and PUTs, and is specified in section 8.4.1. When omitted, a null operand is assumed. The fp operand and otherwise commonly consists of a special character, occasionally followed by other special characters and/or expressions. One form of the fp operand consists of nothing more than a numeric expression. In the forms which follow, special characters are to be used as shown. In those forms showing a prefixing special character adjoining some other character string, the special character does not necessarily have to be contiguous with the rest of the expression; it may be separated from it by a blank or space.

fp Value Meaning

(null)

If the file is an MU, MF or FF type file, and the REMRA is valid, the file is advanced to the next sequential record; in any other case, the current file position is not changed and processing continues from the position left at the termination of data transfer of the previous GET/PUT. Open leaves REMRA marked invalid for all file types, and sets current file position equal to 0 (except for mode "E", which causes current file position to be set equal to the FPDE's EOF value). The first sequential access for record segmented files always starts at current file position.

*

The current file position is not changed. This specification allows the continuation of processing of a particular record by a GET or PUT. It is primarily used to continue processing a record already partially read or written. For MU, MF and FF type files, it cannot be used to advance the file to the next sequential record, even though the file is actually already positioned at that record, having exhausted the bytes of the current record. To sequentially advance to the next record, use fp = (null).

#

If the REMRA is valid, the file is positioned to process that record again; an error condition is raised if the REMRA is invalid. For MU, MF and FF type files, this specification allows the reprocessing of the record currently being processed, from the beginning, perhaps with different variable names or expressions in the IGEs. For MI and FI type files, it allows the reprocessing of the same data item group as was processed by the immediately preceeding GET/PUT.

\$

If the REMBA is valid, the file is positioned to begin processing at again it the point where the previous GET or PUT was at the end of its file positioning phase; an error condition is raised if the REMBA is invalid. This specification allows the reprocessing of a particular group of data by a GET/PUT, and is primarily used to reposition a file for partial-record I/O. It functions in the same fashion for all NEWDOS/80 file types.

Z

This specification performs a "pseudo FIELD" operation. No data transfer takes place; the filearea FCB is not changed; the file does not have to be open when this fp is used. It is used with FF and FI files to allocate user data strings of fixed sizes from the BASIC string storage area in high memory.

&

This specification is used only with PUTs, and has no effect on file positioning. It does however cause the current contents of a filearea buffer to be written to the diskette. It should be used whenever the data in the buffer is particularly sensitive. It may be used specifying the FAN of a PRINT file.

&&

This specification is similar to &, except that in addition the file's EOF is updated from the FCB to the FPDE. PUT fan,&& allows the programmer to force the EOF update to the FPDE without having to do a CLOSE.

lrba

Using this form of fp specification causes GET/PUT processing to begin at the specified location in the file where rba is a BASIC expression evaluating to a RBA value. For MU, MF and FF type files, the system checks to make sure that a record begins at the specified location. In the case of a MU file, the RBA value must point to an SOR item. This form of fp specification demands the greatest amount of care and premeditation on the programmer's part, as if it is used incorrectly, especially with FF and FI type files, it can be most disastrous. It is just about the only way to randomly access data stored in MI, MU and FI type files.

lZ

This specification is basically the same as the lrba form except that the current EOF value is used as the RBA. It is commonly used to position a file for extension - that is, to add records/data to the end of the file. To extend a file it must be opened with mode "R"; mode "D" will yield an error if extension is attempted.

!\$rba

This specification allows the programmer to position the file for the next data transfer for that particular filearea, without regard to the specific access technique or verb used for the transfer; no data transfer to user data areas occurs with this specification. No IGEL may be referred to or included in the GET/PUT using this specification. The positioning resulting from the use of this specification doesn't become effective until the next INPUT/PRINT or GET/PUT, and then only if no additional positioning is specified. It can be used to position a file for random access in a program which uses a subroutine containing a single GET/PUT having a (null) fp to do all file access; such a program could process sequential groups of records randomly distributed throughout a file.

!\$%

The basic function of this specification is identical to !\$rba, except that it uses the current EOF value as the RBA. The GET/PUT using this specification must not refer to or include an IGEL. Again, the file position resulting from this specification doesn't take effect until the next INPUT/PRINT operation, or the next GET/PUT (if another fp isn't specified).

!#rba

Used only with PUT, this specification sets the filearea's EOF value equal to the value rba. For the real EOF value of the file to be altered, that is, the one in the FPDE, the filearea must either be closed or a PUT && statement executed. The EOF value provided must be rational for the file type involved. For MF and FF files it must be an integral multiple of the file's standard record length.

rn (Record Number)

This specification is the same as the one supported by TRSDOS; rn is a numeric BASIC expression which evaluates to an integer value from 1 to 32767, inclusive. The specified record number is converted to an RBA which is then used in the same functional manner as !rba.

As mentioned above, certain forms for fp change REMBA, REMRA or EOF. For your convenience, the fp forms and their effects on these fields are summarized in the following decision table.

fp	REMBA	REMRA	EOF
(null)	1	1	6
*	1	2	6
#	3	4	6
\$	4	4	6
%	4	4	4
&	4	4	4
&&	4	4	4
!RBA	1	1	6
!%	1	1	6
!\$RBA	5	5	4
!\$%	5	5	4
!#RBA	4	4	1
RN	1	1	6

Meanings of codes in the matrix:

- 1 -- The field is set to the RBA resulting from that fp value.
- 2 -- If REMRA is invalid at the beginning of the statements execution, or it is an MI or FI file, the field is set to the RBA resulting from the fp value. In other words, it is set if the current file position is at the beginning of a record, otherwise it is unchanged.
- 3 -- The field is set equal to REMRA.
- 4 -- The field is not changed.
- 5 -- The field is set to an invalid value.
- 6 -- For output/update files, the field is changed if a PUT extends the file.

Altogether, there are four areas in an FCB relevant to file positioning. These are:

Current File Position

This single field can be looked at as being 3 different values, depending upon where the GET/PUT is in its processing:

GPP1

The file position at the start of GET/PUT execution. Unless the file has been closed and re-opened, it is the same value left as GPP3 from the last GET/PUT for that filearea.

GPP2

The resulting RBA value after positioning has been done, and prior to any data transfer. GPP2 is the value saved as REMBA and REMRA whenever these values are set.

GPP3

The RBA value after the last byte of data transfer, if any, real or bypassed, has been accomplished.

REMRA

For MU, MF, FF and field item type files, it contains the RBA value of the beginning of the record in process. For MI, FI and INPUT/PRINT files, it is equal to REMBA. See GPP2 above.

REMBA

The RBA value where the previous data-transferring GET/PUT began its data transfer. If the file is record-segmented, and REMBA is at the start of a record, REMRA is set equal to REMBA. See GPP2 above.

EOF

The RBA value of the last byte of data in the file, plus 1. For MU, MF, FF and field item type files, it effectively points to the next sequential record to be written to the file. For MI, FI and